



PacketFence Installation Guide

PacketFence v15.2.0

Version 15.2.0 - August 2026

Table of Contents

1. About this Guide	2
1.1. Other Guides	2
1.2. Other sources of information	2
2. Introduction	4
3. System Requirements	5
3.1. Assumptions	5
3.2. Minimum Hardware Requirements	5
3.3. Operating System Requirements	5
4. Installation	6
4.1. Installing PacketFence from the ZEN	6
4.2. Installing PacketFence from the ISO	7
4.3. Installing PacketFence on existing Linux	7
4.4. Installing PacketFence on Linode	10
5. Getting Started	11
5.1. Going Through the Configurator	11
5.2. Connecting PacketFence to Microsoft Active Directory	12
5.3. Configuring Cisco Catalyst 2960 Switch	12
5.4. Adding the Switch to PacketFence	13
5.5. Configuring the Connection Profile	14
5.6. Configuring Microsoft Windows Supplicant	14
5.7. Testing	15
5.8. Alerting	15
6. Enabling the Captive Portal	16
6.1. Creating Authentication Source for Guests	16
6.2. Configure switchport for Web Authentication	16
6.3. Adjust Switch Configuration in PacketFence	17
6.4. Enabling Portal on Management Interface	17
6.5. Configuring the Connection Profile	18
6.6. Testing	18
7. Authentication Sources	19
7.1. Email Authentication for Guests	20
7.2. Adding SMS Authentication for Guests	21
7.3. Troubleshooting Authentication Issues	22
8. Introduction to Role-based Access Control	23
8.1. Adding Roles	23
8.2. Using the Employee Role	24
8.3. Using the Corporate_Machine Role	24
9. Supported Enforcement Modes	26
9.1. Technical Introduction to Inline Enforcement	26
9.2. Technical Introduction to Out-of-band Enforcement	27
9.3. Technical Introduction to Hybrid Enforcement	33
9.4. Technical Introduction to RADIUS Enforcement	34
9.5. Technical Introduction to DNS Enforcement	34
10. Adding Inline Enforcement to Existing Installation	36
10.1. Introduction	36
10.2. Preparing the Operating System	36

10.3. Adding Inline Interface	37
10.4. Network Devices	38
10.5. Adding Connection Profile for Inline	38
10.6. Testing the Inline Configuration	38
11. Adding VLAN Enforcement to Existing Installation	40
11.1. Introduction	40
11.2. Adding the Registration, Isolation and Other Interface	41
11.3. Network Devices	42
11.4. Adding Connection Profile for Registration	43
12. Authentication Mechanisms	45
12.1. Microsoft Active Directory (AD)	45
12.2. OAuth2 Authentication	56
12.3. Eduroam	59
12.4. SAML Authentication	62
12.5. Billing Engine	72
12.6. External API Authentication	86
12.7. External API Authentication	88
12.8. Azure AD integration	89
12.9. Google Workspace LDAP Integration	93
12.10. Advanced Access Control For Admin Login	94
13. Advanced Portal Configuration	95
13.1. Portal Modules	95
13.2. Portal Surveys	103
13.3. Self Service - Device Registration	108
13.4. Self Service - Status Page	108
13.5. Passthroughs	109
13.6. Proxy Interception	110
13.7. Parking Devices	110
14. Advanced Access Configuration	112
14.1. Connection Profiles	112
14.2. Filter Engine Macros	119
14.3. VLAN Filters	122
14.4. RADIUS Filters	123
14.5. Advanced LDAP Authentication	125
14.6. Advanced Realm Configuration	126
15. Advanced RADIUS Configuration	127
15.1. Local Authentication	127
15.2. Authentication against Active Directory (AD)	127
15.3. EAP Authentication against OpenLDAP	127
15.4. EAP Guest Authentication on Email, Sponsor and SMS Registration	128
15.5. EAP Local User Authentication	129
15.6. Limit Brute Force EAP Authentication	129
15.7. Testing	129
15.8. RADIUS Accounting	129
15.9. RADIUS Proxy	130
15.10. RADIUS EAP Profiles	135
16. Fingerbank Integration	136
16.1. Onboarding	136
16.2. Update Fingerbank Database	136
16.3. Submit Unknown Data	136
16.4. Upstream Interrogation	136
16.5. Local Entries	136
16.6. Settings	137

16.7. Device change detection	137
17. Network Devices Anomaly Detection	138
17.1. Creating Network Behavior Policies	138
17.2. Integration with Security Events	138
18. Intrusion Detection System Integration	139
18.1. Regex Syslog Parser	139
18.2. FortiGate DHCP Parser	140
18.3. Suricata IDS	142
18.4. Security Onion	144
18.5. Security Onion 2.3.10	146
18.6. ERSPAN	149
19. Firewall SSO Integration	151
19.1. Barracuda	151
19.2. Checkpoint	153
19.3. Cisco ISE-PIC	157
19.4. FortiGate	159
19.5. iBoss	162
19.6. JSON-RPC	162
19.7. Juniper SRX	163
19.8. Palo Alto	165
19.9. Troubleshooting SSO Integration	170
20. Performing Compliance Checks	171
20.1. Installation	171
20.2. Configuration	173
20.3. Rapid7 integration	176
21. Integrating Provisioning Agents	185
21.1. PacketFence Apple, Android and Windows Wireless Provisioning	185
21.2. MobileIron	189
21.3. SentinelOne	199
21.4. Microsoft Intune	202
21.5. Google Chromebook Provisioner	207
21.6. Configure PacketFence	208
21.7. Kandji	209
22. PKI Integration	213
22.1. PacketFence PKI	213
22.2. AirWatch	231
23. MFA Integration	241
23.1. Assumptions	241
23.2. Create the MFA Configuration	241
24. Best Practices	247
24.1. IPTables	247
24.2. Log Rotations	247
24.3. Large Registration Network	247
24.4. Active Directory fail-over	247
25. Performance Optimizations	250
25.1. Multi Machine Account Support	250
25.2. NT Key Caching	251
25.3. NTLM Authentication Caching	259
25.4. SNMP Traps Limit	262
25.5. MariaDB optimizations	262
25.6. Captive Portal Optimizations	265
25.7. Troubleshooting	265
26. Advanced Network Topics	266

26.1. Floating Network Devices	266
26.2. Production DHCP access	267
26.3. Routed Networks	269
26.4. Network Devices Definition	272
26.5. DHCP Option 82	277
27. Additional Integration	278
27.1. DHCP Remote Sensor	278
27.2. Active Directory Integration	279
27.3. Switch Login Access	286
27.4. Syslog forwarding	286
27.5. Monit	286
27.6. FleetDM Integration	288
28. Advanced Topics	295
28.1. Reports	295
28.2. Admin Access	303
28.3. Guest pre-registration	303
28.4. Content-Security-Policy (CSP)	304
28.5. pfacct: track bandwidth usage	304
28.6. Kafka configuration	305
29. Export/Import mechanism	314
29.1. Assumptions and limitations	314
29.2. Export on current installation	315
29.3. Import on new installation	316
30. PacketFence Certificates (for v11.2 and later)	319
30.1. Introduction	319
30.2. Why a certificate	320
30.3. From an existing certificate	326
30.4. Renewal certificate with a CSR	327
30.5. Renew a certificate without the CSR	327
30.6. Renew a certificate signed by the PF_PKI	327
30.7. Useful commands	331
30.8. Glossary	331
31. Troubleshooting PacketFence	332
31.1. RADIUS Audit Log	332
31.2. Log files	332
31.3. RADIUS Debugging	333
31.4. Authentication Failures	333
31.5. Network Connectivity Issues	334
31.6. Service Startup Failures	335
31.7. Database Connectivity Issues	336
31.8. Performance and Optimization Issues	337
31.9. Captive Portal Issues	338
32. Commercial Support and Contact Information	340
33. GNU Free Documentation License	341
34. Appendix	342
Appendix A: Administration Tools	342
Appendix B: Restoring a Percona XtraBackup or Mariabackup dump	343
Appendix C: How to restore a standalone PacketFence server ?	345
Appendix D: How to deploy PacketFence on Linode ?	345

Copyright © 2026 Akamai Technologies Canada Inc.

Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.2 or any later version published by the Free Software Foundation; with no Invariant Sections, no Front-Cover Texts, and no Back-Cover Texts. A copy of the license is included in the section entitled "GNU Free Documentation License".

The fonts used in this guide are licensed under the SIL Open Font License, Version 1.1. This license is available with a FAQ at: <http://scripts.sil.org/OFL>

Copyright © Raph Levien, <http://levien.com/>, with Reserved Font Name: "Inconsolata".



1. About this Guide

This guide covers PacketFence installation and day-to-day administration. It provides comprehensive instructions for system requirements assessment, initial deployment, network integration, authentication configuration, and ongoing maintenance. The guide covers both standalone and distributed deployments, including certificate management, database configuration, and integration with external authentication systems like Active Directory and LDAP.

Find the latest version at <https://www.packetfence.com/docs/>

1.1. Other Guides

Clustering Guide

Comprehensive guide for setting up active/active clustering environments with HAProxy load balancing, Keepalived for high availability, and Galera database clustering. Includes advanced configuration for layer-3 clusters and troubleshooting cluster synchronization issues.

Developer's Guide

Technical documentation for customizing PacketFence including REST API usage, captive portal theming and functionality modifications, SNMP module development, supporting new network equipment, and application code customizations. Essential for integrators and developers extending PacketFence.

Network Devices Configuration Guide

Device-specific configuration instructions for over 80 supported network vendors including switches (802.1X, MAC authentication, VLAN assignment), wireless controllers and access points. Covers RADIUS, SNMP configuration and integration with various network equipment manufacturers.

Upgrade Guide

Step-by-step upgrade procedures with version-specific compatibility changes, manual configuration migration steps, database schema updates, and critical upgrade notes. Includes troubleshooting for common upgrade issues and rollback procedures.

1.2. Other sources of information

<https://www.packetfence.com/news>

Release announcements with detailed feature descriptions, performance improvements, security updates, and comprehensive bug fix listings organized by PacketFence version.

PacketFence Users Mailing List

Community support forum for installation help, configuration questions, troubleshooting assistance, and best practices discussions. Active community of users and developers providing peer-to-peer support.

PacketFence Announcements

Public announcements including new releases, security warnings and important updates regarding PacketFence. Low-traffic list for staying informed about major PacketFence developments.

PacketFence Development

Discussion of PacketFence development including feature requests, architectural discussions, patch submissions and development coordination. For developers contributing to PacketFence core.

Package and release tarballs include the PacketFence guide files.

2. Introduction

PacketFence is a fully supported, trusted, Free and Open Source network access control (NAC) system. It features a captive portal for registration and remediation, centralized wired and wireless management, 802.1X support, layer-2 isolation of problematic devices, and integration with IDS, vulnerability scanners and firewalls. PacketFence effectively secures networks from small to very large heterogeneous environments. Visit <https://www.packetfence.com> for more details.

3. System Requirements

3.1. Assumptions

PacketFence reuses many components in an infrastructure. Nonetheless, it will install the following ones and manage them itself:

- database server (MariaDB)
- web server (Apache)
- DHCP server (PacketFence)
- RADIUS server (FreeRADIUS)
- firewall (iptables)

This guide assumes all components run on the same server as PacketFence.

Understanding these components and GNU/Linux is required. PacketFence installs and manages these services. Ensure other services start automatically with your operating system.

3.2. Minimum Hardware Requirements

Minimum server hardware recommendations

- Intel or AMD CPU 3 GHz, 4 CPU cores
- 16 GB of RAM
- 200 GB of disk space (RAID-1 recommended)
- 1 network card (2 recommended)

3.3. Operating System Requirements

PacketFence supports the following operating systems on the x86_64 architecture:

- Red Hat Enterprise Linux 8.x Server
- Debian 12.x (Bookworm)

Ensure you can install additional packages from your distribution. Red Hat Enterprise Linux requires Red Hat Network subscription.

Other distributions like RHEL or Debian derivatives may work but are not officially supported or documented.

Other Recommendations

- Use logical volume management (LVM) to allocate space

4. Installation

Install PacketFence using the Zero Effort NAC (ZEN) appliance or standard package repository on GNU/Linux installations.

4.1. Installing PacketFence from the ZEN

ZEN (Zero Effort NAC) edition enables rapid PacketFence deployment. It's a fully installed, preconfigured virtual appliance compatible with VMware ESX/ESXi, Microsoft Hyper-V and other products. This section covers VMware-based deployment. Xen-based hypervisors are not supported.

Download the ZEN here: <https://www.packetfence.com/download/#zen>

4.1.1. Virtual Machine

Tested with VMware ESXi, Fusion and Workstation with 16 GB RAM dedicated to the VM. Compatible with other VMware products. Requires 64-bit CPU host for long mode support. PacketFence ZEN comes as a pre-built OVF virtual disk. Import the OVF using vSphere Client or vCenter for ESX hypervisors.

The VM's first network card receives IP through DHCP.

The virtual appliance passwords are:

Management (Console/SSH) user

- Login: root
- Password: p@ck3tf3nc3

WARNING Be sure to change default passwords if you plan to use this image in production.

4.1.2. Import to ESX

Make sure that there is only one virtual network card created, and also make sure that the vEthernet is connected to a virtual switch (vSwitch). That virtual network card will be used as the PacketFence management interface.

4.1.3. Import to VMware Player/Workstation for Linux

Newer versions of VMware Player handle VLAN trunking a lot better. With that in mind, we can use a single interface on the VM. So, ensure that the VM host is plugged into a physical trunk port with VLAN 1,2,3,5,10 and 200 as the allowed VLAN. These VLANs will be used later in configuration examples.

4.2. Installing PacketFence from the ISO

The ISO edition of PacketFence allows you to install PacketFence on Debian 12 with minimal effort. Instead of manually installing Debian 12 and installing PacketFence after, this will perform both tasks and select the optimal parameters and best practices for installing the operating system.

Download the ISO here: <https://www.packetfence.com/download/#packages>

4.2.1. Machine specifications

This setup has been tested using VMware ESXi, Proxmox VE and VirtualBox and works with any hypervisor PacketFence supports as well as bare-metal servers.

A virtual machine or server with 16 GB of RAM dedicated to machine as well as 4 CPUs is required. Allocate at least 200GB of disk space for PacketFence.

4.2.2. Installing the ISO to a virtual machine

Provision a virtual machine with the specifications above, mount the ISO in the CD/DVD drive of the machine and start it. The installer will open. Follow the instructions on screen to complete the installation.

4.2.3. Installing the ISO to a bare-metal server

First, ensure the server follows the specifications above, then burn the ISO onto a DVD or USB key and boot it on the server. The installer will open. Follow the instructions on screen to complete the installation.

4.3. Installing PacketFence on existing Linux

PacketFence provides repositories for **RHEL 8** and **Debian 12** (bookworm) with all required dependencies.

Repository Benefits:

- Streamlined installation with dependency management
- Pre-built RPM (EL8) and DEB (Debian 12) packages
- Simplified upgrade process

4.3.1. Common Prerequisites

All Systems:

- Minimal OS installation (no additional packages)
- UEFI Secure Boot **disabled** (if applicable)
- System updated to latest patches
- No SELinux or Apparmor enabled
- No firewalld (Iptables is used)

4.3.2. RHEL 8 System Preparation

Security Configuration

```
# Disable firewall and SELinux (required)
systemctl disable --now firewalld
sed -i 's/^SELINUX=.*SELINUX=disabled/' /etc/selinux/config

# Update system
yum update

# Reboot to apply SELinux changes
reboot
```

PacketFence will not work properly if SELinux is enabled. Explicitly disable SELinux in the `/etc/selinux/config` file and reboot the machine.

Kernel and Development Tools

Prerequisites:

- Valid RHEL subscription for dependency installation
- Latest kernel running

```
# Install kernel development package for current kernel
yum install kernel-devel-$(uname -r)

# Remove conflicting container tools (PacketFence uses docker)
yum remove runc podman

# Import PacketFence GPG key (required for EL8)
rpm --import https://inverse.ca/downloads/GPG_PUBLIC_KEY
```

PacketFence Software Installation

```
# Install PacketFence repository
yum localinstall
https://www.packetfence.org/downloads/PackageFence/RHEL8/packetfence-release-
15.2.el8.noarch.rpm

# Install PacketFence with all dependencies
# Includes: MariaDB, FreeRADIUS, DHCP server
yum install --enablerepo=packetfence packetfence
```

4.3.3. Debian 12 System Preparation

Security Configuration:

```
# Update system first
apt-get update && apt-get upgrade

# Disable AppArmor (required)
systemctl disable --now apparmor
# Follow: https://wiki.debian.org/AppArmor/HowToUse#Disable_AppArmor

# Disable resolvconf and create static resolv.conf
rm /etc/resolv.conf
echo "nameserver 8.8.8.8" > /etc/resolv.conf

# Reboot to apply changes
reboot
```

Regarding AppArmor, even if they may be wanted by some organizations, PacketFence will not work properly if AppArmor is enabled. Follow instructions on the [Debian wiki](https://wiki.debian.org/AppArmor/HowToUse#Disable_AppArmor).

Regarding resolvconf, remove the symlink to that file and create the `/etc/resolv.conf` file with the desired content.

Kernel and Development Tools

Prerequisites:

- Fresh Debian 12 (bookworm) installation
- Latest kernel running

```
# Install kernel headers for current kernel
apt install linux-headers-$(uname -r)
```

Important: Ensure you're running the latest kernel before installing development packages. Reboot if kernel was updated.

PacketFence Software Installation

```
# Install repository tools and GPG key
apt install gnupg sudo curl
curl -fsSL https://inverse.ca/downloads/GPG_PUBLIC_KEY | gpg --dearmor -o
/etc/apt/keyrings/packetfence.gpg

# Add PacketFence repository (Debian 12 bookworm)
echo "deb [signed-by=/etc/apt/keyrings/packetfence.gpg]
https://inverse.ca/downloads/PackageFence/debian/15.2 bookworm bookworm" >
```

```
/etc/apt/sources.list.d/packetfence.list

# Install PacketFence with all dependencies
# Includes: MariaDB, FreeRADIUS, DHCP server
apt-get update
apt-get install packetfence
```


4.4. Installing PacketFence on Linode

PacketFence v12 includes instructions on deploying PacketFence on Linode IaaS. See the [Appendix](#) below for details.

5. Getting Started

Configure PacketFence after installation. The web-based configurator starts automatically.

This section configures PacketFence as a RADIUS server with 802.1X support through Microsoft Active Directory and a Cisco 2960 access switch. The 802.1X client is a Microsoft Windows 7 computer connected to the Cisco 2960 switch. The architecture diagram shows component interconnections:



NOTE For other access switches, refer to [PacketFence Network Devices Configuration Guide](#).

5.1. Going Through the Configurator

Open PacketFence's configurator at https://@ip_of_packetfence:1443. If unsure of the IP address, run `ip a` in Linux shell. Complete these steps:

- Step 1 - **Configure Network** - Define one interface with "Management" type. This interface connects to the Cisco 2960 access switch. The management interface and Cisco 2960 should be on the same network. Click the logical name to edit interface type
- Step 2 - **Configure PacketFence** - Provide required information for PacketFence database creation, domain name, hostname and admin credentials
- Step 3 - **Fingerbank** - Provide Fingerbank API key. Fingerbank identifies IoT devices, medical devices, industrial and robotics equipment. An API key is recommended for

device profiling

- Step 4 - **Confirmation** - save the passwords in a secure location and start PacketFence!

After services start, the system redirects to PacketFence's admin interface at https://@ip_of_packetfence:1443/. Log in using credentials from Step 2.

5.2. Connecting PacketFence to Microsoft Active Directory

Join PacketFence to the Microsoft Active Directory domain. From the admin interface, go to *Configuration → Policies and Access Control → Domains → Active Directory Domain* and click **New domain**. Provide required fields including domain admin credentials. Click **Create & Join**.

After successful domain join, click the **REALMS** tab. Set the **Default** realm to use the new Active Directory domain. Repeat for the **NULL** realm.

Add Microsoft Active Directory as an authentication source. From *Configuration → Policies and Access Control → Authentication Sources*, click **New internal source AD**. Specify required fields. Use Active Directory Explorer or Adsiedit.mmc tools for field identification.

In this new **Authentication Source**, add an **Authentication Rules** with name **catchall** with no condition and with the following actions:

- Role - default
- Access duration - 5 days

Make sure the information you provided are valid. Click on the **Test** button to validate the provided information. If you see the message **Success! LDAP connect, bind and search successful** - the Microsoft Active Directory authentication source has been properly configured. Save the new authentication source by clicking on the **Save** button.

5.3. Configuring Cisco Catalyst 2960 Switch

Next, we configure a switch so that it integrates with PacketFence using 802.1X. In our example, we will use a Cisco Catalyst 2960 access switch and its IP address will be 172.21.2.3. Our PacketFence's server IP address will be 172.20.100.2 - adjust this according to the environment.

Connect to that switch over SSH as an admin.

5.3.1. Enable 802.1X

As a first configuration step, enable 802.1X globally on the switch. Use the following:

```
dot1x system-auth-control
```

5.3.2. Configure AAA

The next step is to configure AAA so it will use the newly created PacketFence server. Replace the PF_MANAGEMENT_IP variable with the actual PacketFence management IP (172.20.100.2 in this example) in the following commands:

```
aaa new-model
aaa group server radius packetfence
  server PF_MANAGEMENT_IP auth-port 1812 acct-port 1813
aaa authentication login default local
aaa authentication dot1x default group packetfence
aaa authorization network default group packetfence
radius-server host PF_MANAGEMENT_IP auth-port 1812 acct-port 1813 timeout 2
key useStrongerSecret
radius-server vsa send authentication
snmp-server community public R0
snmp-server community private RW
```

5.3.3. Configure Switchport for 802.1X

Once AAA is ready, configure some or all switchports to perform 802.1X. In this example, only configure port no. 10 to use 802.1X:

```
interface fastEthernet 0/10
switchport mode access
authentication host-mode single-host
authentication order dot1x mab
authentication priority dot1x mab
authentication port-control auto
authentication periodic
authentication timer restart 10800
authentication timer reauthenticate 10800
mab
no snmp trap link-status
dot1x pae authenticator
dot1x timeout quiet-period 2
dot1x timeout tx-period 3
```

Write the switch configuration to memory.

5.4. Adding the Switch to PacketFence

PacketFence must be aware of the equipment it manages. From *Configuration* → *Policies and Access Control* → *Network Devices* → *Switches*, click on **New Switch default**. Enter the switch IP address (172.21.2.3 in our example). As a switch type, select **Cisco Catalyst 2960** and select **Production** as the Mode. From the **Roles** tab, make sure **Role by VLAN ID** is checked and that the VLAN ID associated to the default role is set to the normal VLAN

currently in use on the network. In our example, it will be VLAN 20. That means that once a 802.1X authentication is allowed by PacketFence, access will be properly granted in the default role in VLAN 20.

From the **RADIUS** tab, specify the **Secret Passphrase** to use - in our example, it is **useStrongerSecret**. It is very important to correctly set the RADIUS secret passphrase otherwise PacketFence will prevent the switch from communicating to itself.

Finally, from the **SNMP** tab, provide the correct **Community Read** and **Community Write** values.

5.5. Configuring the Connection Profile

Next, configure the connection profile in PacketFence. That is required so that PacketFence knows how to handle a connection coming from the wired network or WiFi network. In this case, create a new connection profile to use the Microsoft Active Directory authentication source and notify PacketFence to automatically register any devices that successfully authenticate using 802.1X on the default connection profile.

From *Configuration → Policies and Access Control → Connection Profiles*, click on **New Connection Profile**. Specify the following information:

- Profile Name: 8021x
- Profile Description: 802.1X wired connections
- Enable profile: checked
- Automatically register devices: checked
- Filters: If any of the following conditions are met:
 - ☐ Connection Type: Ethernet-EAP
- Sources: the newly created Active Directory authentication source

Click on **Create** to save all configuration changes.

5.6. Configuring Microsoft Windows Supplicant

To enable 802.1X on the wired adapter of the Microsoft Windows 7 endpoint, first enable the **Wired AutoConfig** service. From the Microsoft Windows Services control panel, double-click on **Wired AutoConfig**. Make sure **Startup type** is set to **Automatic** and click on **Start** to enable the service.

Then, from Windows' Network Connection panel, open the Properties window of the LAN interface you will use for testing. From the authentication tab, make sure **Enable IEEE 802.1X authentication** is checked. As the authentication method, make sure **Microsoft: Protected EAP (PEAP)** is selected. Then, click on **Settings** and make sure **Validate server certificate** is unchecked. As authentication method, make sure **Secured password (EAP-MSCHAPv2)** is selected. Then, click on **Configure ...** and make sure **Automatically use my Windows logon name and password (and domain if any)** is unchecked.

Save all changes.

5.7. Testing

Now, perform the testing. First restart the `radiusd` service. This is required since a new Active Directory domain controller was added. From *Status* → *Services*, click on the **Restart** button for the `radiusd` service. PacketFence will take care of restarting that service and the `radiusd-acct` and `radiusd-auth` sub-services.

Connect the Microsoft Windows 7 endpoint on port no. 10 from the Cisco Catalyst 2960 switch. From Microsoft Windows, a popup should appear prompting you for a username and password. Enter a valid username and password from the Microsoft Active Directory domain - this should trigger 802.1X (EAP-PEAP) authentication.

To see what's happening in PacketFence, click on the *Auditing* tab from PacketFence's admin interface. An entry should appear for the MAC address of the Microsoft Windows 7 endpoint. Click on the line with the correct MAC address to see the RADIUS exchanges. If the 802.1X authentication is successful, **Accept** appears as the **Auth Status**.

If authentication fails or you don't see RADIUS entries, see [RADIUS Debugging](#) and [RADIUS Audit Log](#) in the Troubleshooting section.

5.8. Alerting

PacketFence can send emails to administrators, users and guests. Therefore, it is important to properly configure the mail sending functionality of PacketFence. From *Configuration* → *System Configuration* → *Alerting*, set at least the following fields:

- Sender - the "From" address of emails being sent by PacketFence
- SMTP server - IP or DNS name of the SMTP server used by PacketFence to send all emails

If the SMTP server requires authentication or encryption to relay emails, properly configure the SMTP encryption, username and password parameters.

6. Enabling the Captive Portal

In the previous section, we have successfully configured 802.1X using PacketFence, Microsoft Active Directory and a Cisco Catalyst 2960 switch. While this demonstrates the fundamental role and capabilities of a NAC solution, most organizations are also looking at providing access to guests for example. One way of handling guests on a network is showing them a captive portal and let them register their own devices. This section will guide you in achieving this with PacketFence.

There are two ways PacketFence can show its captive portal for unknown (or unregistered) devices:

- it can use Web Authentication (or also known as hotspot-style authentication) - this works with numerous equipment vendors
- it can use a registration VLAN, where PacketFence provides DHCP services and DNS black-holing services - this works with any equipment vendors that support RADIUS dynamic VLAN assignment

For our example, we will use Web Authentication, as it is supported by the Cisco Catalyst 2960. For more information on various enforcement modes, please refer to the [Supported Enforcement Modes](#) sections of this document.

6.1. Creating Authentication Source for Guests

To keep our example simple, we will simply create a captive portal for guests where they will only have to accept the terms and conditions prior to gaining network access. To do so, we must first create a [Null](#) authentication source. From *Configuration* → *Policies and Access Control* → *Authentication Sources*, click on [New external source Null](#). As [Name](#) and [Description](#), specify 'null-source'. Then add an [Authentication Rules](#) with name [catchall](#) with no condition and with the following tow [Actions](#):

- Role - guest
- Access duration - 12 hours

Click on [Save](#) to save the new authentication source.

6.2. Configure switchport for Web Authentication

Connect to that switch over SSH as an admin.

First, we need to enable Change-of-Authorization (CoA) in our Cisco Catalyst 2960 switch configuration. We essentially need to allow our PacketFence server (172.20.100.2) to send CoA requests to the switch:

```
aaa server radius dynamic-author
client 172.20.100.2 server-key useStrongerSecret
```

```
port 3799
```

Then, we must enable Web Authentication on switch port no. 10. Add the following configuration to the global section:

```
ip device tracking
ip http server
ip http secure-server
```

Then add the required access list:

```
ip access-list extended registration
deny ip any host 172.20.100.2
permit tcp any any eq www
permit tcp any any eq 443
```

6.3. Adjust Switch Configuration in PacketFence

Next we have to let PacketFence know that Web Auth is to be used on the Cisco Catalyst 2960 switch. From *Configuration* → *Policies and Access Control* → *Switches* and click on the switch's IP to open its configuration options. From the **Definition** tab, make sure **Use CoA** and **External Portal Enforcement** are checked and set the **CoA Port** to 3799. From the **Roles** tab, make the following changes:

- in **Role by VLAN ID**, set the registration and guest VLAN ID to 20 - this will ensure unregistered clients are initially put in VLAN 20 and avoid a VLAN change once they properly authenticate from the captive portal
- make sure **Role by Switch Role** is checked and set the registration role to **registration** - this will ensure the registration access list created in the previous section is returned for unregistered users. This will limit their access to the PacketFence captive portal
- make sure **Role by Web Auth URL** is checked and set the **registration** URL to http://172.20.100.2/Cisco::Catalyst_2960

Click on **Save** to save all configuration changes.

6.4. Enabling Portal on Management Interface

By default the PacketFence's captive portal does not listen on the management interface. To change this, go in *Configuration* → *Network Configuration* → *Interfaces* and click on the logical name of the management interface to bring the configuration panel. In **Additional listening daemon(s)** - make sure you add **portal**.

You must then restart the following services from *Status* → *Services*:

- haproxy-portal
- httpd.portal

6.5. Configuring the Connection Profile

For Web Authentication, we will create a new connection profile in PacketFence. That means the default connection profile will be used for 802.1X while the new connection profile will be used for Web Authentication and will be used to display a captive portal with our **Null** authentication source. From *Configuration* → *Policies and Access Control* → *Connection Profiles* click on **New Profile**. Specify the following information:

- Profile Name: guest
- Filters: If any of the following conditions are met:
- Connection Type: Ethernet-NoEAP
- Sources: null-source

Click on **Save** to save all configuration changes.

6.6. Testing

First make sure that the Microsoft Windows 7 endpoint is unplugged from the Cisco Catalyst 2960 switch. Then, make sure the endpoint is unregistered from PacketFence. To do this, from the *Nodes* configuration module, locate its MAC address and click on it. From the node property window, change the **Status** to **unregistered**.

Next, we need to disable 802.1X from the network configuration card from the Microsoft Windows 7 endpoint. We want to simulate here an authentication by MAC address, so we have to disable 802.1X to do this. From Windows` Network Connection connection panel, ask for the properties of the LAN interface you will use for testing. From the authentication tab, make sure **Enable IEEE 802.1X authentication** is unchecked. Save all changes.

Next, connect the endpoint in the Cisco Catalyst 2960 switch. After a few second, open a web browser and try to open any website - say <https://www.packetfence.com>. You should now see the captive portal. You should only need to accept the terms and conditions for gaining network access.

If the captive portal doesn't appear or redirects fail, check portal-related logs as described in [Log Files](#) and [Network Connectivity Issues](#) in the Troubleshooting section.

7. Authentication Sources

PacketFence authenticates users registering devices via captive portal using various methods:

- Active Directory
- Apache htpasswd file
- BlackHole
- Email
- External HTTP API
- Clickatell
- Facebook (OAuth 2)
- Github (OAuth 2)
- Google (OAuth 2)
- Kerberos
- Kickbox
- LDAP
- LinkedIn (OAuth 2)
- Null
- OpenID Connect (OAuth 2)
- RADIUS
- SMS
- Sponsored Email
- Twilio
- Windows Live (OAuth 2)
- Password of the day

and many others. PacketFence also authenticates users in its internal SQL database. Create authentication sources from the admin interface: *Configuration* → *Policies and Access Control* → *Authentication Sources*. Authentication sources, rules, conditions and actions stored in `/usr/local/pf/conf/authentication.conf`.

Each authentication source has rules, conditions and actions.

Multiple authentication sources are tested in specified order (reorder in admin interface by dragging). Each source can have multiple rules, tested in order. Rules can be reordered like sources. Conditions define rule matching criteria. When criteria match, actions apply and rule testing stops across all sources ("first match wins").

When no condition is defined, the rule will be considered as a catch-all. When a catch-all is

defined, all actions will be applied for any users that match in the authentication source. Once a source is defined, it can be used from *Configuration → Policies and Access Control → Connection Profiles*. Each connection profile has a list of authentication sources to use.

In the previous section, you configured two authentication sources: Microsoft Active Directory and the Null sources. They were both catch-all sources.

7.1. Email Authentication for Guests

This section will show you how to allow guests to register endpoints using their email address. PacketFence sends a PIN code to the guest's email address. That code will then be required to complete the registration process.

7.1.1. Adding Email Authentication Source

From *Configuration → Policies and Access Control → Authentication Sources*, click **New external source** **Email**. As **Name** and **Description**, specify **email-source**.

Additional options available

- **email_activation_timeout** - This is the delay given to a guest who registered by email confirmation to log into his email and click the activation link.
- **allow_localdomain** - Accept self-registration from email address within the local domain
- **activation_domain** - Set this value if you want to change the hostname in the validation link. Changing this requires to restart haproxy to be fully effective.
- **allowed_domains** - A comma-separated list of domains that are allowed for email registration. Allowed domains are checked after banned domains.
- **banned_domains** - A comma-separated list of domains that are banned for email registration. Banned domains are checked before allowed domains.

Then add an **Authentication Rules** with name **catchall** with no condition and with the following two **Actions**:

- Role - guest
- Access duration - 12 hours

Click on **Create** to save the new authentication source.

7.1.2. Configuring the Connection Profile

Now let's add our new Email-based authentication source to our guests captive portal. From *Configuration → Policies and Access Control → Connection Profiles*, click on the **guest** profile that we previously created. In the **Sources**, click on the **(+)** button and add the newly created Email source, **email-source**. Save the changes by clicking on the **Save** button.

NOTE

You can preview at any time the portal associated with connection profile by clicking on the **Preview** button near the Connexion's title.

7.1.3. Testing

Unplug and unregister your endpoint. Reconnect the endpoint - you should see the captive portal with the new Email-based registration option.

7.2. Adding SMS Authentication for Guests

This section will show you how to enable SMS authentication on the captive portal so that guests use their cellular phone number to register their endpoints. PacketFence will send an SMS PIN code to the guest phone number. That code will be required to complete the registration process. The SMS code will be sent by PacketFence over email - using popular SMTP-to-SMS gateways.

Some of the key concepts presented in this section are:

- Authentication sources

7.2.1. Adding SMS Authentication Source

Now that you understand what authentication sources and alerting are, we will add an SMS authentication source on our guest portal. We previously used the 'Null' source but we will add another source. Portal profiles can provide multiple authentication sources.

From *Configuration* → *Policies and Access Control* → *Authentication Sources*, click **New external source** **SMS**. As **Name** and **Description**, specify **sms-source**. Then add an **Authentication Rules** with name **catchall** with no condition and with the following two **Actions**:

- Role - guest
- Access duration - 12 hours

You will also need to select the proper carriers to do your test. Make sure you include the one you are using for your cellular phone.

Click on **Create** to save the new authentication source.

Clickatell Source

To use Clickatell as an SMS source, first register at <https://www.clickatell.com> to get an API Key for the SMS integration. Then add it as an authentication source the same way as above, except choosing **Clickatell** instead of **SMS** in **Add source** **External**. Enter a name, description and your Clickatell API key in the source configuration, then add the authentication rule.

7.2.2. Configuring the Connection Profile

Now let's add our new SMS-based authentication source to our guests captive portal. From *Configuration* → *Policies and Access Control* → *Connection Profiles*, click on the **guest** profile that we previously created. In the **Sources**, click on the **(+)** button and add the newly created SMS source, **sms-source**. Save the changes by clicking on the **Save** button.

NOTE

You can preview at any time the portal associated with connection profile by clicking on the **Preview** button near the Connexion's title.

7.2.3. Testing

First unplug and unregister again the Microsoft Windows 7 endpoint. Then, connect the endpoint in switch port no. 10 – you should see the captive portal with the new SMS-based registration option. Note that the Null option will also be offered.

7.3. Troubleshooting Authentication Issues

For authentication troubleshooting, see [Authentication Failures](#), [Log Files](#), and [RADIUS Debugging](#) in the Troubleshooting section.

8. Introduction to Role-based Access Control

One important key concept from NAC solutions is for segregating network accesses. For example, an employee from the finance department might not have the same network access level as another employee from the marketing department. Guests should also not have the same access level as normal employees within an organization. PacketFence uses roles internally to identify and differentiate users. For segregating network access, PacketFence can use one or all of the following techniques:

- ACL
- VLAN or VLAN pool
- equipment role

The techniques to use depend on the wired/WiFi equipment itself. A role in PacketFence will be eventually mapped to a VLAN, an ACL or an external role. Define the roles to use in the organization for network access.

In our previous configuration examples, we made use of two roles that come by default in PacketFence: default and guest. We will now add two new roles - one for consultants and one used to authenticate machines on the network.

8.1. Adding Roles

Roles in PacketFence can be created from *Configuration → Policies and Access Control → Roles*. From this interface, limit the number of devices users belonging to certain roles can register.

Roles are dynamically computed by PacketFence, based on the rules (ie., a set of conditions and actions) from authentication sources, using a first-match wins algorithm. Roles are then matched to VLAN or VLAN pool or internal roles or ACL on equipment from the *Configuration → Policies and Access Control → Switches* module. For a VLAN pool instead of defining a VLAN identifier, set a value like that: 20..23,27..30 - which means that the VLAN returned by PacketFence can be 20 to 23 and 27 to 30 (inclusively). There are three algorithms: one based on a hash of the username (default one), another one based on a round-robin (last registered device +1) and one that selects a VLAN randomly in the pool.

Configuration → Policies and Access Control → Roles, click on **New Role**. Provide the following information:

- Name: employee
- Description: Role used for employees
- Max nodes per user: 2

Redo the operation of the other role:

- Name: corporate_machine

- **Description:** Corporate owned machines
- **Max nodes per user:** 1

Let's say we have two roles: employee and corporate_machine (defined above).

Now, we want to assign roles to employees and their corporate machines using Active Directory (over LDAP), both using PacketFence's captive portal.

8.2. Using the Employee Role

From the *Configuration* → *Policies and Access Control* → *Authentication Sources*, we select **New internal source AD**. We provide the following information:

- **Name:** ad1
- **Description:** Active Directory for Employees
- **Host:** 192.168.1.2:389 without SSL/TLS
- **Base DN:** CN=Users,DC=acme,DC=local
- **Scope:** subtree
- **Username Attribute:** sAMAccountName
- **Bind DN:** CN=Administrator,CN=Users,DC=acme,DC=local
- **Password:** acme123

Then, we add an **Authentication rules** by clicking on the **Add rule** button and provide the following information:

- **Name:** employees
- **Description:** Rule for all employees
- Don't set any condition (as it's a catch-all rule)
- Set the following **actions**:
- Role - employee
- Access duration - 7 days

Test the connection and save everything. Using the newly defined source, any username that actually matches in the source (using the **sAMAccountName**) will have the employee role and a 7 days Access Duration.

8.3. Using the Corporate_Machine Role

To differentiate user authentication and machine authentication using Active Directory, create a second authentication sources, for machines:

- **Name:** ad2
- **Description:** Active Directory for Corporate Machines
- **Host:** 192.168.1.2:389 without SSL/TLS
- **Base DN:** CN=Computers,DC=acme,DC=local
- **Scope:** One-level

- **Username Attribute:** servicePrincipalName
- **Bind DN:** CN=Administrator,CN=Users,DC=acme,DC=local
- **Password:** acme123

Then, we add an **Authentication rules**:

- **Name:** machines
- **Description:** Rule for corporate machines
- Don't set any condition (as it's a catch-all rule)
- Set the following **actions**:
- Role - corporate_machine
- Access duration - 7 days

Using this configuration, employees can only connect corporate machines, not personal devices.

NOTE

When a rule is defined as a catch-all, it will always match if the username attribute matches the queried one. This applies for Active Directory, LDAP and Apache httpasswd file sources. Kerberos and RADIUS will act as true catch-all, and accept everything.

NOTE

To use other LDAP attributes in an authentication source, add them in *Configuration → System Configuration → Main Configuration → Advanced → Custom LDAP attributes*. They will then be available in the rules defined.

9. Supported Enforcement Modes

Choose appropriate enforcement mode before configuring PacketFence. Enforcement mode is the technique used to enforce device registration and network access. PacketFence supports these enforcement modes:

- Inline
- Out-of-band using SNMP or RADIUS
- Hostpot-style (or Web Auth)
- RADIUS only
- DNS

Enforcement modes can be combined. For example, use out-of-band mode on wired switches and inline mode on older WiFi access points.

Following sections explain these enforcement modes and PacketFence configuration for each.

9.1. Technical Introduction to Inline Enforcement

9.1.1. Introduction

Many NAC solutions cannot support unmanageable devices like entry-level consumer switches or access-points. PacketFence inline mode supports these devices in-band. PacketFence becomes the gateway for the inline network, using IPTables/IPSet to NAT or route traffic to the Internet or other network sections.

9.1.2. Device Configuration

No special configuration needed on unmanageable devices. Simply ensure the device communicates on the inline VLAN. All traffic passes through PacketFence as it serves as the VLAN gateway.

9.1.3. Access Control

Access control relies entirely on IPTables/IPSet. When unregistered users connect to inline VLAN, PacketFence assigns IP addresses. Users are marked as unregistered in ipset session - web traffic redirects to captive portal, other traffic is blocked. After registration through captive portal (like VLAN enforcement), PacketFence updates the device's ipset session to allow the user's MAC address through.

9.1.4. Limitations

Inline enforcement has several limitations due to its nature:

- Everyone behind an inline interface is on the same Layer 2 LAN
- Every packet of authorized users goes through the PacketFence server increasing the server's load considerably: Plan ahead for capacity
- Every packet of authorized users goes through the PacketFence server: it is a single point of failure for Internet access
- Ipset can store up to 65536 entries, so it is not possible to have an inline network class greater than a class B

This is why it is considered a poor man's way of doing access control. We have avoided it for a long time because of the above mentioned limitations. That said, being able to perform both inline and VLAN enforcement on the same server at the same time is a real advantage: it allows admins to maintain maximum security while they deploy new and more capable network hardware providing a clean migration path to VLAN enforcement.

9.2. Technical Introduction to Out-of-band Enforcement

9.2.1. Introduction

VLAN assignment is currently performed using several different techniques. These techniques are compatible one to another, but not on the same switch port. This means that you can use the more secure and modern techniques for your latest switches and another technique on the old switches that doesn't support latest techniques. As it's name implies, VLAN assignment means that PacketFence is the server that assigns the VLAN to a device. This VLAN can be one of your VLANs or it can be a special VLAN where PacketFence presents the captive portal for authentication or remediation.

VLAN assignment effectively isolate your hosts at the OSI Layer2 meaning that it is the trickiest method to bypass and is the one which adapts best to your environment since it glues into your current VLAN assignment methodology.

9.2.2. VLAN assignment techniques

Wired: 802.1X + MAC Authentication

802.1X provides port-based authentication, which involves communications between a supplicant, authenticator (known as NAS), and authentication server (known as AAA). The supplicant is often software on a client device, such as a laptop, the authenticator is a wired Ethernet switch or wireless access point, and the authentication server is generally a RADIUS server.

The supplicant (i.e., client device) is not allowed access through the authenticator to the network until the supplicant's identity is authorized. With 802.1X port-based authentication, the supplicant provides credentials, such as user name / password or digital certificate, to the authenticator, and the authenticator forwards the credentials to the authentication server for verification. If the credentials are valid (in the authentication server database), the supplicant (client device) is allowed to access the network. The protocol for authentication is called Extensible Authentication Protocol (EAP) which have many variants. Both supplicant and authentication servers need to speak the same EAP protocol. Most popular EAP variant is PEAP-MsCHAPv2 (supported by Windows / Mac OSX / Linux for authentication against AD).

In this context, PacketFence runs the authentication server (a FreeRADIUS instance) and will return the appropriate VLAN to the switch. A module that integrates in FreeRADIUS does a remote call to the PacketFence server to obtain that information. More and more devices have 802.1X supplicant which makes this approach more and more popular.


MAC Authentication is a new mechanism introduced by some switch vendor to handle the cases where a 802.1X supplicant does not exist. Different vendors have different names for it. Cisco calls it MAC Authentication Bypass (MAB), Juniper calls it MAC RADIUS, Extreme Networks calls it Netlogin, etc. After a timeout period, the switch will stop trying to perform 802.1X and will fallback to MAC Authentication. It has the advantage of using the same approach as 802.1X except that the MAC address is sent instead of the user name and there is no end-to-end EAP conversation (no strong authentication). Using MAC Authentication, devices like network printer or non-802.1X capable IP Phones can still gain access to the network and the right VLAN.

Wireless: 802.1X + MAC authentication

Wireless 802.1X works like wired 802.1X and MAC authentication is the same as wired MAC Authentication. Where things change is that the 802.1X is used to setup the security keys for encrypted communication (WPA2-Enterprise) while MAC authentication is only used to authorize (allow or disallow) a MAC on the wireless network.

On wireless networks, the usual PacketFence setup dictate that you configure two SSIDs: an open one and a secure one. The open one is used to help users configure the secure one properly and requires authentication over the captive portal (which runs in HTTPS).

The following diagram demonstrates the flow between a mobile endpoint, a WiFi access point, a WiFi controller and PacketFence:



1. User initiates association to WLAN AP and transmits MAC address. If user accesses network via a registered device in PacketFence, go to step 8.
2. The WLAN controller transmits MAC address via RADIUS to the PacketFence server to authenticate/authorize that MAC address on the AP.
3. PacketFence server conducts address audit in its database. If it does not recognize the MAC address, go to step 4. If it does, go to step 8.
4. PacketFence server directs WLAN controller via RADIUS (RFC2868 attributes) to put the device in an "unauthenticated role" (set of ACLs that would limit/redirect the user to the PacketFence captive portal for registration, or we can also use a registration VLAN in which PacketFence does DNS blackholing and is the DHCP server).
5. The user's device issues a DHCP/DNS request to PacketFence (which is a DHCP/DNS server on this VLAN or for this role) which sends the IP and DNS information. At this point, ACLs are limiting/redirecting the user to the PacketFence's captive portal for authentication. PacketFence fingerprints the device (user-agent attributes, DHCP information & MAC address patterns) to which it can take various actions including: keep device on registration portal, direct to alternate captive portal, auto-register the device, auto-block the device, etc. If the device remains on the registration portal the user registers by providing the information (username/password, cell phone number, etc.). At this time PacketFence could also require the device to go through a posture assessment (using Nessus, OpenVAS, etc.).
6. If authentication is required (username/password) through a login form, those credentials are validated via the Directory server (or any other authentication sources - like LDAP, SQL, RADIUS, SMS, Facebook, Google+, etc.) which provides user attributes to PacketFence which creates user+device policy profile in its database.
7. PacketFence performs a Change of Authorization (RFC3576) on the controller and the user must be re-authenticated/reauthorized, so we go back to step 1.
8. PacketFence server directs WLAN controller via RADIUS to put the device in an "authenticated role", or in the "normal" VLAN.

Web Authentication Mode

Web authentication is a method on the switch that forwards HTTP traffic of the device to the captive portal. With this mode, your device will never change of VLAN ID but only the ACL associated to your device will change. Refer to the Network Devices Configuration Guide to see a sample web auth configuration on a Cisco WLC.

Downloadable ACLs

Downloadable ACLs is a method that can be used when the ACL list is greater than the size of a RADIUS access-accept packet. Some vendor support it, like Cisco Switches (IOS 15.2) and Dell (n1500 fw 6.8)

The RADIUS flow is something close to the normal one but in the Access-Accept reply there is an extra RADIUS attribute for the equipment to trigger another RADIUS request to retrieve the ACL.

A second RADIUS request is made with the ACL name as a value of the username and multiples Access-Challenge are made to retrieve the complete ACL.

To enable it you need first to enable the RADIUS filter in the PacketFence authorize section. To do that go in *Configuration* → *System Configuration* → *RADIUS* → *General* and enable [Use](#)

RADIUS filters in packetfence authorize then restart service radiusd-auth.

```
/usr/local/pf/bin/pfcmd service radiusd-auth restart
```

Push ACLs

Push ACLs is a method to write directly the ACLs on the equipment if compatible (needs ssh credentials and admin privileges on the switch). In this scenario if the PushACLs is enable on the switch then PacketFence will take the ACL defined in each role configuration (*Policies and Access Control* → *Roles*, and *ACL in Cisco format*), format it to be compatible with the equipment and will use ansible to push them on the switch (User role will create a User ACL on the equipment). Once this ACL is define on the switch, the RADIUS reply will contain an attribute that tell the switch to apply this ACL on the session. Per example in the case of Cisco, the attribute used is *Filter-ID = User*

Role per Switch role needs to be enable and PacketFence will return the role name and not the role value.

Dynamic/Downloadable ACLs can be combined with Push ACLs but in certain conditions. If an ACL is defined in the role in the switch configuration then this one will take precedence on the Push ACL. If the ACL in the role configuration is empty but you have an ACL defined in the role config then PacketFence will only return the attribute to assign the ACL (no RADIUS reply containing the ACL).

Here an example of what happen when you have a Cisco WLC where you enabled PushACLs and you defined the ACL as following:

Role User

Name: User

Description: User role

Parent role: Select option

Max nodes per user: 0
The maximum number of nodes a user having this role can register. A number of 0 means unlimited number of devices.

Include Parent ACLs: Disabled

Fingerbank Dynamic ACLs: Disabled
Use the Fingerbank dynamic ACLs

ACLs: permit udp any any eq 53
outpermit udp any eq 53 any
permit udp any eq 68 any eq 67
outpermit udp any eq 67 any eq 68
permit ip any host 172.16.0.250
outpermit ip host 172.16.0.250 any

Access Control Lists

Inherit VLAN: Disabled
Inherit VLAN from parent if none is found

Inherit Role: Disabled
Inherit Role from parent if none is found

Inherit Web Auth URL: Disabled
Inherit Web Auth URL from parent if none is found

Save Clone Reset Cancel

it will create or replace the User ACL like that:

General

Access List Name User

Deny Counters 0

Seq	Action	Source IP/Mask	Destination IP/Mask	Protocol	Source Port	Dest Port	DSCP	Direction	Number of Hits	
1	Permit	0.0.0.0 0.0.0.0	/ 0.0.0.0 0.0.0.0	/ UDP	Any	DNS	Any	Inbound	0	☒
2	Permit	0.0.0.0 0.0.0.0	/ 0.0.0.0 0.0.0.0	/ UDP	DNS	Any	Any	Outbound	0	☒
3	Permit	0.0.0.0 0.0.0.0	/ 0.0.0.0 0.0.0.0	/ UDP	DHCP Client	DHCP Server	Any	Inbound	0	☒
4	Permit	0.0.0.0 0.0.0.0	/ 0.0.0.0 0.0.0.0	/ UDP	DHCP Server	DHCP Client	Any	Outbound	0	☒
5	Permit	0.0.0.0 0.0.0.0	/ 172.16.0.250 255.255.255.255	/ Any	Any	Any	Any	Inbound	0	☒
6	Permit	172.16.0.250 255.255.255.255	/ 0.0.0.0 0.0.0.0	/ Any	Any	Any	Any	Outbound	0	☒


Port-security and SNMP

Relies on the port-security SNMP Traps. A fake static MAC address is assigned to all the ports this way any MAC address will generate a security violation and a trap will be sent to PacketFence. The system will authorize the MAC and set the port in the right VLAN. VoIP support is possible but tricky. It varies a lot depending on the switch vendor. Cisco is well supported but isolation of a PC behind an IP Phone leads to an interesting dilemma: either you shut the port (and the phone at the same time) or you change the data VLAN but the PC doesn't do DHCP (didn't detect link was down) so it cannot reach the captive portal.

Aside from the VoIP isolation dilemma, it is the technique that has proven to be reliable and that has the most switch vendor support.

9.2.3. More on SNMP traps VLAN isolation

When the VLAN isolation is working through SNMP traps all switch ports (on which VLAN isolation should be done) must be configured to send SNMP traps to the PacketFence host. On PacketFence, we use `snmptrapd` as the SNMP trap receiver. As it receives traps, it reformats and sends them into a redis queue, managed by `pfqueue` service. The multiprocessed `pfqueue` service reads these traps from the redis queue and takes a decision based on type of traps. For example, it can respond to them by setting the switch port to the correct VLAN. Currently, we support switches from Cisco, Edge-Core, HP, Intel, Linksys and Nortel (adding support for switches from another vendor implies extending the `pf::Switch` class). Depending on your switches capabilities, `pfqueue` will act on different types of SNMP traps.



You need to create a registration VLAN (with a DHCP server, but no routing to other VLANs) in which PacketFence will put unregistered devices. If you want to isolate computers which have open security event in a separate VLAN, an isolation VLAN needs also to be created.

Link Changes (deprecated)

When a host connects to a switch port, the switch sends a linkUp trap to PacketFence. Since it takes some time before the switch learns the MAC address of the newly connected device, PacketFence immediately puts the port in the Registration VLAN in which the device will send DHCP requests in order for the switch to learn its MAC address. Then **pfqueue** will send periodical SNMP queries to the switch until the switch learns the MAC of the device. When the MAC address is known, **pfqueue** checks its status (existing ? registered ? any security event?) in the database and puts the port in the appropriate VLAN. When a device is unplugged, the switch sends a **linkDown** trap to PacketFence which puts the port into the Registration VLAN.

When a computer boots, the initialization of the NIC generates several link status changes. And every time the switch sends a linkUp and a linkDown trap to PacketFence. Since PacketFence has to act on each of these traps, this generates unfortunately some unnecessary load on **pfqueue**. In order to optimize the trap treatment, PacketFence stops every thread for a **linkUp** trap when it receives a 'linkDown' trap on the same port. But

using only linkUp/linkDown traps is not the most scalable option. For example in case of power failure, if hundreds of computers boot at the same time, PacketFence would receive a lot of traps almost instantly and this could result in network connection latency.

MAC Notification Traps (deprecated)

If your switches support MAC notification traps (MAC learned, MAC removed), we suggest that you activate them in addition to the linkUp/linkDown traps. This way, `pfqueue` does not need, after a linkUp trap, to query the switch continuously until the MAC has finally been learned. When it receives a linkUp trap for a port on which MAC notification traps are also enabled, it only needs to put the port in the Registration VLAN and can then free the process. When the switch learns the MAC address of the device it sends a MAC learned trap (containing the MAC address) to PacketFence.

Port Security Traps

In its most basic form, the Port Security feature remembers the MAC address connected to the switch port and allows only that MAC address to communicate on that port. If any other MAC address tries to communicate through the port, port security will not allow it and send a port-security trap.

If your switches support this feature, **we strongly recommend to use it rather than linkUp/linkDown and/or MAC notifications**. Why? Because as long as a MAC address is authorized on a port and is the only one connected, the switch will send no trap whether the device reboots, plugs in or unplugs. This drastically reduces the SNMP interactions between the switches and PacketFence.

When you enable port security traps you should not enable linkUp/linkDown nor MAC notification traps.

9.3. Technical Introduction to Hybrid Enforcement

9.3.1. Introduction

In previous versions of PacketFence, it was not possible to have RADIUS enabled for inline enforcement mode. Now with the new hybrid mode, all the devices that supports 802.1X or MAC-authentication can work with this mode. Let's see how it works.

9.3.2. Device Configuration

You need to configure inline enforcement mode in PacketFence and configure your switch(es) / access point(s) to use the VLAN assignment techniques (802.1X or MAC-authentication). You also need to take care of a specific parameter in the switch configuration window, "Trigger to enable inline mode". This parameter is working like a trigger and you have the possibility to define different sort of triggers:

```
ALWAYS: :  
PORT: :  
MAC: :  
SSID: :
```

where ALWAYS means that the device is always in inline mode, PORT specify the ifIndex of the port which will use inline enforcement, MAC a mac address that will be put in inline enforcement technique rather than VLAN enforcement and SSID an ssid name. An example:

```
SSID::GuestAccess,MAC::00:11:22:33:44:55
```

This will trigger all the nodes that connects to the *GuestAccess* SSID to use inline enforcement mode (PacketFence will return a void VLAN or the *inlineVlan* if defined in switch configuration) and the MAC address *00:11:22:33:44:55* client if it connects on another SSID.

9.4. Technical Introduction to RADIUS Enforcement

9.4.1. Introduction

The concept of having a RADIUS enforcement is to not use registration, isolation, nor the portal capabilities of PacketFence. Everything here is for RADIUS integration only. By default the management interface will be the RADIUS interface. If needed, it is possible to add another interface from *Configuration* → *Network Configuration* → *Networks* → *Interface*. When doing so, you must select *Other* as the type of interface. Moreover, you must select *radius* as an additionnal listening daemon.

Using RADIUS enforcement, everytime a device connects to the network, a matching production VLAN will be assigned, depending on the rules in *Configuration* → *Policies and Access Control* → *Authentication Sources*.

9.5. Technical Introduction to DNS Enforcement

9.5.1. Introduction

DNS enforcement allows you to control the network access of the device by using the *pfdns* service on PacketFence.

The architecture of DNS enforcement is as following :

- DHCP and DNS are provided by the PacketFence server
 - The PacketFence DHCP server will provide the IP of your network equipment as the gateway and the IP address of the PacketFence DNS server to resolve names.
- Routing is provided by another equipment on your network (core switch, firewall, router,...)
- *pfdns* will respond to DNS requests depending on your configuration :
 - user registration on portal : it will return IP address of the captive portal
 - access to another site : it will resolve name externally and use it in reply

This enforcement mode used by itself can be bypassed by the device by using a different DNS server or by using its own DNS cache.

The first can be prevented using an ACL on your routing equipment, the second can be prevented by combining DNS enforcement with Single-Sign-On on your network equipment. Please see the Firewall Single-Sign-On documentation for details on how to accomplish this.

In order to configure DNS enforcement, you first need to go in *Configuration* → *Network Configuration* → *Networks* → *Interface* then select one of your interfaces and set it in DNS enforcement mode.

After, you must configure a routed network for this interface by clicking **New routed network**. See the **Routed Networks** section of this document for details on how to configure it.

NOTE

If you are not using a routed network, you must use Inline enforcement as DNS enforcement can only be used for routed networks.

Once this is done, you must restart the **pfdhcp** and **pfdns** services.

10. Adding Inline Enforcement to Existing Installation

10.1. Introduction

The inline enforcement is a very convenient method for performing access control on older network equipment that is not capable of doing VLAN enforcement or that is not supported by PacketFence.

An important configuration parameter to have in mind when configuring inline enforcement is that the DNS reached by these users should be your actual production DNS server - which shouldn't be in the same broadcast domain as your inline users. The next section shows you how to configure the proper inline interface and it is in this section that you should refer to the proper production DNS.

Inline enforcement uses `ipset` to mark nodes as registered, unregistered and isolated. It is also now possible to use multiple inline interfaces. A node registered on the first inline interface is marked with an IP:MAC tuple (for L2, only ip for L3), so when the node tries to register on another inline interface, PacketFence detects that the node is already registered on the first inline network. It is also possible to enable `inline.should_reauth_on_vlan_change` to force users to reauthenticate when they change inline network - you can change this from *Configuration* → *Network Configuration* → *Inline* - by checking or not the `Reauthenticate node` checkbox.

By default the inline traffic is forwarded through the management network interface but it is possible to specify another one by adding in `conf/pf.conf` the option `interfaceSNAT` in inline section of the `conf/pf.conf` configuration file. Alternatively, you can change this from *Configuration* → *Network Configuration* → *Inline* in the `SNAT Interface` section. It is a comma delimited list of network interfaces like `eth0,eth1.2`. It's also possible to specify a network that will be routed instead of using NAT by adding in `conf/networks.conf` an option `nat=no` under one or more network sections (take care of the routing table of the PacketFence server).

10.2. Preparing the Operating System

In order to build an inline deployment of PacketFence setup you need :

- 2 network interfaces for the VM (1 for the Inline and another one to go out)
- a switch port in the management network for the PacketFence server
- a switch port in the inline network for the PacketFence server which needs to be configured in access mode and in the same access VLAN as every switchport on which devices will be connected

10.3. Adding Inline Interface

PacketFence can be configured right from the start using the PacketFence configurator for inline enforcement. In this example, we will continue building on top of our initial deployment by adding a new inline interface to our PacketFence installation.

The first step is to add a dedicated Network Interface Card (NIC) to your current PacketFence installation. In our example, our new NIC will be named **ens192**. The PacketFence web interface will list all currently installed network interfaces on the system. An IP and a netmask will be visible if the network interface is configured (either by DHCP or already manually configured). You can edit those ones, create/delete VLANs on physical interfaces and enable/disable interfaces. Note that these changes are effective immediately. Persistence will be written only for **enabled** interfaces. Which means that if you change your management IP address, to pursue the configurator, you will need to go on this new IP address you just set. At all time, you will need to set a Management interface. That means that the required interface types for inline enforcement are:

```
Management
Inline layer 2
```

Note that PacketFence will provide these services on its inline interface:

- PacketFence provides its own DHCP service. It will take care of IP address distribution in our Inline network. PacketFence will not provide DHCP services on the management network - this is the responsibility of your own infrastructure.
- PacketFence provides its own DNS service. However, for the inline mode, you will also need to provide access to the DNS server of your infrastructure.

In the admin interface, go to *Configuration* → *Network Configuration* → *Interfaces*, and click on the **ens192** logical name. Provide the following information:

```
IP Address: 192.168.2.1
Netmask: 255.255.255.0
Type: Inline Layer 2
Additional listening daemon(s): portal
DNS Servers: 10.0.0.10
```

Click on **Save** and toggle the new interface to **On**.

Once done, PacketFence server should have the following network layout:

Please refer to the following table for IP and subnet information :

Networ k Card	Name	Subnet	Gateway	PacketFence Address
ens160	Management	172.20.100.0/16	172.20.0.1	172.20.100.2
ens192	Inline	192.168.2.0/24	192.168.2.1	192.168.2.1

Finally, from *Status*→*Services*, restart the `haproxy-portal`, `pfdhcp`, `pfdhcpListener`, `pfdns` services.

10.4. Network Devices

In an inline configuration, the required configurations for network devices (desktops, tablets, printers, etc.) will be to make sure they can all communicate with PacketFence. In other words for a switch you will need to configure every ports on which devices will be connected using the access mode with all of them in the same inline network. Access point will be connected as device to be in the inline subnetwork.

Example with a Cisco switch:

You should be in mode `#conf-t` if not execute `configuration terminal` in your CLI.

```
interface range [port-range]
switchport mode access vlan 1
no shutdown
interface [packetfence_ens192]
switchport mode access vlan 1
no shutdown
end
copy running-configuration startup-configuration
```

Now you can connect any devices that you want to be in the inline network in any of the port you have just configured.

10.5. Adding Connection Profile for Inline

Next thing we do is to add a new connection profile – for devices coming from the inline network. We want to show users the captive portal with our Null authentication sources.

From *Configuration* → *Policies and Access Control* → *Connection Profiles*, click on **Add Profile**. Provide the following information:

- Profile Name: inline
- Filters: If **any** Network 192.168.2.0/24
- Sources: null-source

Then click on **Save**.

10.6. Testing the Inline Configuration

You can now test the registration process. In order to do so:

- connect an unregistered device into the switch
- make sure PacketFence provides an IP address to the device. Look into the following log file: `/usr/local/pf/logs/packetfence.log` or verify on the computer you obtain an IP in the right subnet range

From the computer:

- open a web browser
- try to connect to a HTTP site (eg. <http://www.packetfence.com>, Not HTTPS)
- make sure that whatever site you want to connect to, you have only access to the registration page.

Register the computer using using the Null authentication source.

Once a computer has been registered:

- make sure PacketFence changes the firewall (`ipset -L`) rules so that the user is authorized through. Look into PacketFence log file:
`/usr/local/pf/logs/packetfence.log`
- from the web administrative interface, go under Nodes and make sure you see the computer as **Registered**.
- the computer has access to the network and the Internet.

For inline enforcement issues, check iptables rules and logs as described in [Log Files](#) and [Network Connectivity Issues](#) in the Troubleshooting section.

11. Adding VLAN Enforcement to Existing Installation

11.1. Introduction

VLAN isolation setup requires:

- Supported switch (consult *Network Devices Configuration Guide* for vendor types and uplink information)
- Normal, registration and isolation VLANs (VLAN numbers and subnets)
- Switch port for PacketFence server configured as dot1q trunk (multiple VLANs on port)

Network infrastructure assumptions for this configuration:

- VLAN 20 is the management VLAN
- VLAN 102 is the registration VLAN (unregistered devices will be put in this VLAN)
- VLAN 103 is the isolation VLAN (isolated devices will be put in this VLAN)
- VLAN 104 is the normal VLAN (registered devices will be put in this VLAN)

IP and subnet information:

VLAN ID	VLAN Name	Subnet	Gateway
20	Management	172.20.100.0/16	172.20.0.1
102	Registration	192.168.102.0/24	192.168.102.1
103	Isolation	192.168.103.0/24	192.168.103.1
104	Normal	10.0.104.0/24	10.0.104.1

VLAN ID	VLAN Name	PacketFence Address	DHCP	DNS
20	Management	172.20.100.2	infrastructure DHCP server	infrastructure DNS server
102	Registration	192.168.102.1	PF	PF
103	Isolation	192.168.103.1	PF	PF
104	Normal		infrastructure DHCP server	infrastructure DNS server

Note that PacketFence will provide these services on its registration and isolation VLANs:

- PacketFence provides its own DHCP services. It will take care of IP address distribution in VLANs 102 and 103. PacketFence will not provide DHCP services on VLAN 104 - this is

the responsibility of your own infrastructure

- PacketFence provides its own DNS service. It will take care of naming resolution in VLANs 102 and 103. PacketFence will not provide DNS services on VLAN 104 - this is the responsibility of your own infrastructure

11.2. Adding the Registration, Isolation and Other Interface

First of all, make sure you add a new NIC to your PacketFence server and you set the switch port where that NIC is connected in **trunk**. If you prefer, you can also set your management interface as trunk and set the PVID to your management VLAN on the switch port where that management is connected.

We will create three interfaces VLAN for registration, isolation and normal using the management interface.

The required interface types for VLAN enforcement are:

- Management
- Registration
- Isolation
- Other

Note that you can only set **one** (1) management interface.

In our example, we will create three new VLANs on the wired interface on our new trunk interface (**ens224**) To do so, click the **Add VLAN** button besides the wired interface for each of the needed VLAN:

Here's a sample configuration for both of them:

Registration

```
Virtual LAN ID: 102
IP Address: 192.168.102.1
Netmask: 255.255.255.0
```

Isolation

```
Virtual LAN ID: 103
IP Address: 192.168.103.1
Netmask: 255.255.255.0
```

Normal

```
Virtual LAN ID: 104
```

NOTE

Ignore the High-Availability options for now. If you are interested in a PacketFence cluster, please refer to the PacketFence Clustering Guide.

According to our example, we'll associate the correct type the each interfaces.

```
ens160: Management
ens224 VLAN 102: Registration
ens224 VLAN 103: Isolation
ens224 VLAN 104: Other
```

Make sure that those three interfaces are in an **enabled** state for the persistence to occur. We also need to set the Default Gateway which will generally be the gateway of the management network.

Finally, from *Status*→*Services*, restart the `haproxy-portal`, `pfdhcp`, `pfdhcpListener`, `pfdns` services.

11.3. Network Devices

Now let's modify our switch configuration to enable our new registration and isolation VLANs. In the admin interface, go to *Configuration* → *Policies and Access Control* → *Network Devices* → *Switches*, and click on our Cisco 2960 switch we added earlier (172.21.2.3).

From the Roles tab, make sure you specify the following information:

```
Role by VLAN ID: checked
registration VLAN: 102
isolation VLAN: 103
default: 104
guest: 104
```

Disable `Role by Switch Role` and `'Role by Web Auth URL'`.

Click on the `Save` button once completed.

11.3.1. Configure the Cisco Catalyst 2960

In previous sections, we correctly configured our switch to do 802.1X. Now let's slightly modify that configuration so that we enable MAC authentication and 802.1X on a new switch port. This will demonstrate the configuration differences.

11.3.2. Configure Switchport for MAB

Once AAA is ready, we can configure some or all switchports to perform MAB (MAC Authentication Bypass) and 802.1X. In our example, we will only configure port no. 11 without VoIP support:

```

switchport mode access
authentication host-mode single-host
authentication order mab dot1x
authentication priority mab dot1x
authentication port-control auto
authentication periodic
authentication timer restart 10800
authentication timer reauthenticate 10800
mab
no snmp trap link-status
dot1x pae authenticator
dot1x timeout quiet-period 2
dot1x timeout tx-period 3

```

If you want to test some ports with a VoIP phone (ex: Voice VLAN 200), add the following lines to your interface configuration:

```

switchport voice vlan 200
authentication host-mode multi-domain

```

11.3.3. Configure SNMP

Finally, for some operations (like VoIP), PacketFence still need to have SNMP access to the switch. Make sure you configure the two SNMP communities like:

```

snmp-server community ciscoRead ro
snmp-server community ciscoWrite rw

```

NOTE | You can refer to the [Cisco Catalyst documentation](#) for more options.

11.3.4. Save the Configuration

When done, don't forget to save your configuration changes using the `write mem` command.

11.4. Adding Connection Profile for Registration

Next thing we do is to add a new connection profile - for devices coming from the registration network. We want to show users the captive portal with our Null authentication sources.

In the admin interface, go to *Configuration* → *Policies and Access Control* → *Connection Profiles*, and click on **Add Profile**. Provide the following information:

- Profile Name: registration
- Filters: If **any** VLAN 102

- Sources: null-source

Then click on **Save**.

11.4.1. Testing VLAN Based Enforcement

You can now test the registration process. In order to do so:

- connect an unregistered device into the switch
- make sure PacketFence receives the radius authentication request from the switch. Look into the PacketFence log file: `/usr/local/pf/logs/packetfence.log`
- make sure PacketFence handles RADIUS requests and sets the switch port to the registration VLAN (VLAN 102). Look again into PacketFence log file: `/usr/local/pf/logs/packetfence.log`

On the computer:

- open a web browser
- try to connect to a HTTP site (eg. <http://www.packetfence.com>, Not HTTPS)
- make sure that whatever site you want to connect to, you have only access to the registration page.

Register the computer using the Null authentication source.

Once a computer has been registered, make sure:

- PacketFence puts the switch port into the normal VLAN (VLAN 104)
- The computer has access to the network and the Internet.

For VLAN assignment issues, verify switch configuration and trace RADIUS attributes as described in [RADIUS Debugging](#) and [Network Connectivity Issues](#) in the Troubleshooting section.

12. Authentication Mechanisms

This section covers authentication mechanisms supported by PacketFence. Follow these steps to configure authentication for the captive portal. For PKI integration, refer to the PKI Integration section.

12.1. Microsoft Active Directory (AD)

Go in the Administration interface under *Configuration* → *Policies and Access Control* → *Domains* → *Active Directory Domains*.

- | | |
|-------------|---|
| NOTE | If this section is inaccessible and you previously configured domain binding outside PacketFence, run <code>/usr/local/pf/addons/AD/migrate.pl</code> |
| NOTE | Windows Server 2008 or later required as domain controller. PacketFence 13.1+ uses secure channel for NTLM authentication, supported only in Windows Server 2008 and later. |

Click **New Domain** and fill in the information about the domain.

The screenshot displays the 'New Domain' configuration interface in PacketFence. The left sidebar shows a navigation menu with categories like Policies and Access Control, Compliance, Integration, Advanced Access Configuration, Network Configuration, and System Configuration. The main content area is titled 'New Domain' and has two tabs: 'Settings' (selected) and 'NTLM cache'. The 'Settings' tab contains various configuration fields:

- Identifier:** mydomain
- Workgroup:** DOMAIN
- DNS name of the domain:** DOMAIN.NET (with a note: 'The DNS name (FQDN) of the domain.')
- This server's name:** %h (with a note: 'This server's name (account name) in the Active Directory. Use %h to automatically use this server hostname.')
- Sticky DC:** * (with a note: 'This is used to specify a sticky domain controller to connect to. If not specified, default "" will be used to connect to any available domain controller.')
- Active Directory FQDN:** ad-server-fqdn.domain.net (with a note: 'The FQDN of the Active Directory server.')
- Active Directory IP:** 192.168.1.20 (with a note: 'The IPv4 of the Active Directory server. This field is optional if Active Directory server's FQDN is resolvable using specified DNS servers. Note: If DNS server, Active Directory Server's FQDN and IP are all given, PacketFence will use the resolved IP address instead of this.')
- DNS server(s):** 192.168.1.20 (with a note: 'The IP address(es) of the DNS server(s) for this domain. Comma delimited if multiple. This field is optional if Active Directory server's FQDN and IP are specified.')
- OU:** Computers (with a note: 'Use a specific OU for the PacketFence account. The OU string read from top to bottom without RDNs and delimited by a "/>

Where :

- **Identifier** is a unique identifier for the domain. It's purpose is only visual.
- **Workgroup** is the workgroup of the domain in the old syntax (like NT4).
- **DNS name of the domain** is the FQDN of the domain. The one that suffixes the account names.
- **This server's name** is the name that the server's account will have in the Active

Directory.

- **Sticky DC** is the preferred domain controller to connect to.
- **Active Directory FQDN** FQDN of the Domain Controller.
- **Active Directory IP** IP Address of the Domain Controller.
- **DNS server** is the IP address of the DNS server of this domain. Make sure that the server you put there has the proper DNS entries for this domain.
- **OU** is the OU in the Active Directory where the computer account will be created.
- **Machine account password** password of server's account in the Active Directory
- **Allow on registration** would allow devices in the registration network to communicate with the DC.
- **additional machine accounts** How many **additional** machine accounts will be created to handle NTLM authentication. By default 0. Means only 1 machine account will be created. Maximum is 10, you can only create 10 additional machine accounts.

Always check domain settings by running `net config workstation` on the domain controller. form the output,

- *Full Computer Name* is for **Active Directory FQDN**,
- *Workstation Domain DNS Name* is for **DNS name of the domain**
- *Workstation domain* is for **Workgroup**

NOTE

If using an Active/Active cluster, each member of the cluster must be joined separately. Follow the instructions in the PacketFence Clustering Guide.

NOTE

If using PacketFence in cluster mode, save the domain settings on **each** of the nodes by given the same **clear-text** machine account password. By default, PacketFence will only save the NT hash of the machine account password, and it will be shown in Admin UI. However, PacketFence cannot create a machine account using a password hash. To keep the domain settings identical on all the nodes, type in the same clear-text machine account password on each of the node and save them.

NOTE

after version 14.0, the PacketFence domain.conf will be updated, domain identifier is changed from previously single identifier to "hostname identifier". If running PacketFence in a cluster, check the corresponding sections for each node.

12.1.1. Domain Joining on A PacketFence cluster (v14.x)

We've updated the structure of `domain.conf` file since v14.0, the section name stored in `domain.conf` file has been changed from `domain identifier` to `hostname + domain identifier` combination. This change causes a node in a cluster to read domain settings from its own individual section identified by its unique hostname. Therefore, it is not required to use `%h` as (or as a prefix / suffix of) the machine account anymore. Now it's technically possible to have fully customized domain settings for a specific node.

Setting up a new cluster

There's a difference in domain profile creation for PacketFence cluster running

PacketFence v14.x:

When you create the domain profile from Admin UI for a PacketFence cluster, The profile is actually created **only** on the node that handles the API request. Therefore, go through all the nodes and create a domain profile for each of them.

During the domain profile creation, a machine account used for NTLM authentication is also created in Windows domain controller. Due to the limitation of secure connection binding, we are not able to establish multiple secure connections using a shared machine account. Ensure the machine account names are unique if not using %h as (or as part of) the machine account name.

There are 2 ways of creating the domain profile on a selected node:

- Using API Redirect
- Login into Admin Panel using real IP

To use API Redirect, login into **PacketFence Admin Panel**, navigate to *Status* → *Services* → *API redirect*, choose a node that handles the API request. And you will create the domain profile for the node you selected.

Login into Admin Panel using real IP is also simple: Login into **PacketFence Admin Panel** using the node's real management IP instead of virtual IP. For example, a cluster consists of 3 nodes with a VIP = 192.168.4.70, and real IP = 192.168.4.71, 192.168.4.72, 192.168.4.73. simply iterate the 3 real IPs, login into Admin Panel from https://real_ip:1443.

Upgrade from a version prior to v14.0

If you are doing an upgrade, please refer to the upgrade guide section for v14, you might need to manually combine the domain configuration file and sync them to all cluster members.

NOTE

It is required to use individual machine account for each node to avoid secure connection binding issues.


Domain config file structure and example

Assuming that we have a PacketFence cluster of 3 nodes with hostnames of pf-node1, pf-node2 and pf-node3 and we joined "domainA" an example of domain.conf for a cluster looks like this:

```
[pf-node1 domainA]
ntlm_auth_port=5000
server_name=node1
dns_name=a.com
[....]

[pf-node2 domainA]
ntlm_auth_port=5000
server_name=node2
dns_name=a.com
[...]
```

```
[pf-node3 domainA]
ntlm_auth_port=5000
server_name=node3
dns_name=a.com
[...]
```



Either the steps will allow you to create the domain profile on the selected node.

NOTE

Windows does not allow machine account to be shared when initialize secure connection. Therefore, each node in a cluster has to use a unique machine account. Either include %h as part of the machine account or use a unique fully customized machine account name for each of the node. For example, if using "A" as machine account name in node1's domain profile creation, and continuing to use "A" as machine account name to create a domain profile from another node, this will eventually cause node1 and node2 trying to bind the same machine onto its own secure connection, and cause NTLM authentication interruptions and failures.

After changing the node that handles the API request or choosing the node manually (method 2), do the following steps:

- navigate to "Configuration" → "Policies and Access Control" → "Active Directory Domains"
- fill in the information required to create the domain profile and then click "Create".
- PacketFence will create the domain profile for the node **only** that handles the API request.
- switch back to API redirect and select another node in the cluster
- back to "Configuration" → "Policies and Access Control" → "Active Directory Domains" and create the domain profile for another node.
- Repeat the previous steps until all the nodes are done with domain profile creation.

12.1.2. Troubleshooting

In order to troubleshoot unsuccessful binds, please refer to the following file : `/usr/local/pf/log/packetfence.log`. Search for `ntlm-auth-api-domain` for all ntlm-auth-api entries.

```
grep "ntlm-auth-api-domain" /usr/local/pf/log/packetfence.log
```

To check the service status and journal log, use

```
journalctl -f -u packetfence-ntlm-auth-api-domain@[domain_id]
```

for domain specific logs. Replace [domain_id] with the domain

To test the authentication process, use the following command

```
/usr/local/pf/bin/ntlm_auth_wrapper --username=administrator
```

12.1.3. Default Domain Configuration

Now define the domain to use as the default one by creating the following realm in *Configuration → Policies and Access Control → Domains → REALMS*.


[Status](#)
[Reports](#)
[Auditing](#)
[Nodes](#)
[Users](#)
[Configuration](#)
API
dashboard

Policies and Access Control
Roles
Domains
Active Directory Domains
Realms
Authentication Sources
Network Devices
Switches
Switch Groups
Connection Profiles
Compliance
Integration
Advanced Access Configuration
Network Configuration
System Configuration

Realm DEFAULT

Realm
DEFAULT

NTLM Auth Configuration

Domain
mydomain

The domain to use for the authentication in that realm.

Freeradius Proxy Configuration

Realm Options
strip

You can add FreeRADIUS options in the realm definition.

RADIUS AUTH

The RADIUS Server(s) to proxy authentication.

Type
Keyed Balance

Home server pool type.

Authorize from PacketFence

Should we forward the request to PacketFence to have a dynamic answer or do we use the remote proxy server answered attributes?

RADIUS ACCT

The RADIUS Server(s) to proxy accounting.

Type
Load Balance

Home server pool type.

Freeradius Eduroam Proxy Configuration

Eduroam Realm Options

You can add Eduroam FreeRADIUS options in the realm definition.

Eduroam RADIUS AUTH

The RADIUS Server(s) to proxy authentication.

Type
Keyed Balance

Home server pool type.

Authorize from PacketFence

Should we forward the request to PacketFence to have a dynamic answer or do we use the remote proxy server answered attributes?

Eduroam RADIUS ACCT

The RADIUS Server(s) to proxy accounting.

Type
Load Balance

Home server pool type.

Stripping Configuration

Strip on the portal

Should the usernames matching this realm be stripped when used on the captive portal.

Strip on the admin

Should the usernames matching this realm be stripped when used on the administration interface.

Strip in RADIUS authorization

Should the usernames matching this realm be stripped when used in the authorization phase of 802.1x. Note that this doesn't control the stripping in FreeRADIUS, use the options above for that.

Custom attributes

Allow to use custom attributes to authenticate 802.1x users (attributes are defined in the source).

LDAP source

The LDAP Server to query the custom attributes.

Save

Reset

Clone

Delete

Next, restart PacketFence in *Status → Services*

12.1.4. Multiple Domains Authentication

First configure the domains in *Configuration → Policies and Access Control → Domains → Active Directory Domains*.

Once they are configured, go in *Configuration → Policies and Access Control → Domains → REALMS*.

Create a new realm that matches the DNS name of the domain **AND** one that matches the workgroup. In the case of this example, it will be DOMAIN.NET tied to mydomain.

[Status](#)
[Reports](#)
[Auditing](#)
[Nodes](#)
[Users](#)
[Configuration](#)

[API](#)
[dashboard](#)

Policies and Access Control
Roles
Domains
Active Directory Domains
Realms
Authentication Sources
Network Devices
Switches
Switch Groups
Connection Profiles
Compliance
Integration
Advanced Access Configuration
Network Configuration
System Configuration

New Realm

Realm

DOMAIN.NET

NTLM Auth Configuration

Domain

mydomain

The domain to use for the authentication in that realm.

Freeradius Proxy Configuration

Realm Options

strip

You can add FreeRADIUS options in the realm definition.

RADIUS AUTH

The RADIUS Server(s) to proxy authentication.

Type

Keyed Balance

Home server pool type.

Authorize from PacketFence

☒

Should we forward the request to PacketFence to have a dynamic answer or do we use the remote proxy server answered attributes?

RADIUS ACCT

The RADIUS Server(s) to proxy accounting.

Type

Load Balance

Home server pool type.

Freeradius Eduroam Proxy Configuration

Eduroam Realm Options

You can add Eduroam FreeRADIUS options in the realm definition.

Eduroam RADIUS AUTH

The RADIUS Server(s) to proxy authentication.

Type

Keyed Balance

Home server pool type.

Authorize from PacketFence

☒

Should we forward the request to PacketFence to have a dynamic answer or do we use the remote proxy server answered attributes?

Eduroam RADIUS ACCT

The RADIUS Server(s) to proxy accounting.

Type

Load Balance

Home server pool type.

Stripping Configuration

Strip on the portal

☒

Should the usernames matching this realm be stripped when used on the captive portal.

Strip on the admin

☒

Should the usernames matching this realm be stripped when used on the administration interface.

Strip in RADIUS authorization

☒

Should the usernames matching this realm be stripped when used in the authorization phase of 802.1x. Note that this doesn't control the stripping in FreeRADIUS, use the options above for that.

Custom attributes

☐

Allow to use custom attributes to authenticate 802.1x users (attributes are defined in the source).

LDAP source

The LDAP Server to query the custom attributes.

Create

Reset

Copyright © Akamai Technologies Canada 2014 Authentication Mechanisms


53

Where :

- **Realm** is either the DNS name (FQDN) of the domain or the workgroup
- **Domain** is the Active Directory domain where PacketFence sends the NTLM request
- **Realm options** are any realm options that you want to add to the FreeRADIUS configuration
- **Domain** is the domain which is associated to this realm
- **RADIUS Auth** is the RADIUS authentication server to proxy the request to
- **Type** is the home server pool type
- **Authorize from PacketFence** specifies if we forward the request to PacketFence to have a dynamic answer or do we use the remote proxy server answered attributes
- **RADIUS Acct** is the RADIUS accounting server to proxy the request to
- **Type** is the home server pool type
- **Eduroam Realm Options** You can add Eduroam FreeRADIUS options in the realm definition
- **Eduroam RADIUS Auth** is the RADIUS Eduroam authentication server to proxy the request to
- **Type** is the home server pool type
- **Authorize from PacketFence** specifies if we forward the request to PacketFence to have a dynamic answer or do we use the remote proxy server answered attributes
- **Eduroam RADIUS Acct** is the RADIUS Eduroam accounting server to proxy the request to
- **Type** is the home server pool type
- **Strip on the portal** Should the usernames matching this realm be stripped when used on the captive portal
- **Strip on the admin** Should the usernames matching this realm be stripped when used on the admin interface
- **Strip in RADIUS authorization** Should the usernames matching this realm be stripped when used in the authorization phase of 802.1X
- **Custom attributes** Allow to use custom attributes to authenticate 802.1X users (attributes are defined in the source)
- **LDAP source** The LDAP Server to query the custom attributes

Now associate DEFAULT and NULL realms to the domain.

The following realm configuration should now be in place



12.1.5. Windows subdomain joining limitations

PacketFence supports multiple domain authentications as well as authentications performed against domains and subdomains.

But be aware that according to Windows Domain Controller's architecture and implementation, PacketFence cannot be joined on a subdomain if the subdomain shares the Domain Controller with the existing parent domain.

The only way to join PacketFence on a subdomain is to join it on a subdomain who has its own Domain Controller that belongs to a parent domain.

Check Microsoft's Learn, FAQ and discussions about subdomain computer joining. <https://learn.microsoft.com/en-us/answers/questions/342052/can-create-an-sub-domain-and-add-user-uder-the-cre>

12.1.6. Authenticating using Windows Trusted Domains

PacketFence supports domain trust relations to be passed to the correct Domain Controller. However, there isn't a way to configure the trusted domain settings from the Admin UI.

To authentication resources on a trusted domain, use the "--domain=" option in ntlm_auth_wrapper. Manually modify PacketFence's FreeRADIUS mschap module template file located at `/usr/local/pf/conf/radiusd/mschap.conf`. Locate the best mschap section that works for the situation and add a `--domain=DOMAIN_TRUST_SETTINGS` to the ntlm_auth_wrapper executable path.

After saving the changes, re-generate the FreeRADIUS configuration by restarting radius services and test if it works.

12.2. OAuth2 Authentication

NOTE | OAuth2 authentication does not work with Webauth enforcement

NOTE | OAuth2 authentication will fail by design when previewed through "Connection Profiles"

The captive portal of PacketFence allows a guest/user to register using his Google, Facebook, LinkedIn, Windows Live, OpenID Connect or Github account.

For each providers, we maintain an allowed domain list to punch holes into the firewall so the user can hit the provider login page. This list is available in each OAuth2 authentication source.

Enable the passthrough option in the PacketFence configuration (fencing.passthrough in pf.conf).

12.2.1. Google

To use Google as a OAuth2 provider, get an API key to access their services. Sign up here : <https://code.google.com/apis/console>. In the Google APIs Console, go into *Credentials* → *Create Credentials* → *OAuth client ID* → *Web Application*, then enter a name and use this URI for the *Authorized redirect URIs* field : https://YOUR_PORTAL_HOSTNAME/oauth2/callback. Of course, replace the hostname with the values from *general.hostname* and *general.domain*. Save to get the Client ID and Client secret.

Keep the default configuration, modify the App ID & App Secret (Given by Google on the developer platform) and Portal URL (https://YOUR_PORTAL_HOSTNAME/oauth2/callback).

Also, add the following Authorized domains : **.google.com*, **.google.ca*, **.google.fr*, **.gstatic.com*, *googleapis.com*, *accounts.youtube.com* (Ensure to have the google domain from the appropriate country like Canada □ **.google.ca*, France □ **.google.fr*, etc...)

Once the client id, and API key are available, configure the OAuth2 provider. This can be done by adding a Google OAuth2 authentication source from *Configuration* → *Policies and Access Control* → *Authentication Sources*. Remember to add the Authentication Rules with at least two Actions (example: Role and Access duration).

Moreover, don't forget to add Google as a **Source** from the connection profile definition, available from *Configuration* → *Policies and Access Control* → *Connection Profiles*.

12.2.2. Facebook

To use Facebook as an authentication source, an API code and a secret key are also needed. To get one, go here: <https://developers.facebook.com/apps>. When creating the App, specify the following as the Website URL: https://YOUR_PORTAL_HOSTNAME/oauth2/callback Of course, replace the hostname with the values from *general.hostname* and *general.domain*.

To find the secret, go in the newly created app, and click on *Settings* → *Basic*.

While in *Settings* → *Basic*, add YOUR_PORTAL_HOSTNAME in the **App Domains** field. Next, add the product **Facebook Login**. Click on **Set up**, and choose **Web** platform. Go through the 5 steps, then on the left side of the screen, go in *Settings* under Facebook Login. For **Valid OAuth Redirect URIs**, enter https://YOUR_PORTAL_HOSTNAME/oauth2/callback and then save changes.

Also, add the following Authorized domains : *.facebook.com, *.fbcdn.net, *.akamaihd.net, *.akamaiedge.net, *.edgekey.net, *.akamai.net (May change)

Once the information is available, configure the OAuth2 provider. This can be done by adding a Facebook OAuth2 authentication source from *Configuration* → *Policies and Access Control* → *Authentication Sources*. Remember to add the Authentication Rules with at least two Actions (example: Role and Access duration).

Keep the default configuration, modify the App ID & App Secret (Given by Facebook on the developer platform) and Portal URL (https://YOUR_PORTAL_HOSTNAME/oauth2/callback).

Moreover, don't forget to add Facebook as a **Source** from the connection profile definition, available from *Configuration* → *Policies and Access Control* → *Connection Profiles*.

CAUTION

By allowing OAuth through Facebook, you will give Facebook access to the users while they are sitting in the registration VLAN.

12.2.3. Github

To use Github, an API code and a secret key are also needed. To get one, create an App here: <https://github.com/settings/applications/new>. When creating the App, specify the following as the Callback URL https://YOUR_PORTAL_HOSTNAME/oauth2/callback

Of course, replace the hostname with the values from `general.hostname` and `general.domain`.

Once the information is available, configure the OAuth2 provider. This can be done by adding a GitHub OAuth2 authentication source from *Configuration* → *Policies and Access Control* → *Authentication Sources*. Remember to add the Authentication Rules with at least two Actions (example: Role and Access duration).

Moreover, don't forget to add GitHub as a **Source** from the connection profile definition, available from *Configuration* → *Policies and Access Control* → *Connection Profiles*.

12.2.4. Kickbox

To use Kickbox, an API key is needed. To get one, first create an account on <https://kickbox.io>, then navigate to <https://app.kickbox.com/settings/keys>. Click on **API Keys** → **Create Key**. Pick a name and choose **Production** mode and **Single** verification.

Once the API key is available, configure the OAuth2 provider. This can be done by adding a Kickbox authentication source from *Configuration* → *Policies and Access Control* → *Authentication Sources*. Remember to add the Authentication Rules with at least two Actions (example: Role and Access duration).

Moreover, don't forget to add Kickbox as a **Source** from the connection profile definition, available from *Configuration → Policies and Access Control → Connection Profiles*.

12.2.5. LinkedIn

To use LinkedIn, an API code and a secret key are also needed. To get one, create an App here: <https://developer.linkedin.com/>. When creating the App, specify the following as the Callback URL https://YOUR_PORTAL_HOSTNAME/oauth2/callback

Get more details about how to configure the LinkedIn application inside [Microsoft documentation](#).

Of course, replace the hostname with the values from `general.hostname` and `general.domain`.

Once the information is available, configure the OAuth2 provider. This can be done by adding a LinkedIn OAuth2 authentication source from *Configuration → Policies and Access Control → Authentication Sources*. Remember to add the Authentication Rules with at least two Actions (example: Role and Access duration).

Moreover, don't forget to add LinkedIn as a **Source** from the connection profile definition, available from *Configuration → Policies and Access Control → Connection Profiles*.

NOTE

When testing LinkedIn OAuth2, use a different LinkedIn account to setup the application and to test the Source in the captive portal.

12.2.6. OpenID Connect

Using OpenID Connect is a bit different than other OAuth2 sources. The reason behind that is because setting up a custom OpenID Connect source or depending on a provider for it. Configuration like token path, authorize path or API URL are specific to the setup. For more information on how to create one's own or get a host please visit: <https://openid.net/connect/>.

When creating the App, specify the following as the Callback URL, https://YOUR_PORTAL_HOSTNAME/oauth2/callback.

Of course, replace the hostname with the values from `general.hostname` and `general.domain`.

OpenID connect have different ways to be configured, create a client ID and a client secret to work with PacketFence.

Once the information is available, configure the OAuth2 provider. This can be done by adding an OpenID OAuth2 authentication source from *Configuration → Policies and Access Control → Authentication Sources*. Remember to add the Authentication Rules with at least two Actions (example: Role and Access duration).

Moreover, don't forget to add OpenID as a **Source** from the connection profile definition, available from *Configuration → Policies and Access Control → Connection Profiles*.

12.2.7. Twilio

To use Twilio, first create an account on <https://www.twilio.com>. From the console

(dashboard) <https://www.twilio.com/console> create a **3rd Party Integration**. Note the **Account SID** and **Auth Token** for later use. From the Phone Manager <https://www.twilio.com/console/phone-numbers/incoming> click the + button to **Buy a number** with SMS capability - no payment is needed to start using this phone number right away.

Once the information is available, configure the OAuth2 provider. This can be done by adding a Twilio OAuth2 authentication source from *Configuration → Policies and Access Control → Authentication Sources*. Enter the **Account SID**, **Auth Token** and **Phone Number (From)** from above. Remember to add the Authentication Rules with at least two Actions (example: Role and Access duration).

Moreover, don't forget to add Twilio as a **Source** from the connection profile definition, available from *Configuration → Policies and Access Control → Connection Profiles*.

12.2.8. Windows Live

To use Windows live, an API code and a secret key are also needed. To get one, create an App here: https://portal.azure.com/#blade/Microsoft_AAD_RegisteredApps/ApplicationsListBlade. When creating the App, specify the following as the Callback URL https://YOUR_PORTAL_HOSTNAME/oauth2/callback replacing the hostname with the values from **general.hostname** and **general.domain**.

Once the information is available, configure the OAuth2 provider. This can be done by adding a WindowsLive OAuth2 authentication source from *Configuration → Policies and Access Control → Authentication Sources*. Remember to add the Authentication Rules with at least two Actions (example: Role and Access duration).

The **App ID** in PacketFence will be **Application (client) ID** in the Azure portal.

The **App secret** must be a client secret created in the **Certificates & secrets** section of the app on Azure AD. Note that Azure AD secrets do expire so set a reminder to update the secret before it expires.

Moreover, don't forget to add WindowsLive as a **Source** from the connection profile definition, available from *Configuration → Policies and Access Control → Connection Profiles*.

12.3. Eduroam

Eduroam (education roaming) is the secure, world-wide roaming access service developed for the international research and education community.


Eduroam allows students, researchers and staff from participating institutions to obtain Internet connectivity across campus and when visiting other participating institutions by simply opening their laptop.

— Eduroam, <https://www.eduroam.org/>

PacketFence supports Eduroam and allows participating institutions to authenticate both locally visiting users from other institutions as well as allowing other institutions to authenticate local users.

Understanding of the Eduroam authentication workflow.

12.3.1. Local authentication



1. The device connects on the Eduroam SSID.
2. The access point forwards the authentication request to the wireless controller.
3. The controller sends the RADIUS authentication to PacketFence on port 11812.
4. PacketFence checks if it's a local REALM.
5. If it's local REALM, PacketFence does a NTLM request to the Active Directory (AD) domain controller to verify the identity. [loweralpha]
 - a. The AD validated the credentials.
 - b. The AD did not validate the credentials. PacketFence sends a RADIUS Reject.
 - c. After a successful NTLM authentication, PacketFence returns a Radius Access Accept to the wireless controller to apply the production VLAN for that MAC address.
6. If it's a not local REALM, PacketFence proxies the radius request to the Eduroam servers.
7. The Eduroam servers validate the identity.
8. PacketFence returns a Radius Access Accept to the wireless controller to apply the production VLAN for that MAC address.

12.3.2. Configure the Eduroam source

Open the admin interface and go to *Configuration → Policies and Access Control → Authentication Sources*.

First, create RADIUS sources for each Eduroam servers you want to define.

To do that click **New internal source** and choose RADIUS.

Fill the Name, Description, Host, Port, Secret and disable Monitor. (The information to configure that source could be found on the Eduroam platform)

Next click on **Exclusive Sources** and click on **New exclusive source** then **Eduroam**.

Associate the Radius sources you previously configured in **Eduroam RADIUS AUTH** section, define the radius listening port and keep the type to **Keyed Balance**.

In order to handle correctly external and internal students with the Eduroam source, you will need to:

- define realms used by the internal students in **Local Realms** field
- create a catchall rule which will assign a role (for example: eduroam) to external students
- create two different connection profiles (see next sections)

12.3.3. Create the connection profile to authenticate external students

Go to *Configuration → Policies and Access Control → Connection Profiles → New Connection Profile*.

Create a connection profile named **External Eduroam authentication** Check **Automatically register devices** then create a Realm filter **eduroam**. Make sure to add the previously created Eduroam source to match on the external users.

12.3.4. Create the connection profile to authenticate internal students

Go to *Configuration → Policies and Access Control → Connection Profiles → New Connection Profile*.


Create a connection profile named **Local Eduroam authentication** Check **Automatically register devices** then create a SSID filter **Eduroam**. Make sure to add the AD source to match on the local users.

WARNING

This connection profile need to be **after** **External Eduroam authentication** connection profile. Otherwise, it will also match request for external students and this is not what we want.

12.3.5. Inbound authentication (TLRS to PF)

Inbound eduroam authentication



1. Eduroam sends the RADIUS authentication to a public IP address (NAT/PAT) bound to PacketFence on the management IP address (Management VIP for a cluster) on port 1812.
2. PacketFence forwards the NTLM request to the Active Directory.
3. NTLM response [loweralpha]
 - a. Successful user identify authentication on the AD
 - b. NTLM request fails because of a bad identity
4. PacketFence replies to the Eduroam servers either a RADIUS Access Accept for a successful authentication or a RADIUS access reject for an unsuccessful authentication. PacketFence sets the REALM to Eduroam for all successful authentications.

First, you need to refer to the previous step [Configure the Eduroam source](#).

For this use case, there is no need to create a connection profile in PacketFence. FreeRADIUS will only perform a NTLM Auth and won't send RADIUS request to PacketFence API.

12.4. SAML Authentication

12.4.1. Common SAML configuration

PacketFence supports SAML authentication in the captive portal in combination with another internal source to define the level of authorization of the user.

First, transfer the Identity Provider metadata on the PacketFence server. In this example, it will be under the path [/usr/local/pf/conf/idp-metadata.xml](#).

Then, transfer the certificate and CA certificate of the Identity provider on the server. In this example, they will be under the paths `/usr/local/pf/conf/ssl/idp.crt` and `/usr/local/pf/conf/ssl/idp-ca.crt`. If it is a self-signed certificate, then you will be able to use it as the CA in the PacketFence configuration. Make sure `-----BEGIN CERTIFICATE-----` and `-----END CERTIFICATE-----` headers are present in these certificate files.

Then, to configure SAML in PacketFence, go in *Configuration* → *Policies and Access Control* → *Sources* and then create a new Internal source of the type SAML and configure it.

The screenshot shows the PacketFence web interface with the 'New Authentication Source' form for SAML. The form is titled 'New Authentication Source' with a 'SAML' tab. The left sidebar shows the navigation menu with 'Policies and Access Control' expanded. The form fields are as follows:

Field	Value
Name	mysaml
Description	Acme Inc.
Service Provider entity ID	PF_ENTITY_ID
Path to Service Provider key (x509)	/usr/local/pf/conf/ssl/server.key
Path to Service Provider cert (x509)	/usr/local/pf/conf/ssl/server.crt
Identity Provider entity ID	IDP_ENTITY_ID
Path to Identity Provider metadata	/usr/local/pf/conf/idp-metadata.xml
Path to Identity Provider cert (x509)	/usr/local/pf/conf/ssl/idp.crt
Path to Identity Provider CA cert (x509)	/usr/local/pf/conf/ssl/idp-ca.crt
Attribute of the username in the SAML response.	urn:oid:0.9.2342.19200300.100.1.1
Authorization source	inverse

At the bottom of the form, there are 'Create' and 'Reset' buttons. The 'Create' button is highlighted in blue.

Where :

- **Service Provider entity ID** is the identifier of the Service Provider (PacketFence). Make sure this matches the Identity Provider configuration.
- **Path to Service Provider key** is the path to the key that will be used by PacketFence to sign its messages to the Identity Provider. A default one is provided under the path : `/usr/local/pf/conf/ssl/server.key`
- **Path to Service Provider cert** is the path to the certificate associated to the key above. A self-signed one is provided under the path : `/usr/local/pf/conf/ssl/server.crt`
- **Path to Identity Provider metadata** is the path to the metadata file you transferred

above (should be in `/usr/local/pf/conf/idp-metadata.xml`)

- **Path to Identity Provider cert** is the path to the certificate of the identity provider you transferred on the server above (should be in `/usr/local/pf/conf/ssl/idp.crt`).
- **Path to Identity Provider CA cert** is the path to the CA certificate of the identity provider you transferred on the server above (should be in `/usr/local/pf/conf/ssl/idp-ca.crt`). If the certificate above is self-signed, put the same path as above in this field.
- **Attribute of the username in the SAML response** is the attribute that contains the username in the SAML assertion returned by the Identity Provider. The default should fit at least SimpleSAMLphp.
- **Authorization source** is the source that will be used to match the username against the rules defined in it. This allows to set the role and access duration of the user. The [Authentication](#) section of this document contains explanations on how to configure an LDAP source which can then be used here.

Once this is done, save the source and you will be able to download the Service Provider metadata for PacketFence using the link [Download Service Provider metadata](#) on the page.

Configure the identity provider according to the generated metadata to complete the Trust between PacketFence and the Identity Provider.

In the case of SimpleSAMLPHP, the following configuration was used in `metadata/saml20-sp-remote.php`:

```
$metadata['PF_ENTITY_ID'] = array(  
    'AssertionConsumerService' => 'http://PORTAL_HOSTNAME/saml/assertion',  
    'SingleLogoutService' => 'http://PORTAL_HOSTNAME/saml/looff',  
);
```

NOTE

PacketFence does not support logoff on the SAML Identity Provider. You can still define the URL in the metadata but it will not be used.

12.4.2. Entra ID SAML configuration

Microsoft Entra admin center

You need to make some configuration on the Microsoft Entra admin center in order to create the IDP.

First create a new Enterprise application:



Enterprise applications | All applications

Inverse



New application



Refresh

Overview



Overview



Agent ID (Preview) has been move

Create an application:

Browse Microsoft Entra App Gallery ...



Create your own application



Got feedback?

The Microsoft Entra App Gallery is a catalog of thousands of apps that make it easy to users more securely to their apps. Browse or create your own application here. If you

Define a name and create:

Create your own application



Got feedback?

If you are developing your own application, using Application Proxy, or want to integrate an application that is not in the gallery, you can create your own application here.

What's the name of your app?

PacketFenceSAML



What are you looking to do with your application?



Configure Application Proxy for secure remote access to an on-premises application



Register an application to integrate with Microsoft Entra ID (App you're developing)



Integrate any other application you don't find in the gallery (Non-gallery)

Once the application has been created click on Single sign-on

Home > Enterprise applications | All ap



PacketFenceSAML

Enterprise Application



Overview



Deployment Plan



Diagnose and solve problems

Manage



Properties



Owners



Roles and administrators




Users and groups



Single sign-on

Click on SAML:

Select a single sign-on method [Help me decide](#)



Then fill the information required in the section 1 (Note that the Identifier will need to match with what you will define in PacketFence):

On this page you have to download the Certificate (base64) and the Federation Metadata XML and copy the Azure AD Identifier.

Set up Single Sign-On with SAML

An SSO implementation based on federation protocols improves security, reliability, and end user experiences and is easier to implement. Choose SAML single sign-on whenever possible for existing applications that do not use OpenID Connect or OAuth. [Learn more.](#)

Read the [configuration guide](#) for help integrating PacketFenceSAML.

1

Basic SAML Configuration

Edit

Identifier (Entity ID)	https://radius.accessportal.page
Reply URL (Assertion Consumer Service URL)	https://radius.accessportal.page/saml/assertion
Sign on URL	https://radius.accessportal.page/
Relay State (Optional)	https://radius.accessportal.page/
Logout Url (Optional)	Optional

2

Attributes & Claims

Edit

givenname	user.givenname
surname	user.surname
emailaddress	user.mail
name	user.userprincipalname
Unique User Identifier	user.userprincipalname

3

SAML Certificates

Edit

Token signing certificate

Status	Active
Thumbprint	2683EC4C4FBCEA5A4330FDA5CA0358A83BF3C632
Expiration	1/26/2026, 3:07:58 PM
Notification Email	FabriceDurand@accessportal.onmicrosoft.com
App Federation Metadata Url	https://login.microsoftonline.com/fe329187-b36b...
Certificate (Base64)	Download
Certificate (Raw)	Download
Federation Metadata XML	Download

Verification certificates (optional) (Preview)

Edit

Required	No
Active	0
Expired	0

4

Set up PacketFenceSAML

You'll need to configure the application to link with Azure AD.

Login URL	https://login.microsoftonline.com/fe329187-b36b...
Azure AD Identifier	https://sts.windows.net/fe329187-b36b-4444-9e1f...
Logout URL	https://login.microsoftonline.com/fe329187-b36b...

Last thing to do is to define which users can use this application, to do that go in "Users and Groups" section do add users or groups.

... > Browse Microsoft Entra App Gallery > Enterprise applications | All applications



PacketFenceSAML | Users and groups

Enterprise Application

- Overview
- Deployment Plan
- Diagnose and solve problems
- Manage**
 - Properties
 - Owners
 - Roles and administrators
 - Users and groups**
 - Single sign-on

« + Add user/group Edit assignment

i The application will appear for assignment

Assign users and groups to app-roles for

m First 200 shown, search all users & groups

Display name

No application assignments found

Azure SAML Source

On the PacketFence side, create a new Authentication Source SAML:

Authentication Source Azure SAML

Name	Azure
Description	Azure
Service Provider entity ID	https://radius.accessportal.page
Service Provider key (x509)	 /usr/local/pf/conf/ssl/server.key
Service Provider cert (x509)	 /usr/local/pf/conf/ssl/server.crt
Identity Provider entity ID	https://sts.windows.net/fe329187-b36b-4444-9e1f-fcdddf5dc44/
Identity Provider metadata	 /usr/local/pf/conf/uploads/sources/Azure_idp_metadata_path_upload.crt
Identity Provider cert (x509)	 /usr/local/pf/conf/uploads/sources/Azure_idp_cert_path_upload.crt
Identity Provider CA cert (x509)	 /usr/local/pf/conf/uploads/sources/Azure_idp_ca_cert_path_upload.crt
If your Identity Provider uses a self-signed certificate, put the path to its certificate here instead.	
Username Attribute	http://schemas.xmlsoap.org/ws/2005/05/identity/claims/name
Main reference attribute that contain the username.	
Authorization source	AzureAD
The source to use for authorization (rule matching).	

Save
Clone
Reset
Cancel
Delete
View Service Provider Metadata

Where :

- **Service Provider entity ID** is the identifier of the Service Provider (PacketFence). In this example it's "https://radius.accessportal.page".
- **Path to Service Provider key** is the path to the key that will be used by PacketFence to sign its messages to the Identity Provider. A default one is provided under the path : </usr/local/pf/conf/ssl/server.key>
- **Path to Service Provider cert** is the path to the certificate associated to the key above. A self-signed one is provided under the path : </usr/local/pf/conf/ssl/server.crt>
- **Path to Identity Provider metadata** Upload the XML file you previously downloaded from Azure.
- **Path to Identity Provider cert** Upload the certificate you previously downloaded from Azure.
- **Path to Identity Provider CA cert** Upload the certificate you previously downloaded from Azure (the same as the section above).
- **Attribute of the username in the SAML response** is the attribute that contains the username in the SAML assertion returned by the Identity Provider. The one that can be used with Azure is this one <http://schemas.xmlsoap.org/ws/2005/05/identity/claims/name> who return the "Unique User Identifier" (Edit the section 2 of the Azure SAML configuration detail to see which attribute can be used).
- **Authorization source** is the source that will be used to match the username against the

rules defined in it. This allows to set the role and access duration of the user or also the access level of the admin interface (if you have configured the "Advanced Access Control For Admin Login"). The **Authentication** section of this document contains explanations on how to configure an Azure source which can then be used here.

12.4.3. Passthroughs

For users to access the Identity Provider login page, activate passthroughs and add the Identity Provider domain to the allowed passthroughs.

To do so, go in *Configuration* → *Network Configuration* → *Networks* → *Fencing*, then check **Passthroughs** and add the Identity Provider domain name to the **Passthroughs** list.

Next, restart **pf dns** services to apply the new passthroughs.

12.5. Billing Engine

PacketFence integrates the ability to use a payment gateway to bill users to gain access to the network. When configured, the user who wants to access the network / Internet is prompted by a page asking for it's personal information as well as it's credit card information.

PacketFence currently supports two payment gateways: Authorize.net, Paypal and Stripe.

To activate the billing, configure the following components :

- Billing source(s)
- Billing tier(s)

12.5.1. Configuring a billing source

First select a billing provider and follow the instructions below.

Paypal

NOTE

This provider requires that the PacketFence server is accessible on the public domain. For this the PacketFence portal should be available on a public IP using the DNS server name configured in PacketFence.

If having a business account and not wanting to configure a test environment, skip the next section.

Sandbox account

To configure a sandbox paypal account for use in PacketFence, head to <https://developer.paypal.com/> and either sign up or login into an existing account.

Then in the Sandbox menu, click **Accounts**

Create an account that has the type **Personal** and one that has the type **Business**.

Afterwards, go back into accounts, and expand the business account, then click **Profile**

SANDBOX

Accounts

Notifications

API Calls

IPN Simulator

Webhooks Events

MOCK

Webhooks Simulator

Credit Card Generator

Negative Testing

LIVE

- Create and manage more sandbox accounts as needed.

To link other accounts created in sandbox to your developer account, authenticate with the credentials of the [test account you want to link](#).

Developers outside of the US should read our [international developer questions](#).

See also: the [Sandbox Testing Guide](#).

Sandbox Accounts:

Create bulk accounts

Create account

Total Accounts: 2

☐	Account name	Type	Country	Date created	Manage accounts
☐	sb-llk2nz14067759@business.examl... (SBTEST)	Business	CA	21 Feb 2022	...
☐	sb-4y3a4714003823@personal.exam... (SBTEST)	Personal	CA	21 Feb 2022	...

Now, click the **Change password** link and change the password and note it.

Account details

ProfileAPI CredentialsFundingSettings

First name:

John

Last name:

Doe

Email ID:

sb-lk2nz14067759@business.example.com

System Generated Password:

6R{7+lw}

Password:

[Change password](#)

i

Note: If your system generated password is changed, your new password will not be displayed because of one-way password encryption.

Phone Number:

6135549121

Account type:

Business [Upgrade to Pro](#)

Account ID:

K79FYKWYF83QE

Status:

Verified

Do the same thing with the personal account you created

Configuring the merchant account

Login into the Paypal business account that you created at <https://www.sandbox.paypal.com/> if you are using a sandbox account or on <https://www.paypal.com/> if you are using a real account.

Next, go to *Account_Settings* on the top right below the user account.

Copyright © Akamai Technologies Canada 2014 Authentication Mechanisms

74

Encrypted website payments

Using encryption enhances the security of website payments by decreasing the possibility that a 3rd party could manipulate the data in your button code. If you plan on only using encrypted buttons you can block payments from non-encrypted ones. [Learn more](#)

Note: If you enable encrypted website payments, all of your buy now, donations, and subscriptions buttons must be encrypted via one of the following methods:

- Using the [PayPal payment button](#) with the security settings enabled.
- You encrypt all website payments before sending them to PayPal using your own code.

By enabling this feature, any buy now, donations, or subscription button that is not encrypted will be rejected by PayPal.

Block non-encrypted website payment

- ☒ On
- ☐ Off

PayPal account optional

When this feature is turned on, your customers will go through an optimized checkout experience. This feature is available for buy now, donations, and shopping cart buttons, but not for subscription buttons. [Learn more](#)

PayPal account optional

- ☒ On
- ☐ Off

Contact telephone number

When you activate this option, your customers will be asked to include a telephone number with their payment information. [Learn more](#)

Note: Selecting **On (required field)** could result in a customer not completing the transaction.

Contact telephone

- ☐ On (optional field)
- ☐ On (required field)
- ☒ Off (PayPal recommends this option)

Express Checkout settings

With this setting you determine if you technically support bank transfer in your Express Checkout implementation.

Support Giropay and bank transfer payments

- ☐ Yes
- ☒ No

Next go back in *Account_Settings* on the top right below the user account, select *Website Payment* → *Encrypted payment settings*

Now on this page submit the certificate used by PacketFence to Paypal (`/usr/local/pf/conf/ssl/server.crt` by default).

Once submitted, note it's associated **Cert ID** as it will need to be configured in PacketFence.

Still on that page, click the **Download** link to download the Paypal public certificate and put it

on the PacketFence server under path : `/usr/local/pf/conf/ssl/paypal.pem`

Website Payment Certificates [Back to My Profile](#)

Dynamically encrypt your Website Payments by downloading PayPal's public certificate and provide PayPal your public certificate. You will need to dynamically encrypt Website Payments with your own code to use this feature. [Learn more](#)

For added protection, you may also block payments that are made using non-encrypted buttons by setting this option on the [Website Payment Preferences](#) page.

You can create simple encrypted Website Payments without downloading keys by using the PayPal [Button Factory](#)

PayPal Public Certificate

PayPal requires that you use the PayPal Public Certificate with your code to encrypt buttons so that only PayPal can decipher the encrypted contents. Click the **Download** button below to download the PayPal Public Certificate.

[Download](#)

Your Public Certificates

PayPal will use your public certificate to decipher the encrypted content of your website buttons. You may add up to 6 different certificates.

Cert ID	Certifying Authority	Expiration Date
☒ Z7AQJV4PUXK8A	/C=GB/ST=Greater Manchester/L=Salford/O=Sectigo Limited/CN=Sectigo RSA Domain Validation Secure Server CA	20-Jun-2022 02:59:59 GMT-04:00

[Download](#) [Remove](#) [Add](#)

CAUTION The certificate will **NOT** be the same if you use a sandbox account or a real account.

Configuring PacketFence

Now, in the admin interface, go to *Configuration* → *Policies and Access Control* → *Authentication Sources* and create a new source of type *Billing* → *Paypal*.


Status Reports Auditing Nodes Users Configuration
API dashboard admin ? ✕ 13

Policies and Access Control
Roles
Domains
Active Directory Domains
Realms
Authentication Sources
Network Devices
Switches
Switch Groups
Connection Profiles

Compliance
Integration
Advanced Access Configuration
Network Configuration
System Configuration

New Authentication Source Paypal

Name

Paypal-test

Description

Paypal

Currency

CAD

Send billing confirmation

☐

Test mode

☒

Identity token

A-BCDE-FGHIJKLMNOP

Cert ID

RE2IIIIIIING

Cert file

/usr/local/pf/conf/ssl/server.crt

The path to the certificate you submitted to Paypal.

Key file

/usr/local/pf/conf/ssl/server.key

The path to the associated key of the certificate you submitted to Paypal.

Paypal cert file

/usr/local/pf/conf/ssl/paypal.pem

The path to the Paypal certificate you downloaded.

Email address

Christopher.test@test.com

The email address associated to your paypal account.

Payment type

Buy Now

Authorized domains

,paypal.com,.paypalobjects.com

Comma-separated list of domains that will be resolve with the correct IP addresses.

Create Local Account

☐

Create a local account on the PacketFence system based on the username provided.

Database passwords hashing method

NTLM

The algorithm used to hash the passwords in the database.This will only affect newly created or reset passwords.

Password length

8

The length of the password to generate.

Amount of logins for the local account

0

The amount of times, the local account can be used after its created. 0 means infinite.

Create

Reset

Where :

- **Identity token** is the one you noted when on the 'Website Payment Preferences' page.
- **Cert ID** is the one you noted when on the 'Encrypted Payment Settings'.
- **Payment type** is whether the access is donation based (not mandatory to pay for it).

- **Email address** is the email address of the merchant paypal account.
- **Cert file** is the path to the PacketFence certificate (`/usr/local/pf/conf/ssl/server.crt` by default).
- **Key file** is the path to the PacketFence certificate (`/usr/local/pf/conf/ssl/server.key` by default).
- **Paypal cert file** is the path to the Paypal certificate (`/usr/local/pf/conf/ssl/paypal.pem` in this example).
- **Currency** is the currency that will be used in the transactions.
- **Test mode** should be activated if you are using a sandbox account.

NOTE

If they aren't already enabled, enable passthroughs so that users can reach the domains of this provider. Refer to the [Passthroughs](#) section of this document for details

Stripe

Stripe account

First go on <https://dashboard.stripe.com>, create an account and login.

Next on the top right click [Account](#) then [Account settings](#).

Navigate to the [API keys](#) tab and note the key and secret. The test key should be used when testing the configuration and the live key when putting the source in production.

Home Payments Balances Customers Products Reports Connect More ▾

TEST DATA

Developers Test mode ☐

API keys [Learn more about API authentication →](#)

☒ Viewing test API keys. Toggle to view live keys. ☐ Viewing test data

Standard keys
These keys will allow you to authenticate API requests. [Learn more](#)

NAME	TOKEN	LAST USED	CREATED
Publishable key	pk_test_51Gq0pNIHkusDcikdXRxaHB4udcWvfnj5 HaXQeXSRBLWlkvgGCJ8wyfcf10akEH5CpVlvXefYe7 F51zbuBpJfq7s00m1pNUbn6	Oct 1, 2020	Jun 4, 2020
Secret key	Reveal test key	Oct 1, 2020	Jun 4, 2020

Configuring PacketFence

Now, in the admin interface, go to *Configuration → Policies and Access Control → Authentication Sources* and create a new source of type *Billing → Stripe*

The screenshot shows the PacketFence configuration interface. The top navigation bar includes 'Status', 'Reports', 'Auditing', 'Nodes', 'Users', and 'Configuration'. The left sidebar lists various configuration categories: Policies and Access Control, Roles, Domains, Active Directory Domains, Realms, Authentication Sources, Network Devices, Switches, Switch Groups, Connection Profiles, Compliance, Integration, Advanced Access Configuration, Network Configuration, and System Configuration. The main content area displays the 'New Authentication Source' form for Stripe. The form includes fields for Name (Stripe-test), Description (stripe), Currency (CAD), Send billing confirmation (toggle), Test mode (toggle), Secret key (YourSecretKey), Publishable key (YourPublishableKey), Style (Charge), Authorized domains (*.stripe.com), Create Local Account (toggle), Database passwords hashing method (NTLM), Password length (8), and Amount of logins for the local account (0). At the bottom of the form are 'Create' and 'Reset' buttons.

Where :

- **Secret key** is the secret key obtained from the Stripe account.
- **Publishable key** is the publishable key obtained from the Stripe account.
- **Style** is whether you are doing a one-time charge or subscription based billing (recurring). See section [Subscription based registration](#) below for details on how to configure it.
- **Currency** is the currency that will be used in the transactions.
- **Test mode** should be activated if you are using the test key and secret account.

NOTE

If they aren't already enabled, enable passthroughs so that users can reach the domains of this provider. Refer to the [Passthroughs](#) section of this document for details.

Stripe customer portal

PacketFence supports integrating with the Stripe customer portal and will handle subscription cancellations by default using webhooks. Additional hooks can be supported by extending `lib/pf/billing/custom_hook.pm`.

In order to enable the customer portal in Stripe, go in *Settings → Product settings → Billing → Customer portal*. Next, enable the options you want for the customer portal.

PacketFence supports the following options:

- Allow customers to view their invoice history
- Allow customers to update their billing information
- Allow customers to update their payment method
- Allow customers to cancel subscriptions

Optionally, once this is configured, ensure the captive portal is accessible publicly for Stripe to send it webhooks if subscription cancellations support is desired. Once its accessible publicly, configure a webhook to receive the event `customer.subscription.deleted` on https://PF_DOMAIN_NAME/hook/billing/STRIPE_SOURCE_ID. Replace `STRIPE_SOURCE_ID` by the identifier (name) of the Stripe source in the PacketFence configuration.

Next, in PacketFence, go in the Stripe source (*Configuration → Policies and Access Control → Authentication Sources*) and enable the option `Customer portal` in the Stripe source.

Now when users visit the status page (https://PF_DOMAIN_NAME/status), they will have the option to manage their subscriptions and visit the Stripe customer portal.

12.5.2. Adding billing tiers

Once you have configured one or more billing source, you need to define billing tiers which will define the price and target authentication rules for the user.

In the admin interface, go to *Configuration → Advanced Access Configuration → Billing tiers*

Then click `Add billing tier` and configure it.

The screenshot shows the PacketFence Configuration page with the 'New Billing Tier' form open. The form contains the following fields and values:

- Billing Tier:** Simple
- Name:** Simple access
- Description:** This tier will grant you basic access to the network for a duration of 24 hours.
- Price:** 1.99 (The price that will be charged to the customer.)
- Role:** guest (The target role of the devices that use this tier.)
- Access Duration:** 24 hours (The access duration of the devices that use this tier.)
- Use Time Balance:** ☐ (Check this box to have the access duration be a real time usage. This requires a working accounting configuration.)

At the bottom of the form are 'Create' and 'Reset' buttons.

Where :

- **Billing tier** is the unique identifier of the billing tier.
- **Name** is the friendly name of the billing tier.
- **Description** is an extended description of the billing tier.
- **Price** is the amount that will be charged to the user.
- **Access duration** is the amount of time the user will be granted access to the network.
- **Role** is the target role the user should be in.
- **Use time balance** defines if the access duration should be computed on real-time access duration meaning if the user buys 24 hours of access he can use the network for 24 hours in different time blocks. This requires a valid RADIUS accounting configuration.

NOTE If don't want to use all the billing tiers that are defined, you can specify the ones that should be active in the [Connection profile](#).

12.5.3. Subscription based registration

PacketFence supports subscription based billing using Stripe as a billing provider.

Stripe configuration

In the Stripe dashboard, go in *Products* → *Add product*.

Then create a new product.

Product information

Product details

Name ⓘ

base

Image ⓘ Optional

↑ Upload

Description ⓘ Optional

Base access

[Additional options](#) ▾

Price information

Pricing details

... ^

Pricing model ⓘ

Standard pricing

Price ⓘ

CA\$ 3.99

CAD

Recurring

One time

Billing period

Monthly

☐ Usage is metered ⓘ

[Additional options](#) ▾

+ Add another price

Where :

- **Price** is the price of the plan. It is **important** that this matches the price of the billing tier in PacketFence.
- **Currency** is the currency that will be used in the transactions. It is **important** that this matches the currency of the Stripe source in PacketFence.
- **Billing period** is the interval at which the customer should be billed. In the case of this example, it is monthly.

Save it and edit the product to see details information

The screenshot shows the 'Products' page in PacketFence. The left sidebar has 'Overview' selected. The main content area shows details for a product named 'base' with a price of '\$3.99 CAD / month'. Below this, there's a 'Details' section with fields for Name, Description, ID, Created, and Statement descriptor. The 'Pricing' section shows a table with columns for Price, API ID, Subscriptions, and Created. The 'Metadata' section shows 'No metadata'. The 'Logs' section shows two log entries. The 'Events' section shows one event.

PRICE	API ID	SUBSCRIPTIONS	CREATED
\$3.99 CAD / month	price_1KW0jVIHkusDci	0 active	Feb 22

Where :

- **API ID** is the billing tier identifier. It is **important** that this matches the ID of the billing tier in PacketFence.

Now, following the same procedure, create the advance plan.

Billing tier

When using subscription based billing, it is advised to configure the billing tier so it has an almost infinite access duration (e.g. 20 years) as the billing provider will be contacting the PacketFence server when the subscription is canceled.

You should configure a billing tier for each subscription plan you want to have. This example will use the plan **base** and **advance** configured using the following parameters. In this case price_1KW0jVIHkusDcikdVCGcvCii and price_1HFI6mIHkusDcikdZflh5Bcj are the **API ID** copied from the 2 products.

```
[price_1KW0jVIHkusDcikdVCGcvCii]
```

```

name=Base access
description=Click here if you are poor
price=3.99
role=guest
access_duration=10Y
use_time_balance=disabled

[price_1HF16mIHkusDcikdZfIh5Bcj]
name=Advanced network access
description=Click here if you are poor
price=9.99
role=advanced_guest
access_duration=10Y
use_time_balance=disabled

```

Receiving updates from Stripe


As the subscription can be cancelled by a user, the PacketFence installation needs to be set up to receive updates from Stripe.

Updates are sent using HTTP requests on a public IP.

Ensure that the PacketFence server is available through a public IP on port 80 and that the PacketFence server hostname resolves on the public domain.

Then, in Stripe, configure a **Webhook** so Stripe informs PacketFence of any event that happens in this Stripe merchant account.

In order to do so go in *Your Account* → *Developers* → *Webhooks* and click **Add an endpoint**.



Listen to Stripe events

Listen to Stripe events

Add an endpoint

Test in a local environment

Set up your webhook endpoint to receive live events from Stripe or [learn more about Webhooks](#).

Endpoint URL

http://YOUR_PORTAL_HOSTNAME/hook/billing/stripe

Description

An optional description of what this webhook endpoint is used for...

☐ Listen to events on Connected accounts ⓘ

Version

Your current version (2020-03-02) ↕

Select events to listen to

+ Select events

Add endpoint

Cancel

Where :

- **URL** is the URL to the PacketFence server. This should be http://YOUR_PORTAL_HOSTNAME/hook/billing/stripe
- **Select events to listen to** Select all the events

Now every time a user unsubscribes from a plan, PacketFence will be notified and will unregister that device from the network.

12.5.4. Extending access before it ends

PacketFence allows users to extend their access before it has ended. In order to do so, enable [Allow access to registration portal when registered](#) accessible via the [Captive Portal](#) tab of the [Connection Profiles](#). Once this is activated, the users can reach https://PORTAL_IP/status and select [Extend access](#) in order to be able to access the billing section after they have registered.

12.6. External API Authentication

PacketFence also supports calling an external HTTP API as an authentication source. The

external API needs to implement an authentication action and an authorization action.

12.6.1. Authentication

This should provide the information about whether or not the username/password combination is valid

These information are available through the POST fields of the request

The server should reply with two attributes in a JSON response

- **result** : should be 1 for success, 0 for failure
- **message** : should be the reason it succeeded or failed

Example JSON response :

```
{"result":1,"message":"Valid username and password"}
```

12.6.2. Authorization

This should provide the actions to apply on a user based on it's attributes

The following attributes are available for the reply : **access_duration**, **access_level**, **sponsor**, **unregdate**, **category**.

Sample JSON response, note that not all attributes are necessary, only send back what you need.

```
{"access_duration":"1D","access_level":"ALL","sponsor":1,"unregdate":"2030-01-01","category":"default"}
```

NOTE

See /usr/local/pf/addons/example_external_auth for an example implementation compatible with PacketFence.

12.6.3. PacketFence Configuration

In PacketFence, you need to configure an HTTP source in order to use an external API.

Here is a brief description of the fields :

- **Host** : First, the protocol, then the IP address or hostname of the API and lastly the port to connect to the API.
- **API username and password** : If the API implements HTTP basic authentication (RFC 2617) these can be added in these fields. Leaving any of those two fields empty will make PacketFence do the requests without any authentication.
- **Authentication URL** : URL relative to the host to call when doing the authentication of a user. Note that it is automatically prefixed by a slash.
- **Authorization URL** : URL relative to the host to call when doing the authorization of a user. Note that it is automatically prefixed by a slash.

12.7. External API Authentication

PacketFence also supports calling an external HTTP API as an authentication source. The external API needs to implement an authentication action and an authorization action.

12.7.1. Authentication

This should provide the information about whether or not the username/password combination is valid

These information are available through the POST fields of the request

The server should reply with two attributes in a JSON response

- **result** : should be 1 for success, 0 for failure
- **message** : should be the reason it succeeded or failed

Example JSON response :

```
{"result":1,"message":"Valid username and password"}
```

12.7.2. Authorization

This should provide the actions to apply on a user based on it's attributes

The following attributes are available for the reply : **access_duration**, **access_level**, **sponsor**, **unregdate**, **category**.

Sample JSON response, note that not all attributes are necessary, only send back what you need.

```
{"access_duration":"1D","access_level":"ALL","sponsor":1,"unregdate":"2030-01-01","category":"default"}
```

NOTE

See /usr/local/pf/addons/example_external_auth for an example implementation compatible with PacketFence.

12.7.3. PacketFence Configuration

In PacketFence, you need to configure an HTTP source in order to use an external API.

Here is a brief description of the fields :

- **Host** : First, the protocol, then the IP address or hostname of the API and lastly the port to connect to the API.
- **API username and password** : If the API implements HTTP basic authentication (RFC 2617) these can be added in these fields. Leaving any of those two fields empty will make PacketFence do the requests without any authentication.
- **Authentication URL** : URL relative to the host to call when doing the authentication of a

user. Note that it is automatically prefixed by a slash.

- **Authorization URL** : URL relative to the host to call when doing the authorization of a user. Note that it is automatically prefixed by a slash.

12.8. Azure AD integration

PacketFence supports integrating with the Azure Active Directory for authenticating users on the captive portal, the admin interface and for 802.1X users using EAP-TTLS PAP. If your only goal is to authenticate users on the captive portal, using the OpenID implementation of Azure AD may be better suited. This section is aimed at providing username/password authentication through Azure AD.

12.8.1. Creating the PacketFence app

1. Open the 'Microsoft Entra ID' in your Azure portal
2. Go in 'Manage→App registrations→New registration'
3. Settings for the app
 - a. Name: PacketFence
 - b. Supported account types: Single tenant only - xyz (Single tenant)
 - c. Redirect URI must be left blank
 - d. Save the app
4. Note down the 'Application (client) ID' and 'Directory (tenant) ID' for later usage
 - a. In your application, go in 'Certificates & secrets' and select 'New client secret'
 - i. Description: PacketFence
 - ii. Make sure you note down its expiry date so you can renew it before its expiration. Failure to do so will prevent authentication from working on PacketFence
 - iii. Save the secret
 - b. Note down the 'Value' of your client secret for later usage
 - c. Still in your application, go to 'API permissions'
 - i. Click on 'Add a permission'
 - A. Go to the 'Microsoft APIs' tab
 - B. Select 'Microsoft Graph'
 - C. Select 'Application permissions'
 - D. Add the permission **Directory.Read.All**
 - E. Click on 'Grant admin consent'
 - ii. Make sure **User.Read** is already there as a delegated permission

12.8.2. Disabling MFA

Currently, PacketFence requires that multi-factor authentication be disabled for the PacketFence app. If you use Azure AD premium, you can create a rule to exclude this only for the PacketFence application. If you don't use Azure AD premium, this must be disabled for all your users.

Disabling MFA using Azure AD premium

1. Open the "Microsoft Entra ID" in your Azure portal
2. Go in 'Manage→Properties'
 - a. Click 'Manage Security defaults'
 - b. Disable the toggle 'Enable Security defaults' and save
3. Next, go in 'Manage→Security→Conditional Access'
 - a. Click 'New policy' and enter the following settings:
 - i. Name: 2FA policy
 - ii. Under 'Users and groups', select 'All users'
 - iii. Under 'Cloud apps or actions', go in the 'Exclude' section and select the 'PacketFence' app you created earlier in the 'Select excluded cloud apps'
 - iv. Under 'Grant', select 'Grant access' and check 'Require multi-factor authentication' and any other settings your organization requires.
 - v. At the bottom, make sure 'Enable policy' is set to 'On' and save your policy

Disabling MFA without Azure AD premium

WARNING

This will disable common recommended settings from Microsoft. Using Azure AD premium is the correct way to perform this. This option is only suggested for testing or when its impossible to have access to Azure AD premium.

1. Open the "Microsoft Entra ID" in your Azure portal
2. Under 'Manage', open 'Properties'
 - a. Click 'Manage Security defaults'
 - b. Disable the toggle 'Enable Security defaults' and save

12.8.3. Configuring PacketFence

1. In the admin interface, go to *Configuration → Policies and Access Control → Authentication Sources*, and create a new 'Azure Active Directory' internal source
 - a. Client ID: the 'Client ID' that was displayed while configuring the 'PacketFence' app inside Azure
 - b. Client Secret: the secret you created inside the 'PacketFence' app in Azure AD
 - c. Tenant ID: the 'Tenant ID' that was displayed while configuring the 'PacketFence' app inside Azure
 - d. User Groups URL: the API Url where to verify the groupmembership
 - e. Add any authentication or administration rules and then save the source

With this configuration, you can now use this source in your connection profiles to authenticate and authorize users on the captive portal and use it with EAP-TLS to authorize users (getting the role and access duration) as long as your EAP-TLS certificates use the distinguished name of the Azure AD users as their common name. Additionally, you can use this source for authenticating users in the admin interface and for VPN access.

Using Azure AD in 802.1X

You can perform 802.1X authentication of users using Azure AD but this will only work with supplicants configured to perform EAP-TTLS PAP which provides the RADIUS server with the plain-text password of the user. Support for this type of authentication is not as broad as EAP-PEAP MSCHAPv2 in the 802.1X supplicants but unfortunately Azure AD doesn't support MSCHAP authentication. Refer to the documentation of your operating system on how to configure EAP-TTLS PAP. This section will only focus on enabling EAP-TTLS PAP for your Azure AD users in PacketFence.

1. In the admin interface, go to *Configuration → Policies and Access Control → Realms*, and create a new realm
 - a. Realm: enter the realm of your Azure AD users. Example, if the usernames have the following format `bob@inverseinc.onmicrosoft.com`, then your realm is `inverseinc.onmicrosoft.com`
 - b. Go in the 'Stripping' tab of the realm and select your Azure AD source under 'Azure AD Source for TTLS PAP'
 - c. Still in the 'Stripping' tab, disable (uncheck), the following settings:
 - i. Strip on the portal
 - ii. Strip on the admin
 - iii. Strip in RADIUS authorization
 - d. Save the realm
2. Restart radiusd using `/usr/local/pf/bin/pfcmd service radiusd restart`
3. All the users matching this realm will now authenticate against Azure AD. Make sure you also have a connection profile with auto-registration enabled and the Azure AD source in it so that your users are correctly authorized when connecting.

Using Azure AD EAP-TLS machine authentication

You can perform a EAP-TLS authentication and verify the machine group membership in order to provide a access to the network.

To do that first you will have to provide to the end device a certificate that contains the Device ID, to do this go in the Intune management interface and configure the template like this:

SCEP certificate

Windows 8.1 and later

1 Configuration settings 2 Review + save

Certificate type Device

Subject name format * ① CN={{AAD_Device_ID}}

Subject alternative name ①

Attribute	Value
⌵	Not configured

As you can see the CN (Common Name) will contain the Device Identifier, so when the device will connect on the secure SSID, the username will be equal to the device ID (like 8df07f7e-d98e-4579-aa97-bfcfaaa7fe38)

Now it's just a matter to retrieve the group membership associated with the device ID, in order to do that you will need to change the "User Groups URL" parameter in the "Azure Active Directory" authentication source.

The URL will be [https://graph.microsoft.com/v1.0/devices\(deviceId='%USERNAME'\)/memberOf](https://graph.microsoft.com/v1.0/devices(deviceId='%USERNAME')/memberOf) (for more information <https://learn.microsoft.com/en-us/graph/api/device-list-memberof?view=graph-rest-1.0&tabs=http>)

In this example the API call will be `https://graph.microsoft.com/v1.0//devices(deviceId='8df07f7e-d98e-4579-aa97-bfcfaaa7fe38')/memberOf?$select=id,displayName` and the reply will be:

```
{ "value": [ { "displayName": "ZaymLed-Devices", "id": "5c5f932c-08d4-46c3-bd93-11807f80ae35", "@odata.type": "#microsoft.graph.group" }, { "id": "6ae04238-8e95-4f1b-8088-17c0d6cfbd98", "displayName": "3D printer Laptop manager", "@odata.type": "#microsoft.graph.group" }, { "id": "c2e304d6-f245-4ab2-8f60-58d78e57c526", "displayName": "Windows 11 Feature Updates", "@odata.type": "#microsoft.graph.group", "id": "1bcd11e-0cae-4689-8afa-060ec0b3341f", "displayName": "ZaymLed - 3D software" }, ], "@odata.context": "https://graph.microsoft.com/v1.0/$metadata#directoryObjects(id,displayName)" }
```

From the "Azure Active Directory" authentication source, create an authentication rule like this:

Authentication Rules

3D_Laptop

Status ☒ Enabled

Name 3D_Laptop

Description

Matches All

Conditions	1	memberOf	equals	3D printer Laptop manager
Actions	1	Role	Machine	
	2	Access duration	5 days	

12.9. Google Workspace LDAP Integration

1. Go to <https://admin.google.com/> and sign in as a Google Workspace domain administrator.
1. Go to Apps > LDAP > Add Client.
2. Provide an LDAP client name and an optional Description. Any descriptive values are acceptable. For example, the name could be 'PacketFence' and the description could be 'PacketFence LDAP Client'. Click the Continue button.
1. Set Access Permission as needed. You must choose either 'Entire domain (PacketFence)' or 'Selected organizational units' for both 'Verify user credentials' and 'Read user information'. Select 'Add LDAP Client'
1. Download the generated certificate. This is required for PacketFence to communicate with the Google Secure LDAP service. Save the downloaded certificates for later use. After downloading, click the Continue to Client Details button.
1. Expand the Service Status section and turn the LDAP client 'ON for everyone'. After selecting 'Save', click on the 'Service Status' bar again to collapse and return to the rest of the settings.
1. Expand the Authentication section and choose 'Generate New Credentials'. Copy/note these credentials for later use. After selecting 'Close', click on the 'Authentication' bar again to collapse and return to the rest of the settings.

12.9.1. Configuring PacketFence

1. Under 'Configuration→Policies and Access Control→Authentication Sources', create a new 'Google Workspace LDAP' internal source
 - a. The following are the configuration values obtained during the LDAP client configuration earlier:
 - i. Bind DN: The access credentials username
 - ii. Password: The access credentials password
 - iii. Client Certificate: The .crt file text from the downloaded certificate bundle
 - iv. Client Key: The .key file text from the downloaded certificate bundle
 - b. You will also need to these properties for the Authentication Source:
 - i. Host: [ldap.google.com](https://admin.google.com/) / Port: 636 / Type: SSL
 - ii. SSL Verify Mode: None
 - iii. Base DN: (this is the ldap path for your domain.. usually something like this: [dc=example,dc=com](#) if your email is @example.com) You might have to add [ou=Users](#), as a prefix in some cases, so it would be [ou=Users,dc=example,dc=com](#)
 - iv. Scope: Subtree
 - v. Username Attribute: uid (unless you've heavily customized your Google Workspace directory)
 - vi. Email Attribute: mail
 - vii. Associated Realms: You'll need to match a previously created realm which

matches your `example.com` domain. This will let the system strip the domain part when searching for the user and also let the system know which source to use for which specific realms (the `@example.com` part of the username) are used for each source.

- c. For Authentication and Administration rules, you can match against google group membership (if you have configured google to allow group membership access - this is done when creating the LDAP client on the Google workspace configuration page on Google's side, not on PacketFence). In that case, you will want to use the condition `memberOf`, a match of `equals` and the value of `cn=mygroupname,ou=Groups,dc=example,dc=com` if your group is called "mygroupname". Keep in mind that nested group membership does not work via ldap for google workspace.

12.10. Advanced Access Control For Admin Login

PacketFence admin interface allows username/password login via any Internal authentication source (local database, LDAP, etc) by default.

For other admin interface authentication types (SAML, multi-factor auth, etc), leverage captive portal capabilities for administrator authentication.

12.10.1. Basic Configuration

In the admin interface, go to *Configuration* → *System Configuration* → *Admin Login* and enable 'SSO Status'. To enforce SSO policy for login (disable username/password), disable 'Allow username/password authentication'.

Configure 'SSO Base URL' if PacketFence captive portal uses different name than 'Hostname' and 'Domain' values in 'General Configuration'.

Configure connection profile for administrator authentication. In the admin interface, go to *Configuration* → *Policies and Access Control* → *Connection Profiles* and create new connection profile:

- Root Portal Module: 'Default admin SSO policy'
- Filter: URI with value '/admin-ssu'
- Sources: The authentication sources that should be used for the login.

Restart `api-frontend` and `httpd.portal`. Admin interface login page shows new 'Single Sign On' option (text changeable in 'Admin Login' configuration).

Any portal authentication mechanism (SAML, Akamai MFA, TOTP, etc) can authenticate administrators. Refer to appropriate sections in this guide to configure features on administrator authentication connection profile.

12.10.2. Advanced Configuration

Adjust captive portal policy configuration for administrator authentication as needed. Portal modules provide flexibility and customization. Modify 'Default admin SSO policy' in *Configuration* → *Advanced Access Configuration* → *Portal Modules* or create custom policy for administrator authentication connection profile. See [Portal Modules](#) section for captive portal customization.

13. Advanced Portal Configuration

13.1. Portal Modules

PacketFence captive portal flow is highly customizable. *Portal Modules* define captive portal behavior.

NOTE Upgrades from versions without portal modules include defaults that maintain previous behavior: authentication uses configured Connection Profile sources, then provisioners.

Available Portal Modules:

- **Root**: Container defining modules applied in chain to user. Device is released after completing all Root modules.
- **Choice**: Choice between multiple modules. See *default_registration_policy* example.
- **Chained**: Ordered modules for user completion. Example: Google+ registration then PayPal payment.
- **Authentication**: Multiple types available. Define modules to override required fields, source, template or other attributes.
 - **Billing**: One or more billing sources.
 - **Choice**: Multiple sources and modules with advanced filtering. See *Authentication Choice module* below.
 - **Login**: Username/password for multiple internal sources (Active Directory, LDAP, etc.).
- **Other**: Modules based on assigned source type, allowing source selection, AUP acceptance, and mandatory fields.
 - **Message**: Display message to user. Example in *Displaying a message to the user after registration*.
 - **SelectRole**: Override role during device registration. Admin users can choose device role during registration, bypassing authentication rules.
 - **URL**: Redirect to local or external URL that may return to portal. Example in *Calling an external website*.

13.1.1. Examples

Creating a custom root module

In *Configuration* → *Advanced Access Configuration* → *Portal Modules*, create a *New Root Module* that won't affect default policy. Name it *my_first_root_module* with description "My first root module", then click Save.

In *Configuration* → *Policies and Access Control* → *Connection Profiles*, select the

connection profile (likely `default`) and set *Root Portal Module* to `my_first_root_module`, then click Save.

NOTE

Captive portal will show error since *Root module* is empty. Add pre-configured modules to new *Root module* to suppress error.

Prompting for fields without authentication

To prompt fields to users without authentication, use the *Null source* with the *Null Portal Module*.

A pre-configured *Null source* is included. If it has not been modified or deleted it can be used for this example. Otherwise, in *Configuration* → *Policies and Access Control* → *Sources*, create a new *Null source* with a *catchall rule* that assigns a role and access duration.

In *Configuration* → *Advanced Access Configuration* → *Portal Modules*, click "New Module" and select "*Authentication* → *Authentication::Null*". Set the "*Identifier*" to `prompt_fields` and configure the Portal Module with the desired "*Mandatory fields*" and uncheck "*Require AUP*" so users do not have to accept the AUP before submitting the form.

In `my_first_root_module` add the `prompt_fields` module (remove all previous modules), then click Save. The portal will now prompt users for the fields defined in the module. Once submitted these fields are used to assign the role and access duration that is defined in the "*Null source*".

Prompting additional fields with authentication

To prompt additional fields to users during authentication, define a Module based on the source which specifies additional mandatory fields.

Additional mandatory fields can be added to the default pre-configured policies.

Example requiring users to enter a value for "first name", "last name" and "address" before registering:

In *Configuration → Advanced Access Configuration → Portal Modules*, choose *"Authentication::Choice → Guest Signup"* (`default_guest_policy`). Add `firstname`, `lastname` and `address` to *"Mandatory fields"*, then click Save.

In `my_first_root_module` add the `default_guest_policy` module (removing any previous modules). Any guest sources configured in connection profiles now require users to enter the mandatory fields of the source (ex: phone + mobile provider) **AND** the mandatory fields defined in the `default_guest_policy`.

NOTE | Not all sources support additional mandatory fields (ex: OAuth sources like Google, Facebook, ...).

Chained authentication

Two or more modules may be chained together in order to make users accomplish all of the actions of each module in the desired order.

Example requiring users to login using any configured OAuth source (Github, Google+, ...) and then validate their phone number with SMS registration:

Use the `default_oauth_policy` for OAuth login, and ensure an OAuth source is configured and available in Connection Profiles.

Create a Portal Module that will contain the SMS registration definition.

In *Configuration → Advanced Access Configuration → Portal Modules*, click *"New Module"* and select type *"Authentication → SMS"*. Set the *"Identifier"* to `prompt_sms` and configure the Portal Module with with `sms` Authentication Source, and uncheck *"Require AUP"* since users will already have accepted the AUP earlier when registering with OAuth.

[Status](#)
[Reports](#)
[Auditing](#)
[Nodes](#)
[Users](#)
[Configuration](#)

[API](#)
[dashboard](#)
admin
?
✕
1

Policies and Access Control
Compliance
Integration
Advanced Access Configuration
Captive Portal
Filter Engines
Billing Tiers
PKI Providers
Provisioners
Portal Modules
Access Duration
Self Service Portal
Network Configuration
System Configuration

New Portal Module Authentication::SMS

Name sms

Description SMS registration

The description that will be displayed to users

PID field telephone

Which field should be used as the PID.

Authentication Source sms

The source to use in the module. If no source is specified, all the sources of the connection profile will be used.

Mandatory fields

The additional fields that should be required for registration

Fields to save

These fields will be saved through the registration process

Require AUP

Require the user to accept the AUP

AUP template aup_text.html

The template to use for the Acceptable Use Policy

Signup template signin.html

The template to use for the signup

Add Action

If none are specified, the default ones of the module will be used.

Create

Reset

Add another "New Module" of type "Multiple → Chained", name it `chained_oauth_sms`, provide a relevant description, add `default_oauth_policy` and `prompt_sms` to the "Modules", then click Create.

The screenshot shows the configuration page for the 'chained_oauth_sms' portal module. The sidebar on the left contains a search filter and a list of configuration categories: Policies and Access Control, Compliance, Integration, Advanced Access Configuration (expanded), Captive Portal, Filter Engines, Billing Tiers, PKI Providers, Provisioners, Portal Modules, Access Duration, Self Service Portal, Network Configuration, and System Configuration. The main panel is titled 'Portal Module chained_oauth_sms' and includes a 'Chained' status indicator. It contains fields for Name (chained_oauth_sms), Description (Chained OAuth + SMS), and Actions (Add Action). Below these is a list of modules: 1. default_oauth_policy and 2. sms. At the bottom are buttons for Save, Reset, Clone, and Delete.

In `my_first_root_module` add the `chained_oauth_sms` module (removing any previous modules), then click Save. The portal will now prompt users for authentication using an OAuth source and then with SMS.

NOTE

Portal Module "Saved Fields" save and persist user responses. Adding `telephone` to the first module's "Saved Fields" will persist through all subsequent modules in the chain, and subsequent modules will not prompt users again for a field that is already saved.

Mixing login and Secure SSID on-boarding on the portal

Devices can access an open SSID with LDAP username/password, and then a Provisioner handles the remainder of the device on-boarding.

Configure the Provisioners for Secure SSID onboarding. Refer to the *Apple and Android Wireless Provisioning* section of this guide to configure the provisioners and add them to the Connection Profile.

Create a new provisioner with type Deny at the bottom of the list with the existing provisioners. This ensures the device is not allowed if no other provisioner is matched.

In the Connection Profile set the Sources to only the LDAP source, removing any other sources.

In *Configuration* → *Advanced Access Configuration* → *Portal Modules*, click "New Module" and select type "Other → Provisioning". Set the "Identifier" to `secure_boarding`, provide a relevant description, and uncheck "Skippable" so users are forced to board the SSID if this option is chosen.

In *Configuration* → *Advanced Access Configuration* → *Portal Modules*, click "New Module" and select type "Multiple → Choice". Set the "Identifier" to `login_or_boarding`, and provide a relevant description. Add `secure_boarding` and `default_login_policy` to the "Modules", then click Create.

The screenshot shows the 'New Portal Module' configuration window in the PacketFence interface. The window has a sidebar on the left with navigation links like 'Policies and Access Control', 'Compliance', 'Integration', 'Advanced Access Configuration', 'Captive Portal', 'Filter Engines', 'Billing Tiers', 'PKI Providers', 'Provisioners', 'Portal Modules', 'Access Duration', 'Self Service Portal', 'Network Configuration', and 'System Configuration'. The main area is titled 'New Portal Module' and contains the following fields:

- Name:** Login_or_boarding
- Description:** Login or Boarding (with a subtext: 'The description that will be displayed to users')
- Show first module when none is selected:** A toggle switch that is currently turned off.
- Template:** content-with-choice.html
- Actions:** An 'Add Action' button with a note: 'If none are specified, the default ones of the module will be used.'
- Modules:** A list of two modules:
 - 1 default_login_policy
 - 2 Secure_boarding

At the bottom of the window are 'Create' and 'Reset' buttons.

In `my_first_root_module` add the `login_or_boarding` module (removing any previous modules), then click Save. The portal will now prompt users with a choice to either login to the network directly with the LDAP source, or use provisioning to configure the device for a Secure SSID.

Display a message to the user after registration

A custom message can be displayed to users using the Message Portal Module.

In *Configuration* → *Advanced Access Configuration* → *Portal Modules*, click "New Module" and select type "Other → Message". Set the "Identifier" to `hello_world`, provide a relevant description.

Add the following text in the "Message" field, then click Create:

```
Hello World !
<a href="https://www.packetfence.com">Click here to access the PacketFence
website!</a>
```

The screenshot shows the 'Portal Module Hello_world' configuration window. The left sidebar contains a navigation menu with categories: Policies and Access Control, Compliance, Integration, Advanced Access Configuration, Network Configuration, and System Configuration. The main panel has the following fields:

- Name:** Hello_world
- Description:** Hello World (with a subtext: 'The description that will be displayed to users')
- Message:** Hello World !
Click here to access the PacketFence (with a subtext: 'The message that will be displayed to the user. Use with caution as the HTML contained in this field will NOT be escaped.'
- Template:** message.html
- Skippable:** A toggle switch is turned on (with a subtext: 'Whether or not, this message can be skipped')
- Actions:** An 'Add Action' button is present (with a subtext: 'If none are specified, the default ones of the module will be used.'

At the bottom of the window are four buttons: Save, Reset, Clone, and Delete.

In `my_first_root_module` add the `default_registration_policy` and `hello_world` modules (removing any previous modules), then click Save. The portal will now prompt users for authentication using the Sources defined in the Connection Profile, and once registered the Hello World Message is displayed.

The screenshot shows the 'New Portal Module Root' configuration window. The left sidebar is identical to the previous screenshot. The main panel has the following fields:

- Name:** My_first_root_module
- Description:** My first root module (with a subtext: 'The description that will be displayed to users')
- Modules:** A list of two modules:
 - default_registration_policy
 - Hello_world

At the bottom of the window are two buttons: Create and Reset.


Redirect to an external website

Users can be redirected to either a local or external URL (if included in passthroughs) using the "URL" Portal Module. In order for the Portal flow to continue the Module must accept a callback, otherwise users are redirected without the possibility to continue with the

registration process.

An example script redirecting users to an externally hosted PHP script that provides a random token and performs a callback to the portal in order to complete the registration process is located in `/usr/local/pf/addons/example_external_auth/token.php` including a README to help set it up.

Once the script is installed and working at the URL: http://YOUR_PORTAL_HOSTNAME:10000/token.php, in *Configuration* → *Advanced Access Configuration* → *Portal Modules*, click "New Module" and select type "Other → URL". Set the "Identifier" to `token_system`, provide a relevant description, and set the "URL" to http://YOUR_PORTAL_HOSTNAME:10000/token.php.



In `my_first_root_module` add the `token_system` module (removing any previous modules), then click Save. The portal will now prompt users for authentication using the Sources defined in the Connection Profile, and then users are redirected to the `token_system` URL. From there, once users continue they are redirected back to the Portal in order to complete the registration process.

13.1.2. Authentication Choice module (Advanced)

Provides users a choice between multiple sources using advanced filtering rules, manual selection of the Sources and selection of the Portal Modules.

NOTE The `default_guest_policy` and `default_oauth_policy` provide good examples.

All the defined "Sources" and "Modules" are available for use. Mandatory fields can be defined in the module, but they will only be shown if applicable to the Source.

Dynamically select a Source from the Connection Profile based on an object attribute (Object Class, Authentication Type, Authentication Class).

- **Source(s) by Class:** Specify the perl class name of the available source(s).

- ex: `pf::Authentication::Source::SMSSource` selects all the SMS source(s).
- ex: `pf::Authentication::Source::BillingSource` selects all the billing sources (Paypal, Stripe, ...).
- **Source(s) by Type:** Filter sources with the `type` attribute of the Authentication object.
- **Source(s) by Auth Class:** Filter sources with the `class` attribute of the Authentication object.

NOTE All authentication objects are found in `/usr/local/pf/lib/pf/Authentication/Source`.

13.1.3. SelectRole

Manually define specific roles when registering a device. This is useful for a technical crew to register new devices.

In *Configuration* → *Advanced Access Configuration* → *Portal Modules*, click "New Module" and select type "Other → Select Role". In "Admin Roles" chose the user role(s) that is required to use this module. In "Roles" choose the user role(s) that can then be assigned.

For example; technicians in the AD group technical support will have the role `technical support` while registering. In "Admin Roles" add `technical support`, then in "Roles" add `default`, `voice` and `guest`. Technicians that have the `technical support` role will be prompted to assign either the `default`, `voice` or `guest` role when registering a new device.

13.1.4. Actions on_failure and on_success

The `on_failure` and `on_success` "Actions" allow the creation of a more complex workflow and permit the root portal module change based on the result of authentication.

Consider that a root portal module is linked to an `Authentication::Login` module and associated with a Connection Profile. In order to present a Guest authentication if the login failed, configure a New Root Module called "Guest portal policy" with the "Module" set to `Authentication::SMS`, and in the previous "Authentication::Login" module add the "Action" `on_failure Guest portal policy`.

13.2. Portal Surveys

Surveys can be presented on the Captive Portal where results are stored in a dedicated database.

13.2.1. Database Setup

To automatically create the database tables required by the Survey, the MySQL `pf` user must be granted the CREATE and ALTER privileges. The MySQL `root` user must be used to GRANT these privileges.

Access the MYSQL CLI as the `root` user:

```
mysql -uroot -p
```

From the MySQL CLI grant the privileges:

```
GRANT CREATE,ALTER ON pf.* TO 'pf'@'%';  
GRANT CREATE,ALTER ON pf.* TO 'pf'@'localhost';  
FLUSH PRIVILEGES;
```

NOTE

The MySQL `root` password was only provided during Configuration and not stored on disk.

13.2.2. Configuring the survey

Configure the survey in `/usr/local/pf/conf/survey.conf`. Here is an example of a survey:

```
[survey1]  
description=Mustard Turkey Sandwich Brothers  
  
[survey1 field gender]  
label=What is your gender?  
type=Select  
choices=<<EOT  
M|Male  
F|Female  
EOT  
required=yes  
  
[survey1 field firstname]  
label=What is your firstname?  
type=Text  
required=yes  
  
[survey1 field lastname]  
label=What is your lastname?  
type=Text  
required=yes  
  
[survey1 field sandwich_quality]  
label=On a scale of 1 to 5, how good was your sandwich today?  
type=Scale  
minimum=1  
maximum=5  
required=yes  
  
[survey1 field preferred_sandwich]  
label=What is your preferred sandwich?  
type=Select  
choices= <<EOT  
Classic|Classic
```

```
Extra Turkey|Sandwich with extra turkey
Extra Mustard|Sandwich with extra mustard
EOT
required=yes
```

```
[survey1 field comments]
label=Enter any additional comments here
type=TextArea
required=no
```

```
[survey1 data ssid]
query=node.last_ssid
```

```
[survey1 data ip]
query=ip
```

NOTE

Once saved, reload the configuration to apply the changes with `/usr/local/pf/bin/pfcmd configreload hard`

The Captive Portal will now collect some data from the user (ex: `survey1 field firstname`) and some data contextually (ex: `survey1 data ssid`).

The available parameters to collect user data are defined as:

- **Label:** The input field label.
- **Table:** The database table to store the data. The ID of the survey will be used if this is empty. Database tables are prefixed with `survey_`.
- **Type:** The type of input field. The following types are available:
 - **Select:** A predefined list of choices.
 - **Text:** A single-line text input.
 - **TextArea:** A multi-line text input.
 - **Scale:** A numeric scale. The `minimum` and `maximum` attributes control the range of available numbers.
 - **Checkbox:** An on/off checkbox.
 - **Email:** A single-line text field with email validation (formatting only).
- **Required:** Whether the field is mandatory or optional.

The available parameters to use contextual data are defined as:

- `node.last_ssid`: The SSID the device is connected to (if applicable).
- `node.device_class`: The Fingerbank device class.
- `node.last_switch`: The switch/controller/access point the device is connected to.
- `person.source`: The source that was used (if authenticated).
- `person.email`: The email that was used (if authenticated).
- `ip`: The IP address of the device.

NOTE | See all available node fields by executing:

```
perl -I/usr/local/pf/lib -I/usr/local/pf/lib_perl/lib/perl5 -Mpf::node -
MData::Dumper -e 'print Dumper(node_view("00:11:22:33:44:55"))'
```

NOTE | See all available person fields by executing:

```
perl -I/usr/local/pf/lib -I/usr/local/pf/lib_perl/lib/perl5 -Mpf::person -
MData::Dumper -e 'print Dumper(person_view("admin"))'
```

13.2.3. Configuring the Captive Portal

In *Configuration* → *Advanced Access Configuration* → *Portal Modules*, click "New Module" and select type "Other → Survey". Use the following setting then click Create:

The screenshot shows the 'New Portal Module' configuration form. The form has a title bar with 'New Portal Module' and a 'Survey' tab. The main content area contains the following fields:

- Name:** survey1
- Description:** My first survey (with a subtext: 'The description that will be displayed to users')
- Survey:** survey1 (with a dropdown arrow and a subtext: 'The survey to use in this portal module. Surveys are defined in survey.conf')
- Template:** survey.html
- Actions:** Add Action (with a subtext: 'If none are specified, the default ones of the module will be used.')

At the bottom of the form, there are two buttons: 'Create' (in blue) and 'Reset' (in white).

Add the survey to an existing Portal Module (Choice, Chained or Root) or create a New Root Module dedicated for the survey:

In "Policies and Access Control → Connection Profiles → Name of the profile", ensure the correct "Root Portal Module" is selected.

13.2.4. Explore the collected data

The data collected from the example survey is stored in the `survey_survey1` database table. Create a *Report* for the survey in `/usr/local/pf/conf/report.conf` and add the following parameters:

```
[survey1]
description=My first survey report
base_table=survey_survey1
columns=firstname as "Firstname", lastname as "Lastname", preferred_sandwich as
"Preferred Sandwich", gender as "Gender"
```

NOTE | Once saved, reload the configuration to apply the changes with

```
/usr/local/pf/bin/pfcmd configreload hard
```

Refer to the [Reports](#) section of this document for advanced configuration.

13.2.5. Cleaning up

Once configured, optionally for security, it is recommended to revoke the `CREATE` and `ALTER` privileges from the `pf` user. The MySQL `root` user must be used to REVOKE these privileges.

Access the MYSQL CLI as the `root` user:

```
mysql -uroot -p
```

From the MySQL CLI revoke the privileges:

```
REVOKE CREATE,ALTER ON pf.* FROM 'pf'@'%';  
REVOKE CREATE,ALTER ON pf.* FROM 'pf'@'localhost';  
FLUSH PRIVILEGES;
```

NOTE

The MySQL **root** password was only provided during Configuration and not stored on disk.

13.3. Self Service - Device Registration

Once a user is registered they can self-register any device on the Portal by entering a MAC address that is matched with an authorized device list through Fingerbank. The device is registered to the user and can be assigned into a specific category.

NOTE

The user can access the portal within the network, or in any VLAN that can reach PacketFence on a *portal* interface (see below) at: https://YOUR_PORTAL_HOSTNAME/device-registration.

Device registration page is disabled by default. To enable it, configure a self service policy and assign it to a connection profile.

A self-service portal policy can be configured in *Configuration → Advanced Access Configuration → Self Service Portal*. Define the behavior by either modifying the default policy, or creating a new policy. If the "Role to assign" is left empty, the role of the user that is registering the device will be reused. Optionally select one or more "Allowed OS" to restrict which operating systems can be registered - as it may be useful to only allow gaming devices.

In *Configuration → Policies and Access Control → Connection Profiles*, assign the "Self service policy", then click Save.

WARNING

The **portal** listening daemon may need to be added to the management interface for the "self service portal" to be accessible.

13.4. Self Service - Status Page

Once a user is registered they can self-service and manage all their own devices on the Portal. Devices can be unregistered, reported as stolen (trigger a "LOST of Stolen" Security Event). Local users which are defined in the PacketFence database can manage their password.

NOTE

The user can access the portal within the network at https://YOUR_PORTAL_HOSTNAME/status.

By default all users can manage all their own devices through the self-service portal. In *Configuration → Advanced Access Configuration → Self Service Portal*, choose a *Self Service Portal*, specify the "Self Service Portal → Allowed roles", then click Save.

Status page is available by default, even if a self service policy is not configured. Optionally, it can be disabled in all but the PacketFence management network (registration, isolation, inline) by enabling **Status URI only on management interface** in *Configuration → Advanced Access Configuration → Captive Portal*.

In *Configuration → Policies and Access Control → Connection Profiles*, assign the "Self service policy", then click Save.

WARNING

The **portal** listening daemon may need to be added to the management interface for the "self service portal" to be accessible.

13.5. Passthroughs

Passthroughs allow access from users confined inside the registration network to specific resources on the outside. An example is to allow clients on the Captive Portal access to an external password reset server.

Passthroughs can be done with either *DNS resolution and iptables*, or with *Apache's mod_proxy module*, or both. A domain configured for both gives priority to DNS passthroughs.

In *Configuration → Network Configuration → Networks → Fencing*, enable "Passthrough", then click Save.

Then run the following commands so that passthroughs become effective:

```
/usr/local/pf/bin/pfcmd configreload hard
/usr/local/pf/bin/pfcmd service pfdns restart
```

13.5.1. DNS passthroughs

NOTE

In active-active cluster, **pfdns** must listen only on the VIP. In *Configuration → System Configuration → Cluster*, enable "pfdns on VIP only", then click Save.

In *Configuration → Network Configuration → Networks → Fencing → Passthroughs*, add passthroughs with the format:

- **example.com**: opens TCP ports 80 and 443 for example.com
- **example.com:1812**: opens TCP and UDP port 1812 for example.com
- **example.com:tcp:1812**: opens TCP port 1812 for example.com
- **example.com:udp:1812**: opens UDP port 1812 for example.com
- ***.example.com:tcp:443**: opens TCP port 443 all subdomains for example.com (ex: www.example.com, secure.example.com)
- **example.com,example.com:udp:1812,example.com:udp:1813**: opens TCP ports 80 and 443, UDP port 1812, UDP port 1813 for example.com

When **pfdns** receives a DNS request for a passthrough domain it will forward the unaltered DNS record for the FQDN instead of a response for the Captive Portal. An **ipset** entry will be added to permit the device to access the real external IP address for the FQDN via iptables routing.

13.5.2. Apache mod_proxy passthroughs

NOTE | `mod_proxy` does not support non-HTTP (including HTTPS) protocols.

In *Configuration* → *Network Configuration* → *Networks* → *Fencing*, add a comma-separated list of FQDNs in "Proxy Passthroughs", including wildcard domains like *.example.com. Only TCP port 80 is used, so do not specify ports. Click Save.

When `pfdns` receives a DNS request it will respond with the IP address of the Captive Portal, and when the device makes a HTTP request on the Captive Portal for a FQDN that has a configured passthrough the request is forwarded through `mod_proxy`.

13.6. Proxy Interception

Proxy requests can be intercepted and forwarded to the Captive Portal. This only works on Layer-2 networks where PacketFence is the default gateway.

In *Configuration* → *Network Configuration* → *Networks* → *Fencing*, enable "Proxy Interception". Add all the ports to intercept in "Proxy Interception Port", then click Save.

WARNING | For Apache to receive the proxy requests, manually add a new entry in `/etc/hosts` to resolve the FQDN of the Captive Portal to the IP address of the registration interface.

13.7. Parking Devices

Idle devices (ex: unregistered students) consume resources and generate unnecessary load on the Captive Portal and registration DHCP server.

In large registration networks Parking can be used to provide a longer lease and provide a lightweight Captive Portal that minimizes resource consumption. When a device is parked the Captive Portal provides a message to the user explaining the device is unregistered and has exceeded the parking threshold, and a button to **unpark** the device.

In *Configuration* → *Network Configuration* → *Networks* → *Device Parking*, set the "Parking Threshold" (seconds). A value of 21600 / 6 hours is suggested. If a device is idle in the registration network for more than 6 hours, Security Event 1300003 (see below) will be triggered and the device will be **parked**.

Optionally the lease length (seconds) can also be set in "Parking lease length". If the device is parked with a "Parking lease length" of 1 hour, then immediately unparked, the next detection will occur in 1 hour, even if the "Parking threshold" is a lower value.

NOTE | Parking is detected when a device requests DHCP and only works if PacketFence is the DHCP server for the registration network.

13.7.1. Security Event 1300003

In *Configuration* → *Compliance* → *Security Events*, choose Security Event 1300003, configure how the event is handled when a device is parked:

- In "Event Actions" add actions with the predefined ones (ex: `Email administrator` or `Execute script`).

- In *"Event Actions → Isolate → Role while isolated"* set the destination role (VLAN) of the user. Leave as **registration** unless a dedicated role is needed for parking.
- In *"Event Actions → Isolate → Template to use"* set the template used in the registration Portal, not the template used for parking. To use the non-parking portal disable *"Show parking portal"* in *Configuration → Network Configuration → Networks → Device Parking*.
- In *"Grace"* set the amount of grace time between two parking security events. Once a device is **unparked**, wait at least this amount of time for the user to register before re-triggering the Security Event.

14. Advanced Access Configuration

14.1. Connection Profiles

PacketFence provides a default connection profile. The follow parameters are important to configure whether the default connection profile is used or a new one is created:

Redirect URL under *Configuration → Policies and Access Control → Connection Profile → Profile Name*

For some browsers, it is preferable to redirect the user to a specific URL instead of the URL originally intended to visit. For these browsers, the URL defined in `redirecturl` will be where the user is redirected. Affected browsers are Firefox 3 and later.

IP under *Configuration → Advanced Access Configuration → Captive portal*.

This IP is used as the web server that hosts the `common/network-access-detection.gif` which is a pixel-gif used to detect network access. The IP cannot be a domain name since it is used during Registration and Isolation where DNS is black-holed. Allow users to reach the PacketFence server with the PacketFence LAN IP.

In some cases, a different captive portal may be presented (see below for the available customizations) according to the SSID, the VLAN, the switch IP/MAC or the URI the client connects to. To do so, PacketFence uses the concept of connection profiles to provide this possibility.

When configured, connection profiles will override default values. When no values are configured in the profile, PacketFence will use the values from the "default" connection profile.

Below the different configuration parameters for each connection profile are provided. The only mandatory parameter is "filter", otherwise, PacketFence will not be able to correctly apply the connection profile. The parameters are set in `/usr/local/pf/conf/profiles.conf`:

`/usr/local/pf/conf/profiles.conf`

```
[profilename1]
description = the description of the connection profile
filter = the name of the SSID or the VLAN to apply the profile
sources = a comma-separated list of authentications sources (IDs) to use
```

Connection profiles should be managed from the admin interface - from the *Configuration → Policies and Access Control → Connection Profiles* section. Adding a new connection profile will make a copy of the default templates - which can then be modified as desired.

Filters under *Configuration → Policies and Access Control → Connection Profile → Profile Name → Filters*

PacketFence offers the following filters:

```
Connection Type
Network
Node Role
Port
Realm
SSID
Switch
Switch Port
URI
VLAN
Time period
```

Example with common filters:

- **SSID:** Guest-SSID
- **VLAN:** 100
- **Time period:** wd {Mon Tue} hr {1pm-3pm} — See <https://metacpan.org/pod/release/PYAN/Period-1.20/Period.pm>
- **Switch Port:** <SwitchId>-<Port>
- **Network:** IP address or Network CIDR

CAUTION | Node role is only used with 802.1X connections and VLAN filters.

Advanced filter under *Configuration* → *Policies and Access Control* → *Connection Profile* → *Profile Name* → *Advanced Filter*

This section defines how to create an advanced filter to match specific attributes.

The following attributes are supported:

Using a previous connection (database, profiling):

```
autoreg
status
bypass_vlan
bandwidth_balance
regdate
bypass_role
device_class
device_type
device_version
device_score
pid
machine_account
category
mac
last_arp
```

```
last_dhcp
user_agent
computername
dhcp_fingerprint
detect_date
voip
notes
time_balance
sessionid
dhcp_vendor
unregdate
fingerbank_info.device_name
fingerbank_info.device_fq
fingerbank_info.device_hierarchy_names
fingerbank_info.device_hierarchy_ids
fingerbank_info.score
fingerbank_info.version
fingerbank_info.mobile
radius_request.User-Name
radius_request.NAS-IP-Address
radius_request.NAS-Port-Id
```

Using the current connection:

```
connection_sub_type
connection_type
switch
port
vlan
ssid
dot1x_username
realm
machine_account
```

Operators:

```
&& and
|| or
!= is not equal
== equal
() group precedence
```

Special values:

```
__NULL__ the value is NULL in the database
```

14.1.1. Examples

Match machine authentication on secure wireless ssid:

```
machine_account != "" && connection_type == Wireless-802.11-EAP
```

Match machine authentication from a previous connection and is connected on a secure ssid:

```
machine_account != "" && ssid == Secure
```

Match user authentication and machine authentication on a secure ssid:

```
last_connection_type == "Wireless-802.11-EAP" && machine_account != "" &&  
last_dot1x_username !~ "^host/"
```

Match user authentication without machine authentication on a secure ssid:

```
last_connection_type == "Wireless-802.11-EAP" && ( machine_account == "" ||  
machine_account == \_\_NULL__ ) && last_dot1x_username !~ "^host/"
```

Match without machine authentication (BYOD):

```
machine_account == \_\_NULL__
```

Example of attributes that can be filtered:

```
'radius_request' => {  
  'NAS-Port-Type' => 15,  
  'Service-Type' => 2,  
  'State' => '0x7cfd15627dba0f5a45baee16526652a6',  
  'Called-Station-Id' => '00:8e:73:5d:f6:9e',  
  'FreeRADIUS-Proxied-To' => '127.0.0.1',  
  'Realm' => 'null',  
  'EAP-Type' => 26,  
  'NAS-IP-Address' => '172.30.255.13',  
  'NAS-Port-Id' => 'GigabitEthernet1/0/30',  
  'SQL-User-Name' => 'gwten',  
  'Calling-Station-Id' => '00:11:22:33:44:55',  
  'PacketFence-Domain' => 'ZAYM',  
  'Cisco-AVPair' => 'service-type=Framed',  
  'User-Name' => 'zaym',  
  'Event-Timestamp' => 'Aug 15 2019 17:10:03 BST',
```

```

    'EAP-Message' => '0x024700061a03',
    'Framed-IP-Address' => '172.30.250.149',
    'NAS-Port' => 50130,
    'Stripped-User-Name' => 'gwten',
    'Framed-MTU' => 1500
  },
  'autoreg' => 'yes',
  'last_port' => '37',
  'device_class' => 'Windows OS',
  'bandwidth_balance' => undef,
  'bypass_role' => undef,
  'device_type' => 'Windows OS',
  'pid' => 'gwten',
  'dhcp6_enterprise' => '',
  'last_seen' => \[
    'NOW()'
  ],
  'dhcp6_fingerprint' => '',
  'category' => 'Wire',
  'mac' => '00:11:22:33:44:55',
  'portal' => 'Wire',
  'eap_type' => 26,
  'last_dhcp' => '0000-00-00 00:00:00',
  'user_agent' => 'ccmhttp',
  'computername' => 'zamtop',
  'dhcp_fingerprint' => '1,15,3,6,44,46,47,31,33,121,249,43',
  'detect_date' => '2019-08-15 15:33:30',
  'last_vlan' => '0',
  'last_connection_sub_type' => 26,
  'fingerbank_info' => {
    'device_fq' => 'Operating System/Windows OS',
    'device_name' => 'Windows OS',
    'version' => '',
    'score' => '73',
    'mobile' => 0,
    'device_hierarchy_names' => [
      'Windows OS',
      'Operating System'
    ],
    'device_hierarchy_ids' => [
      1,
      16879
    ]
  },
  'bypass_role_id' => undef,
  'last_role' => 'Wire',
  'dhcp_vendor' => 'MSFT 5.0',
  'unregdate' => '2019-08-15 20:10:04',

```

```

'last_switch' => '172.20.20.1',
'auto_registered' => 1,
'__from_table' => 1,
'source' => 'Wire',
'last_ifDesc' => 'GigabitEthernet1/0/30',
'device_version' => '',
'status' => 'reg',
'bypass_vlan' => undef,
'regdate' => '2019-08-15 17:10:04',
'last_dot1x_username' => 'zayme',
'tenant_id' => '1',
'category_id' => '166',
'machine_account' => '',
'last_connection_type' => 'Ethernet-EAP',
'last_ssid' => '',
'realm' => 'null',
'last_ip' => '172.20.20.2',
'device_score' => '73',
'last_arp' => '0000-00-00 00:00:00',
'last_start_timestamp' => '1565885356',
'stripped_user_name' => 'zayme',
'__old_data' => {
  'autoreg' => 'yes',
  'device_class' => 'Windows OS',
  'bandwidth_balance' => undef,
  'bypass_role' => undef,
  'device_type' => 'Windows OS',
  'pid' => 'gwten',
  'dhcp6_enterprise' => '',
  'last_seen' => '2019-08-15 16:09:16',
  'dhcp6_fingerprint' => '',
  'category' => 'Wire',
  'mac' => '00:11:22:33:44:55',
  'last_dhcp' => '0000-00-00 00:00:00',
  'user_agent' => 'ccmhttp',
  'dhcp_fingerprint' => '1,15,3,6,44,46,47,31,33,121,249,43',
  'computername' => 'zamtop',
  'detect_date' => '2019-08-15 15:33:30',
  'bypass_role_id' => undef,
  'dhcp_vendor' => 'MSFT 5.0',
  'unregdate' => '2019-08-15 20:09:16',
  'device_version' => '',
  'status' => 'reg',
  'bypass_vlan' => undef,
  'regdate' => '2019-08-15 17:09:16',
  'category_id' => '166',
  'tenant_id' => '1',
  'machine_account' => undef,

```

```

    'last_arp' => '0000-00-00 00:00:00',
    'device_score' => '73',
    'voip' => 'no',
    'device_manufacturer' => 'Toshiba',
    'notes' => 'AUTO-REGISTERED',
    'time_balance' => undef,
    'sessionid' => undef
  },
  'voip' => 'no',
  'device_manufacturer' => 'Toshiba',
  'notes' => 'AUTO-REGISTERED',
  'time_balance' => undef,
  'last_switch_mac' => '00:8e:73:5d:f6:9e',
  'sessionid' => undef,
  'last_start_time' => '2019-08-15 16:09:16'

```

PacketFence uses Apache for its captive portal, administration interface and Web services. The PacketFence Apache configuration is located in `/usr/local/pf/conf/httpd.conf.d/`.

In this directory the following important files are used for different purposes:

- `httpd.admin`: used to manage PacketFence admin interface
- `httpd.portal`: used to manage PacketFence captive portal interface
- `httpd.webservices`: used to manage PacketFence webservices interface
- `httpd.aaa`: used to manage incoming RADIUS requests

These files are dynamically generated with Perl and services are only activated on the network interfaces needed for each purpose.

The other files in this directory are managed by PacketFence using templates, so it is easy to modify these files based on the configuration. SSL is enabled by default to secure access.

During installation self-signed certificates will be created in `/usr/local/pf/conf/ssl/` (`server.key` and `server.crt`). The certificates can be replaced anytime by either a 3rd-party or existing wildcard certificate without issue. Please note that the CN (Common Name) needs to be the same as the one defined in the PacketFence configuration file `/usr/local/pf/conf/pf.conf`.

14.1.2. Reuse 802.1X credentials

In certain circumstances - for example to show an AUP after a successful 802.1X connection - "SSO emulation" may be used so that users do not need to re-enter their credentials on the portal after having entered them during 802.1X EAP. The connection profile option `Reuse 802.1X credentials` can be enabled for this purpose. The username used during the 802.1X connection will be reused with the different authentication sources to recompute the role from the portal.

As a security precaution, this option will only reuse 802.1X credentials if there is an authentication source matching the provided realm. This means, when users use 802.1X

credentials with a domain part (`username@domain`, `domain\username`), the domain part needs to be configured as a realm under the RADIUS section and an authentication source needs to be configured for that realm. When users do not use 802.1X credentials with a domain part, only the NULL realm will be matched IF an authentication source is configured for it.

14.2. Filter Engine Macros

Filter engines support the use of macros in the text field:

```
uc
lc
join
substr
macToEUI48
random_from_range
log
replace
BuildFromMatch
```

14.2.1. uc

Upper case string.

Example:

```
PacketFence-UserName = ${uc($radius_request.Calling-Station-Id)}
```

assigns the upper case value of Calling-Station-Id to PacketFence-UserName.

```
Calling-Station-Id = "00:10:7f:38:89:9d" ->
PacketFence-UserName = "00:10:7F:38:89:9D"
```

14.2.2. lc

Lower case string.

Example:

```
PacketFence-UserName = ${lc($radius_request.User-Name)}
```

assigns the lower case value of User-Nam to PacketFence-UserName.

```
User-Name = "ZAMMIT" -> PacketFence-UserName = "zammit"
```

14.2.3. join

Join strings.

Example:

```
PacketFence-UserName = ${join(":",$radius_request.User-Name,"Super")}
```

assign the joined string of the values and separator to PacketFence-UserName.

```
User-Name = "bobey" -> PacketFence-UserName = "bobey:Super"
```

14.2.4. substr

A part of a string.

Example:

```
PacketFence-UserName = ${substr($radius_request.User-Name,0, 5)}
```

assigns the first 6 characters of a string to PacketFence-UserName.

```
User-Name = "ZammitLudovic" -> PacketFence-UserName = "Zammit"
```

14.2.5. macToEUI48

EUI48 format of a MAC address.

Example:

```
PacketFence-UserName = ${macToEUI48($radius_request.Calling-Station-Id)}
```

assigns the EUI48 MAC address to PacketFence-UserName.

```
Calling-Station-Id = "00:10:7f:38:89:9d" ->  
PacketFence-UserName = "00-10-7F-38-89-9D"
```

14.2.6. random_from_range

A random integer between a range.

Example:

```
Session-Timeout = ${random_from_range("10620..12600")}
```

assigns a random integer between 10620 and 12600 to Session-Timeout.

```
Session-Timeout = 11343
```

14.2.7. log

Log a message in `packetfence.log`.

Example:

```
PacketFence-UserName = ${log($radius_request.User-Name." logged")}
```

logs the value of the RADIUS request attribute User-Name appended with " logged".

```
User-Name = "zammit" -> "Zammit logged"
```

14.2.8. replace

Replace a string or character.

Example:

```
PacketFence-UserName = ${replace($radius_request.User-Name,"z","r")}
```

replace the character "z" by the character "r" from User-Name and assign it to PacketFence-UserName.

```
User-Name = "zabbit" -> PacketFence-UserName = "rabbit"
```

14.2.9. BuildFromMatch

Regular expression match on a string or character.

Example:

```
TLS-Stripped-UserName =  
  ${BuildFromMatch($radius_request.TLS-Client-Cert-Common-Name,"  
  [^@]+","$0")}
```

extract the value from TLS-Client-Cert-Common-Name before the @ sign and assign it to

TLS-Stripped-UserName.

```
TLS-Client-Cert-Common-Name = "zammit@packetfence.org" ->
  TLS-Stripped-UserName = "zammit"
```

14.3. VLAN Filters

Filters can be defined directly in the portion of code that re-evaluates the VLAN or performs API calls when a RADIUS request is received. These filters can be defined in *Configuration* → *Advanced Access Configuration* → *Filter engines*.

These rules are available in different scopes:

```
IsolationRole
RegistrationRole
RegisteredRole
InlineRole
AutoRegister
NodeInfoForAutoReg
```

And can be defined using different criteria:

```
node_info.attribute (like node_info.status)
switch
ifIndex
mac
connection_type
username
ssid
time
owner.attribute (like owner.pid)
radius_request.attribute (like radius_request.Calling-Station-Id)
```

Default VLAN filters are defined in the configuration that can be used to achieve the following goals:

EXAMPLE_Reject_between_11am_2pm

prevent a registered device from connecting when its role is default, the SSID is SECURE, the current time is between 11am and 2pm, from Monday to Friday.

EXAMPLE_Trigger_event_if_user

create a security event if the SSID is OPEN and the owner is igmout (the security event needs to have a custom trigger with the value 12345).

EXAMPLE_Autoregister_if_user

autoregister the device and assign the role staff to each device if the username is igmout.

EXAMPLE_Autoregister_windows_devices

autoregister all Windows devices and assign them the default role.

EXAMPLE_Reject_specific_MAC

filter a MAC address and reject it by assigning the REJECT role.

EXAMPLE_Detect_VOIP

set Avaya and Polycom as phones by matching vendor MAC and set to default role.

EXAMPLE_Reject_User_Unless_Machine

refuse user authentication without prior machine authentication.

EXAMPLE_Autoregister_Printer_Scanner

autoregister printers and scanners and add a note.

Several examples on how to use and define filters are included in [/usr/local/pf/conf/vlan_filters.conf.defaults](#).

14.4. RADIUS Filters

Filters can be defined directly in the portion of code that returns RADIUS attributes or performs API calls when a RADIUS request is received. These filters can be defined in *Configuration → Advanced Access Configuration → Filter engines*.

We added the ability to specify filters directly in the portion of code that return RADIUS attributes or do a call to the API. These filters can be defined in *Configuration → Advanced Access Configuration → Filter engines*.

These rules are available in those scopes:

```
returnRadiusAccessAccept: return the answer for a device's access
returnAuthorizeRead: return the answer for the switch read login access
returnAuthorizeWrite: return the answer for the switch write login access
returnAuthorizeVoip: return the answer for a VoIP device
preProcess: manipulate the RADIUS context (example: add custom attributes
to the request)
```

```
packetfence.authorize: call the RADIUS filter in the packetfence authorize
section
packetfence.authenticate: call the RADIUS filter in the packetfence
authenticate section
packetfence.pre-proxy: call the RADIUS filter in the packetfence pre-proxy
section
packetfence.post-proxy: call the RADIUS filter in the packetfence
post-proxy section
packetfence-tunnel.authorize: call the RADIUS filter in the
packetfence-tunnel authorize section
packetfence.preacct: call the RADIUS filter in the packetfence preacct
section
```

```

packetfence.accounting: call the RADIUS filter in the packetfence
    accounting section
eduroam.authorize: call the RADIUS filter in the eduroam accounting section
eduroam.pre-proxy: call the RADIUS filter in the pre-proxy accounting
section
eduroam.post-proxy: call the RADIUS filter in the post-proxy accounting
    section
eduroam.preacct: call the RADIUS filter in the eduroam preacct section

```

All the `packetfence.` and `eduroam.` scopes are explained in `/usr/local/pf/conf/radius_filters.conf`.

And can be defined using different criteria like:

```

node_info.attribute (like node_info.$attribute)
switch
ifIndex
mac
connection_type
username
ssid
time
owner.attribute (like owner.$attribute)
radius_request.attribute (like radius_request.$attribute)
security_event
user_role
vlan

```

Default RADIUS filters are defined in the configuration that can be used to achieve the following goals:

EXAMPLE_Ethernet-EAP-Accept

returns Access-Accept (with Cisco-AVPair attribute) when the connection is Ethernet-EAP and no security event exists.

EXAMPLE_Session-timeout_Idle-Timeout_Terminate_action

filter on the switch IP addresses and add the Session-Timeout (with a value between 10620 and 12600), the Idle-Timeout and Terminate-Action RADIUS attributes.

EXAMPLE_ipad_by_name

use Fingerbank to target specific devices (Apple iPad) and add Cisco ACL(s) to them.

EXAMPLE_eap-tls-preProcess

create RADIUS attributes that will be used internally (like authentication rules). Add the TLS-Stripped-UserName RADIUS attribute in the request which can be used in the authentication/administrations rules.

Several examples on how to use and define filters are included in `/usr/local/pf/conf/radius_filters.conf.defaults`.

14.5. Advanced LDAP Authentication

14.5.1. LDAPfilter actions

LDAPfilter actions override the internal LDAP filter that PacketFence creates internally (uid=\$username) so a custom filter can be created that matches specific needs.

Example user search that checks permission based on some criteria:

```
(&(|(cn=${radius_request.Stripped-User-Name})(cn=${radius_request.User-Name}))( |(permitWifi=*)(grade=staff)(memberOf=CN=WifiGroup,OU=Security Groups,DC=ad,DC=zammitcorp,DC=com)))
```

14.5.2. Action set_role_on_not_found

`set_role_on_not_found` defines a role if the rule does not match.

Adding the action `set_role_on_not_found = REJECT` will reject the device if the LDAP filter match returns empty. On the other hand, if a filter match is found then the `set_role` action is applied.

14.5.3. Action role_from_source

`role_from_source` checks if the LDAP attribute exists, if so it is added in the `ldap_attribute` context (available in the RADIUS filters).

Example that takes the LDAP attribute `customRadius` value and adds it in the RADIUS answer. In the authentication rule add an action "Role from source" to `customRadius`. Next create a RADIUS filter that will add the custom RADIUS attributes:

```
[IF_SET_ROLE_FROM_SOURCE]
status=enabled
answer.0=reply:Packetfence-Raw = $ldap_attribute.customRadius
top_op=and
description=If the role has been computed from the action
    set_role_from_source then return the value of the role as a RADIUS
attribute
scopes=returnRadiusAccessAccept
radius_status=RLM_MODULE_OK
merge_answer=no
condition=action == "set_role_from_source"
```

NOTE

This supports multiple LDAP attributes, like `customRadius:Airespace-Interface-Name=internet` and `customRadius:Aruba-User-Vlan=666`.

14.5.4. Append search attributes LDAP filter

This option will add an AND condition (&) to the LDAP filter generated by PacketFence.

Example of an LDAP filter that is generated by PacketFence:

```
(&(|(sAMAccountName=%{User-Name})(sAMAccountName=%{Stripped-User-Name})(cn=%{User-Name})(cn=%{Stripped-User-Name})(sAMAccountName=%{%{Stripped-User-Name}}:-%{User-Name})))
```

If an LDAP filter is manually defined as:

```
(|(memberOf=CN=Staff,OU=Security Groups,DC=ad,DC=zammitcorp,DC=com)(wifi=enabled))
```

The filter will be combined and generated as:

```
(&(|(sAMAccountName=%{User-Name})(sAMAccountName=%{Stripped-User-Name})(cn=%{User-Name})(cn=%{Stripped-User-Name})(sAMAccountName=%{%{Stripped-User-Name}}:-%{User-Name})))|(memberOf=CN=Staff,OU=Security Groups,DC=ad,DC=zammitcorp,DC=com)(wifi=enabled))
```

If the "Search Attributes" feature is not required, this will still store the users` DN in the PacketFence-UserDN attribute.

14.5.5. basedn condition

This condition overrides the default **basedn** in the LDAP source and will test if an object is in a specific OU.

14.6. Advanced Realm Configuration

Multiple realms can be defined to select which domain is used to authenticate users.

A Realm is defined with a regex in order to match multiple formats.

For example in the ZAMMITCORP realm we define the regex like this:

```
.*\..zammitcorp.com\.com$
```

Thus in the case of username [mickey@le.zammitcorp.com](#), the realm is defined as *le.zammitcorp.com* - which is included in the RADIUS request - and the user is mapped with the *ZAMMITCORP* realm.

15. Advanced RADIUS Configuration

FreeRADIUS configuration steps. RADIUS server is required for network access in WPA2-Enterprise (Wireless 802.1X), MAC authentication and Wired 802.1X. RADIUS authenticates users and devices, then pushes roles or VLAN attributes to network equipment.

15.1. Local Authentication

Add user entries to `/usr/local/pf/raddb/users` file:

```
username Cleartext-Password := "password"
```

For RADIUS authentication issues, see [RADIUS Debugging](#) in the Troubleshooting section for debug commands and log analysis.

15.2. Authentication against Active Directory (AD)

For EAP-PEAP authentication with Microsoft Active Directory, refer to Active Directory documentation in Authentication Mechanism section.

15.3. EAP Authentication against OpenLDAP

For 802.1X authentication against OpenLDAP, define LDAP connection in `/usr/local/pf/raddb/modules/ldap` and ensure user password is NTHASH or clear text.

```
ldap openldap {
    server = "ldap.zammitcorp.com"
    identity = "uid=admin,dc=zammitcorp,dc=com"
    password = "password"
    basedn = "dc=district,dc=zammitcorp,dc=com"
    filter = "(uid=%{mschap:User-Name})"
    ldap_connections_number = 5
    timeout = 4
    timelimit = 3
    net_timeout = 1
    tls {
    }
    dictionary_mapping = ${confdir}/ldap.attrmap
    edir_account_policy_check = no

    keepalive {
```

```

# LDAP_OPT_X_KEEPALIVE_IDLE
idle = 60

# LDAP_OPT_X_KEEPALIVE_PROBES
probes = 3

# LDAP_OPT_X_KEEPALIVE_INTERVAL
interval = 3
}
}

```

Next in `/usr/local/pf/raddb/sites-available/packetfence-tunnel` add in the authorize section:

```

authorize {
    suffix
    ntdomain
    eap {
        ok = return
    }
    files
    openldap
}

```

15.4. EAP Guest Authentication on Email, Sponsor and SMS Registration

This section will allow local credentials created during guest registration to be used in 802.1X EAP-PEAP connections.

NOTE Be sure to select `plaintext` or `ntlm` as the "Database passwords hashing method" to make it work.

First create a guest SSID with the guest access you want to use (Email, Sponsor or SMS, ...) and activate `Create local account` on that source.

At the end of the guest registration, PacketFence will send an email with the credentials for Email and Sponsor and SMS.

NOTE This option doesn't currently work with the **Reuse dot1x credentials** option of the captive portal.

To enable this feature, in the admin interface go to *Configuration* → *System Configuration* → *RADIUS* → *General* and enable 'Authenticate against local users database'. Once saved, restart the radiusd service.

15.5. EAP Local User Authentication

The goal here is to use the local user to authenticate 802.1X device.

To enable this feature, in the admin interface go to *Configuration* → *System Configuration* → *RADIUS* → *General* and enable 'Authenticate against local users database'. Once saved, restart the radiusd service.

CAUTION

Take care of the "Database passwords hashing method" that has been configured in *Configuration* → *System Configuration* → *Main Configuration* → *Advanced* or in the authentication source configuration (when you enabled "create local account"), the hash method must be **plaintext** or **ntlm** to be able to work.

15.6. Limit Brute Force EAP Authentication

This section will allow you to limit a brute force attack and prevent the locking of Active Directory accounts.

Edit `/usr/local/pf/conf/radiusd/packetfence-tunnel`

```
# Uncomment the following lines to enable this feature
packetfence-control-ntlm-failure
packetfence-cache-ntlm-hit
```

By default it will reject for 5 minutes a device that has been rejected twice in the last 5 minutes. Feel free to change the default values in `raddb/policy.d/packetfence` and in `raddb/mods-enabled/cache_ntlm`

15.7. Testing

Test your setup with **radtest** using the following command and make sure you get an **Access-Accept** answer:

```
# radtest dd9999 Abcd1234 localhost:18120 12 testing123
Sending Access-Request of id 74 to 127.0.0.1 port 18120
  User-Name = "dd9999"
  User-Password = "Abcd1234"
  NAS-IP-Address = 255.255.255.255
  NAS-Port = 12
rad_recv: Access-Accept packet from host 127.0.0.1:18120, id=74, length=20
```

15.8. RADIUS Accounting

RADIUS Accounting is usually used by ISPs to bill clients. In PacketFence, we are able to use this information to determine if the node is still connected, how much time it has been connected, and how much bandwidth the user consumed.

PacketFence uses RADIUS Accounting to display Online/Offline status in webadmin in *Nodes* menu.

15.8.1. IP log updates

If you send the IP address of nodes in accounting data and want to update iplog entries of your nodes, you can enable **Update the iplog using the accounting** setting from *Configuration* → *System configuration* → *Main configuration* → *Advanced*.

15.8.2. Security Events

Using PacketFence, it is possible to add security events to limit bandwidth abuse. The format of the trigger is very simple:

```
Accounting::[DIRECTION][LIMIT][INTERVAL(optional)]
```

Let's explain each chunk properly:

- **DIRECTION**: You can either set a limit to inbound(IN), outbound(OUT), or total(TOT) bandwidth
- **LIMIT**: You can set a number of bytes(B), kilobytes(KB), megabytes(MB), gigabytes(GB), or petabytes(PB)
- **INTERVAL**: This is actually the time window we will look for potential abuse. You can set a number of days(D), weeks(W), months(M), or years(Y).

Example triggers

Look for Incoming (Download) traffic with a 50GB/month

```
Accounting::IN50GB1M
```

Look for Outgoing (Upload) traffic with a 500MB/day

```
Accounting::OUT500MB1D
```

Look for Total (Download + Upload) traffic with a 200GB limit in the last week

```
Accounting::TOT200GB1W
```

Grace Period

When using such security event feature, setting the grace period is really important. You don't want to put it too low (ie. A user re-enable his network, and get caught after 1 bytes is transmitted!) or too high. We recommend that you set the grace period to one interval window.

15.9. RADIUS Proxy

RADIUS Proxy is a way to proxy authentication and accounting requests to other radius server(s) based on the realm. Let's say you want to authenticate users on an Active Directory where there is a NPS server running and you don't want to join the PacketFence's server to this domain or in the case you want to integrate PacketFence in a Passpoint setup then this section is for you.

To do that in PacketFence you need first to define the target RADIUS server(s) in *Configuration → Policies and Access Control → Authentication Sources*, and create the RADIUS source(s) (ZAMMITCORP1 ZAMMITCORP2). In the Source configuration, fill the mandatory fields and add the options to define the home_server in FreeRADIUS. (<https://github.com/FreeRADIUS/freeradius-server/blob/v3.0.x/raddb/proxy.conf>)

Per example for the RADIUS Source ZAMMITCORP1:

The screenshot shows the 'New Authentication Source' configuration form in PacketFence. The form is titled 'New Authentication Source' with a 'RADIUS' tab selected. The left sidebar contains a navigation menu with categories like 'Policies and Access Control', 'Compliance', 'Integration', 'Advanced Access Configuration', 'Network Configuration', and 'System Configuration'. The main form fields include:

- Name:** ACME1
- Description:** Radius Server 1
- Host:** 192.168.0.20
- Port:** 1812 (with a note: 'If you use this source in the realm configuration the accounting port will be this port + 1.')
- Secret:** A masked field with a toggle to show/hide.
- Timeout:** 1
- Monitor:** A toggle switch (currently off) with the text 'Do you want to monitor this source?'
- Options:** A text area containing configuration options for FreeRADIUS:

```
type = auth+acct
response_window = 6
status_check = status-server
revive_interval = 120
check_interval = 30
num_answers_to_alive = 3
src_ipaddr = $src_ip
```

Below the text area is a note: 'Define options for FreeRADIUS home_server definition (if you use the source in the realm configuration). Need a radiusd restart.'
- Associated Realms:** A dropdown menu with the text 'Realms that will be associated with this source.'
- Authentication Rules:** An 'Add Rule' button.
- Administration Rules:** An 'Add Rule' button.
- Buttons:** 'Create' (blue) and 'Reset' (white) buttons at the bottom.

\$src_ip is a way to dynamically use the correct source ip address of the system in case of multiples network interfaces.

Next go in *Configuration → Policies and Access Control → REALMS*, and add a new realm.


[Status](#)
[Reports](#)
[Auditing](#)
[Nodes](#)
[Users](#)
[Configuration](#)
API
dashboard

Policies and Access Control
Roles
Domains
Active Directory Domains
Realms
Authentication Sources
Network Devices
Switches
Switch Groups
Connection Profiles

Compliance
Integration
Advanced Access Configuration
Network Configuration
System Configuration

New Realm

Realm
acme.com

NTLM Auth Configuration

Domain
The domain to use for the authentication in that realm.

Freeradius Proxy Configuration

Realm Options
strip
You can add FreeRADIUS options in the realm definition.

RADIUS AUTH
ACME1 x ACME2 x
The RADIUS Server(s) to proxy authentication.

Type
Keyed Balance
Home server pool type.

Authorize from PacketFence
Should we forward the request to PacketFence to have a dynamic answer or do we use the remote proxy server answered attributes?

RADIUS ACCT
ACME1 x ACME2 x
The RADIUS Server(s) to proxy accounting.

Type
Load Balance
Home server pool type.

Freeradius Eduroam Proxy Configuration

Eduroam Realm Options
You can add Eduroam FreeRADIUS options in the realm definition.

Eduroam RADIUS AUTH
The RADIUS Server(s) to proxy authentication.

Type
Keyed Balance
Home server pool type.

Authorize from PacketFence
Should we forward the request to PacketFence to have a dynamic answer or do we use the remote proxy server answered attributes?

Eduroam RADIUS ACCT
The RADIUS Server(s) to proxy accounting.

Type
Load Balance
Home server pool type.

Stripping Configuration

Strip on the portal
Should the usernames matching this realm be stripped when used on the captive portal.

Strip on the admin
Should the usernames matching this realm be stripped when used on the administration interface.

Strip in RADIUS authorization
Should the usernames matching this realm be stripped when used in the authorization phase of 802.1x. Note that this doesn't control the stripping in FreeRADIUS, use the options above for that.

Custom attributes
Allow to use custom attributes to authenticate 802.1x users (attributes are defined in the source).

LDAP source
The LDAP Server to query the custom attributes.

Create
Reset

(type definition can be found here <https://wiki.freeradius.org/features/Proxy>)

Authorize from PacketFence will send the request to PacketFence to compute the role and access duration of the device.

In this case the easiest way to achieve that is to create a Authorization source (with rules), assign this source to a connection profile where you enabled "Automatically register devices" and where you defined a filter like Realm = zammitcorp.com .

Click on **Save** and restart radiusd service.

```
/usr/local/pf/bin/pfcmd service radiusd restart
```

Now when a device connect with the username [bob@zammitcorp.com](#) then the authentication and accounting requests will be forwarded to one of the ZAMMITCORP RADIUS servers.

15.9.1. RADIUS Proxy Advanced

In this section we will explain how to proxy RADIUS requests based on an advanced criteria.

First you have to create RADIUS authentication source like above and create for example two realms "to_NPS" and "to_ISE" (associate the RADIUS sources in the REALMs)

Next you have to enable the RADIUS filters in the packetfence.authorize and packetfence.post-proxy scope, to do that you have to go in *Configuration* → *System Configuration* → *RADIUS* → *General* , and enable "Use RADIUS filters in packetfence authorize" and "Use RADIUS filters in packetfence post-proxy".

After this step restart the packetfence-radiusd-auth service (systemctl restart packetfence-radiusd-auth.service).

Here are some examples of what you can do with the RADIUS filters (the content of the radius_filters.conf file):

Proxy the RADIUS request to the to_NPS realm if the Calling-Station-Id or Colubris-AVPair attribute matches the regex ZAMMITCORP\$

```
[NPS]
scopes=packetfence.authorize
description=to_NPS
condition=radius_request.Called-Station-Id =~ "ZAMMITCORP$" ||
radius_request.Colubris-AVPair =~ "ZAMMITCORP$"
status=disabled
merge_answer=yes
answer.0=control:Proxy-To-REALM = to_NPS
```

Proxy the RADIUS request the to_ISE realm if the Calling-Station-Id or Colubris-AVPair attribute contains ZAMMITCORP_Admin\$ and add the attribute Realm with the value to_ISE in the RADIUS request (can be for example used as a filter in a connection profile)

```
[ISE]
merge_answer=yes
status=disabled
condition=contains(radius_request.Called-Station-Id, "ZAMMITCORP_Admin") ||
    contains(radius_request.Colubris-AVPair, "ZAMMITCORP_Admin")
scopes=packetfence.authorize,packetfence.post-proxy
description=to_ISE
answer.0=control:Proxy-To-Realm = to_ISE
answer.1=request:Realm = to_ISE
```

Proxy the RADIUS request to the NULL realm if the Calling-Station-Id or Colubris-AVPair attribute matches the regex Guest\$

```
[NULL]
scopes=packetfence.authorize
description=to_null
status=enabled
merge_answer=yes
condition=radius_request.Called-Station-Id =~ "Guest$" ||
    radius_request.Colubris-AVPair =~ "Guest$"
answer.0=control:Proxy-To-Realm = NULL
```

Proxy the RADIUS request to the to_ISE realm if the Calling-Station-Id attribute matches the regex ZAMMITCORP\$

```
[NO_REALM]
merge_answer=no
scopes=packetfence.authorize
status=enabled
condition=radius_request.Called-Station-Id =~ "ZAMMITCORP$" &&
    not_contains(radius_request.User-Name, "@") &&
    not_contains(radius_request.User-Name, "\\")
description=NO_REALM
answer.0=control:Proxy-To-Realm = to_ISE
```

Proxy the RADIUS request to the to_ISE realm if the device role is Employee and the status is registered

```
[Employee]
merge_answer=no
scopes=packetfence.authorize
status=enabled
condition=node_info.category == "Employee" && node_info.status == "reg"
description=Employee
```



```
answer.0=control:Proxy-To-Realm = to_ISE
```

CAUTION

Those examples can be added in `/usr/local/pf/conf/radius_filters.conf` and after, perform a

```
/usr/local/pf/bin/pfcmd configreload hard
```

15.10. RADIUS EAP Profiles

RADIUS EAP Profiles allow you to select a specific EAP profile in PacketFence based on the realm of the user.

In this EAP profile you can define:

- Certificates configuration.
- OCSP configuration
- EAP-Fast configuration
- TLS Configuration

And link all these configuration together.

For example the realm ZAMMITCORP.COM needs to use the CA certificate from ZAMMITCORP CA and the other realms need to use the default one.

To do that go in *Configuration → System Configuration → RADIUS → SSL Certificates* and create a new profile. Next go in *Configuration → System Configuration → RADIUS → TLS Profiles* and create a new TLS profile and select the Certificate profile created just before. Then create the EAP profile in *Configuration → System Configuration → RADIUS → EAP Profiles* and create a new EAP profile and select the TLS profile created before (PEAP Profile for exemple)

The last thing to do is to link the EAP profile with your realm configuration, to achieve that go in *Configuration → Policies and Access Control → Domains → REALMS* and edit the ZAMMITCORP.COM realm (create it if it's not already the case) then choose the EAP profile you created before in the EAP configuration parameter.

Restart `packetfence-radiusd-auth.service` to generate the new RADIUS configuration. (`systemctl restart packetfence-radiusd-auth.service`)

16. Fingerbank Integration

Fingerbank device profiling tool integrates with PacketFence, enabling administrators to trigger security events based on device types, device parents, DHCP fingerprints, DHCP vendor IDs, MAC vendors and browser user agents.

Core integration enables PacketFence to interact with Fingerbank upstream project for daily fingerprint database updates, sharing unknown data for complex algorithm processing, global database integration, and upstream database queries for unknown matches.

Fingerbank is PacketFence's primary device profiling tool, designed for simple configuration and use. Working PacketFence systems have Fingerbank ready in "local" mode (no upstream interaction).

16.1. Onboarding

Onboarding creates API key for upstream project interaction. Go to "Settings" under "Fingerbank" in PacketFence "Configuration" tab. Follow the process to create and save user/organization-specific API key. Once completed, full Fingerbank features are available.

16.2. Update Fingerbank Database

Updating Fingerbank data is simple. Requires onboarding for upstream interaction. "Update Fingerbank DB" option appears at top of "Fingerbank" menu sections. Process takes 1-2 minutes depending on database size and internet connectivity. Success or error message displayed afterward. "Local" records remain unmodified.

16.3. Submit Unknown Data

The "Submit Unknown/Unmatched Fingerprints" option (available after onboarding) submits unknown fingerprinting data from your network to the upstream Fingerbank project for analysis and global database integration.

16.4. Upstream Interrogation

By default, PacketFence interrogates the upstream Fingerbank project (after onboarding) to fulfill queries with unmatched local results. Unmatched local results may indicate older database version or requirement for complex algorithm processing. This behavior is transparent and configurable via "Settings" under "Fingerbank" in the PacketFence "Configuration" tab.

16.5. Local Entries

Administrators can customize or create records using "Local" entries. Upstream records

(DHCP Fingerprint, DHCP Vendor, MAC Vendor, User Agent, Device type, Combination) can be cloned and modified locally. Local records are matched first to override existing ones. Local combinations can match "Local", "Upstream", or both entries for device identification.

16.6. Settings

Fingerbank settings are accessible via "Settings" under "Fingerbank" in the PacketFence "Configuration" tab. Each parameter includes documentation for easier understanding.

16.7. Device change detection

Fingerbank detects potential MAC spoofing when devices change device class (e.g., Windows to printer), triggering security events and potentially isolating endpoints. Example security event ID 1300006 ("Fingerbank device class change") demonstrates this trigger.

This feature is disabled by default. Configure it in *Configuration* → *Compliance* → *Fingerbank Profiling* → *Device Change Detection*.

Check **Enabled** to activate this feature. Choose between triggering security events on any device class change or specific changes.

16.7.1. Triggering on any device class change

NOTE	Perform non-enforcing actions initially to identify corner cases requiring device class transition whitelisting.
-------------	--

The easiest detection method triggers on any device class change, firing security events when devices transition between classes. Since some transitions may be normal, add whitelisting via "Device class change whitelist" parameter (e.g., "Windows OS" to "Mac OS X or macOS").

16.7.2. Manual triggers

Instead of detecting all transitions, trigger security events on specific device class transitions. Declare transitions in "Manual device class change triggers".

If device profiling isn't working, check fingerbank logs as described in [Log Files](#) in the Troubleshooting section.

17. Network Devices Anomaly Detection

Starting with version 10, PacketFence integrates network devices anomaly detection capabilities. This means that PacketFence can detect abnormal network activities from devices - that is, if they are talking to a compromised host, if they are deviating from their pristine network profile and more. These capabilities come from the integration of the Fingerbank technology. That is, the Fingerbank Cloud API is responsible for producing pristine network device profiles while the Fingerbank Collector, included in PacketFence, does consume the pristine profiles and does anomaly detection based on its templating engine.

17.1. Creating Network Behavior Policies

A network behavior policy is a template, used by the Fingerbank Collector, to determine if the devices matching the criteria defined in the template ultimately deviate from a normal network usage pattern. You can create new templates from *Configuration* → *Compliance* → *Network Anomaly Detection*.

Network behavior policies can be consumed from PacketFence's Security Events module.

17.2. Integration with Security Events

After creating a network behavior policy, you can use it from the Security Events module of PacketFence. From *Configuration* → *Compliance* → *Security Events*, click on **New Security Event**.

You can use your policy by first adding a new trigger. The network behavior policy can be selected after defining an internal event on the following attributes:

- **fingerbank_blacklisted_ips_threshold_too_high** - Fingerbank Collector detected traffic to blacklisted IPs
- **fingerbank_blacklisted_ports** - Fingerbank Collector detected traffic to blacklisted ports
- **fingerbank_diff_score_too_low** - Fingerbank Collector detected a network behavior that doesn't match the known profile

Once done, the appropriate policy can be selected. If you want your entire network policy to be checked in the Security Events module, you must create three triggers - one with each of the attribute listed above together with your appropriate policy selected. You can look at the default security events Fingerbank profile anomaly (1300007) and Fingerbank detected blacklisted communication (1300008) for some examples on how to create customized security events to fulfill your requirements.

18. Intrusion Detection System Integration

18.1. Regex Syslog Parser

You are now able to create syslog parser using regex. This will allow you complex filters and rules to work on data receive via syslog.

Configuring a Regex Syslog Parser

- Enabled - You can enable/disable the parser from running
- Alert Pipe - A previously created alert pipe (FIFO)
- Rules - The list of rules that defines how to match log file entries and what action(s) to take when matching

Regex Syslog Parser Rule

- Name - The name of the rule
- Regex - The regex to match against a log entry. The regex may have [named captures](#) which can be used for parameter replacement start a '\$'.
- Actions - A list of actions to take when the regex matches
- IP to MAC - Perform automatic translation of IPs to MACs and the other way around
- Last if matches - Stop processing the other rules if this rule matched

Defining Actions

An action have two parts

- method - The name of the action you want to take
- parameter list - The list of parameters you want to provide to the method. Each parameter is separated by a comma. The parameters that are to be replaced by a named capture.

Example Action

Regex -

```
mac\s*:\s*(?P<mac>[a-zA-Z0-9]{2}(:[a-zA-Z0-9]{2}){5}),
notes\s*:\s*(P?<notes>.*)
```

Action -

```
modify_node: mac, $mac, notes, $notes
```

18.2. FortiGate DHCP Parser

PacketFence is able to receive DHCP information from the FortiGate firewall.

On the PacketFence server:

Modify rsyslog configuration to allow incoming UDP packets by uncommenting the following two lines in `/etc/rsyslog.conf`:

```
$ModLoad imudp
$UDPServerRun 514
```

Configure `/etc/rsyslog.d/fortigate.conf` so it contains the following which will redirect fortigate log entries and stop further processing of current matched message (in that case 192.168.40.1 is the ip of the FortiGate):

```
if $fromhost-ip=='192.168.40.1' then /usr/local/pf/var/fortigate
& ~
```

Make sure the receiving alert pipe (FIFO) exists

```
mkfifo /usr/local/pf/var/fortigate
```

Restart the rsyslog daemon

```
service rsyslog restart
```

On the FortiGate side make sure to configure the syslog configuration as the following:

Dashboard >

Security Fabric >

FortiView >

Network >

System 1 >

Policy & Objects >

Security Profiles >

VPN >

User & Device >

Log & Report >

Forward Traffic

Local Traffic

Sniffer Traffic

Events

SSL

DNS Query

Application Control

Anomaly

VoIP

FortiGate Cloud Reports

Log Settings ☆

Email Alert Settings

Monitor >

Log Settings

Local Log

Memory

Remote Logging and Archiving

Send logs to FortiAnalyzer/FortiManager

Send logs to syslog

IP Address/FQDN

Cloud Logging

UUIDs in Traffic Log ⓘ

Policy

Address

Log Settings

Event Logging All Customize

☒ System activity event

☐ VPN activity event

☐ User activity event

☐ Router activity event

☐ WiFi activity event

☐ Explicit web proxy event

☐ Endpoint event

☐ HA event

☐ Security Rating event

☐ FortiExtender event

☐ SDN connector Event

Local Traffic Log All Customize

☐ Log Allowed Traffic

☐ Log Denied Unicast Traffic

☐ Log Local Out Traffic

☐ Log Denied Broadcast Traffic

GUI Preferences

Resolve Hostnames ⓘ

Resolve Unknown Applications ⓘ

18.3. Suricata IDS

PacketFence already contains a event handler for Suricata. This is an example to raise a security event from a syslog alert on the Suricata SID.

The first step is to create the syslog regex parser and then create the security event.

18.3.1. Syslog regex parser configuration

To create the syslog regex parser you will need to go to *Configuration → Integration → Event Handlers → Add a Event Handler → regex*

Here is the configuration of the syslog regex parser:

```
Detector *: Suricata
Enabled: checked
Alert pipe: /usr/local/pf/var/suricata (To create the fifo file, do: mkfifo
/usr/local/pf/var/suricata)
```

Rules:

Rule - New:

```
Name *: ET P2P Kaaza Media desktop p2pnetworking.exe
Regex *: (?P<date>\d{2}\/\d{2}\/\d{4}-\d{2}:\d{2}:\d{2}.*) \[.*\]
\[\d+:(?P<sid>\d+):\d+\] (?P<message>.*) \[.*\].*
(?P<srcip>\d{1,3}(\.\d{1,3}){3}):(?P<srcport>\d+) ->
(?P<ip>\d{1,3}(\.\d{1,3}){3}):(?P<port>\d+)
Action: trigger_security_event mac, $mac, tid, $sid, type, detect
Last if match: unchecked
IP to MAC: checked
```

Save the regex rule.

You can directly test your rule. In the previous example the parser expect a syslog string like this:

```
02/26/2017-14:29:00.524309 [**] [1:2000340:10] ET P2P Kaaza Media desktop
p2pnetworking.exe Activity [**] [Classification: Potential Corporate Privacy
Violation] [Priority: 1] {UDP} 173.194.7.75:443 -> 1.2.3.4:46742
```

In order to have a correct match in the rule, you will need to have a valid iplog entry in the database. Put the string in the test box and then click on the **RUN TEST** button, you should get:


```
Click to see actions for - 02/26/2017-14:29:00.524309 [**] [1:2000340:10] ET
P2P Kaaza Media desktop p2pnetworking.exe Activity [**] [Classification:
Potential Corporate Privacy Violation] [Priority: 1] {UDP} 173.194.7.75:443
-> 1.2.3.4:46742
```

- ET P2P Kaaza Media desktop p2pnetworking.exe : trigger_security_event('mac', '00:11:22:33:44:55', 'tid', '2000340', 'type', 'detect')

We can see that PacketFence will execute the security event on the MAC address 00:11:22:33:44:55.

18.3.2. Security Event Creation

Now you will need to create the security event with the trigger id '2000340' in order to isolate the device. In order to do so, go to *Configuration* → *Compliance* → *Security Events* → *New Security Event*

Definition:

```
Enabled: ON
Identifier: 1500001
Description: ET P2P Kaaza Media
Action: Reevaluate Access Action; Log message
Priority: 1
```

Triggers:

- Click on the (+) button
- Look for 'detect' in the dropdown list
- Add the trigger ID: 2000340 and click the ADD button
- Click on the < button next to 'Select Some Options'

Remediation:

```
Auto Enable: checked
Max Enables: 2
Grace: 5 minutes
Template: p2p.html
```

Click on the SAVE button.

Now you will need to restart the pfqueue and the pfdetect services.

```
/usr/local/pf/bin/pfcmd service pfqueue restart
```

```
/usr/local/pf/bin/pfcmd service pfdetect restart
```

Make sure that you have your pipe file otherwise the process won't start.

18.4. Security Onion

18.4.1. Installation and Configuration

Security Onion is a Ubuntu-based security suite. The latest installation instructions are available directly from the Security Onion website, <https://github.com/Security-Onion-Solutions/security-onion/wiki/Installation>

Since a security suite consists of multiple pieces of software tied together, you may be prompted for different options during the installation process. A detailed "Production Deployment" guide can also be found directly from the Security Onion website: <https://github.com/Security-Onion-Solutions/security-onion/wiki/ProductionDeployment>

18.4.2. PacketFence Integration

Once Security Onion is installed and minimally configured, integration with PacketFence is required to be able to raise security events based on sensor(s) alerts. syslog is used to forward sensor(s) alerts from Security Onion to the PacketFence detection mechanisms.

The simplest way is as follow (based on <https://github.com/Security-Onion-Solutions/security-onion/wiki/ThirdPartyIntegration>);

On the Security Onion server:

NOTE | Must be done on the master server running 'sguild'.

Configure `/etc/syslog-ng/syslog-ng.conf` by adding the following to enable sending sguild log entries to PacketFence:

```
### PacketFence / IDS integration
# This line specifies where the sguild.log file is located
# -> Make sure to configure the right path along with the right filename (on a
Security Onion setup, that should be pretty much standard)
source s_sguild { file("/var/log/nsm/securityonion/sguild.log"
program_override("securityonion_ids")); };
# This line filters on the string "Archived Alert"
filter f_sguild { match("Archived Alert"); };
# This line tells syslog-ng to send the data read to the PacketFence
management IP address using UDP 514
# -> Make sure to configure the right PacketFence management interface IP
address
destination d_packetfence_alerts { udp("PACKETFENCE_MGMT_IP" port(514)); };
# This line indicates syslog-ng to use the s_sguild source, apply the f_sguild
filter and send it to the d_packetfence_alerts destination
```

```
log { source(s_sguild); filter(f_sguild); destination(d_packetfence_alerts); };
```

NOTE

Ensure you change PACKETFENCE_MGMT_IP to the management IP address of your PacketFence server

Sending sguild alert output to syslog requires DEBUG to be changed from 1 to 2 under [/etc/sguild/sguild.conf](#)

```
set DEBUG 2
```

A restart of the sguild daemon is then required

```
sudo nsm_server_ps-restart
```

A restart of the syslog-ng daemon is then required

```
service syslog-ng restart
```

On the PacketFence server:

Modify rsyslog configuration to allow incoming UDP packets by uncommenting the following two lines in [/etc/rsyslog.conf](#):

```
$ModLoad imudp
$UDPServerRun 514
```

Configure [/etc/rsyslog.d/securityonion_ids.conf](#) so it contains the following which will redirect Security Onion sguild log entries and stop further processing of current matched message:

```
if $programname == 'securityonion_ids' then
    /usr/local/pf/var/securityonion_ids
    & ~
```

Make sure the receiving alert pipe (FIFO) exists

```
mkfifo /usr/local/pf/var/securityonion_ids
```

Restart the rsyslog daemon

```
service rsyslog restart
```

At this point, Security Onion should be able to send detected alerts log entries to PacketFence.

A configuration of a new 'syslog parser' as well as some security events are the only remaining steps to make full usage of the Security Onion IDS integration.

Configuration of a new 'syslog parser' should use the followings:

```
Type: security_onion
Alert pipe: the previously created alert pipe (FIFO) which is, in this case,
/usr/local/pf/var/securityonion_ids
```

Configuration of a new security event can use the following trigger types:

```
Type: detect
Triggers ID: The IDS triggered rule ID
```

```
Type: suricata_event
Trigger ID: The rule class of the triggered IDS alert
```

18.5. Security Onion 2.3.10

This documentation is based on Security Onion v2.3. You can review its documentation at: <https://docs.securityonion.net/en/2.3>

All commands are done through the SSH CLI.

18.5.1. Suricata configuration on SO

First we need to modify the Suricata configuration to output the alerts into a fast.log file.

```
sudo vim /opt/so/saltstack/default/salt/suricata/defaults.yaml
```

Locate the outputs section and modify the fast options as follow:

```
outputs:
  - fast:
      enabled: "yes"
      filename: /nsm/fast.log
      append: "yes"
  - eve-log:
      enabled: "yes"
      filetype: regular
      filename: /nsm/eve-%Y-%m-%d-%H:%M.json
      rotate-interval: hour
```

```
#prefix: "@cee: "  
#identity: "suricata"  
#facility: local5  
#level: Info  
#redis:  
# server: 127.0.0.1
```

Reload the configuration on all minions with (it will take few minutes to apply):

```
sudo salt '*' state.highstate
```

You can verify the configuration done under:

```
sudo vim /opt/so/conf/suricata/suricata.yaml
```

If you want to disable some rules in suricata, you can use so-rule:

```
so-rule disabled add 're:STUN'  
so-rule disabled add 2101411
```

You can also check this video to understand how to manage suricata rules:

```
https://www.youtube.com/watch?v=1jEkFIEUCuI
```

18.5.2. Rsyslog configuration on SO

Now we need to send the alerts from the /nsm/fast.log to PacketFence.

```
sudo vim /etc/rsyslog.d/SO.conf
```

Replace the PACKETFENCE_MGMT_IP with your PacketFence management IP interface.

```
$ModLoad imfile  
$InputFileName /nsm/suricata/fast.log  
$InputFileTag suricata  
$InputFileStateFile stat-suricata  
$InputFileSeverity error  
$InputFileFacility local3  
$InputRunFileMonitor  
local3.* @PACKETFENCE_MGMT_IP:514
```

Restart Rsyslog:

```
sudo systemctl restart rsyslog
```

18.5.3. Configure PacketFence to process the syslog traffic

On the PacketFence server:

Modify rsyslog configuration to allow incoming UDP packets by uncommenting the following two lines in `/etc/rsyslog.conf`:

```
$ModLoad imudp
$UDPServerRun 514
```

Configure `/etc/rsyslog.d/securityonion_ids.conf` so it contains the following which will redirect Security Onion sguild log entries and stop further processing of current matched message:

```
if $programname == 'suricata' then /usr/local/pf/var/securityonion_ids
& ~
```

Make sure the receiving alert pipe (FIFO) exists

```
mkfifo /usr/local/pf/var/securityonion_ids
```

Restart the rsyslog daemon

```
service rsyslog restart
```

At this point, Security Onion should be able to send detected alerts log entries to PacketFence.

A configuration of a new 'syslog parser' as well as some security events are the only remaining steps to make full usage of the Security Onion IDS integration.

Configuration of a new 'syslog parser' should use the followings:

```
Type: suricata
Alert pipe: the previously created alert pipe (FIFO) which is, in this case,
/usr/local/pf/var/securityonion_ids
```

Configuration of a new security event can use the following trigger types:

```
Type: detect
```

Triggers ID: The IDS triggered rule ID

Type: suricata_event

Trigger ID: The rule class of the triggered IDS alert

18.6. ERSPAN

ERSPAN permits to mirror a local port traffic (low bandwidth) to a remote IP, E.G: your Security Onion already deployed box. ERSPAN encapsulates port traffic into ERSPAN then GRE and send that traffic to one/multiple destination(s). ERSPAN is a Cisco technology which is available only on some platforms, including: Catalyst 6500, 7600, Nexus, and ASR 1000.

One way of accessing encapsulated traffic at the destination host is through a software called RCD CAP, which is a daemon that creates a virtual interface if not existing, on which both GRE and ERSPAN headers are decapsulated prior to the traffic being injected to the previous interface. Security Onion can then feed on that interface like it would on any other, and if the RCD CAP daemon dies, continue to listen to that interface even though decapsulated traffic won't be available anymore.

Assumptions for the example: The switch is at IP 172.16.0.1, the monitored switch port is GigabitEthernet0/10 and the Security Onion monitoring destination IP is 10.10.10.10 on eth2, eth2 ideally being a dedicated interface.

On Security Onion:

- Enable Inverse repository for Security Onion:

```
sudo bash -c 'cat << EOL >/etc/apt/sources.list.d/securityonion-inverse.list
deb https://inverse.ca/downloads/PacketFence/securityonion trusty trusty
EOL'
```

```
gpg --keyserver keyserver.ubuntu.com --recv 19CDA6A9810273C4
gpg --export --armor 19CDA6A9810273C4 | sudo apt-key add -
```

- Install RCD CAP

```
sudo apt-get update
sudo apt-get install rcdcap
```

- Modify network file (/etc/network/interfaces) so that eth2 has an IP and a proper MTU. Decapsulated traffic will be injected on mon1. Make sure that the configuration is similar to the following:

```
auto eth2
iface eth2 inet static
```

```

address 10.10.10.10
netmask 255.255.255.240
up ip link set $IFACE arp on up
up ip link set dev $IFACE mtu 1900
post-up ethtool -G $IFACE rx 4096; for i in rx tx sg tso ufo gso gro lro; do
ethtool -K $IFACE $i off; done
post-up echo 1 > /proc/sys/net/ipv6/conf/$IFACE/disable_ipv6

auto mon1
iface mon1 inet manual
pre-up rcdcap -i eth1 --erspan --tap-persist --tap-device $IFACE --expression
"host 172.16.0.1" -d
up ip link set $IFACE promisc on arp off up
down ip link set $IFACE promisc off down
post-up ethtool -G $IFACE rx ; for i in rx tx sg tso ufo gso gro lro; do
ethtool -K $IFACE $i off; done
post-up echo 1 > /proc/sys/net/ipv6/conf/$IFACE/disable_ipv6

```

- Rerun Security Onion wizard and make sure to skip network configuration step. Make sure that mon1 is selected for monitoring purposes, note that eth2 doesn't need to.

```
sudo sosetup
```

On the Switch:

```

monitor session 10 type erspan-source
description ERSPAN to 10.10.10.10
source interface GigabitEthernet0/10
destination
erspan-id 10
ip address 10.10.10.10
origin ip address 172.16.0.1
no shutdown ! Default is shutdown

```


19. Firewall SSO Integration

PacketFence updates firewalls based on device information like IP address and connected username. Integration guides below show firewall configuration with PacketFence. PacketFence uses DHCP traffic by default to trigger firewall updates, but RADIUS accounting traffic is also supported.

To configure firewall updates, go to *Configuration → System Configuration → Main Configuration → Advanced*:

- Trigger Single-Sign-On on accounting.
- Trigger Single-Sign-On on DHCP

Using both methods simultaneously creates duplicate SSO requests when receiving DHCP and accounting for the same device, potentially overloading your firewall.

19.1. Barracuda

19.1.1. Configuration of the Barracuda in PacketFence

Go to **Configuration → Integration → Firewall SSO → Add Firewall → Barracuda**.

- **Hostname or IP Address:** IP of your Barracuda
- **Firewall type:** Barracuda (Barracuda = SSH requests)
- **Password:** secret
- **Port:** 22
- **Roles:** add the roles that you want to do SSO

[Status](#)
[Reports](#)
[Auditing](#)
[Nodes](#)
[Users](#)
[Configuration](#)

[API](#)
[dashboard](#)
admin
?
✕
🔔

Policies and Access Control
Compliance
Integration
Firewall SSO
Cisco Mobility Services Engine
Web Services
Syslog Parsers
Syslog Forwarding
WRIX
Advanced Access Configuration
Network Configuration
System Configuration

New Firewall SSO BarracudaNG

Hostname or IP Address192.168.100.3

Usernameroot

Secret or Key

Port of the service22

If you use an alternative port, please specify.

RolesStaff

Nodes with the selected roles will be affected.

Networks on which to do SSO

Comma delimited list of networks on which the SSO applies.

Format : 192.168.0.0/24

Cache updates

Enable this to debounce updates to the Firewall.

By default, PacketFence will send a SSO on every DHCP request for every device. Enabling this enables "sleep" periods during which the update is not sent if the informations stay the same.

Cache timeout

Adjust the "Cache timeout" to half the expiration delay in your firewall.

Your DHCP renewal interval should match this value.

Username format\$pf_username

Defines how to format the username that is sent to your firewall. \$username represents the username and \$realm represents the realm of your user if applicable. \$pf_username represents the unstripped username as it is stored in the PacketFence database. If left empty, it will use the username as stored in PacketFence (value of \$pf_username).

Default realm

The default realm to be used while formatting the username when no realm can be extracted from the username.

Create

Reset

19.1.2. Step 2: Verification

For our example, when the user registers on the portal it will be registered and the role staff will be assigned. The PacketFence server will send a request to the Barracuda database.

If you want to see if it's working, open an SSH access to your Barracuda and run this

command following commands:

```
acpfctrl auth show
```

You will get that:

```
[root@baracudafw:~]# acpfctrl auth show
1 entries
172.20.20.152/0
origin=PacketFence
service=PacketFence
user=Jdoe
```

19.2. Checkpoint

19.2.1. Enabling Identity Awareness on the Security Gateway


To enable Identity Awareness:

1. Log in to 'SmartDashboard'.
2. From the 'Network Objects tree', expand the 'Check Point branch'.
3. Double-click the 'Security Gateway' on which to enable 'Identity Awareness'.
4. In the 'Software Blades' section, select 'Identity Awareness' on the 'Network Security tab'. The 'Identity Awareness Configuration' wizard opens.
5. Select 'one or more options'. These options set the methods for acquiring identities of managed and unmanaged assets.
6. Select 'AD Query - Lets the Security Gateway seamlessly identify Active Directory users and computers' and click Next. The 'Integration With Active Directory' window opens.
7. Select the Active Directory to configure from the list that shows configured LDAP account units or create a new domain. If you have not set up Active Directory, you need to enter a domain name, username, password and domain controller credentials.
8. Enter the Active Directory credentials and click Connect to verify the credentials. (Important - For AD Query you must enter domain) administrator credentials.
9. Click Finish.

19.2.2. Enabling RADIUS Accounting on a Security Gateway

To enable RADIUS Accounting for a Security Gateway: 1. In the 'SmartDashboard Network Objects tree', open the Security Gateway. 2. On the 'General Properties' page, make sure that the Identity Awareness Blade is enabled. 3. On the 'Identity Awareness' page, select RADIUS Accounting.

19.2.3. Configuring RADIUS Accounting



1. In the 'Check Point Gateway' window > 'Identity Awareness' panel, click 'Settings' (to the right of the RADIUS Accounting option).
2. In the 'RADIUS Accounting Settings' window, configure the 'Message Attribute Indices' like this:
 - **Device Name:** Calling-Station-Id (31) (MAC Address of the device)
 - **User Name:** User-Name (1) (Username put on the PacketFence Portal)
 - **Device Name:** Framed-IP-Address (8) (IP Address of the device in the production network)


19.2.4. RADIUS Client Access Permissions

Gateway interfaces must be authorized to accept connections from PacketFence RADIUS Accounting.

To select gateway interfaces: 1. In the 'RADIUS Client Access Permissions' section, click Edit. 2. Select 'All Interfaces - All Security Gateway interfaces can accept connections from RADIUS Accounting clients'. 3. Leave the default port to 1813. 4. Click OK on both windows to submit the configuration. 5. Select 'Policy' > 'Install' from the SmartDashboard menu.

19.2.5. LDAP Groups

Make sure that you have the correct LDAP Objects created on the Checkpoint.



19.2.6. SSO Configuration in PacketFence

Go to '*'Configuration' → 'Firewall SSO' → 'Add Firewall' → 'Checkpoint' *.

- **Hostname or IP Address:** IP of your Checkpoint firewall
- **Secret or Key:** secret (radius shared secret)
- **Port:** 1813
- **Roles:** add the roles that you want to do SSO with

[Status](#)
[Reports](#)
[Auditing](#)
[Nodes](#)
[Users](#)
[Configuration](#)

[API](#)
[dashboard](#)
admin
?
✕
🔔

Policies and Access Control
Compliance
Integration
Firewall SSO
Cisco Mobility Services Engine
Web Services
Syslog Parsers
Syslog Forwarding
WRIX
Advanced Access Configuration
Network Configuration
System Configuration

New Firewall SSO

Checkpoint

✕

Hostname or IP Address

192.168.100.2

Secret or Key

.....

👁

Port of the service

1813

If you use an alternative port, please specify.

Roles

Staff

✕

▼

Nodes with the selected roles will be affected.

Networks on which to do SSO

Comma delimited list of networks on which the SSO applies.
Format : 192.168.0.0/24

Cache updates

☐

Enable this to debounce updates to the Firewall.
By default, PacketFence will send a SSO on every DHCP request for every device. Enabling this enables "sleep" periods during which the update is not sent if the informations stay the same.

Cache timeout

Adjust the "Cache timeout" to half the expiration delay in your firewall.
Your DHCP renewal interval should match this value.

Username format

\$pf_username

Defines how to format the username that is sent to your firewall. \$username represents the username and \$realm represents the realm of your user if applicable. \$pf_username represents the unstripped username as it is stored in the PacketFence database. If left empty, it will use the username as stored in PacketFence (value of \$pf_username).

Default realm

The default realm to be used while formatting the username when no realm can be extracted from the username.

Create

Reset

19.2.7. Verification

You can check the correct log in with the SmartView Tracker under **'Network & Endpoint Queries' → 'Predefined' → 'Identity Awareness Blade' → 'Login Activity'**

19.3. Cisco ISE-PIC

19.3.1. Preliminary steps

First, attach ISE-PIC to Active Directory and set it up as an Identity Provider as described here: https://www.cisco.com/c/en/us/td/docs/security/ise/2-6/pic_admin_guide/PIC_admin26/PIC_admin26_chapter_010.html

19.3.2. Syslog template

Add a new Template and call it **PacketFence**. Make it match the following:

Syslog Template X

Name * PacketFence

Mapping Operations

New Mapping * assigned to session

Removed Mapping

User Data

IP Address * Address <([^\s]+)>|address ([^\s]+)

User Name User <([^\s]+)>

Domain

MAC address

Test Template

Paste one line of syslog

Data Identified

User name
IP Address
Domain
MAC Address

Test

Cancel Save

- The new mapping should be set to: **assigned to session**
- The regular expression for the IP address is: **Address <()>|address ([^\s])**
- The regular expression for the username is: **User <([^\s]+)>**

19.3.3. Syslog provider

To add PacketFence as an identity provider, hover over "Providers" and click "Syslog Providers.", then click "Add".

Then add each of your PacketFence servers as Syslog providers using the syslog template you created above. In the case of a cluster, add each member management IP and the management virtual IP.

NOTE In your DNS servers, make sure the FQDN and reverse lookup entries match your PacketFence server FQDN.

Syslog Providers

Name *	MyPFInstance	
Description		
Status *	Enabled	
Host FQDN *	pf1.mydomain.com	
Connection Type *	UDP - Port 40514	
Template *	PacketFence	Edit New
Default Domain	mydomain.com	

Cancel

Save

Make sure your syslog header configuration matches this:

Syslog Custom Header



If some or all of the syslogs are not being accepted, it may be because they have an uncommon header format. Define a custom header here.

Paste sample syslog *	Paste sample syslog here
Separator *	* Space 
Position of hostname in header *	2 
Hostname	Following analysis of sample syslog; the hostname will appear here. If correct, then save this custom header. 

Cancel

Submit

19.3.4. PacketFence configuration

Add a Cisco ISE-PIC firewall SSO entry in "Configuration→Integration→Firewall SSO"

New Firewall SSO Cisco ISE-PIC

Hostname or IP Address: 192.168.1.100

Port of the service: 40514
If you use an alternative port, please specify.

Roles: default
Nodes with the selected roles will be affected.

Networks on which to do SSO
Comma delimited list of networks on which the SSO applies.
Format : 192.168.0.0/24

Cache updates: ☐
Enable this to debounce updates to the Firewall.
By default, PacketFence will send a SSO on every DHCP request for every device. Enabling this enables "sleep" periods during which the update is not sent if the informations stay the same.

Cache timeout:
Adjust the "Cache timeout" to half the expiration delay in your firewall.
Your DHCP renewal interval should match this value.

Username format: \$pf_username
Defines how to format the username that is sent to your firewall. \$username represents the username and \$realm represents the realm of your user if applicable. \$pf_username represents the unstripped username as it is stored in the PacketFence database. If left empty, it will use the username as stored in PacketFence (value of \$pf_username).

Default realm:
The default realm to be used while formatting the username when no realm can be extracted from the username.

Create **Reset**

- **Hostname or IP Address:** IP of your Cisco ISE-PIC instance
- **Port:** 40514
- **Roles:** add the roles that you want to do SSO with

You should then see User Sessions populating under "Live Logs" in ISE-PIC. The source should say "syslog"

19.4. FortiGate

19.4.1. Configuration of the RSSO Agent

In FortiGate administration: **User & Device** → **User** → **User Groups** → **Create New**.

- **Name:** RSSO_group
- **Type:** RADIUS Single Sign-On (RSSO)
- **RADIUS Attribute Value:** RSSO_Student (use PacketFence rolename, case-sensitive)

FortiWiFi 60C Help Wizard Logout **FORTINET**

Edit User Group

Name: RSSO_Student

Type: ☐ Firewall ☐ Fortinet Single Sign-On (FSSO) ☒ Guest ☒ RADIUS Single Sign-On (RSSO)

RADIUS Attribute Value: RSSOStudent

OK **Cancel**

User & Device

- User
 - User Definition
 - User Groups**
 - Guest Management
- Device

View at **User & Device → Monitor → Firewall**.

19.4.2. Configure the endpoint attribute


Default endpoint attribute is Calling-Station-Id (MAC address shows as User Name).
Change via CLI:

```
config user radius
edit RSS0_agent
set rso-endpoint-attribute User-Name
end
```

19.4.3. Activate the Accounting Listening

Go to **System → Network → Interfaces**.

Select PacketFence communication interface, check 'Listen for RADIUS Accounting Messages', confirm.



19.4.4. SSO Configuration in PacketFence

Go to **Configuration → Integration → Firewall SSO → Add Firewall → FortiGate**.

- **Hostname or IP Address:** IP of your firewall
- **Secret or Key:** secret (radius shared secret)
- **Port:** 1813
- **Roles:** add the roles that you want to do SSO

[Status](#)
[Reports](#)
[Auditing](#)
[Nodes](#)
[Users](#)
[Configuration](#)

[API](#)
[dashboard](#)
admin
?
✕
🔔

Policies and Access Control
Compliance
Integration
Firewall SSO
Cisco Mobility Services Engine
Web Services
Syslog Parsers
Syslog Forwarding
WRIX
Advanced Access Configuration
Network Configuration
System Configuration

New Firewall SSO

FortiGate

✕

Hostname or IP Address

192.168.100.2

Secret or Key

.....

👁

Port of the service

1813

If you use an alternative port, please specify.

Roles

Staff

✕

▼

Nodes with the selected roles will be affected.

Networks on which to do SSO

Comma delimited list of networks on which the SSO applies.
Format : 192.168.0.0/24

Cache updates

☒

Enable this to debounce updates to the Firewall.
 By default, PacketFence will send a SSO on every DHCP request for every device. Enabling this enables "sleep" periods during which the update is not sent if the informations stay the same.

Cache timeout

Adjust the "Cache timeout" to half the expiration delay in your firewall.
 Your DHCP renewal interval should match this value.

Username format

\$pf_username

Defines how to format the username that is sent to your firewall. \$username represents the username and \$realm represents the realm of your user if applicable. \$pf_username represents the unstripped username as it is stored in the PacketFence database. If left empty, it will use the username as stored in PacketFence (value of \$pf_username).

Default realm

The default realm to be used while formatting the username when no realm can be extracted from the username.

Create

Reset

19.4.5. Verification

If you want to see if it's working, you can log into the firewall over SSH and run these following commands:

```
di debug enable
di debug application radiusd -1
```

19.5. iBoss

19.6. JSON-RPC

19.6.1. JSON-RPC interface

The JSONRPC module shipped with PacketFence is meant as a generic firewall SSO module to be used with Linux or BSD firewalls that do not by default ship with a vendor-specific interface to do SSO with.

A compatible server must implement the methods **Start** and **Stop**, both with the identical set of parameters provided below.

- **Protocol:** JSON-RPC 2.0 over HTTPS
- **Authentication:** HTTP Basic authentication
- **Methods:** **Start** and **Stop**
- **Parameters:**
 - **user** (*string*): Username that registered the device
 - **mac** (*string*): MAC address of the device
 - **ip** (*string*): IP address of the device
 - **role** (*string*): PacketFence role assigned to the device
 - **timeout** (*int*): Duration until the registration expires in seconds
- **Response:** Success must be indicated by "**result**": ["OK"]. Every string other than **OK** is taken as an error message.

A simple JSON-RPC server written in Python that is compatible with this specification and creates ipsets based on the SSO information provided by PacketFence can be found at <https://github.com/tribut/ipset-rpcd>.

19.6.2. SSO Configuration in PacketFence

Go to '**Configuration**' → '**Integration**' → '**Firewall SSO**' → '**Add Firewall**' → '**JSONRPC**'.

- **Hostname or IP Address:** IP of your JSON-RPC server
- **Username** and **Password:** HTTP Basic credentials
- **Port of the service:** 9090
- **Roles:** Add the roles that you want to do SSO with

[Status](#)
[Reports](#)
[Auditing](#)
[Nodes](#)
[Users](#)
[Configuration](#)

[API](#)
[dashboard](#)
admin
?
✕
🔔

Policies and Access Control
Compliance
Integration
Firewall SSO
Cisco Mobility Services Engine
Web Services
Syslog Parsers
Syslog Forwarding
WRIX
Advanced Access Configuration
Network Configuration
System Configuration

New Firewall SSO

Hostname or IP Address

192.168.100.1

Username

Jsonrpc-updater

Password

.....

👁

Port of the service

9090

If you use an alternative port, please specify.

Roles

gaming

guest

▼

Nodes with the selected roles will be affected.

Networks on which to do SSO

Comma delimited list of networks on which the SSO applies.

Format : 192.168.0.0/24

Cache updates

🔘

Enable this to debounce updates to the Firewall.
 By default, PacketFence will send a SSO on every DHCP request for every device. Enabling this enables "sleep" periods during which the update is not sent if the informations stay the same.

Cache timeout

Adjust the "Cache timeout" to half the expiration delay in your firewall.
 Your DHCP renewal interval should match this value.

Username format

\$pf_username

Defines how to format the username that is sent to your firewall. \$username represents the username and \$realm represents the realm of your user if applicable. \$pf_username represents the unstripped username as it is stored in the PacketFence database. If left empty, it will use the username as stored in PacketFence (value of \$pf_username).

Default realm

The default realm to be used while formatting the username when no realm can be extracted from the username.

Create

Reset

19.7. Juniper SRX

19.7.1. Configuration of the Juniper SRX in PacketFence

Go to **Configuration** → **Integration** → **Firewall SSO** → **Add Firewall** → **JuniperSRX**.

- **Hostname or IP Address:** IP of your JuniperSRX
- **Firewall type:** JuniperSRX (JuniperSRX = HTTPS requests)
- **Password:** secret
- **Port:** 8443
- **Roles:** add the roles that you want to do SSO

19.7.2. Step 1: webapi configuration

You need to setup webapi management as follows

```
set system services webapi user PF
set system services webapi user password YOURPASSWORD
set system services webapi client PF_MANAGEMENT_IP_ADDRESS
```

```
set system services webapi https port PORT_YOU_WANT_TO_USE i.e. 8443
set system services webapi https default-certificate
```

Next setup user entry settings

```
set services user-identification authentication-source aruba-clearpass
authentication-entry-timeout 120
set services user-identification authentication-source aruba-clearpass no-user-
query
set services user-identification device-information authentication-source
network-access-controller
```

Then you need to allow traffic from the PacketFence management interface to port you set up on webapi settings (i.e. 8443) on SRX device.

19.7.3. Step 2: Verification

For debugging the webapi set (disable it when you won't need it anymore):

```
set system services webapi debug-log api-log
set system services webapi debug-level notice
```

To check registered device entries on SRX use

```
show services user-identification authentication-table authentication-source
all ( extensive for more detailed informations)
```

or

```
run show services user-identification device-information table all extensive
```

to see more details about OS, device type etc.

19.8. Palo Alto


19.8.1. Installation using XMLAPI

Create a SSO role

Create SSO role on PaloAlto firewall web interface.

Go to **Device → Admin Roles → Add**.

Create role 'SSO_Role', under 'XML API' tab enable everything, validate with 'OK'.




Create the account in PAN-OS

Associate user with created role.

Go to **Device → Administrators → Add**.

- **Name:** xmluser
- **Authentication Profile:** None
- **Password:** xmluser
- **Role:** Role Based

- **Profile:** SSO_Role (Previously created)
- **Password Profile:** None



Get the XML Key

Go on this URL: <https://@IP-of-PaloAlto/api/?type=keygen&user=xmuser&password=xmuser>.

It should display:

```
<response status="success">
<result>
<key>
LUFRPT1jeFV6SHd1QnJHaU55dnYvRlFNSkJNeTR6Uzg9TDgzNVlj0=
</key>
</result>
</response>
```

SSO Configuration in PacketFence

Now that we have the key, we will configure the PaloAlto firewall in PacketFence.

Go to **Configuration → Integration → Firewall SSO → Add Firewall → PaloAlto**.

- **Hostname or IP Address:** IP of your firewall
- **Transport:** HTTP
- **Secret or Key:** LUFRPT1jeFV6SHd1QnJHaU55dnYvRlFNSkJNeTR6Uzg9TDgzNVlj0= (use the key previously generated)
- **Port of the service:** 443
- **Roles:** add the roles that you want to do SSO with

[Status](#)
[Reports](#)
[Auditing](#)
[Nodes](#)
[Users](#)
[Configuration](#)

[API](#)
[dashboard](#)
admin
?
✕
🔔

Policies and Access Control
Compliance
Integration
Firewall SSO
Cisco Mobility Services Engine
Web Services
Syslog Parsers
Syslog Forwarding
WRIX
Advanced Access Configuration
Network Configuration
System Configuration

New Firewall SSO
PaloAlto

Hostname or IP Address
192.168.100.1

Vsys
1
Please define the Virtual System number. This only has an effect when used with the HTTP transport.

Transport
HTTP

Port of the service
443
If you use an alternative port, please specify. This parameter is ignored when the Syslog transport is selected.

Secret or Key

If using the HTTP transport, specify the password for the Palo Alto API.

Roles
gaming x guest x
Nodes with the selected roles will be affected.

Networks on which to do SSO
Comma delimited list of networks on which the SSO applies.
Format : 192.168.0.0/24

Cache updates
☒
Enable this to debounce updates to the Firewall.
By default, PacketFence will send a SSO on every DHCP request for every device. Enabling this enables "sleep" periods during which the update is not sent if the informations stay the same.

Cache timeout
Adjust the "Cache timeout" to half the expiration delay in your firewall.
Your DHCP renewal interval should match this value.

Username format
\$pf_username
Defines how to format the username that is sent to your firewall. \$username represents the username and \$realm represents the realm of your user if applicable. \$pf_username represents the unstripped username as it is stored in the PacketFence database. If left empty, it will use the username as stored in PacketFence (value of \$pf_username).

Default realm
The default realm to be used while formatting the username when no realm can be extracted from the username.

Create
Reset

Verification

Now we will check that PacketFence is sending information when a user registers on the portal. If the process worked, you will see the entry in the PaloAlto database.

Use SSH on the PaloAlto firewall and run this command:

```
admin@PA-VM> show user ip-user-mapping all
```

IP	Vsys	From	User	IdleTimeout(s)
MaxTimeout(s)				
-----	-----	-----	-----	-----
192.168.100.10	vsys1	XMLAPI	domain\user1	Never
Never				


19.8.2. Installation using syslog

NOTE

This installation mode is not suggested unless you use the SSO for informational purposes (no enforcement). PacketFence will use easily spoofable UDP packets to communicate with the Palo Alto firewall. If you require encryption and origin validation of the SSO messages, please use the XML API.


Create a filter

You will first need to create a filter to parse the SSO line that PacketFence will send. This can be done in 'User Identification→User Mapping'



Assign the filter to a 'Monitored Server'

Next, configure the filter to be used in a syslog receiver on the Palo Alto. In order to do so, go in 'User Identification→User Mapping' and configure a syslog sender.



SSO Configuration in PacketFence

Next you need to configure the firewall in PacketFence.

Go to **Configuration → Integration → Firewall SSO → Add Firewall → PaloAlto**.

- **Hostname or IP Address:** IP of your firewall
- **Transport:** Syslog
- **Secret or Key:** Ignore this parameter
- **Port of the service:** Ignore this parameter
- **Roles:** add the roles that you want to do SSO with

Verification

Now we will check that PacketFence is sending information when a user registers on the portal. If the process worked, you will see the entry in the PaloAlto database.

Use SSH on the PaloAlto firewall and run this command:

```
admin@PA-VM> show user ip-user-mapping all
```

IP	Vsys	From	User	IdleTimeout(s)
192.168.100.10	vsys1	syslog	domain\user1	Never

NOTE

If the process is not working and you get the following error **Usage: Socket::inet_ntoa(ip_address_sv)**, check that the hostname of your PacketFence server can be resolved correctly on the server itself. If its not, make sure you adjust your hosts file or your DNS server.

19.9. Troubleshooting SSO Integration

For SSO integration issues, verify firewall API connectivity and check integration logs as described in [Log Files](#) and [Network Connectivity Issues](#) in the Troubleshooting section.

20. Performing Compliance Checks

PacketFence supports either Nessus and OpenVAS as a scanning engine for compliance checks. Since PacketFence v5.1 it is possible to create multiple scan engine configurations and assign them on specific captive portals. It means for example that it is now possible to activate a scan for specific Operating System only on a specific SSID.

20.1. Installation

20.1.1. Nessus

Please visit <https://www.tenable.com/downloads/nessus> to download Nessus v7 and install the Nessus package for the operating system. Also register for the HomeFeed (or the ProfessionalFeed) in order to get the plugins.

After installing Nessus, follow the Nessus documentation for the configuration of the Nessus Server, and to create a user for PacketFence.

NOTE

Some issues may occur while using Nessus with the Net::Nessus::XMLRPC module (which is the default behavior in PacketFence). Please refer to the [bug tracking system](#) for more information.

20.1.2. OpenVAS

Requirements

First install OpenVAS along with XYZ and ABC in order to manage OpenVAS remotely via the `omp` command line.

In order to validate proper connectivity from PacketFence to OpenVAS for remote management, execute the following command (replacing admin by the user to use for PacketFence to communicate with OpenVAS):

```
# omp -u admin -p 9390 -X "<get_version/>"
```

The output of the above command should provide the version of OpenVAS. Otherwise, ensure all the necessary components are in place for management through the `omp` command line client and that PacketFence is able to communicate with OpenVAS on port 9390.

Configuring the alert

Configure an alert policy in OpenVAS to inform PacketFence of the completion of a task. The `httpd.portal` daemon takes care of handling this callback so ensure that "portal" is in the additional listening daemons on the management interface in PacketFence.

In order to create the alert policy, go in the Greenbone Security Assistant, then in "Configuration → Alerts" and create a new alert with the following configuration

The screenshot shows the 'New Alert' configuration window in the Greenbone Security Assistant. The window has a green title bar with the text 'New Alert' and a close button. The form is divided into several sections:

- Name:** A text input field containing 'Alert PacketFence'.
- Comment:** An empty text input field.
- Event:** A radio button selected for 'Task run status changed to', followed by a dropdown menu showing 'Done'.
- Condition:** A radio button selected for 'Always'. Below it are options for 'Severity at least' (0.1) and 'Severity level' (changed).
- Report Result Filter:** A dropdown menu showing '--'.
- Method:** A dropdown menu showing 'HTTP Get'.
- HTTP Get URL:** A text input field containing 'http://192.168.1.5/hook/openvas?task=\$n'.

 There are also additional options for 'NVTs' and 'matches at least' with input fields for '1' and '1' respectively. A green 'Create' button is located at the bottom right of the form.

Where:

- Name is of the value chosen
- Ensure the event is set to "Task run status changed to: Done"
- Ensure the condition is set to "Always"
- Method is set to "HTTP Get"
- HTTP Get URL is set to: [http://PF_MANAGEMENT_IP/hook/openvas?task=\\$n](http://PF_MANAGEMENT_IP/hook/openvas?task=$n)
 - In the URL above, only change PF_MANAGEMENT_IP to the management IP of the PacketFence server. Leave the rest of the URL untouched as this exact URL and format is expected by PacketFence.

Collecting the identifiers

Once connectivity is working between PacketFence and OpenVAS, use the Greenbone Security Assistant to obtain the following information for configuring PacketFence

Alert ID

Navigate to *Configuration → Alerts*, then click on the alert configured above to view it, and note down the ID of the alert.

Greenbone Security Assistant

Logged in as Admin **admin** | Logout
Tue Nov 27 17:37:46 2018 UTC

Dashboard Scans Assets SecInfo Configuration Extras Administration Help

Alert: Alert PacketFence

ID: de0b6876-0554-41e4-befc-344619ee7b4f
Created: Tue Nov 27 17:06:08 2018
Modified: Tue Nov 27 17:06:08 2018
Owner: admin

Comment:
Condition: Always
Event: Task run status changed (to Done)
Method: HTTP Get
URL: http://192.168.1.5/hook/openvas?task=\$n
Filter: None

Scan config ID

Navigate to *Configuration* → *Scan Configs* and then select the scan configuration to use to scan the hosts. In this scan config view, note down the ID.

Greenbone Security Assistant

Logged in as Admin **admin** | Logout
Tue Nov 27 17:39:27 2018 UTC

Dashboard Scans Assets SecInfo Configuration Extras Administration Help

Scan Config: Discovery

ID: 8715c877-47a0-438d-98a3-27c7a6ab2196
Created: Tue Aug 21 18:53:13 2018
Modified: Tue Aug 21 18:53:13 2018

Comment: Network Discovery scan configuration.

Report format ID

Navigate to *Configuration* → *Report Formats* and then select the **CSV Results** report format. In this view, note down the ID.

Greenbone Security Assistant

Logged in as Admin **admin** | Logout
Tue Nov 27 17:41:13 2018 UTC

Dashboard Scans Assets SecInfo Configuration Extras Administration Help

Report Format: CSV Results

ID: c1645568-627a-11e3-a660-406186ea4fc5
Created: Tue Aug 21 18:53:13 2018
Modified: Tue Aug 21 18:53:13 2018
Owner:

Extension: csv
Content Type: text/csv
Trust: yes
Active: yes
Summary: CSV result list.

Description:
List of results.

20.2. Configuration

In order for the compliance checks to correctly work with PacketFence (communication and generate security events inside PacketFence), configure these sections:

20.2.1. Scanner Definition

First go in Configuration and Scanner Definition: *Configuration* → *Compliance* → *Scan Engines*

Then add a [New Scan Engine](#)

Scan Engine

Name	Scan Engine
Add Scan ▾ Nessus OpenVAS wmi	

There are common parameters for each scan engines:

Name: the name of the scan engine
Roles: Only devices with these role(s) will be affected (Optional)
OS: Only devices with this Operating System will be affected (Optional)
Duration: Approximate duration of scan (Progress bar on the captive portal)
Scan before registration: Trigger the scan when the device appear on the registration vlan
Scan on registration: Trigger the scan just after registration on the captive portal
Scan after registration: Trigger the scan on the production network (pfdhcp listener must receive production dhcp traffic)

Specific to Nessus:

Hostname or IP Address: Hostname or IP Address where Nessus is running
Username: Username to connect to Nessus scan
Password: Password to connect to Nessus scan
Port of the service: port to connect (default 8834)
Nessus client policy: the name of the policy to use for the scan (Must be defined on the Nessus server)

Specific to OpenVAS:

Hostname or IP Address: Hostname or IP Address where OpenVAS is running
Username: Username to connect to OpenVAS scan
Password: Password to connect to OpenVAS scan
Port of the service: port to connect (default 9390)
Alert ID: the ID of the alert configuration on the OpenVAS server

Scan config ID: the ID of the scanning configuration on the OpenVAS server
Report format ID: the ID of the report format for the "CSV Results"

Rules syntax

The syntax of the rules are simple to understand and use same syntax as [VLAN filters](#).

- *Request* is the SQL request to launch on the remote device, must know what the request will return to write the test.

Inside the *Rules Actions* field we define 2 sorts of blocs:

- The test bloc (i.e. `[explorer]`)
- The action bloc (i.e. `[1:explorer]`)

The test bloc is a simple test based on the result of the request:

- attribute is the attribute to test
- operator can be:
 - is
 - is_not
 - match
 - match_not
 - advance
- value is the value to compare

Multiple test blocs can be defined.

The action bloc is where the logic will be defined. All actions available are identical to [VLAN filters](#). Take a look at `/usr/local/pf/conf/vlan_filters.conf.example` for all available actions.

20.2.2. Security Events Definition

Create a new security event section and specify:

Using Nessus:

```
trigger=Nessus:<security event ID>
```

Using OpenVAS:

```
trigger=OpenVAS:<security event ID>
```

Where `security event ID` is either the ID of the Nessus plugin or the OID of the OpenVAS plugin to check for. Once the configuration is finished, reload the security event related database contents using:

```
pfcmd reload security_events
```

NOTE

Security events will trigger if the plugin is higher than a low severity vulnerability.

20.2.3. Assign Scan definition to connection profiles

The last step is to assign one or more scanner configured to one or more connection profiles. Go in *Configuration → Policies and Access Control → Connection Profiles → Edit a Profile → Add Scan*

Hosting Nessus / OpenVAS remotely

Because of the CPU intensive nature of an automated vulnerability assessment, we recommend that it is hosted on a separate server for large environments. To do so, a couple of things are required:

- PacketFence needs to be able to communicate to the server on the port specified by the vulnerability engine used
- The scanning server need to be able to access the targets. In other words, registration VLAN access is required if scan on registration is enabled.

If using the OpenVAS scanning engine:

- The scanning server need to be able to reach PacketFence's Admin interface (on port 1443 by default) by its DNS entry. Otherwise PacketFence won't be notified of completed scans.
- A valid SSL certificate must be on the PacketFence server

If using the Nessus scanning engine:

- Just change the host value to the Nessus server IP.

20.3. Rapid7 integration

PacketFence supports integration with Rapid7 to start scans automatically when a device connects to the network and also to receive the Rapid7 alerts via syslog.

20.3.1. Rapid7 installation

- Install the InsightVM application
 - <https://insightvm.help.rapid7.com/docs/installing-in-linux-environments#section-installing-in-red-hat>
- Run the application
 - <https://insightvm.help.rapid7.com/docs/running-the-application#section-managing-the-application-in-linux>
- Logon to the server: <https://YourRapid7ServerIP:3780>

NOTE

Make sure to create a site for the devices to manage in Rapid7, it will need to be referenced in the PacketFence configuration

20.3.2. Configuring the scan engine

Rapid7 PacketFence user

First, create credentials for PacketFence so that it can perform API calls on Rapid7. In order to do so, on Rapid7, go in *Administration* → *Users* and click on **Create**. Then configure the appropriate username and password and make sure the account is enabled.

The screenshot shows the 'User Configuration' form in Rapid7. The 'GENERAL' tab is selected. The form includes the following fields and options:

- User name:** packetfence
- Authentication method:** InsightVM user (dropdown)
- Full name:** PacketFence
- E-mail address:** packetfence@example.com
- Password:** (masked with dots)
- Confirm password:** (masked with dots)
- Account enabled:** ☒ (checked)
- Require password reset upon login:** ☐ (unchecked)

At the top right of the form, there are 'Save' and 'Cancel' buttons. A small note at the top of the form states: 'Enter information that will identify this user. Select an authentication method if more than one is available. Consult your network administrator about multiple authentication options. This user cannot access the Security Console unless you select the check box to enable the account. You can clear the check box at any time to take away access.'

Next, in the roles of that user, select the "Custom" role and assign at least the following privileges to the new user:

- Manage Sites
- Manage Scan Enginespfcron
- View Site Asset Data
- Specify Scan Targets
- View Group Asset Data

Next, in "Site access" and "Asset group access", ensure to provide access to this user to all the assets and sites it needs to manage. When in doubt, grant access to all sites and asset groups.

User Configuration

GENERAL

ROLES

SITE ACCESS

ASSET GROUP ACCESS

Specify asset groups that this user can access. The user's permissions for these asset groups are based on his or her role.

☒ Allow this user to access all asset groups

☐ Create a custom list of asset groups that this user can access

Configure the scan engine in PacketFence

Once the user is created, create the scan engine by going in *Configuration* → *Compliance* → *Scan Engines* and creating a **New Scan Engine** of the type **Rapid7**

Notes on the configuration:

- 172.20.20.230 is the IP address (hostname can also be configured) of the Rapid7 server
- Verify Hostname must be disabled unless a valid SSL certificate is configured for the configured Rapid7 hostname
- Roles and OS represents the roles and operating systems for which to apply this scan engine. Leaving them empty will apply the policy to all devices.
- Scan before/on/after registration controls when the automated scans are started for the devices PacketFence sees. To only start the scans manually, leave those unchecked.
- It will not be possible to select a scan template, site and scan engine when initially configuring the engine. First configure the access and credentials and edit the engine again to be able to select those from the available values in Rapid7.

[Status](#)
[Reports](#)
[Auditing](#)
[Nodes](#)
[Users](#)
[Configuration](#)

[API](#)
[dashboard](#)
admin
?
✕
1

Policies and Access Control
Compliance

Fingerbank Profiling
General Settings
Device change detection
Combinations
Devices
DHCP Fingerprints
DHCP Vendors
DHCPv6 Fingerprints
DHCPv6 Enterprises
MAC Vendors
User Agents

Scans
Scan Engines
WMI Rules

Security Events

Integration
Advanced Access Configuration
Network Configuration
System Configuration

New Scan Engine rapid7

Name

MyRapid7Scan

Hostname or IP Address

172.20.20.230

Username

packetfence

Password

.....

👁

Port of the service

3780

If you use an alternative port, please specify.

Verify Hostname

☐

Verify hostname of server when connecting to the API.

Scan Engine

After configuring this scan engine for the first time, you will be able to select this attribute from the available ones in Rapid7.

Scan Template

After configuring this scan engine for the first time, you will be able to select this attribute from the available ones in Rapid7.

Site

After configuring this scan engine for the first time, you will be able to select this attribute from the available ones in Rapid7.

Roles

Nodes with the selected roles will be affected.

OS

Type to search.

Nodes with the selected OS will be affected.

Duration

20

seconds

Approximate duration of a scan. User being scanned on registration are presented a progress bar for this duration, afterwards the browser refreshes until scan is complete.

Scan before registration

☐

If this option is enabled, the PF system will scan host before the registration.

Scan on registration

☐

If this option is enabled, the PF system will scan each host after registration is complete.

Scan after registration

☐

If this option is enabled, the PF system will scan host after on the production vian.

Create

Reset

Assign the engine to a connection profile

With the scan engine now created, assign it to the connection profile that the endpoints use. In order to do so, go in *Configuration* → *Connection Profiles*, select the connection profile and add the scan engine there.

Automatically designate devices on accounting stop ☐ This activates automatic designation of devices for the profile if PacketFence receives a RADIUS accounting stop.

VLAN pool technique: The algorithm used to calculate the VLAN in a VLAN pool.

Filters:

Filter: With no filter specified, an advanced filter must be specified.

Advanced filter:

Sources: With no source specified, all internal and external sources will be used.

Billing Tiers: With no billing tiers specified, all billing tiers will be used.

Provisioners: With no provisioners specified, the provisioners of the default profile will be used.

Scanners: With no scan specified, the scan engine will not be triggered.

Self service policy:

Viewing data on endpoints

With the scan engine integration completed, PacketFence will now automatically start scans on the endpoints it sees DHCP for and it will be possible to view the Rapid7 information of the endpoints by going in the *Nodes* tab in PacketFence and then viewing a node and browsing its Rapid7 tab.

MAC 00:0c:29:30:17:84 ×

[Info](#)
[Fingerbank](#)
[IPv4 Address](#)
[IPv6 Address](#)
[Location](#)
[Violations](#)
[WMI Rules](#)
[Option82](#)
[Rapid7](#)

[Summary](#)
[Device Profiling](#)
[Top Vulnerabilities](#)
[Last Scan](#)

Assessed For Policies	true
Assessed For Policies	false
OS Profiling	CentOS Linux
Risk Score	9993.353515625
Exploits Found	8
Critical Vulnerabilities Found	3
Severe Vulnerabilities Found	44
Moderate Vulnerabilities Found	4
Malware Kits Found	0

20.3.3. Configuring the syslog integration

PacketFence also supports integration with the syslog forwarding of Rapid7 (with or without the scan engine integration) in order to receive vulnerability alerts from Rapid7.

Sending syslog information to PacketFence

In Rapid7:

- First select the site to have alerts for and click on *Manage Site*
- In the site management tabs select **Alerts**, then create a new alert

Enable: Must be checked. **Alert Name:** Rsyslog to PacketFence or else. **Maximum Alerts to send:** blank (none) **Scan events:** Check all. **Vulnerability Events:** Any severity ; Check as well Confirmed, Unconfirmed, Potential **Notification Method:** Select Syslog message **Syslog Server:** PacketFence cluster VIP or server IP for a standalone

The screenshot shows the 'New Alert' configuration window in the Site Configuration | LAB interface. The window has a sidebar with 'MANAGE ALERTS' and 'CREATE ALERT' options. The main form contains the following fields and values:

- Enable:** ☒
- Alert Name:** packetfencealerts
- Maximum Alerts to Send:** (blank)
- Scan Events:** ☒ Started, ☒ Stopped, ☒ Failed, ☒ Paused, ☒ Resumed
- Vulnerability Events:** ☒ Any severity, ☒ Confirmed, ☒ Unconfirmed, ☒ Potential
- Notification Method:** Syslog message
- Syslog Server:** 192.168.1.5

Buttons for 'SAVE' and 'CANCEL' are present at the bottom of the form.

Creating the alert pipe on PacketFence

WARNING

If using a PacketFence cluster, these steps will need to be done on all the PacketFence servers.

First, logon to PacketFence Server with a ssh terminal, then create the fifo pipe file that PacketFence will use to get data from Rapid7.

```
mkfifo /usr/local/pf/var/run/nexpose_pipe
```

Create a new file named /etc/rsyslog.d/nexpose-log.conf with the following content

```
# rsyslog conf for Rapid7 Nexpose server logs reception
if $programname == 'Nexpose' then /usr/local/pf/var/run/nexpose_pipe
& ~
```

Next, modify /etc/rsyslog.conf to accept syslogs data on 'udp 514' by uncommenting the following two lines:

```
$ModLoad imudp
$UDPServerRun 514
```

Restart the 'rsyslog' service


```
service rsyslog restart
```


At this point PacketFence must be able to get the Rapid7 audit results via syslog.

TIP

To see if the Nexpose server is sending to the right server, monitor the traffic using `tcpdump -i any dst host PACKETFENCE_SERVER_IP` on the Rapid7 Nexpose server and `tcpdump -i any src host RAPID7_IP` on the PacketFence server.

Creating the event handler

In the PacketFence admin interface, go to *Configuration* → *Integration* → *Event Handlers* and add a new Nexpose event handler



- As Detector, put the name chosen for this parser.
- In Alert pipe, put the 'absolute' path to our nexpose pipe (`/usr/local/pf/var/run/nexpose_pipe` if the same name as above was used)

Once done, restart the following services

```
/usr/local/pf/pfcmd service pfdetect restart  
/usr/local/pf/pfcmd service pfqueue restart
```

Now that PacketFence is properly configured to receive information from Nexpose, we can configure it to perform some actions on the alerts it receives. In the PacketFence admin interface, go to *Configuration* → *Compliance* → *Security Events* and create a new security event.

Make sure to set the following parameters in the 'Definition' tab:

- Enable: Set it to **ON**
- Action: This is where to put what PacketFence should do, refer to the security events

documentation in this guide for details on these.

Next, in the 'Triggers' tab:

- Click on the plus (+), on the right side of the page.
- On the second line, choose the appropriate trigger between "**nexpose_event_contains**" or "**nexpose_event_start_with**"
- Choose "**nexpose_event_contains**" if knowing, for example, the "**Common Vulnerabilities and Exposures**" to take action on.
- For "**nexpose_event_contains**": Put there the CVE or the vulnerability name to look for.
- For "**nexpose_event_start_with**": Put there the full vulnerability name that can be found in the Nexpose report, on the Nexpose GUI
- Click on **ADD**, then **SAVE**

The screenshot displays the 'New Security Event' configuration interface. On the left, a sidebar lists navigation options under 'Policies and Access Control' and 'Compliance'. The main area contains a form with the following fields:

- Enable security event:** A toggle switch that is currently turned on.
- Identifier:** A text field containing the value '3000006'.
- Description:** An empty text field.
- Priority:** A text field containing the value '4'. Below it, a note states: 'When multiple violations are opened for an endpoint, the one with the lowest priority takes precedence.'
- Ignored Roles:** A text field.
- Event Triggers:** A section with a dropdown menu showing 'Nexpose event starts with ..' and 'CVE'. Below this, a logic builder shows a sequence of conditions: 'No condition' AND 'All device types' AND 'Any data usage' AND 'Nexpose event starts with ... CVE'.

A modal window titled 'Event' is open, showing a dropdown menu with 'Nexpose event starts with ..' and 'CVE'. Below the modal, a logic builder shows a sequence of conditions: 'No condition' AND 'All device types' AND 'Any data usage' AND 'Nexpose event starts with ... CVE'.

For more info on security event actions, go to the *Blocking malicious activities with security events* section of this guide.

21. Integrating Provisioning Agents

21.1. PacketFence Apple, Android and Windows Wireless Provisioning

Provisioners enable automatic device configuration for proper SSID connection, authentication method (e.g., EAP-TLS), and CA certificate trust.

Apple devices (iPhones, iPads, iPods, Mac OS X 10.7+) support wireless profile importation via mobileconfig XML format. Android supports this through Android PacketFence Agent profile import. Installing files automatically configures wireless settings for given SSID, simplifying manual configuration for hidden SSIDs. PacketFence generates profiles per administrator preferences, pre-populating user credentials (excluding password). Users install generated file to use new SSID.

Windows agent imports and applies provisioned profile; users only enter username and password.

21.1.1. Configure the feature

NOTE

If EAP-TLS provisioning is desired, you have to configure a PKI before going any further. See [PacketFence PKI](#) for details.

Configure SSID for devices after authentication.

In administration interface: *Configuration* → *Advanced Access Configuration* → *Provisioners*. Select 'android'/'ios'/'Windows' provisioner. Enter SSID information and applicable roles. Repeat for desired provisioners. Default RADIUS certificate path: [/usr/local/pf/raddb/certs/server.crt](#).

Add 'Android', 'iOS' and 'Windows' provisioners to 'Connection Profile' configuration. If no profile defined, configure 'default' connection profile with created provisioners.

NOTE

For different connection profiles (open/secure networks), configure provisioners on both profiles.

Add provisioner for other device classes: click [Add Provisioner](#), complete form with different Provisioning ID per provisioner.

- **Roles:** Defines affected devices; if empty, affects all devices for this class.
- **SSID:** Defines SSID configured on device using authentication profile.
- **EAP-Type:** Authentication method; set to EAP-TLS for PacketFence PKI integration.
- **Security type:** Set to WPA2-Enterprise for PacketFence PKI integration.
- **PKI Provider:** Must match provider configured in PKI provider section.

Configure provisioning SSID (e.g., [OnBoarding-PF](#)) open with MAC Authentication pointing

to PacketFence. Create **New Portal Profile**, add **filter SSID** with SSID name, add authentication source and provisioners. Logged-in users follow captive portal instructions to receive certificates.

Android specifications

For Android provisioning support, you must activate and adjust the passthroughs. You might need to adapt them depending on your geolocality.

NOTE | Please refer to the 'Passthroughs' section of this guide if needed.

In the administration interface, go in *Configuration* → *Network Configuration* → *Networks* → *Fencing*. Activate 'Passthrough' and make sure the following passthroughs domains are present:

```
*.ggpht.com,*.*googleusercontent.com,android.clients.google.com,*.*googleapis.com
,*.*android.clients.google.com,*.*gvt1.com,*.*l.google.com,play.google.com,*.*gstatic.com
```

Then run the following commands so that passthroughs become effective:

```
/usr/local/pf/bin/pfcmd configreload hard
/usr/local/pf/bin/pfcmd service pfdns restart
```

Next, make sure you are using a valid SSL certificate on your captive portal since Android devices will only be able to be provisioned on a captive portal that uses valid HTTPS

NOTE | Some Android devices may use their cellular connection when running the PacketFence agent during the onboarding process. If that is the case, enable the airplane mode on the Android device and then only enable WiFi during the onboarding process.

iOS specifications

Mac OS X/iOS require the provisioning profile to be signed if you want to remove the **untrusted** warning when installing the profile. For more information, please refer to the PKI guides referred earlier in 'Configure the feature' above.

Other Corporate Devices

Let's say that you now need to add some 'Linux computers' as 'corporate' devices.

Those devices cannot be authenticated via Machine Authentication, so we will need to use EAP-TLS and provide those devices with a certificate.

First of all make sure that your RADIUS certificate from the PacketFence server and the certificates that you will be provided are delivered from the same CA, else your authentication will not work. To enable EAP-TLS you will need to reconfigure the new RADIUS server certificate in the file `conf/radiusd/eap.conf`.

While creating the RADIUS server certificate make sure to have the **Extended key usage:**

servAuth.

Under the section `tls-config` `tls-common`, search for ``private_key_file'`, ``certificate_file'` and ``ca_file'`. Those should contain respectively the path of:

- the private key for your PacketFence server,
- the server certificate issued by your CA for your PacketFence server,
- the public key of your CA.

If you have an `OCSP` capable PKI you can configure it in the section `OCSP` in the `eap.conf` file.

Lastly you will need to restart RADIUS to ensure the use of the new configuration and certificates. Please do the following:

```
/usr/local/pf/bin/pfcmd configreload hard
/usr/local/pf/bin/pfcmd service radiusd restart
```

Make sure everything happens without errors.

Now that your RADIUS is ready to handle EAP-TLS, configure your SSID connection profile on the `corporate` device using this method. Generate a client certificate for your device and install it on.

Please configure an EAPTLS source which can be found while adding a new sources under *Configuration → Policies and Access Control → Authentication Sources* `New internal Source` `EAPTLS`, simply give it a name, a description and a catch-all rule. This will allow you to validate the authentication via EAP-TLS.

You can now create a new Portal Profile for EAP-TLS. Under the tab configuration, section *Configuration → Policies and Access Control → Connection Profiles*, `New Connexion Profile` and select as a filter the Sub Connection Type as EAP-TLS, add your source EAP-TLS. Check the box "Automatically register devices".

You now have a full flow working for your corporate devices.


The following is an example on how to configure an EAP-TLS connection for Windows/Android/Mac OS X/iOS

The screenshot shows the 'New Provisioner' configuration window in the Akamai dashboard. The window is titled 'New Provisioner' with a 'windows' tab. The left sidebar contains a navigation menu with categories: Policies and Access Control, Compliance, Integration, Advanced Access Configuration, Captive Portal, Filter Engines, Billing Tiers, PKI Providers, Provisioners, Portal Modules, Access Duration, Self Service Portal, Network Configuration, and System Configuration. The main configuration area includes the following fields:

- Provisioning ID:** EAPTLS
- Description:** Windows EAP-TLS
- Roles:** default (with a dropdown arrow and a note: 'Nodes with the selected roles will be affected.')
- SSID:** PF-Secure
- Broadcast network:** A toggle switch is turned on, with a note: 'Uncheck this box if you are using a hidden SSID.'
- Security type:** WPA2 (with a dropdown arrow and a note: 'Select the type of security applied for your SSID.')
- EAP type:** EAP-TLS (with a dropdown arrow and a note: 'Select the EAP type of your SSID. Leave empty for no EAP.')
- PKI Provider:** MS-SCEP (with a dropdown arrow)

At the bottom of the window, there are two buttons: 'Create' (in blue) and 'Reset' (in white).

Mac OS X/iOS require the provisioning profile to be signed if you want to remove the **untrusted** warning when installing the profile. You need to sign it with a Certification Authority already trusted by the device such as e.g. VeriSign. Configuring this has to be done in the 'Signing' tab in the "Apple devices".



21.1.2. Profile generation

Upon registration, instead of showing the default release page, the user will be showing another version of the page saying that the wireless profile has been generated with a clickable link on it. To install the profile, Apple user owner simply need to click on that link, and follow the instructions on their device. Android user owner simply click to the link and will be forwarded to Google Play to install PacketFence agent. Simply launch the application and click to configure will create the secure SSID profile. It is that simple.

21.2. MobileIron

21.2.1. Configure MobileIron

First of all you will need to configure the basic functionality of MobileIron using their documentation.

MDM profile

One important step is to enable the MDM profile like in this screenshot. Note that this will require you to create an MDM certificate with Apple. Refer to the MobileIron documentation for specifics about this step.

MobileIron
ADMIN PORTAL

DASHBOARD USERS & DEVICES ADMIN APPS POLICIES & CONFIGS **SETTINGS** LOGS & EVENTS

Preferences Sentry Connector LDAP Operators Local CA Service Diagnostics Templates ▾

Remove Wi-Fi Settings

- ☐ Remove Wi-Fi settings for cellular-enabled devices
- ☐ Remove Wi-Fi settings for cellular-enabled and Wi-Fi only devices
- ☒ Clear passcode

APNs Preferences

☐ Use Enterprise Issued APNs certificate ⓘ
[View Certificate](#)

MDM Preferences

- ☒ Enable MDM Profile
- ☒ View MDM Alerts
- ☒ Enable Profile Encryption
- ☒ Permit expired client certificates [MDM Certificate Report](#)
- ☒ Enable MDM for iOS 4.1 and greater ⓘ
[Install MDM Certificate](#) [View Certificate](#)

Save User Password Preferences

Save User Password: ☐ Yes ☒ No

Registration PIN code Preferences

Passcode Length: (6-12)

[Save](#) [Cancel](#)

21.2.2. Create an API user

Next, we will need a user that has the rights to access the MobileIron API in order to verify the state of the devices directly from PacketFence.

First go in the 'USERS & DEVICES' tab and then in 'Users' and click 'Add local user'.

MobileIron ADMIN PORTAL

DASHBOARD **USERS & DEVICES** ADMIN APPS POLICIES & CONFIGS SETTINGS LOGS & EVENTS

Devices ActiveSync Associations Labels **Users**

Actions Add Resync With LDAP

EDIT Add Local User

		USER ID	EMAIL	CREATION DATE
☐ ☐	admin	admin	address@domain.com	2014-07-31 5:17:39 PM
☐ ☐	julien semaan	julien	jsemaan@inverse.ca	2014-08-06 1:28:26 PM
☐ ☐	zammit	zammit	zammit@zammit.com	2014-08-15 11:16:40 AM

https://m.mobileiron.net/inverseca/admin/vsp.html#

Now enter the information about your user and note the user ID and password for usage in the PacketFence configuration, then hit 'Save'.

ARD **USERS & DEVICES** ADMIN APPS POLICIES & CONFIGS SETTINGS LOGS & EVENTS

is ActiveSync Associations Labels **Users**

To Authorized Users

USER ID

admin

julien

pfapi

zammit

per page

Add New User

User ID pfapi

First Name pf

Last Name api

Display Name

Password *****

Confirm Password *****

Email pfapi@example.com

Save

SOURCE ROLES

Local User Portal


Local User Portal

Local User Portal

Local User Portal

Now go in the 'ADMIN' tab, check the box next to your newly created user and then in

'Actions' select 'Assign to Space'.



The screenshot shows the MobileIron Admin Portal interface. The top navigation bar includes 'DASHBOARD', 'USERS & DEVICES', 'ADMIN' (highlighted), 'APPS', 'POLICIES & CONFIGS', 'SETTINGS', and 'LOGS & EVENTS'. Below this, there are tabs for 'ADMINS' and 'DEVICE SPACES'. The 'ADMINS' tab is active, displaying a table of users. The 'Actions' dropdown menu is open, showing 'Edit Roles' and 'Assign to Space'. The table lists the following users:

	USER ID	EMAIL	SOURCE	ROLES
☐	admin	address@domain.com	Local	API, Add de
☐	julien semaan	jsemaan@inverse.ca	Local	
☒	pf api	pfapi@inverse.ca	Local	
☐	zammit	zammit@zammit.com	Local	


The URL at the bottom of the browser is <https://m.mobileiron.net/inverseca/admin/vsp.html#>.

Select the Global space at the top and then check API at the bottom. You should now see API in the roles list of your newly created user when viewing the users list.

21.2.3. Gather the boarding host

To find the boarding host, add a fake device to MobileIron and at the end of the process you will see the registration instructions.

In it you will find the boarding host and port for the PacketFence configuration. In this case, the boarding host is **m.mobileiron.net** and the boarding port is **50291**.



The screenshot shows the MobileIron Admin Portal interface with the 'USERS & DEVICES' tab selected. A modal window titled 'Registration instructions for: zammit' is displayed. The instructions state: 'An SMS containing a link to the registration page has been sent to'. It also mentions that if the 'Email User' option was selected, an email containing registration instructions would be received. The following information is provided:

- Server Address: m.mobileiron.net:50291
- User Name: zammit
- Password: your password

If the text message does not arrive or the recipient is not able to follow the link, the recipient should go directly to the following site using the device's web browser:

<https://m.mobileiron.net/inverseca/cid/android.html>

The modal window has an 'OK' button at the bottom right.

21.2.4. Configure PacketFence

In PacketFence, MDM are referred to as provisioners. This will walk you through adding MobileIron as a provisioner.

Create the provisioner

Login to the admin interface, then go to *Configuration* → *Advanced Access Configuration* → *Provisioners*. Click 'Add provisioner' then select 'mobileiron'.

The screenshot shows the Akamai Provisioning Agent configuration interface. The top navigation bar includes links for Status, Reports, Auditing, Nodes, Users, and Configuration. The Configuration tab is active, showing a sidebar with various configuration categories: Policies and Access Control, Compliance, Integration, Advanced Access Configuration, Captive Portal, Filter Engines, Billing Tiers, PKI Providers, Provisioners, Portal Modules, Access Duration, Self Service Portal, Network Configuration, and System Configuration. The main content area displays the configuration for a provisioner named 'mobileiron'. The configuration fields are as follows:

Field	Value
Provisioning ID	mobileiron
Description	Mobile Iron
Roles	(Empty dropdown)
OS	Type to search. (Empty dropdown)
Username	admin
Client Secret	*****
Host	m.mobileiron.ca/inverseca
Android download URI	https://m.mobileiron.net/accountName/c/d/android.html
IOS download URI	https://m.mobileiron.net/accountName/c/d/ios.html
Windows phone download URI	https://m.mobileiron.net/accountName/EnrollmentServer/Discovery.svc
Boarding host	m.mobileiron.net
Boarding port	50291

At the bottom of the configuration form, there are four buttons: Save, Reset, Clone, and Delete.

Now configure this new provisioner with the information you got above.

- The Provisioning ID is the friendly name of the provisioner.
- The Username is the user you created with API access above.
- The password is the password of the API user.

- The host is the domain name of the instance + your account name if you have a cloud account (ex: m.mobileiron.net/accountName)
- Now add the download URI for the agent. See below for more details.
- The Boarding host is the host that you got in step 3.
- The Boarding port is the port that you got in step 3.

Here are the URIs that should work by default. Replace [accountName](#) by your real account/instance name at MobileIron.

- Android: <https://m.mobileiron.net/accountName/c/d/android.html>
- IOS devices: <https://m.mobileiron.net/accountName/c/d/ios.html>
- Windows: <https://m.mobileiron.net/accountName/EnrollmentServer/Discovery.svc>

Add the provisioner to the connection profile

In order for the provisioner to be used by your captive portal you need to add it in its configuration. Go in 'Connection Profiles', then select the portal you want to modify and add 'mobileiron' as a provisioner.

[Status](#)
[Reports](#)
[Auditing](#)
[Nodes](#)
[Users](#)
[Configuration](#)

[API](#)
[dashboard](#)
admin

Policies and Access Control

Roles

Domains

Active Directory Domains

Realms

Authentication Sources

Network Devices

Switches

Switch Groups

Connection Profiles

Compliance

Integration

Advanced Access

Configuration

Network Configuration

System Configuration

Connection Profile default
Preview

Settings
Captive Portal
Files

Profile Name
default

A profile id can only contain alphanumeric characters, dashes, period and or underscores.

Profile Description
Default Profile

Root Portal Module
Default portal policy

The Root Portal Module to use.

Activate preregistration

This activates preregistration on the connection profile. Meaning, instead of applying the access to the currently connected device, it displays a local account that is created while registering. Note that activating this disables the on-site registration on this connection profile. Also, make sure the sources on the connection profile have "Create local account" enabled.

Automatically register devices

This activates automatic registration of devices for the profile. Devices will not be shown a captive portal and RADIUS authentication credentials will be used to register the device. This option only makes sense in the context of an 802.1x authentication.

Reuse dot1x credentials

This option emulates SSO when someone needs to face the captive portal after a successful 802.1x connection. 802.1x credentials are reused on the portal to match an authentication and get the appropriate actions. As a security precaution, this option will only reuse 802.1x credentials if there is an authentication source matching the provided realm. This means, if users use 802.1x credentials with a domain part (username@domain, domain/username), the domain part needs to be configured as a realm under the RADIUS section and an authentication source needs to be configured for that realm. If users do not use 802.1x credentials with a domain part, only the NULL realm will be match IF an authentication source is configured for it.

Dot1x recompute role from portal

When enabled, PacketFence will not use the role initially computed on the portal but will use the dot1x username to recompute the role.

MAC Auth recompute role from portal

When enabled, PacketFence will not use the role initially computed on the portal but will use an authorized source if defined to recompute the role.

Dot1x unset on unmatched

When enabled, PacketFence will unset the role of the device if no authentication sources returned one.

Enable DPSK

This enables the Dynamic PSK feature on this connection profile. It means that the RADIUS server will answer requests with specific attributes like the PSK key to use to connect on the SSID.

Default PSK key

This is the default PSK key when you enable DPSK on this connection profile. The minimum length is eight characters.

Automatically deregister devices on accounting stop

This activates automatic deregistration of devices for the profile if PacketFence receives a RADIUS accounting stop.

VLAN pool technique
username_hash

The algorithm used to calculate the VLAN in a VLAN pool.

Sources
1
null

Billing Tiers
Add Billing Tier
With no billing tiers specified, all billing tiers will be used.

Provisioners
1
mobileiron

Scanners
Add Scanner
With no scan specified, the scan engine will not be triggered.

Self service policy

Save
Reset
Clone

21.2.5. Add the necessary passthroughs

Next, still in the PacketFence administration console, go in 'Fencing' in the left menu, then scroll then to 'Passthroughs'.

Check the 'Passthrough' box above the field and add the following domains to the passthrough list.

- m.mobileiron.net
- *.itunes.apple.com
- itunes.apple.com
- play.google.com
- *.play.google.com

Status
Reports
Auditing
Nodes
Users
Configuration

API
dashboard
admin

Filter

Policies and Access Control
Compliance
Integration
Advanced Access Configuration
Network Configuration

Networks
Network Settings
Interfaces
Inline
Inline Traffic Shaping
Fencing
Device Parking
SNMP
Floating Devices
System Configuration

Networks

Network Settings
Interfaces
Inline
Inline Traffic Shaping
Fencing
Device Parking

Fencing

Wait for redirect
1

How many seconds the webservice should wait before deassociating or reassigning VLAN. If we don't wait, the device may switch VLAN before it has a chance to load the redirection page.

Whitelist

Comma-separated list of MAC addresses that are immune to isolation. In inline Level 2 enforcement, the firewall is opened for them as if they were registered. This feature will probably be reworked in the future.

Addresses ranges

Address ranges/CIDR blocks that PacketFence will monitor/detect/trap on. Gateway, network, and broadcast addresses are ignored. Comma-separated entries should be of the form a.b.c.0/24 a.b.c.0-255 a.b.c.0-a.b.c.255 a.b.c.d

Passthrough

When enabled, PacketFence uses pfdns if you defined Passthroughs or Apache mod-proxy if you defined Proxy passthroughs to allow trapped devices to reach web sites. Modifying this parameter requires to restart pfdns and iptables to be fully effective.

Passthroughs Domains
m.mobileiron.net

Comma-separated list of domains to allow access from the registration VLAN. If no port is specified for the domain (ex: example.com), it opens TCP 80 and 443. You can specify a specific port to open (ex: example.com:tcp:25) which opens port 25 in TCP. When no protocol is specified (ex: example.com:25), this opens the port for both the UDP and TCP protocol. You can specify the same domain with a different port multiple times and they will be combined. The configuration parameter passthrough must be enabled for passthroughs to be effective. These passthroughs are only effective in registration networks, for passthroughs in isolation, use fencing.isolation_passthroughs.

Proxy Passthroughs

Built-in Proxy Passthroughs:
crl.geotrust.com
ocsp.geotrust.com
crl.thawte.com
ocsp.thawte.com
crl.comodoca.com
ocsp.comodoca.com
crl.incommon.org
ocsp.incommon.org
crl.usertrust.com
ocsp.usertrust.com
mscrl.microsoft.com
crl.microsoft.com
ocsp.apple.com
ocsp.digicert.com
ocsp.entrust.com
svintl-crl.verisign.com
ocsp.verisign.com
crl.windowsupdate.com
crl.globalsign.net
pki.google.com
www.microsoft.com
crl.godaddy.com
ocsp.godaddy.com
certificates.godaddy.com
crl.globalsign.com
secure.globalsign.com
cacerts.digicert.com
crl.comodoca.com
crl.incommon-rsa.org
crl.quovadisglobal.com
crl.incommon.org
crl.usertrust.com
crl.verisign.com
crl.starfieldtech.com
developer.apple.com
ts-crl.ws.symantec.com
certificates.intel.com

m.mobileiron.net
*.itunes.apple.com
itunes.apple.com
play.google.com
*.play.google.com

Comma-separated list of domains to be used with apache passthroughs. The configuration parameter passthrough must be enabled for passthroughs to be effective.

Isolation Passthrough

When enabled, PacketFence uses pfdns if you defined Isolation Passthroughs to allow trapped devices in isolation state to reach web sites. Modifying this parameter requires to restart pfdns and iptables to be fully effective.

Isolation Passthroughs Domains

Comma-separated list of domains to allow access from the isolation VLAN. If no port is specified for the domain (ex: example.com), it opens TCP 80 and 443. You can specify a specific port to open (ex: example.com:tcp:25) which opens port 25 in TCP. When no protocol is specified (ex: example.com:25), this opens the port for both the UDP and TCP protocol. You can specify the same domain with a different port multiple times and they will be combined. The configuration parameter isolation_passthrough must be enabled for passthroughs to be effective.

Proxy Interception

If enabled, we will intercept proxy request on the specified ports to forward to the captive portal.

Proxy Interception Port
8080
3128

Comma-separated list of port used by proxy interception.

Save
Reset
● pfdns
● iptables

Copyright © Akamai Technologies Canada Inc. Integrating Provisioning Agents

198

Restart PacketFence

Then run the following commands so that passthroughs become effective:

```
/usr/local/pf/bin/pfcmd configreload hard
/usr/local/pf/bin/pfcmd service pfdns restart
```

21.2.6. Testing

You can now test that MobileIron is mandatory after the device registration. Connect a device to your test network and register like you normally would. At the end of the registration process you will be presented a page asking you to install the MobileIron on your device. After you install the agent click 'Continue'. If your access is enabled than this means the connectivity between PacketFence and MobileIron is good.

21.3. SentinelOne

21.3.1. Download the agents

You will first need to download the SentinelOne agents in order to host them on the PacketFence server.

In order to do so, in your SentinelOne management console, go in 'Settings→Updates', then download the Windows and Mac OSX agents on your computer. Once they have been download transfer them on your PacketFence server using SCP. This example will use `/usr/local/pf/html/common/SentinelOne.exe` as the Windows agent path and `/usr/local/pf/html/common/SentinelOne.pkg` as the Mac OSX agent path.

PLATFORM	FILENAME	SIZE	SHA1
Windows	SentinelOne_windows_v1.8.4	62.79 MB	4327911a2...
Windows	SentinelOne_windows_v1.8.4	61.91 MB	23ba07ba...
OS X	SentinelOne_osx_v1.8.4_20s	2.91 MB	7c3b8a6b8...

NOTE

All files in `/usr/local/pf/html/common/` are accessible to users that are on the captive portal. Make sure you put the agents file there or in another user-

accessible location.

21.3.2. Create an API user

PacketFence will need a user on your SentinelOne instance in order to access the SentinelOne API. To create it, go in 'Settings→Users' and create a new user. Make sure, you note the password you put here for configuration in PacketFence.

The screenshot shows the SentinelOne web interface. On the left is a dark sidebar with navigation links: Dashboard, Activity, Analyze, Network, Black / White, Reports, and Settings (highlighted with a gear icon). At the bottom of the sidebar is the copyright notice: "© 2017 SentinelOne. All rights reserved. Version: v1.8.4k25". The main content area is titled "SETTINGS" and has a sub-header "USERS". Below this is a table with two columns: a list of users (each with a black square icon and the name "Admin") and a "DETAILS" column. The "DETAILS" column for the selected user shows the following fields: Username (packetfence), Full name (packetfence), Email (packetfence@example.com), Role (Admin), Password (masked with asterisks), and Confirm password (masked with asterisks). To the right of the form are three sections of explanatory text: "User Details" (explaining Username, Full name, and Role), "Password" (stating it must be at least 8 characters long), and "API Token" (explaining its use for REST API clients). At the bottom right of the form are "CANCEL" and "CREATE" buttons. The top right of the interface shows the user "julien" and a search icon.

21.3.3. Configure PacketFence

Create a new provisioner

Login to the admin interface, then go to *Configuration → Advanced Access Configuration → Provisioners*. Click 'Add provisioner' then select **SentinelOne**.

The screenshot displays the 'New Provisioner' configuration window in the PacketFence management interface. The left sidebar shows the navigation menu with 'Advanced Access Configuration' expanded. The main form contains the following fields:

- Provisioning ID:** sentinelone
- Description:** SentinelOne
- Roles:** (empty dropdown menu)
- OS:** (empty dropdown menu with placeholder text 'Type to search.')
- Host:** packetfence.sentinelone.net
- Port:** 443
- Protocol:** https
- API username:** packetfence
- API password:** (masked with dots and an eye icon for toggling visibility)
- Windows agent download URI:** /common/SentinelOne.exe
- Mac OSX agent download URI:** /common/SentinelOne.pkg

At the bottom of the form are two buttons: 'Create' (in blue) and 'Reset' (in white).

Where:

- 'Provisioning ID' is the user-defined identifier of the provisioner.
- 'Description' is a user friendly description of the provisioner.
- 'Host' is the hostname of your SentinelOne instance.

- 'Port' should be left to default unless your SentinelOne management console is on another port.
- 'API username' is the username of the user you created above in SentinelOne.
- 'API password' is the password of the API user.
- 'Windows agent download URI' is the URI on which the users should download the Windows agent. If you followed the path in this guide, it should be [/common/SentinelOne.exe](#).
- 'Mac OSX agent download URI' is the URI on which the users should download the Mac OS agent. If you followed the path in this guide, it should be [/common/SentinelOne.pkg](#).

Add the provisioner to the profile

Now that you have created the provisioner, go in the 'Connection Profiles' menu on the left and select the default connection profile. Click 'Add Provisioner' and select the new SentinelOne that was created earlier.

NOTE Make sure you have passthroughs enabled before proceeding further. Instructions on how to enable passthroughs can be found in the 'Passthroughs' section of the Administration Guide.

Once you have completed the configuration, you need to restart pfdns in order for the SentinelOne specific passthroughs to be taken into consideration.

```
# /usr/local/pf/bin/pfcmd service pfdns restart
```

21.3.4. Testing

You can now test that the installation of the SentinelOne client is mandatory after the device registration. Connect a device to your test network and register like you normally would. At the end of the registration process you will be presented a page asking you to install the SentinelOne client on your device. After you install the client click continue. If your access is enabled then this means the connectivity between PacketFence and SentinelOne is good.

PacketFence polls SentinelOne at a regular interval (30 seconds by default) to find devices that have uninstalled their agent. When it detects them as uninstalled, it automatically brings the device back to the portal so the agent is installed.

Everytime your device connects to PacketFence using RADIUS, it schedules a provisioning check to occur 2 minutes after the connection (controlled via security event 1300002). If the agent is inactive on the device or was uninstalled, PacketFence will bring the device back to the portal so the agent is installed again or brought back to an active state.

21.4. Microsoft Intune


21.4.1. Configure from the Azure portal

Connect to Azure portal and verify Intune licenses.

Creating the application

After portal login, create application to allow Graph API access.

Click 'Azure Active Directory' > 'App registrations' > 'New registration'



Set application name (e.g., PacketFence), choose 'Supported account types': 'Accounts in this organizational directory only', click 'Register'

Register an application

*** Name**
The user-facing display name for this application (this can be changed later).

PacketFence ✓

Supported account types
Who can use this application or access this API?

☒ Accounts in this organizational directory only (Inverse inc)

☐ Accounts in any organizational directory

☐ Accounts in any organizational directory and personal Microsoft accounts (e.g. Skype, Xbox, Outlook.com)

[Help me choose...](#)

Redirect URI (optional)
We'll return the authentication response to this URI after successfully authenticating the user. Providing this now is optional and it can be changed later, but a value is required for most authentication scenarios.

Web ▼ e.g. <https://myapp.com/auth>

On next page, copy 'Application (client ID)' and 'Directory (tenant ID)' (needed for provisioner definition).


PacketFence

«

🗑️ Delete
🌐 Endpoints

 Overview
  Quickstart

Manage
 Branding
  Authentication
  Certificates & secrets
  API permissions


 Welcome to the new and improved App registrations. Looking

Display name : [PacketFence](#)
 Application (client) ID : 724cad4f-4d1c-4970-b405-e4bd6f9475ab
 Directory (tenant) ID : 5c21efa5-a2ab-4ce4-96fd-1fad347ebcab
 Object ID : 838f146f-f4a9-466e-af0d-71538ab63621

Click 'Certificates & secrets' > 'New client secret' for application password (save immediately; won't be available later).

Home > Inverse inc - App registrations > PacketFence - Certificates & secrets

PacketFence - Certificates & secrets

Search (Ctrl+/)

- Overview
- Quickstart
- Manage
 - Branding
 - Authentication
 - Certificates & secrets**
 - API permissions
 - Expose an API
 - Owners
 - Roles and administrators (Previ...
 - Manifest
- Support + Troubleshooting
 - Troubleshooting
 - New support request

Copy the new client secret value. You won't be able to retrieve it after you leave this blade.

Credentials enable applications to identify themselves to the authentication service when receiving tokens at a web addressable location (using an HTTPS scheme). For a higher level of assurance, we recommend using a certificate (instead of a client secret) as a credential.

Certificates

Certificates can be used as secrets to prove the application's identity when requesting a token. Also can be referred to as public keys.

[Upload certificate](#)

No certificates have been added for this application.

THUMBPRINT	START DATE	EXPIRES
------------	------------	---------

Client secrets

A secret string that the application uses to prove its identity when requesting a token. Also can be referred to as application password.

[New client secret](#)

DESCRIPTION	EXPIRES	VALUE
Password uploaded on Thu Aug 01 2019	12/31/2299	POWOJL7ciWxdTpko1dEuC/hMJ8S3:5+j

Add API permissions: click 'API permissions' > 'Microsoft Graph', select 'Application permissions', add:


```
Device.ReadWrite.All
DeviceManagementManagedDevices.Read.All
```

And click on 'Grant admin consent for (Name of your app)'

21.4.2. Configure PacketFence

Create a new provisioner

Login to the admin interface, then go to *Configuration* → *Advanced Access Configuration* → *Provisioners*. Click 'Add provisioner' then select Microsoft Intune.




Now configure this new provisioner with the information you got above.

- The Provisioning ID is the friendly name of the provisioner.
- The Application ID is the 'Application (client ID)'.
- The Application Secret is the 'Client secret'.
- The Tenant ID is the 'Directory (tenant ID)'.
- The Client Secret is the secret of the application you created in the developer account.
- The default host should work.
- The default Login URL should work.
- The port and protocol should be left to default.
- The 'Agent download URI' should be ok.
- Authorized domains need to be adapted to allow the device to reach the download URI (per example google play needs multiple domains to be able to install the agent).

Add the provisioner to the profile

Now that you have created the provisioner, go in the 'Connection Profiles' menu on the left and select the default portal. Click 'Add Provisioner' and select the new Microsoft Intune provisioner that was created earlier.



The screenshot shows a configuration interface for Provisioners. It includes sections for Sources, Billing Tiers, Provisioners, and Scanners. The Provisioners section shows a list with one entry: 'Intune'. There are buttons for 'Add Source', 'Add Billing Tier', and 'Add Scanner'. Below the Provisioners section is a 'Device registration' dropdown menu.

21.4.3. Testing

You can now test that the installation of the Microsoft Intune client is mandatory after the device registration. Connect a device to your test network and register like you normally would. At the end of the registration process, you will be presented a page asking you to install the Intune client on your device. After you install the client click continue. If your access is enabled then this means the connectivity between PacketFence and Azure is good.

21.5. Google Chromebook Provisioner

21.5.1. Creating a service account JSON config

In order to communicate with the Google API you must configure a service account, and download JSON security keys, and create a user to impersonate with the proper permissions.

These instructions have been adapted from <https://developers.google.com/identity/protocols/oauth2/service-account>.

- Open the Service accounts page <https://console.developers.google.com/iam-admin/serviceaccounts>.
- If prompted, select a project, or create a new one.
- Click add Create service account.
- Under Service account details, type a name, ID, and description for the service account, then click Create.
- Click on the newly created service account.
- Click on SHOW DOMAIN-WIDE DELEGATION
- Select Enable Google Workspace Domain-wide Delegation
- Save
- Copy the Client ID provided
- Click on Keys > Add Key > Create New Key > Key Type JSON > Create.
- Note where the JSON file is stored.

21.5.2. Delegating domain-wide authority to the service account

- Go to <https://admin.google.com/> click on the Main Menu > Security > API Controls.
- Scroll down to the Domain wide delegation pane, select Manage Domain Wide Delegation.
- Click Add new.
- In the Client ID field, enter the newly created service account's Client ID.
- In the OAuth scopes (comma-delimited) field, enter the scope <https://www.googleapis.com/auth/admin.directory.device.chromeos.readonly>
- Click Authorize.

21.5.3. Create Role

- Go to <https://admin.google.com/> click on the Main Menu > Account > Admin roles.
- Click 'Create new role'
- Enter Name and Description click 'CONTINUE'
- Search for the Admin console privilege 'Manage Chrome OS Devices (read only)'
- Select 'Manage Chrome OS Devices (read only)' then click 'CONTINUE'
- Click 'CREATE ROLE'

21.5.4. Create a user if needed.

- Go to <https://admin.google.com/> click on the Main Menu > Directory > Users.
- Click 'Create new user'
- Enter First Name, Last Name and Primary email. then click 'ADD NEW USER'.

21.5.5. Assign Role to a user.

- Go to <https://admin.google.com/> click on the Main Menu > Directory > Users.
- Select user for service account
- Click 'Admin roles and privileges'
- Assign the Role previously created.

21.6. Configure PacketFence

21.6.1. Create a new provisioner

Login to the admin interface, then go to *Configuration* → *Advanced Access Configuration* → *Provisioners* → *New provisioner* → *Google Workspace Chromebook*.

New Provisioner Google Workspace Chromebook ✕

Provisioning ID ID required.

Description

Enforce ☐ Disabled
Whether or not the provisioner should be enforced. This will trigger checks to validate the device is compliant with the provisioner during RADIUS authentication and on the captive portal.

Auto register ☐ Disabled
Whether or not devices should be automatically registered on the network if they are authorized in the provisioner.

Apply role ☐ Disabled
When enabled, this will apply the configured role to the endpoint if it is authorized in the provisioner.

Role to apply
When 'Apply role' is enabled, this defines the role to apply when the device is authorized with the provisioner.

Roles
Nodes with the selected roles will be affected.

OS
Nodes with the selected OS will be affected.

Non compliance security event
Which security event should be raised when non compliance is detected.

User
User the service account will impersonate.

Service Account JSON data

Service Account JSON data

Now configure this new provisioner with the information you got above.

- The Provisioning ID is the friendly name of the provisioner.
- User for service account to impersonate.
- The JSON security keys for Service Account created.

21.7. Kandji

21.7.1. Configure Kandji

First of all you will need to configure the basic functionality of Kandji using their documentation and enable a blueprint to apply on your devices.

21.7.2. Create an API token

Next, we will need a user that has the rights to access the Kandji API in order to verify the state of the devices directly from PacketFence.

In the Kandji admin panel, first go in the 'Settings' tab and then in 'Access'.

Note down the value of **Your organization's API URL** for usage in the PacketFence configuration.

Now, click 'Add token' under 'API token'.

Create your API token by giving it a meaningful name and you will then be presented the API token

Note the API token for usage in the PacketFence configuration, then hit 'Next'.

21.7.3. Configure the API permissions

After creating your API token, you will be offered the option to configure the API permissions for the token, you should select the following permissions:

- Device list (/devices)
- Device ID (/devices/{device_id})

21.7.4. Configure PacketFence

In PacketFence, MDM are referred to as provisioners. This will walk you through adding Kandji as a provisioner.

Create the provisioner

Login to the admin interface, then go to *Configuration* → *Advanced Access Configuration* → *Provisioners*. Click 'Add provisioner' then select 'Kandji'.

Now configure this new provisioner with the information you got above.

- The API token is the token you obtained in the instructions above
- The host is obtained by the value of your organization's API URL. For example, if your API URL is <https://foo.clients.us-1.kandji.io/api/v1/>, the host will be foo.clients.us-1.kandji.io
- The enroll URL can be obtained in the 'Add devices' menu of the Kandji admin panel under 'Enrollment Portal Link'

Add the provisioner to the connection profile

In order for the provisioner to be used by your captive portal you need to add it in its configuration. Go in 'Connection Profiles', then select the portal you want to modify and add your new provisioner in the list.

21.7.5. Add the necessary passthroughs

NOTE

This step is only necessary if you wish to enroll devices via the PacketFence captive-portal. Adding these passthroughs may prevent the Apple CNA (Captive-Network Assistant) from opening when the user is unregistered.

Next, still in the PacketFence administration console, go in 'Fencing' in the left menu, then scroll then to 'Passthroughs'.

Check the 'Passthrough' box above the field and add the following domains to the passthrough list.

- [.<your instance>.<your region>.kandji.io](https://<your instance>.<your region>.kandji.io) (this is your API URL)
- *.devices.<your region>.kandji.io (you can obtain your region from the API URL)
- *.hs-analytics.net
- *.hs-banner.com
- *.hs-scripts.com

- *.hsadspixel.net
- *.hubapi.com
- *.hubspot.com
- *.kandji.io
- *.push.apple.com
- *.usemessages.com
- *.web-api.kandji.io
- albert.apple.com
- deviceenrollment.apple.com
- deviceservices-external.apple.com
- gateway.icloud.com
- gdmf.apple.com
- gs.apple.com
- humb.apple.com
- identity.apple.com
- iprofiles.apple.com
- kandji-prd-managed-library-items.s3.amazonaws.com
- kandji-prd.s3.amazonaws.com
- mdmenrollment.apple.com
- setup.icloud.com
- sq-device.apple.com
- static.ips.apple.com
- tbsc.apple.com
- time-ios.apple.com
- time-macos.apple.com
- time.apple.com
- vpp.itunes.apple.com

Restart PacketFence

Then run the following commands so that passthroughs become effective:

```
/usr/local/pf/bin/pfcmd configreload hard
/usr/local/pf/bin/pfcmd service pfdns restart
```

21.7.6. Testing

You can now test that Kandji enrollment is mandatory after the device registration. Connect a device to your test network and register like you normally would. At the end of the registration process you will be presented a page asking you to install the Kandji MDM on

your device. After you install the agent click 'Continue'. If your access is enabled than this means the connectivity between PacketFence and Kandji is good.


22. PKI Integration

22.1. PacketFence PKI

This section provides quick start configuration for PacketFence PKI. For advanced EAP-TLS troubleshooting, refer to EAP-TLS, RADIUS and OpenSSL documentation. PKI comes installed by default since PacketFence version 10. All certificates are saved in database. To migrate certificates from old PacketFence PKI, see upgrade section.

22.1.1. Certificate Authority creation

Create new certificate authority. In PacketFence web administration, go to Configuration → Integration → PKI → Certificate Authorities and click **New Certificate Authority**.



For sub-CA configuration: click 'Generate CSR' (top right of CA form), modify information if needed, click 'Generate CSR'. Copy CSR and provide to external CA for signed certificate retrieval. Provide signed certificate and click 'Save'.

For expiring CA certificate: generate new CSR or click Resign CA Certificate (self-signed).

Here's a CA example:

The screenshot shows a web interface for configuring a new Certificate Authority (CA). The left sidebar contains a navigation menu with categories like Policies and Access Control, Compliance, Integration, Advanced Access Configuration, Network Configuration, and System Configuration. The main area is titled 'New Certificate Authority' and contains a form with the following fields:

- Common Name: Inverse_Root_CA
- Email: administrator@inverse.ca
- Organisation: Inverse Inc.
- Country: Canada (dropdown)
- State or Province: Quebec
- Locality: Montreal
- Street Address: Park Avenue
- Postal Code: H3N 1X1
- Key type: KEY_RSA (dropdown)
- Key size: 4096 (dropdown)
- Digest: SHA256WithRSA (dropdown)
- Key usage: (dropdown with optional values: digitalSignature, nonRepudiation, keyEncipherment, dataEncipherment, keyAgreement, keyCertSign, cRLSign, encipherOnly, decipherOnly)
- Extended key usage: (dropdown with optional values: serverAuth, clientAuth, codeSigning, emailProtection, timeStamping, msCodeInd, msCodeCom, msCTLSign, msSGC, msEFS, nsSGC)
- Days: 750 (Number of days the CA will be valid.)

At the bottom of the form are 'Create' and 'Reset' buttons.

Once you have created the CA, you should see the Root CA certificate displayed at the bottom of the page:

Status Reports Auditing Nodes Users Configuration

API dashboard admin

Filter

Policies and Access Control

Compliance

Integration

- Firewall SSO
- Cisco Mobility Services Engine
- Web Services
- Switch Templates
- Syslog Parsers
- Syslog Forwarding
- WRIX
- PKI
 - Certificate Authorities
 - Templates
 - Certificates
 - Revoked Certificates

Advanced Access Configuration

Network Configuration

System Configuration

Certificate Authority

Identifier2

Common NameInverse_Root_CA

Emailadministrator@inverse.ca

OrganisationInverse Inc.

CountryCanada

State or ProvinceQuebec

LocalityMontreal

Street AddressPark Avenue

Postal CodeH3N 1X1

Key typeKEY_RSA

Key size4096

DigestSHA256WithRSA

Key usageOptional. One or many of: digitalSignature, nonRepudiation, keyEncipherment, dataEncipherment, keyAgreement, keyCertSign, cRLSign, encipherOnly, decipherOnly.

Extended key usageOptional. One or many of: serverAuth, clientAuth, codeSigning, emailProtection, timeStamping, msCodeInd, msCodeCom, msCTLSign, msSGC, msEFS, nsSGC.

Days750

Number of days the CA will be valid.

Certificate-----BEGIN CERTIFICATE-----MIIGHDCCBASgAwIBAgIBATANBgkqhkiG9w0BAQsFADCBijELMAkGA1UEBhMCQ0ExDzANBgNVBAGTBIF1ZWJlYzERMA8GA1UEBxMlT9udHJlYWwxFDASBgNVBAkTC1Bhcm5gQXZlbnVlMRAwDgYDVQQREwdIM04gMVgxMRUwEwYDVQQKEwxBb2ZlcnNlIEluYy4xGDAwBgNVBAMMD0ludmVyc2VfUm9vdF9DQTAEfW0yMDAyMjc5NTESNDZaFw0yMjAzMjg5NDZaMIGKMQswCQYDVQQGEwJDQTEPMA0GA1UECBMUGXVlYmVjMREwDwYDVQQHEwNlMjU0cmVhbDEUMBIGA1UECRMLUGFyayBBdmVudWUxEDA0BgNVBBETB0gzTlAxWDExFTATBgNVBAoTDEludmVyc2UgSW51LjEjYmBYGA1UEAwP SW552ZXJzZV9Sb290X0NBMIICjANBgkqhkiG9w0BAQEFAAOCAg8AMIICGKCAgE Au0lEI6G5j2For+UtPoakcMkkKhQRjMbrzjf/hUEIje8/h16en7SNyzTrzHXXIb5pttNomRobP8KWHNy7hqlcybOc9YOKd2ilgEcrOl/hdSuf992cT8djMXU+hDZ6ygdgJWJPs3M5qwuVML/RJBXC4jlxk2rXki3fGFRIVW7UAfEvqqrRtiH9i9DQ9oxhDGno4FJ6UwMf9PdN36In9YdmXHyOkjJISJz7DWVFT3zCV7Nr4DiZohoLLbbRdPC0z3HBvd1OoxslLh2uV2gN/htLzEDF/wADGaF4xsSROkQ+QH3FV7j8rV6g9BhUFdLYKLP1JQJv06MGwa1SCRw2P28TweZqL0qLAqXu5cROHqVYnby2wUbgdx386ijukedc9NVqXJyevC+Gj3Sc/nmoFqrZgk6o05Plx4p+O8phwL9lhbQm+DuC+xYFWIMisMKFoH2O6rwvyTXMFYHsPGTDBETlTPIExbLXGRWOcPhUU4/65Nax9srNhAtOCOEwrQQtuw2CgK7lIXRPI5D2O1nY96kMgFyZF8bQgzlJON9lvNKOOr0dVrLHpt3Bj+Fe2yzFaal8gKtt3OzarMeXoJE9FKzfzS6QQYkwLKlZ0s4YCqYBPXDR/nS5NQkpW

Clone


Once done copy the certificate in the clipboard from the Certificate Authorities list (Configuration → Integration → PKI → Certificate Authorities and click on **Copy Certificate**) then edit the RADIUS certificate section in Configuration → System Configuration → SSL Certificates → RADIUS → Edit and paste the public key in "Certificate Authority" and Save. (Don't forget to restart radiusd-auth)

This will authorize the EAP TLS authentications using the PKI issued certificates.

22.1.2. Template creation

Now you will need to create a certificate template that will gather all the settings for your certificate like the validity period or the certificate usage.

Select the Certificate Authority previously created:



Here's a template example:

The screenshot shows the 'New Profile' configuration page in a web interface. The page is titled 'New Profile' and has a close button (X) in the top right corner. The page is divided into two main sections: 'General' and 'PKCS 12'. The 'General' section is currently active and contains the following fields:

- Certificate Authority:** A dropdown menu with 'Inverse_Root_CA' selected.
- Name:** A text input field with 'User_Certificate' entered. Below it, the text 'Profile Name.' is displayed.
- Validity:** A text input field with '365' entered. Below it, the text 'Number of days the certificate will be valid.' is displayed.
- Key type:** A dropdown menu with 'KEY_RSA' selected.
- Key size:** A dropdown menu with '2048' selected.
- Digest:** A dropdown menu with 'SHA256WithRSA' selected.
- Key usage:** A dropdown menu with 'DigitalSignature' selected. Below it, the text 'Optional. One or many of: digitalSignature, nonRepudiation, keyEncipherment, dataEncipherment, keyAgreement, keyCertSign, cRLSign, encipherOnly, decipherOnly.' is displayed.
- Extended key usage:** A dropdown menu with 'ServerAuth' and 'ClientAuth' selected. Below it, the text 'Optional. One or many of: serverAuth, clientAuth, codeSigning, emailProtection, timeStamping, msCodeInd, msCodeCom, msCTLSign, msSGC, msEFS, nsSGC.' is displayed.

At the bottom of the page, there are two buttons: 'Save' and 'Reset'.

Key usage clientAuth: To use your certificate for a client authentication.

Key usage serverAuth: If you want to install your certificate on a server.

P12 mail password emailed to the users:



Status Reports Auditing Nodes Users Configuration

API dashboard admin

Filter

Policies and Access Control

Compliance

Integration

Firewall SSO

Cisco Mobility Services Engine

Web Services

Switch Templates

Syslog Parsers

Syslog Forwarding

WRIX

PKI

Certificate Authorities

Templates

Certificates

Revoked Certificates

Advanced Access Configuration

Network Configuration

System Configuration

Template

General PKCS 12

P12 mail password

☒

Email the password of the pkcs12 file.

P12 mail subject

Email subject.

P12 mail from

Sender email address.

P12 mail header

Email header.

P12 mail footer

Email footer.

Save

Reset

Clone

SCEP

You can choose to enable SCEP on this template.

Enable SCEP	☒	Enable SCEP for this template.
SCEP challenge password	password	SCEP challenge password.
SCEP days before renewal	14	Number of days before SCEP authorize renewal
Enable Cloud Integration	☐	Enable Cloud integration for this template.
Cloud Service	Select option	Cloud Service to integrate.
SCEP Server Enabled	☒	
SCEP Server	prod	

IMPORTANT

Common name and Subject Alt Name attributes provided in CSR to get a certificate through SCEP will override values in PKI template. Other values like Signature Algorithm, Key usage, Extended key usage will be taken from PKI template.

Optionally, enable 'SCEP Server Enabled' and define an external SCEP server to proxy the request.

SCEP Test

Let's do a scep request by hand. Directly from the PacketFence server do that:

Create a private key and a csr file:

```
openssl req -newkey rsa:2048 -keyout PRIVATEKEY.key -out MYCSR.csr
```

Generating a 2048 bit RSA private key

```
.....  
.....  
.....+++  
.....+++
```

writing new private key to 'PRIVATEKEY.key'

Enter PEM pass phrase:

Verifying - Enter PEM pass phrase:

You are about to be asked to enter information that will be incorporated into your certificate request.

What you are about to enter is what is called a Distinguished Name or a DN.

There are quite a few fields but you can leave some blank

For some fields there will be a default value,

If you enter '.', the field will be left blank.

Country Name (2 letter code) [XX]:CA

State or Province Name (full name) []:QC

Locality Name (eg, city) [Default City]:Montreal

Organization Name (eg, company) [Default Company Ltd]:Acme

Organizational Unit Name (eg, section) []:IT

Common Name (eg, your name or your server's hostname) []:acme.com

Email Address []:admin@acme.com

Please enter the following 'extra' attributes to be sent with your certificate request

A challenge password []:password

An optional company name []:

Get the CA certificate:

```
sscep getca -u http://ip_address/scep/template_name -c ./ca-prefix -i MyPKI -v  
-d
```

sscep: starting sscep, version 0.6.1

sscep: new transaction

sscep: transaction id: SSCEP transactionId

sscep: hostname: ip_address

sscep: directory: scep/template_name

sscep: port: 80

sscep: SCEP_OPERATION_GETCA

sscep: requesting CA certificate

sscep: scep msg: GET /scep/template_name?operation=GetCACert&message=MyPKI

HTTP/1.0

```
sscep: server returned status code 200
sscep: MIME header: application/x-x509-ca-cert
sscep: valid response from server
sscep: MD5 fingerprint: 22:DE:09:17:8B:5F:94:1E:EB:0D:9C:12:EF:05:F0:C5
sscep: CA certificate written as ./ca-prefix
```

Remove the private key passphrase:

```
openssl rsa -in PRIVATEKEY.key -out private.key
Enter pass phrase for PRIVATEKEY.key:
writing RSA key
```

Send the CSR and retrieve the certificate:

```
sscep enroll -c ./ca-prefix -k ./private.key -r ./MYCSR.csr -u
http://ip_address/scep/template_name -S sha1 -l ./cert.crt
```

22.1.3. Certificate creation

The screenshot shows the Palo Alto Networks configuration interface. The left sidebar contains a navigation menu with categories like Policies and Access Control, Compliance, Integration, and PKI. The PKI section is expanded, showing sub-items: Certificate Authorities, Templates, Certificates, and Revoked Certificates. The main content area is titled 'PKI' and has tabs for Certificate Authorities, Templates, Certificates (selected), and Revoked Certificates. Under the 'Certificates' tab, there is a search bar and a 'New Certificate' button. Below this, a dropdown menu is open, showing 'Choose Certificate Authority - Profile' with 'Inverse_Root_CA - User_Certificate' selected and highlighted by a red circle. The table below the dropdown is empty, with columns for Name, Profile, Common Name, Email, and Valid Until. A message at the bottom of the table states 'No certificates found. Please refine your search.'

New Certificate

Certificate Template: Inverse_Root_CA - User_Certificate
Certificate profile used for this certificate.

Common Name: Test_User_1
Username for this certificate.

Email: test-user@inverse.ca
Email address of the user. The email with the certificate will be sent to this address.

Organisation: Inverse

Country: Canada

State or Province: Quebec

Locality: Montreal

Street Address: Park Avenue

Postal Code: H3N 1X1

[Create](#) [Reset](#)

Once it's created, you can send it to the email user or download the p12 format:

PKI

[Certificate Authorities](#) [Templates](#) [Certificates](#) [Revoked Certificates](#)

Certificates

Search by identifier, certificate authority, profile, common name or email [Clear](#) [Search](#)

[New Certificate](#) [pfpk1](#) 25 [«](#) [<](#) [1](#) [>](#) [»](#)

Identifier	Certificate Authority	Profile	Common Name	Email	Valid Until	
2	Inverse_Root_CA	User_Certificate	Test_User_1	test-user@inverse.ca	2021-02-25 10:56-05:00	Download Email Revoke

22.1.4. PEM format


The PacketFence PKI hand out PKCS12 certificates, if you want to convert your certificate to PEM format, you can use the commands:

```
openssl pkcs12 -in YourCert.p12 -nocerts -out YourCert.key -nodes
openssl pkcs12 -in YourCert.p12 -out YourCert.pem -clcerts -nokeys
```

22.1.5. Revoke a certificate

If you revoke a certificate it can't be recovered and you would need to recreate a new one. You will need to specify a reason of the revocation.

Click on the Revoke button on the certificate:



22.1.6. Resign a certificate


Resign-ing an existing Certificate will extend the duration by reusing the private-key to generate a new public certificate. Click the 'Resign' button (top-right), modify the

information (if needed) and click 'Resign'.

22.1.7. PKI Provider

You can hand out certificate to non-BYOD device on a captive portal.

First, you would need to create the PKI provider that will query the PacketFence PKI for new certificate. Go to Configuration → Advanced Access Configuration → PKI provider



Create a certificate per user or per device mac address, this example will cover one certificate per device:

The screenshot displays the PacketFence configuration interface. The top navigation bar includes links for Status, Reports, Auditing, Nodes, Users, and Configuration. The left sidebar shows a hierarchy of configuration options: Policies and Access Control, Compliance, Integration, Advanced Access Configuration, Captive Portal, Filter Engines, Billing Tiers, PKI Providers, Provisioners, Portal Modules, Access Duration, Self Service Portal, Network Configuration, and System Configuration. The main content area is titled 'PKI Provider PF-PKI' and contains the following settings:

- PKI Provider Name:** PF-PKI
- Profile:** Inverse_Root_CA - User_Certificate
- Country:** Canada
- State:** Quebec
- Organization:** Inverse
- Common Name Attribute:** MAC address
- Common Name Format:** %s
- Revoke on unregistration:** (Toggle switch)
- CA cert path:** /usr/local/pf/raddb/certs/ca.pem
- Server cert path:** /usr/local/pf/raddb/certs/server.crt

At the bottom of the configuration panel are four buttons: Save, Reset, Clone, and Delete.

22.1.8. Intune Integration

Azure configuration

You can hand out certificates when you use intune enrolment.

First you need to create an application on Azure that allow PacketFence to connect to the Intune API.

To do that first you have to go in Azure portal and App registration then click **New registration**

Microsoft Azure

Home > inverse inc



inverse inc | App registrations

Azure Active Directory

Overview

Getting started

Preview features

Diagnose and solve problems

Manage

Users

Groups

External Identities

Roles and administrators

Administrative units

Enterprise applications

Devices

App registrations

New registration

Try out the new App reg

Starting June 30th, 2020

All applications

Owner

Start typing a name or /

Display name

PA PacketFence

Next set a Name and in "Supported account types" select "Accounts in this organizational directory only" then click **Register**

Microsoft Azure

Home > inverse inc >

Register an application ...

*

Name

The user-facing display name for this application (this can be changed later).

PacketFence

Supported account types

Who can use this application or access this API?

☒

Accounts in this organizational directory only (inverse inc only - Single tenant)

☐

Accounts in any organizational directory (Any Azure AD directory - Multitenant)

☐

Accounts in any organizational directory (Any Azure AD directory - Multitenant) and personal Microsoft accounts (e.g. Skype, Xbox)

☐

Personal Microsoft accounts only[Help me choose...](#)

Redirect URI (optional)

We'll return the authentication response to this URI after successfully authenticating the user. Providing this now is optional and it can be changed later, but a value is required for most authentication scenarios.

Web

e.g. https://example.com/auth

On the next page you have to copy the "Application (Client) ID" and the "Directory (tenant) ID", those will be needed to configure PacketFence.

Microsoft Azure

Search resources, services, and docs (G+)

Home > inverse inc >

PacketFence

Search (Ctrl+V)

Delete Endpoints Preview features

Overview

Quickstart

Integration assistant

Manage

Branding

Authentication

Essentials

Display name : PacketFence

Application (client) ID : 36e3f54a-e38f-4e37-9470-91ba9d3c0158

Object ID : 20cd24e1-a989-47ad-ab45-3911464317b4

Directory (tenant) ID : 045285d8-2ed4-4c86-9763-e4a3564d5d55

Supported account types : My organization only

Client credentials : Add a certificate or secret

Redirect URIs : Add a Redirect URI

Application ID URI : Add an Application ID URI

Managed application in L : PacketFence

Then you need to generate a "Client secrets", to do that click on "Add a certificate or secret"

Microsoft Azure

Home > inverse inc > PacketFence

PacketFence | Certificates & secrets

Search (Ctrl+/) Got feedback?

Overview
Quickstart
Integration assistant

Manage

Branding
Authentication
Certificates & secrets
Token configuration
API permissions
Expose an API
App roles
Owners
Roles and administrators | Preview
Manifest

Support + Troubleshooting

Troubleshooting
New support request

Credentials enable confidential applications to identify themselves to the authentication service when receiving tokens at a web addressable location (using an HTTPS scheme). For a higher level of assurance, we recommend using a certificate (instead of a client secret) as a credential.

Certificates

Certificates can be used as secrets to prove the application's identity when requesting a token. Also can be referred to as public keys.

Upload certificate

Thumbprint	Start date	Expires	Certificate ID
No certificates have been added for this application.			

Client secrets

A secret string that the application uses to prove its identity when requesting a token. Also can be referred to as application password.

+ New client secret

Description	Expires	Value	Secret ID
No client secrets have been created for this application.			

Add a client secret

Description

Expires

Copy the "Value" of the secret, this is the only time you should be able to see it.

Microsoft Azure

Home > inverse inc > PacketFence

PacketFence | Certificates & secrets

Search (Ctrl+/) Got feedback?

Overview
Quickstart
Integration assistant

Manage

Branding
Authentication
Certificates & secrets
Token configuration
API permissions
Expose an API
App roles
Owners
Roles and administrators | Preview
Manifest

Support + Troubleshooting

Troubleshooting
New support request

Credentials enable confidential applications to identify themselves to the authentication service when receiving tokens at a web addressable location (using an HTTPS scheme). For a higher level of assurance, we recommend using a certificate (instead of a client secret) as a credential.

Certificates

Certificates can be used as secrets to prove the application's identity when requesting a token. Also can be referred to as public keys.

Upload certificate

Thumbprint	Start date	Expires	Certificate ID
No certificates have been added for this application.			

Client secrets

A secret string that the application uses to prove its identity when requesting a token. Also can be referred to as application password.

+ New client secret

Description	Expires	Value	Secret ID
PacketFence_SCEP	11/13/2021	_d87e2AcSIS14233k.VNLxSua40~v-N96Y	48b92945-d0e8-4095-bd0e-da0bca1fef32

Next you have to add API permissions, click on "API permissions" → "Add a Permissions":

Intune -> "Application permissions" and select "scep_challenge_provider"
Microsoft Graph -> "Application permissions" and select "Application.Read.All"
Microsoft Graph -> "Delegated permissions" and select "User.Read"

For more details about permissions <https://techcommunity.microsoft.com/t5/intune-customer-success/support-tip-intune-service-discovery-api-endpoint-will-require/ba-p/2428040>

Previous versions used Azure Active Directory Graph which is now deprecated and will stop working after December 2022, if you have granted those permissions you must remove them and add the new permissions instead.

[+ Add a permission](#) [✓ Grant admin consent for](#)

API / Permissions name	Type	Description	Admin consent requ...
▼ Intune (1)			
scep_challenge_provider	Application	SCEP challenge validation	Yes
▼ Microsoft Graph (2)			
Application.Read.All	Application	Read all applications	Yes
User.Read	Delegated	Sign in and read user profile	No

Last step is to "Grant admin", just click on "Grant admin consent for ..." and click **Yes**

Microsoft Azure

Home > inverse inc > PacketFence

PacketFence | API permissions

Search (Ctrl+/) Refresh Got feedback?

Overview Quickstart Integration assistant

Manage

- Branding
- Authentication
- Certificates & secrets
- Token configuration
- API permissions**
- Expose an API
- App roles
- Owners
- Roles and administrators | Preview
- Manifest

Support + Troubleshooting

- Troubleshooting
- New support request

Do you want to grant consent for the requested permissions for all accounts in inverse inc? This will update any existing admin consent records this application already has.

[Yes](#) [No](#)

Configured permissions

Applications are authorized to call APIs when they are granted permissions by users/admins as part of the consent process. The list of configured permissions should include all the permissions the application needs. [Learn more about permissions and consent](#)

[+ Add a permission](#) [✓ Grant admin consent for inverse inc](#)

API / Permissions name	Type	Description	Admin consent req...	Status
▼ Intune (1)				
scep_challenge_provider	Application	SCEP challenge validation	Yes	Not granted for inverse inc
▼ Microsoft Graph (1)				
User.Read	Delegated	Sign in and read user profile	No	

To view and manage permissions and user consent, try [Enterprise applications](#).

CAUTION | Key storage provider (KSP) needs to be set to **Enroll to Software KSP**

devices to reject the certificate before it's installed.

- **Key storage provider (KSP):**

(Applies to: Windows 8.1, and Windows 10/11)

Specify where the key to the certificate is stored. Choose from the following values:

- Enroll to Trusted Platform Module (TPM) KSP if present, otherwise Software KSP
- Enroll to Trusted Platform Module (TPM) KSP, otherwise fail
- Enroll to Windows Hello for Business, otherwise fail (Windows 10 and later)
- **Enroll to Software KSP**

- **Key usage:**

Select key usage options for the certificate:

PacketFence configuration

Intune definition

First of all you have to define the configuration parameters to reach the Intune API. To do that go in Configuration → Integration → Cloud Services → New Cloud → Microsoft Intune

Next fill the field with the values taken from the Azure portal ("Application (Client) ID", "Directory (tenant) ID" and "Client secrets") and **Create**.

Cloud Service **Intune** Intune

Name	Intune
The tenant ID of the intune service	045285d8-2ed4-4c86-9763-e4a3564d5d55 Define the tenant ID defined in the Azure admin portal.
The client ID of the intune service	36e3f54a-e38f-4e37-9470-91ba9d3c0158 Define the client ID defined in the Azure admin portal.
The client secret of the intune service	 Define the client secret defined in the Azure admin portal.


Save **Clone** **Reset** **Cancel** **Delete**

SCEP configuration

Now let's configure the PKI template to enable SCEP on it. (go to the previous section on how to configure a template in the PKI)

Go in Configuration → Integration → PKI → Templates and edit the one you created previously.

You can see that there is a SCEP section. Enable SCEP and check Enable Cloud Integration and select the Cloud Service you created previously. (In the case the SCEP challenge password is not mandatory).



Starting from now the scep server will be available on each ip where the portal is running (you need to enable the portal on the management interface if you want to be able to do SCEP on this interface).

The URL of the SCEP server will be available on http://ip_address/scep/template_name (https too) where template_name is the name of your template in the PKI.

Intune configuration

For this section you can follow the instruction on the Microsoft web site:

<https://docs.microsoft.com/en-us/mem/intune/protect/certificates-profile-scep>

From the PacketFence server you will need to extract the PKI Ca certificate associated to the template and put it in Intune as a "trusted certificate"

Then set the SCEP URL to http://ip_address/scep/template_name or https://ip_address/scep/template_name

22.2. AirWatch

This section has been created to give a quick overview to configure AirWatch (VMware) with PacketFence. This guide does not include advanced troubleshooting of EAP-TLS connections. Refer to the relevant documentation of EAP-TLS, RADIUS and OpenSSL for advanced features. The PKI comes installed by default since PacketFence version 10. All certificates would be saved in the database. If you want to migrate your certificate from the old PacketFence PKI please see the upgrade section.

22.2.1. Assumptions

You have a functional PacketFence PKI and you already have created a Certificate Authority and its templates with SCEP enabled. The template used here is: 'airwatch2'

NOTE

Make sure that your PacketFence PKI Root CA validity is under 825 days and your PacketFence PKI Template is under 398 days. References: <https://support.apple.com/en-us/HT211025> and <https://support.apple.com/en-ca/HT210176>

Create the Certificate Authority (SCEP):

Certificate Authority - Add/Edit

Name *

PacketFence-SCEP

Description

Authority Type *

Generic SCEP

SCEP Provider *

Basic

SCEP URL *

http://[REDACTED]/scep/airwatch2

Challenge Type *

STATIC

NO CHALLENGE

Static Challenge

CHANGE

Max Retries When Pending *

5

Enable Proxy

ENABLED

DISABLED

SAVE

SAVE AND ADD TEMPLATE

TEST CONNECTION

CANCEL

Create a Certificate template:

Certificate Template - Add/Edit

Name *

PF-AirWatch

Description

AirWatch devices

Certificate Authority *

PacketFence-SCEP

Issuing Template

Subject Name

CN={DeviceSerialNumber}

Private Key Length *

2048

Private Key Type *

☒ Signing

☐ Encryption

SAN Type

Add

Automatic Certificate Renewal

ENABLED

DISABLED

Auto Renewal Period (days) *

45

Publish Private Key

ENABLED

DISABLED

SAVE

SAVE AND ADD TEMPLATE

CANCEL

Create the SSID profile:

iOS PF-SCEP-Test

Find Payload

General

Passcode

Restrictions

Wi-Fi 1

VPN

Email

Exchange ActiveSync

Notifications

LDAP

CalDAV

Subscribed Calendars

CardDAV

Web Clips

Credentials 2

SCEP 1

Global HTTP Proxy

Single App Mode

Content Filter

Managed Domains

Network Usage Rules

macOS Server Accounts

Single Sign-On

Skip Setup Assistant

SSO Extension

AirPlay Mirroring

AirPrint

Cellular

Home Screen Layout

Wi-Fi

Service Set Identifier *

Hidden Network

Auto-Join

Security Type

Prevent MAC address randomization

Protocols *

Passpoint

Authentication

☐

☒

WPA/WPA2 Enterprise

☐

☒ EAP-TLS

☐ TTLS

☐ LEAP

☐ PEAP

☐ EAP-FAST

☐ EAP-SIM

☐ EAP-AKA

Wi-Fi Hotspot 2.0

Username

User Per-Connection Password

Password

Identity Certificate

☐

Show Characters

SCEP #1

iOS 5

iOS 14

iOS 7

ADD VERSION

SAVE AND PUBLISH

CANCEL

iOS PF-SCEP-Test

Find Payload

- General
- Passcode
- Restrictions
- Wi-Fi** ①
- VPN
- Email
- Exchange ActiveSync
- Notifications
- LDAP
- CalDAV
- Subscribed Calendars
- CardDAV
- Web Clips
- Credentials ②
- SCEP** ①
- Global HTTP Proxy
- Single App Mode
- Content Filter
- Managed Domains
- Network Usage Rules
- macOS Server Accounts
- Single Sign-On
- Skip Setup Assistant
- SSO Extension
- AirPlay Mirroring
- AirPrint
- Cellular
- Home Screen Layout

User Per-Connection Password ☐

Password ☐ Show Characters

Identity Certificate SCEP #1

TLS Minimum Version OS Default iOS 11

TLS Maximum Version OS Default iOS 11

Trust

Trusted Certificates

- ☒ Certificate #1
- ☒ Certificate #2
- ☒ SCEP #1

Trusted Server Certificate Names

✕

✕

✕

[+ ADD](#)

Allow Trust Exceptions ☒

Proxy

Gateway Platform None iOS 5

QoS Marking Policy

Fastlane QoS Marking Do Not Restrict QoS Marking iOS 10

Captive Portal

Bypass Captive Portal ☐ iOS 10

[ADD VERSION](#) [SAVE AND PUBLISH](#) [CANCEL](#)

Add the Root CA certificate that issued the PacketFence RADIUS certificate:

iOS PF-SCEP-Test

Find Payload

General

Passcode

Restrictions

Wi-Fi 1

VPN

Email

Exchange ActiveSync

Notifications

LDAP

CalDAV

Subscribed Calendars

CardDAV

Web Clips

Credentials 2

SCEP 1

Global HTTP Proxy

Single App Mode

Content Filter

Managed Domains

Network Usage Rules

macOS Server Accounts

Single Sign-On

Skip Setup Assistant

SSO Extension

AirPlay Mirroring

AirPrint

Cellular

Home Screen Layout

Credentials #1

Credential Source: Upload

Credential Name *

Certificate * Certificate Uploaded: CHANGE

Type: Cert

Valid From: 4/23/2021

Valid To: 5/18/2022

Thumbprint

CLEAR

ADD VERSION SAVE AND PUBLISH CANCEL

Add the PacketFence RADIUS certificate:

iOS PF-SCEP-Test

Find Payload

General

Passcode

Restrictions

Wi-Fi 1

VPN

Email

Exchange ActiveSync

Notifications

LDAP

CalDAV

Subscribed Calendars

CardDAV

Web Clips

Credentials 2

SCEP 1

Global HTTP Proxy

Single App Mode

Content Filter

Managed Domains

Network Usage Rules

macOS Server Accounts

Single Sign-On

Skip Setup Assistant

SSO Extension

AirPlay Mirroring

AirPrint

Cellular

Home Screen Layout

Credentials #2

Credential Source: Upload

Credential Name *

Certificate * Certificate Uploaded CHANGE

Type: Cert

Valid From: 5/25/2021


Valid To: 6/19/2022

Thumbprint

CLEAR

ADD VERSION SAVE AND PUBLISH CANCEL

Create the SCEP profile:



Assign and deploy the profile:

iOS PF-SCEP-Test

Find Payload

General

Passcode

Restrictions

Wi-Fi

VPN

Email

Exchange ActiveSync

Notifications

LDAP

CalDAV

Subscribed Calendars

CardDAV

Web Clips

Credentials

SCEP

Global HTTP Proxy

Single App Mode

Content Filter

Managed Domains

Network Usage Rules

macOS Server Accounts

Single Sign-On

Skip Setup Assistant

SSO Extension

AirPlay Mirroring

AirPrint

Cellular

Home Screen Layout

General

Name *

PF-SCEP-Test

Version

32

Description

PF SCEP Test

Deployment

Managed

Assignment Type

Auto

Allow Removal

Always

Managed By

Inspire Development Centers

Smart Groups

SCEP Test

Start typing to add a group

Exclusions

NO

YES

VIEW DEVICE ASSIGNMENT

Additional Assignment Criteria

☐ Install only on devices inside selected areas

☐ Enable Scheduling and install only during selected time periods

Removal Date

M/D/YYYY

Hub Required

ADD VERSION

SAVE AND PUBLISH

CANCEL

23. MFA Integration

This section provides quick overview for MFA integration with PacketFence.

23.1. Assumptions

Functional PacketFence server with configured Internal Source (e.g., Active Directory Source) associated to Connection Profile. RADIUS client performing PAP (e.g., VPN server or switch with CLI access using RADIUS).

23.2. Create the MFA Configuration

23.2.1. Akamai MFA

This section provides quick overview for configuring Akamai MFA in PacketFence.

23.2.2. Assumptions

You have Akamai MFA information required for PacketFence configuration.

Create the Multi-Factor configuration

Configure Akamai MFA from admin interface.

Go to "Configuration→Integration→Multi-Factor Authentication", click new MFA, select Akamai.

Complete form with following information:

Name: Define name

The App ID of the Akamai MFA: App ID provided by Akamai

The signing key of the Akamai MFA: Signing key provided by Akamai

The verify key of the Akamai MFA: Verify key provided by Akamai

The host of the Akamai MFA: Default: mfa.akamai.com

The callback URL to redirect back the user to PacketFence: This parameter is used when you trigger the MFA on the portal, once authenticate on Akamai Bind v2, it redirects to this specific URL to reach back the PacketFence's portal. This value should be the FQDN of the portal with /mfa at the end (<https://portal.acme.com/mfa>)

RADIUS OTP Method: It is where you define which method you want to use in RADIUS (Explanation is covered in the next section)

Character separator: The character used to split the password and OTP when "Strip OTP"

RADIUS method is selected.

Cache duration: The amount of time PacketFence will store the MFA information of the user (used for "Strip OTP" and "Second Password Field" since PacketFence deal with multiple RADIUS requests)

Multi-Factor Authentication Akamai MFA Gateway 

Name	Akamai MFA Gateway
The App ID of the Akamai MFA	app_4kB1YKE7wazaEunEMQZW6k Define the App ID provided by Akamai MFA.
The signing key of the Akamai MFA	 Define the signing key provided by Akamai MFA.
The verify key of the Akamai MFA	 Define the verify key provided by Akamai MFA.
The host of the Akamai MFA	mfa.akamai.com Define the host of the Akamai MFA.
The callback url to redirect back the user to PacketFence	http://172.20.20.152/mfa Define the callback URL to redirect the user to PacketFence.
RADIUS OTP Method	Strip OTP Define the method to be used in RADIUS to trigger OTP.
Character separator	, Please specify the char to split password field to get the code.
Cache duration	60 seconds The duration time that is use to cache the MFA information. This approximately represent the time for the user to complete the authentication.

If MFA authentication fails, verify configuration and check [RADIUS Audit Log](#) to trace authentication flow.

23.2.3. TOTP MFA

This section has been created to give a quick overview on how to configure TOTP MFA in PacketFence.

23.2.4. Assumptions

You have a phone where you have an MFA application compatible with TOTP (Akamai MFA, Google Authenticator, Microsoft Authenticator, DUO).

Create the Multi-Factor configuration

In this section we will configure the OTP MFA from the admin interface.

Go in "Configuration → Integration → Multi-Factor Authentication" then click on new MFA and select TOTP.

In the form you have the following information to fill:

Name: Define a name

RADIUS OTP Method: It is where you define which method you want to use in RADIUS (Explanation are covered in the next section)

Character separator: The character used to split the password and OTP when "Strip OTP" RADIUS method is selected.

Cache duration: The amount of time PacketFence will store the MFA information of the user (used for "Strip OTP" and "Second Password Field" since PacketFence deal with multiple RADIUS requests)

New Multi Factor Authentication **OTP**

Name	Generic TOTP	
RADIUS OTP Method	Strip OTP	
	Define the method to be used in RADIUS to trigger OTP.	
Character separator	,	
	Please specify the char to split password field to get the code.	
Cache duration	60	seconds
	The duration time that is use to cache the MFA information. This approximately represent the time for the user to complete the authentication.	

If MFA authentication fails, verify configuration and check [RADIUS Audit Log](#) to trace authentication flow.

23.2.5. Associate the source

MFA is triggered by authentication rule in Internal Source. Create rule with condition like "memberof equals cn=otp_user,dc=acme,dc=com" and assign Action:

"Trigger RADIUS MFA" for RADIUS triggering "Trigger Portal MFA" for Portal triggering.

Authentication Rules

▼ MFA_Group (MFA Group)

Status ☒ Enabled

Name MFA_Group

Description MFA Group

Matches All

Conditions	1	memberof	equals	cn=mfa_group,dc=a	⊖ ⊕
Actions	1	Trigger RADIUS MFA		Akamai MFA Gateway	⊖ ⊕
	2	Trigger Portal MFA		Akamai MFA Gateway	⊖ ⊕
	3	Role		default	⊖ ⊕
	4	Access duration		1 hour	⊖ ⊕

23.2.6. Portal Flow

Portal flow varies by MFA provider.

Akamai Bind v2

This section has been created to give a quick overview on how to configure Akamai Bind V2 in PacketFence.

Assumptions

You have all the Akamai MFA configuration made in PacketFence.

Connection Profile

First you need to have a connection profile that use the Internal Source where you defined a authentication rule that "Trigger Portal MFA" and also use the "Default portal policy" Root Portal Module (There is already the MFA policy defined in it).

Akamai Bind V2 portal

Once you are able to hit the portal and register with your credentials, the portal will forward you to the Akamai Bind V2 interface. From this page you will be able to onboard your device and also trigger any type of MFA. Once done and authenticated, Akamai Bind V2 portal will forward you back to PacketFence's portal and will grant you the access.

Note: Before using Akamai MFA in the RADIUS flow, you need to onboard your device and it is a way to do it in PacketFence.

TOTP

This section has been created to give a quick overview on how to configure TOTP in PacketFence.

Assumptions

You have all the TOTP MFA configuration made in PacketFence.

Connection Profile

First you need to have a connection profile that use the Internal Source where you defined a authentication rule that "Trigger Portal MFA" and also use the "Default portal policy" Root Portal Module (There is already the MFA policy defined in it).

PacketFence Portal

Once you are able to hit the portal and register with your credentials, the portal will show you a QRcode you will need to scan with your device (Akamai / Google / Microsoft / DUO Authenticator per example). This will configure an account where you will be able to see "username.packetfence" and the OTP PIN code.

With that, you will be able to use this OTP on the portal to register your device.

Note: Before using OTP MFA in the RADIUS flow, you need to onboard your device on the portal.

23.2.7. RADIUS Flow

RADIUS flow depends on MFA provider features and RADIUS client capabilities.

Simple RADIUS client

In this use case only the username and password is sent in the RADIUS request, the only method available is the "push" notification. Once the user authenticated, a push notification

will be sent on his phone and the user will have to validate in order to be granted.

Simple RADIUS client with password,<code>

In this user scenario the username and password is sent but the password can be splitted with a special character to obtain the code.

OTP code (123456):

OTP code from device (changes every 30s).

push code (push):

The code can be "push" to use the default phone or "pushx" (x represent the telephone index in the list if you have multiples one), push1 will trigger a push on the first phone, push2 on the second one. The user needs to validate on his phone in order to grant the access.

sms code (sms):

The code can be "sms" to use the default phone or "smsx" (x represent the telephone index in the list if you have multiples one), sms1 will trigger a push on the first phone, sms2 on the second one. The RADIUS request will be rejected and the RADIUS client will prompt again for the credentials.

Once the user receives the code by SMS he will need to reauthenticate with his username and password and append the SMS code. (like password,smscode)

phone code (phone):

The code can be "phone" to use the default phone or "phonex" (x represent the telephone index in the list if you have multiples one), phone1 will trigger a push on the first phone, phone2 on the second one. The RADIUS request will be rejected and the RADIUS client will prompt again for the credentials.

Once the user receives the code by phone call he will need to reauthenticate with his username and password and append the code. (like password,smscode)

Simple RADIUS client with 2nd password

In this user scenario the VPN client presents a login page with one username, password and a second password field. In this 2nd password field you can set multiples things like:

OTP code (123456):

OTP code from device (changes every 30s).

push code (push):

The code can be "push" to use the default phone or "pushx" (x represent the telephone index in the list if you have multiples one), push1 will trigger a push on the first phone, push2 on the second one. The user needs to validate on his phone in order to grant the access.

sms code (sms):

The code can be "sms" to use the default phone or "smsx" (x represent the telephone index in the list if you have multiples one), sms1 will trigger a push on the first phone, sms2 on the

second one. The RADIUS request will be rejected and the RADIUS client will prompt again for the credentials.

Once the user receives the code by SMS he will need to reauthenticate with his username and password and set the code received by SMS in the 2nd password field.

phone code (phone):

The code can be "phone" to use the default phone or "phonex" (x represent the telephone index in the list if you have multiples one), phone1 will trigger a push on the first phone, phone2 on the second one. The RADIUS request will be rejected and the RADIUS client will prompt again for the credentials.

Once the user receives the code by phone call he will need to reauthenticate with his username and password and set the code received by phone in the 2nd password field.

24. Best Practices

24.1. IPTables

PacketFence manages IPTables entirely. For custom rules, create entries in `/usr/local/pf/conf/iptables-custom.conf.inc` or modify `/usr/local/pf/conf/iptables.conf.tt`. Default template works for most users. More information available in Advanced topics → Iptables.

24.2. Log Rotations

PacketFence generates many log entries in large production environments. Use `logrotate` for periodic log rotation. A working logrotate script is provided in `/etc/logrotate.d/` with daily rotation and compressed old logs. Added during PacketFence installation.

24.3. Large Registration Network

Inline or VLAN enforcement in large environments may cause ARP table overflows when many devices are on the same layer 2 segment. Symptoms include DHCP not assigning IPs properly or failed pings in registration/quarantine VLANs. Check `dmesg` log for `Neighbour table overflow` messages.

Mitigate by tweaking kernel settings. Enlarge ARP cache table by changing these `sysctl.conf` values:

```
net.ipv4.neigh.default.gc_thresh1 = 2048
net.ipv4.neigh.default.gc_thresh2 = 4096
net.ipv4.neigh.default.gc_thresh3 = 8192
```

Enable changes as root:

```
# sysctl -p
```

Layer 2 garbage collection starts at 2048 MAC addresses, with aggressive collection at 8192. This should suffice for most deployments - increase if needed (uses more kernel memory). Alternative solution: increase layer 2 network segmentation.

24.4. Active Directory fail-over

PacketFence authentication and authorization layers use 2 components for Active Directory 802.1x connections. Authentication: winbindd performs NTLM authentication for EAP-PEAP MSCHAPv2. Authorization: LDAP connections compute user roles. When using

the captive portal or 802.1x authentication that doesn't rely on NTLM authentication (EAP-TLS, EAP-TTLS, etc), then only LDAP is used.

When using multiple Active Directory servers, apply the following set of best practices to the installation so that PacketFence is able to efficiently detect a failure of one AD server and switch to the next one. This is even more important when the PacketFence deployment points to Active Directory servers located in 2 different availability zones (i.e. 2 different datacenters).

24.4.1. Authentication layer

To ensure the authentication layer will be able to fail-over efficiently, ensure that the 'Sticky DC' parameter of the domain configuration is set to *. Additionally, specify more than one DNS servers in that configuration. When using more than one availability zone, alternate the order of the servers. For example, when using the following DNS servers in the first availability zone: 10.0.1.100,10.0.1.101 and the following in the second availability zone: 10.0.2.100,10.0.2.101, the DNS servers list should be: 10.0.1.100,10.0.2.100,10.0.1.101,10.0.2.101 which will ensure the second DNS server to be queried is part of a different availability zone than the first one when winbindd queries DNS to find an available Active Directory domain controller.

Additional safety using monit

Some versions of samba/winbindd may not failover correctly when one of the DC fails, even with the best practices above. For this reason, it is suggested to enable monit on the installation. This will automatically activate an additional check that will restart winbindd if authentication fails to the current DC. Upon restart, a new DC will be found and authentication will resume. To enable this mechanism, enable monit as described [in this section of the document](#) and it be added automatically.

24.4.2. Authorization layer

The authorization layer of PacketFence uses the DNS servers setup on the operating system to resolve names. With that in mind, ensure that the servers in `/etc/resolv.conf` allow for proper fail-over should one of them fail. Similarly to the authentication layer, alternate the order of the servers based on the different availability zones. Also configure aggressive settings for fail-over to the next DNS server. For example, when using the following DNS servers in the first availability zone: 10.0.1.100,10.0.1.101 and the following in the second availability zone: 10.0.2.100,10.0.2.101, the resulting `/etc/resolv.conf` should be:

```
search example.com

options timeout:1
options retries:1

nameserver 10.0.1.100
nameserver 10.0.2.100
nameserver 10.0.1.101
nameserver 10.0.2.101
```

Once the DNS servers of the OS are setup to fail-over efficiently, review the configuration of the different Active Directory sources in PacketFence (*Configuration → Policies and Access Control → Authentication Sources*). In these sources, ensure that either a DNS name that resolves to multiple servers of the Active Directory domain is used or that multiple IP addresses are specified to connect. When uncertain about the robustness of the DNS layer, use multiple IP addresses.

25. Performance Optimizations

25.1. Multi Machine Account Support

PacketFence 14.1+ includes ntlm-auth-api multi-process support for NTLM requests. Previously, single machine account creation meant new NTLM auth requests waited for completion of previous requests. Single thread model slows performance in heavy load scenarios like large enterprises with extensive Windows AD databases and devices.

Multiple machine accounts can now be created, each registered with a dedicated process when NTLM auth API starts.

Enable by setting `additional_machine_accounts` to non-zero value. Machine accounts will be created based on the previous machine account name.

The name pattern of additional machine account is: "base_machine_account_name"-N, N will be 0..9 Example: Previous machine account NODE-PF with `additional_machine_accounts` set to 2 creates `NODE-PF-0` and `NODE-PF-1` in Windows AD.

NOTE

Windows systems limit machine account names to 14 characters. To enable this feature, ensure machine account name length is under 12 characters so PacketFence can add "-N" suffix.

25.1.1. How does this work

PacketFence regenerates config file, determines required sub-processes for machine accounts, then unicorn master process launches sub-processes to handle requests. Each sub-process uses dedicated machine account for authentication.

25.1.2. Limitations

1. Maximum 10 additional machine accounts per domain.
2. Machine account name cannot exceed 12 characters for `additional_machine_accounts`.
3. Using %h as machine account name requires parsed %h value under 12 characters.

25.1.3. Benchmarks and suggested settings

Benchmark results for reference: All the tests are done on VMs by ESXi 7.0 hosted on a SuperMicro server with 1 CPU of Intel D2123-IT (4C8T @2.2G), 128 G DDR4 RDIMM.

we are testing this using ab (apache benchmark) to directly test against NTLM auth API with:

1. 2 additional machine accounts is added (total 3)
2. The PacketFence is hosted on a 4 vCPU 32 Gig VM on ESXi.
3. The Windows AD is hosted on a 2 vCPU 8 Gig VM on ESXi in the same local network with

PacketFence.

```
ab -n 20000 -c 1 -p ~/eapol_test/payload.admin-akam.json -T 'application/json'
http://127.0.0.1:5002/ntlm/auth
```

```
Requests per second:    448.22 [#/sec] (mean)
Time per request:       2.231 [ms] (mean)
Time per request:       2.231 [ms] (mean, across all concurrent requests)
```

```
ab -n 20000 -c 2 -p ~/eapol_test/payload.admin-akam.json -T 'application/json'
http://127.0.0.1:5002/ntlm/auth
```

```
Requests per second:    721.03 [#/sec] (mean)
Time per request:       2.774 [ms] (mean)
Time per request:       1.387 [ms] (mean, across all concurrent requests)
```

```
ab -n 20000 -c 3 -p ~/eapol_test/payload.admin-akam.json -T 'application/json'
http://127.0.0.1:5002/ntlm/auth
```

```
Requests per second:    932.21 [#/sec] (mean)
Time per request:       3.218 [ms] (mean)
Time per request:       1.073 [ms] (mean, across all concurrent requests)
```

Based on the test results, with a single machine account created on Windows AD, the backend API is possible to handle around 400 requests/s, with 3 machine accounts, the capacity will raise up to around 1000 req/s, which is a quite busy and heavy-load case.

We suggest creating no more than 5 additional machine accounts (6 total) to maximize the performance as well as keeping the Windows Event log clean and easy for debugging.

For low worker loads cases, 1 additional machine account is recommended - just to avoid jitter when the master process terminates the old process after 10k requests and re-spawn a new one.

25.2. NT Key Caching

NOTE

This section assumes that you already have an Active Directory domain configuration both in *Configuration* → *Policies and Access Control* → *Domains* → *Active Directory Domains* and *Configuration* → *Policies and Access Control* → *Authentication Sources*. If you don't, you need to first configure those. Refer to the appropriate sections of this guide for details on how to configure these two components.

Using NTLM authentication against an Active Directory for 802.1X EAP-PEAP connections can become a bottleneck when handling dozens of authentications per second. It is possible for PacketFence to cache NT keys in order to reduce external NTLM authentications. The NT key cache temporarily stores the NT session key for all connected devices, not the

password or NT hashes.

When NT key caching is enabled, PacketFence will perform a transitive login with the Domain Controller, and cache the NT key of all connected devices that have successfully authenticated. Subsequent authentications will skip the transitive login with the Domain Controller and use the cached NT key. Wrong password and old password attempts are counted and cached to prevent the user account from being locked out from the Domain Controller.

CAUTION

The cache requires minimally *Windows Server 2008*. Older versions will not work. To ensure a better performance and flexible NTLM authentication caching, *Windows 2012 R2* or later version is recommended.

CAUTION

The NT key cache uses timestamps to determine the NT key expiration time and dirty-status, Timezone settings for PacketFence and the Windows Domain Controller must be identical and system clocks should be synchronized using NTP.

25.2.1. PacketFence Configuration

Create Domain

To Enable NT key caching, create a valid Domain config entry in *Configuration → Policies and Access Control → Domains → Active Directory Domains*

In the *NT Key cache* tab,

- Enable NT Key cache.
- Specify a cache expiration time. Ranges from 60 to 86400. Default is 12000 (in seconds).
- Fill in the Windows Group Policy Settings
 - ☐ Account Lockout Threshold
 - ☐ Reset Account Lockout Counter After
 - ☐ Account Lockout Duration
 - ☐ Old Password Allowed Period

NOTE

Cache expiration time: a value longer than reauth period settings on the switch is recommended. E.g., If the reauth period on a Cisco switch is set to 10800s, a value less than 10800 may cause the cache entry to expire before reauth.

25.2.2. Restart NTLM Auth API

Restart the PacketFence NTLM Auth API to commit the changes.

```
systemctl restart packetfence-ntlm-auth-api
```

Windows Account Policies

Those settings can be found on the Windows Domain Controller by the following steps:

Go to *Start menu* → *Administrative Tools* → *Group Policy Management*.


In the console tree, expand **Forest** → **Domains** → **Domain Name** → **Group Policy Objects** → **Default Domain Policy**

In the right panel, navigate to **Settings** page, You will have these parameters in **Policies** → **Windows Settings** → **Security Settings** → **Account Policies, Account lockout policies**

For **Old Password Allowed Period**, There's no group policy settings. The default value is 60 (in minutes). It can be changed using the following guide:

<https://learn.microsoft.com/en-US/troubleshoot/windows-server/windows-security/>

new-setting-modifies-ntlm-network-authentication



NOTE

Steps may vary on different versions of *Windows*. The steps and screenshots above are from *Windows Server 2022*.

NOTE

In newer version of Windows Server, if you didn't see some of the values listed above, they might be in default value. You can check the values by clicking "Edit" on domain policies to check its default values.

Create PacketFence User

Create a dedicated user that receives Windows Events from Domain Controller and reports the events to NT Key caching service:

- In the PacketFence Admin UI **Users** section, create a new local user with a unique **username** and a strong **password**. Remember these for *Config Windows Event Notifier*
- Change **Access Level** to **Windows Event Receiver NTLM**

25.2.3. Active Directory Configuration

Report the account **Account Password Change**, **Account Password Reset** (and optionally **User Account Unlock**) to PacketFence in order to help NT Key cache invalidate cache entries accurately.

Windows Event Notifier Configuration

Windows Event Notifier is a powershell script used to filter, analyze and report account management events to PacketFence.

Events include: * Account password change (Windows Event ID: 4723): mandatory for NT key cache * Account password reset (Windows Event ID: 4724): mandatory for NT key


cache * User account unlock (Windows Event ID: 4767): optional, recommended - when disabled a user lock state is cached 60s after unlock from Domain Controller

Preparation


Copy the powershell script and replace: * Copy `/usr/local/pf/addons/AD/password_change_notifier.ps1` to **each** Domain Controller that requires NT Key caching. * Change **\$base_url** and replace **#PACKETFENCE_IP** with the IP address of the PacketFence server. * Enter **\$username** and **password** from *Create PacketFence User* above. * Enter **\$domainID** from *Create Domain* above.

Config Scheduled Tasks


- Open **Windows Task Scheduler** and in the left-panel expand **Event Viewer Tasks**, on the right-panel, right-click on the blank area and select **Create new task...**
- In the popup window, **Name** the task and in **Security options** select **Run whether user is logged on or not**.



- Click on **Trigger** tab, then click **New...**
- In the popup window, for **Begin the task** select **On an event**, for **Log** select **Security**, for **Event ID** type in **4723**, click "OK".
- Repeat these steps to add event trigger(s) for the **Account Password Reset** and optionally **User Account Unlock** events.




- Click on **Action** tab, for **Action** select **Start a program**, in **Program/script** type the full path to powershell.exe (usually `C:\Windows\System32\WindowsPowerShell\v1.0\powershell.exe`).
- In **Add arguments** type the full path to the powershell script (eg: `C:\Users\Administrator\Desktop\event-notifier.ps1`).
- In **Start in** type the working directory (eg: `C:\Users\Administrator\Desktop`).




- Click "OK" to save the changes, Enter the Administrator password.

or

- Open **Windows Event Viewer** and click an event with EventID of **4723** (password change) or **4724** (password reset).
- Repeat the following steps for each Event ID.



- Select **Attach tasks to this event** in the right panel, then choose **Launch a program** for action option, fill in the `powershell REAL_ABSOLUTE_PATH_OF_THE_NOTIFIER_SCRIPT`, click "Save".
- Run the script with **Administrator Privilege** otherwise it will fail to read windows events.



Test Password Change

Manually reset a user password in **Active Directory Users and Computers** and check to see if PacketFence received the event. The JSON entry in the `chi_cache` value should contain **dirty: 1**. If PacketFence fails to receive the Event, check the logs in the working directory from *Config Scheduled Tasks* above for more information.

On the PacketFence server, use the cache query below and replace the `[domainID]` with the Domain ID from *Create Domain* above, and the `[username]` of the account user.

```
mysql pf

mysql> SELECT value from chi_cache WHERE
key='nt_key_cache:[domainID]:[username]';
```

25.3. NTLM Authentication Caching

NOTE

This section assumes that you already have an Active Directory domain configuration both in *Configuration → Policies and Access Control → Domains → Active Directory Domains* and *Configuration → Policies and Access Control → Authentication Sources*. If you don't, you need to first configure those. Refer to the appropriate sections of this guide for details on

how to configure those two components.

CAUTION

The cache requires minimally Windows Server 2008. Older versions will not work.

When using NTLM authentication against an Active Directory for 802.1X EAP-PEAP connections, this can become a bottleneck when handling dozens of authentications per seconds.

To overcome this limitation, it is possible to use a Redis driven cache inside PacketFence to reduce the amount of authentications requiring an external NTLM authentication call. Should a user be in the cache, PacketFence will attempt to compare the 802.1X credentials with those. In the event that the validation fails, a call to `ntlm_auth` is made. In the event of a cache miss, an `ntlm_auth` call is made as well. This ensures that even if a user changes his password, his new password is immediately valid for 802.1X EAP-PEAP connections even if the cache contains the outdated entry.

NOTE

The NTLM cache doesn't cache clear text passwords, it caches the NT hash of the user password.


25.3.1. PacketFence Configuration

First of all, you will need to enable the NTLM caching globally by enabling 'NTLM Redis cache' in *Configuration* → *System Configuration* → *Radius* → *General*. You then need to restart `radiusd-auth` service.

Once that is done, you need to configure PacketFence to start caching the credentials. In order to do so, go in *Configuration* → *Policies and Access Control* → *Domains* → *Active Directory Domains* and select the domain you want to cache the credentials for.

Next, go in the **NTLM cache** tab and:

- Enable 'NTLM cache'
- Select the Active Directory authentication source that is tied to this domain.
- Adjust the 'Expiration'



Once done, click on **Save** to commit the changes.

After that, you will need to enable the `redis_ntlm_cache` service which is used by PacketFence to store the cached credentials. In order to do so, go in *Configuration* → *System Configuration* → *Main Configuration* → *Services* and enable 'redis_ntlm_cache' and save the changes.

Next, start the service via pfcmd:

```
/usr/local/pf/bin/pfcmd service redis_ntlm_cache start
```

25.3.2. Active Directory configuration

In order for PacketFence to be able to fetch the NTLM credentials from the Active Directory, it will need a user who has replication rights. The user to which you have to grant the rights, is the one that is configured in the authentication source that was associated in the 'NTLM cache' section of the domain.

Please refer to the following Microsoft KB entry to configure the replication rights (Replicating Directory Changes and Replicating Directory Changes All): <https://support.microsoft.com/en-us/kb/303972>

25.4. SNMP Traps Limit

PacketFence mainly rely on SNMP traps to communicate with equipment. Due to the fact that traps coming in from approved (configured) devices are all processed by the daemon, it is possible for someone who want to generate a certain load on the PacketFence server to force the generation of non-legitimate SNMP traps or a switch can randomly generate a high quantity of traps sent to PacketFence for an unknown reason.

Because of that, it is possible to limit the number of SNMP traps coming in from a single switch port and take action if that limit is reached. For example, if over 100 traps are received by PacketFence from the same switch port in a minute, the switch port will be shut and a notification email will be sent.

Here's the default config for the SNMP traps limit feature. As you can see, by default, PacketFence will log the abnormal activity after 100 traps from the same switch port in a minute. These configurations are in the `conf/pf.conf` file:

```
[snmp_traps]
trap_limit = enabled
trap_limit_threshold = 100
trap_limit_action =
```

Alternatively, you can configure these parameters from the admin interface, in the *Configuration* → *Network Configuration* → *SNMP* section.

25.5. MariaDB optimizations

25.5.1. Tuning MariaDB

If the PacketFence system is acting very slow, this could be due to the MariaDB configuration. You should do the following to tune performance:

Check the system load

```
# uptime
11:36:37 up 235 days,  1:21,  1 user, load average: 1.25, 1.05, 0.79
```

Check iostat and CPU

```
# iostat 5
avg-cpu:  %user   %nice    %sys %iowait    %idle
           0.60    0.00    3.20   20.20   76.00
Device:            tps    Blk_read/s    Blk_wrtn/s    Blk_read    Blk_wrtn
cciss/c0d0          32.40         0.00       1560.00         0       7800
avg-cpu:  %user   %nice    %sys %iowait    %idle
           0.60    0.00    2.20    9.20   88.00
Device:            tps    Blk_read/s    Blk_wrtn/s    Blk_read    Blk_wrtn
```



```
cciss/c0d0      7.80      0.00      73.60      0      368
avg-cpu:  %user  %nice   %sys %iowait  %idle
           0.60   0.00   1.80  23.80  73.80
Device:            tps   Blk_read/s   Blk_wrtn/s   Blk_read   Blk_wrtn
cciss/c0d0      31.40      0.00      1427.20      0      7136
avg-cpu:  %user  %nice   %sys %iowait  %idle
           0.60   0.00   2.40  18.16  78.84
Device:            tps   Blk_read/s   Blk_wrtn/s   Blk_read   Blk_wrtn
cciss/c0d0      27.94      0.00      1173.65      0      5880
```

As you can see, the load-average is 1.25 and iowait is peaking at 20% - this is not good. If the iowait is low but the MariaDB is taking over 50% CPU this is also not good. Check the MariaDB install for the following variables:

```
MariaDB> show variables;
| innodb_additional_mem_pool_size | 1048576 |
| innodb_autoextend_increment     | 8       |
| innodb_buffer_pool_ave_mem_mb   | 0       |
| innodb_buffer_pool_size         | 8388608 |
```

PacketFence relies heavily on InnoDB, so you should increase the **buffer_pool** size from the default values.

Go in the admin interface , in *Configuration* → *System Configuration* → *Database* → *Advanced* and raise the value of **InnoDB buffer pool size**.

Then restart packetfence-mariadb

```
# systemctl restart packetfence-mariadb
```

Wait 10 minutes re-check iostat and CPU

```
# uptime
12:01:58 up 235 days,  1:46,  1 user, load average: 0.15, 0.39, 0.52
# iostat 5
Device:            tps   Blk_read/s   Blk_wrtn/s   Blk_read   Blk_wrtn
cciss/c0d0      8.00      0.00      75.20      0      376

avg-cpu:  %user  %nice   %sys %iowait  %idle
           0.60   0.00   2.99  13.37  83.03

Device:            tps   Blk_read/s   Blk_wrtn/s   Blk_read   Blk_wrtn
cciss/c0d0      14.97      0.00      432.73      0      2168
avg-cpu:  %user  %nice   %sys %iowait  %idle
           0.20   0.00   2.60   6.60  90.60
```

Device:	tps	Blk_read/s	Blk_wrtn/s	Blk_read	Blk_wrtn
cciss/c0d0	4.80	0.00	48.00	0	240

25.5.2. Avoid "Too many connections" problems

In a wireless context, there tends to be a lot of connections made to the database by our **freeradius** module. The default MariaDB value tends to be low (100) so we encourage you to increase that value to at least 300. See <https://dev.mysql.com/doc/refman/5.0/en/too-many-connections.html> for details.

25.5.3. Avoid "Host <hostname> is blocked" problems

In a wireless context, there tend to be a lot of connections made to the database by our **freeradius** module. When the server is loaded, these connection attempts can timeout. If a connection times out during connection, MariaDB will consider this a connection error and after 10 of these (by default) he will lock the host out with a:

```
Host 'host_name' is blocked because of many connection errors. Unblock with
'mysqldadmin flush-hosts'
```

This will grind PacketFence to a halt so you want to avoid that at all cost. One way to do so is to increase the number of maximum connections (see above), to periodically flush hosts or to allow more connection errors. See <https://dev.mysql.com/doc/refman/5.0/en/locked-host.html> for details.

25.5.4. Using MariaDB-backup

When dealing with a large database, the database backup and maintenance script (**/usr/local/pf/addons/exportable-backup.sh**) which uses **mysqldump** may create a long lock on the database which may cause service to hang.

This is fixed easily by using MariaDB-backup which can complete a full database backup without locking the tables.

RHEL-based systems

```
yum install MariaDB-backup --enablerepo=packetfence
```

Debian-based systems (for PacketFence versions 11.0 and later)

```
apt install mariadb-backup
```

Debian-based systems (for PacketFence versions prior to 11.0)

```
apt install mariadb-backup-10.2
```

Once this is done, grant the proper rights to the **pf** user (or the one you configured in **pf.conf**):

```
# mysql -u root -p
MariaDB> GRANT PROCESS, RELOAD, LOCK TABLES, REPLICATION CLIENT ON *.* TO
'pf'@'localhost';
MariaDB> FLUSH PRIVILEGES;
```

Next, run the maintenance script `/usr/local/pf/addons/exportable-backup.sh` and ensure that the following line is part of the output:

```
Exportable backup is done
```

If the backup fails, check `/usr/local/pf/logs/innobackup.log` for details and refer to the MariaDB-backup documentation for troubleshooting.

NOTE

In the event that MariaDB-backup should no longer be used for MariaDB backups, simply uninstall it and the database script will fallback to mysqldump.

25.6. Captive Portal Optimizations

25.7. Troubleshooting

This section will address specific problems and known solutions.

25.7.1. "Internet Explorer cannot display the webpage"

Problem: Internet Explorer 8-10 may raise an "Internet Explorer cannot display the webpage" error while attempting to access PacketFence admin interface because TLSv1.2 is not activated but required since PacketFence 7.

Solution:

- PacketFence admin interface is not started:

```
# cd /usr/local/pf
# bin/pfcmd service httpd.admin start
```

- It is strongly advised to update the browser to Internet Explorer 11 or download an alternative.
- TLSv1.2 needs to be activated manually in Internet Explorer 8-10.

Within Internet Explorer: click 'Tools -> Internet Options -> Advanced' and make sure that TLS v1.2 is enabled under the security section. Retry.

26. Advanced Network Topics

26.1. Floating Network Devices

PacketFence supports floating network devices. A Floating network device is a device for which PacketFence has a different behavior compared to a non-floating (regular) network device. This functionality was originally added to support mobile Access Points.

CAUTION

Currently only Cisco and Nortel switches configured with port-security are supported.

A regular device is placed in the VLAN corresponding to its status (Registration, Isolation or Production VLAN) and is authorized on the port (port-security). This is not managed the same way as a floating network device.

When a floating network device is connected, PacketFence will let/allow all the MAC addresses are connected to this device or appear on the port. If necessary the port is configured as multi-vlan (trunk) the PVID is set and VLANs are tagged on the port.

When a floating network device is disconnected, PacketFence will reconfigure the port to what it was before the device connected.

26.1.1. How it works

Configuration:

- floating network devices have to be identified using their MAC address.
- linkup/linkdown traps are not enabled on the switches, only port-security traps are enabled.

When a port-security trap is received for a floating network device, the port configuration is changed with:

- disable port-security
- set the PVID
- eventually set the port as multi-vlan (trunk) and set the tagged VLANs
- enable linkdown traps

When a linkdown trap is received on a port in which a floating network device was connected, the port configuration is changed with:

- enable port-security
- disable linkdown traps

26.1.2. Identification

Each floating network device has to be identified. There are two ways to do this:

- by editing `/usr/local/pf/conf/floating_network_device.conf`
- through the admin interface, in *Configuration* → *Network Configuration* → *Floating Device*

Available settings:

MAC Address

MAC address of the floating device.

IP Address

IP address of the floating device (not required, informational only).

trunkPort

Should the port be configured as a multi-vlan port (yes/no)?

pvid

Port VLAN.

taggedVlan

Comma separated list of VLANs. If the port is a multi-vlan, these are the VLANs that are tagged on the port.

26.2. Production DHCP access

MAC addresses need to be mapped to IP addresses in order to perform access control.

To have the ability to isolate a node or to have IP information about a node within a network or VLAN, **one** of the following techniques must be used.

NOTE

This is not required for the Registration or Isolation VLANs and inline interfaces since PacketFence acts as the DHCP server within these networks.

26.2.1. IP Helpers

If IP-helpers for your production DHCP in your production VLANs are already being used then this approach is the simplest to setup and works the best.

Add PacketFence's management IP address as the last `ip helper-address` in your network equipment. PacketFence will receive a copy of all DHCP requests for that VLAN and will record the IP addresses that were leased to each device using the `pfdhcplistener` daemon.

No DHCP Server should be listening on the interface where these requests are being sent, otherwise PacketFence would pointlessly reply to all DHCP requests.

26.2.2. Copy of the DHCP traffic

To copy all the DHCP Traffic from a dedicated physical interface of the PacketFence server

run `pfdhcpListener` on the desired interface. This will properly configure the switch in order to perform port mirroring (network span) and sets the proper interface parameters to the operating system and in `/usr/local/pf/conf/pf.conf`.

`/etc/sysconfig/network-scripts/ifcfg-eth2:`

```
DEVICE=eth2
ONBOOT=yes
BOOTPROTO=none
```

Add to `/usr/local/pf/conf/pf.conf`:

```
[interface eth2]
mask=255.255.255.0
type=dhcp-listener
gateway=192.168.1.5
ip=192.168.1.1
```

NOTE | The IP address is not important and is only used to start PacketFence.

Restart PacketFence to apply the changes.

26.2.3. Interface in every VLAN

Because DHCP traffic is broadcast traffic, an alternative for small networks with few local VLANs is to put a VLAN interface for every VLAN on the PacketFence server and have a `pfdhcpListener` listen on that VLAN interface.

On the network side ensure that the VLAN reaches from your client to the DHCP infrastructure to the PacketFence server.

First configure an operating system VLAN interface in PacketFence like the example below `/etc/sysconfig/network-scripts/ifcfg-eth0.1010`:

```
# Engineering VLAN
DEVICE=eth0.1010
ONBOOT=yes
BOOTPROTO=static
IPADDR=10.0.101.4
NETMASK=255.255.255.0
VLAN=yes
```

Then specify `type=dhcp-listener` in `/usr/local/pf/conf/pf.conf` within the VLANs using DHCP:


```
[interface eth0.1010]
mask=255.255.255.0
```

```
type=dhcp-listener
gateway=10.0.101.1
ip=10.0.101.4
```

Repeat the above steps for all production VLANs then restart PacketFence to apply the changes.

26.3. Routed Networks

PacketFence will need to be configured if the Isolation and Registration networks are not reachable locally (at layer 2) on the network, but instead routed to the PacketFence server. PacketFence is able to provide DHCP and DNS in these routed networks.



For dhcpd, ensure the clients DHCP requests are being forwarded correctly (IP Helpers in the remote routers) to the PacketFence server.

Considering the network architecture illustrated above, `/usr/local/pf/conf/pf.conf` will include the local Registration and Isolation interfaces only.

```
[interface eth0.2]
enforcement=vlan
ip=192.168.2.1
type=internal
mask=255.255.255.0
```

```
[interface eth0.3]
enforcement=vlan
ip=192.168.3.1
type=internal
mask=255.255.255.0
```

NOTE

PacketFence will not start unless at least one 'internal' interface is detected, thus local Registration and Isolation VLANs will need to be created even if they are not needed. The `dhcpd` daemon only listens on the 'internal' interfaces, therefore the remote Registration and Isolation subnets need to point their DHCP helper-address to those particular IP addresses.

Provide the routed networks to PacketFence through the admin interface in *Configuration* → *Network Configuration* → *Networks* or manually in `/usr/local/pf/conf/networks.conf`.

Example `/usr/local/pf/conf/networks.conf`:

```
[192.168.2.0]
netmask=255.255.255.0
gateway=192.168.2.1
next_hop=
domain-name=registration.example.com
dns=192.168.2.1
dhcp_start=192.168.2.10
dhcp_end=192.168.2.200
dhcp_default_lease_time=300
dhcp_max_lease_time=600
type=vlan-registration
named=enabled
dhcpd=enabled
```

```
[192.168.3.0]
netmask=255.255.255.0
gateway=192.168.3.1
next_hop=
domain-name=isolation.example.com
dns=192.168.3.1
dhcp_start=192.168.3.10
dhcp_end=192.168.3.200
dhcp_default_lease_time=300
dhcp_max_lease_time=600
type=vlan-isolation
named=enabled
dhcpd=enabled
```



```
[192.168.20.0]
netmask=255.255.255.0
gateway=192.168.20.254
next_hop=192.168.2.254
domain-name=registration.example.com
dns=192.168.2.1
dhcp_start=192.168.20.10
dhcp_end=192.168.20.200
dhcp_default_lease_time=300
dhcp_max_lease_time=600
type=vlan-registration
named=enabled
dhcpd=enabled
```

```
[192.168.30.0]
netmask=255.255.255.0
gateway=192.168.30.254
next_hop=192.168.3.254
domain-name=isolation.example.com
dns=192.168.3.1
dhcp_start=192.168.30.10
dhcp_end=192.168.30.200
dhcp_default_lease_time=300
dhcp_max_lease_time=600
type=vlan-isolation
named=enabled
dhcpd=enabled
```

Restart `packetfence-keepalived` to apply the changes:

```
/usr/local/pf/bin/pfcmd service keepalived restart
```

DHCP clients on the Registration and Isolation networks receive the PacketFence server IP as their DNS server in their lease, then DNS responses are spoofed to force clients via the portal. However, clients could manually configure their DNS settings to escape the portal. To prevent this, apply an ACL on the access router nearest to the clients, permitting access only to the PacketFence server and local DHCP broadcast traffic.

Example for VLAN 20 remote Registration network:

```
ip access-list extended PF_REGISTRATION
 permit ip any host 192.168.2.1
 permit udp any any eq 67
 deny ip any any log
 interface vlan 20
```

```
ip address 192.168.20.254 255.255.255.0
ip helper-address 192.168.2.1
ip access-group PF_REGISTRATION in
```

If the edge switches support 'vlan-isolation' the ACL can also be applied there. This has the advantage of preventing machines in Isolation from attacking each other.

26.4. Network Devices Definition

Used only for VLAN enforcement. Inline enforcement can skip this section.

PacketFence needs to know which switches, access points or controllers it manages, their type and configuration. You can modify this configuration directly in </usr/local/pf/conf/switches.conf> or from the admin interface in *Configuration → Policies and Access Control → Switches* (recommended).

The </usr/local/pf/conf/switches.conf> configuration file contains a default section including:

- Default SNMP read/write communities for the switches
- Default working mode (see the note below about possible working modes)

A switch section for each switch (managed by PacketFence) including:

- Switch IP/MAC/Range
- Switch vendor/type
- Switch uplink ports (trunks and non-managed IfIndex)
- per-switch re-definition of the VLANs (if required)

Reload the configuration to apply the changes:

```
/usr/local/pf/bin/pfcmd configreload
```

NOTE

Any ports declared as uplinks are ignored and not managed by PacketFence. This parameter is defined in the [default] section of </usr/local/pf/conf/switches.conf>. A different uplink list for each switch can be defined.

26.4.1. Working modes

Switches utilize three different working modes:

Testing

pfsetvlan writes in the log files what it would normally do, but no VLAN changes are performed.

Registration

pfsetvlan automatically registers all MAC addresses seen on the switch ports, but no VLAN changes are performed.

Production

pfsetvlan sends the SNMP writes to change the VLAN on the switch ports.

26.4.2. RADIUS

To set the RADIUS secret, set it from the Web Administrative GUI when adding a switch. Alternatively, edit the switch configuration file `/usr/local/pf/conf/switches.conf` and set the following parameters

```
radiusSecret = secretPassPhrase
```

NOTE

The RADIUS secret is required to support the RADIUS Dynamic Authentication (CoA or Disconnect) as defined in RFC3576.

26.4.3. SNMP v1, v2c and v3

SNMP is used to communicate with most switches. PacketFence also supports SNMPv3 which is used for bi-directional communication, from the switch to PacketFence and from PacketFence to the switch. SNMP usage is discouraged, as RADIUS should now be used. However, even if RADIUS is being used, some switches may also require SNMP configuration to work properly.

From PacketFence to a switch

Set the following parameters in the switch configuration file `/usr/local/pf/conf/switches.conf`:

```
SNMPVersion = 3
SNMPEngineID = AA5ED139B81D4A328D18ACD1
SNMPUserNameRead = readUser
SNMPAuthProtocolRead = MD5
SNMPAuthPasswordRead = authpwdread
SNMPPrivProtocolRead = AES
SNMPPrivPasswordRead = privpwdread
SNMPUserNameWrite = writeUser
SNMPAuthProtocolWrite = MD5
SNMPAuthPasswordWrite = authpwdwrite
SNMPPrivProtocolWrite = AES
SNMPPrivPasswordWrite = privpwdwrite
```

From a switch to PacketFence

Set the following parameters in the switch configuration file `/usr/local/pf/conf/switches.conf`:

```
SNMPVersionTrap = 3
SNMPUserNameTrap = readUser
```

```
SNMPAuthProtocolTrap = MD5
SNMPAuthPasswordTrap = authpwdread
SNMPPrivProtocolTrap = AES
SNMPPrivPasswordTrap = privpwdread
```

Switch Configuration

Set the following switch configuration in order to enable SNMPv3 in both directions on a Cisco Switch.

```
snmp-server engineID local AA5ED139B81D4A328D18ACD1
snmp-server group readGroup v3 priv
snmp-server group writeGroup v3 priv read v1default write v1default
snmp-server user readUser readGroup v3 auth md5 authpwdread priv aes 128
privpwdread
snmp-server user writeUser writeGroup v3 auth md5 authpwdwrite priv aes 128
privpwdwrite
snmp-server enable traps port-security
snmp-server enable traps port-security trap-rate 1
snmp-server host 192.168.0.50 version 3 priv readUser port-security
```

Obtain the SNMPv3 engine identifier (SNMPEngineID) with `show snmp engineid`.

Test from a PacketFence server

The `net-snmp` package can test SNMPv3 communication with a switch:

```
snmpget -v3 -l authPriv -u readUser -a MD5 -A "authpwdread" \
-x AES -X "privpwdread" IP_OF_YOUR_SWITCH sysName.0
```

NOTE | Passwords should be at least 8 characters in length.

26.4.4. Command-Line Interface: Telnet and SSH

WARNING | Privilege detection is disabled in the current PacketFence version due to some issues (see [#1370](#)). Ensure that the `cliUser` and `cliPwd` provided grants privileged mode (except for Trapeze hardware).

PacketFence can occasionally establish an interactive command-line session with a switch. This can be done using either Telnet or SSH. Edit the switch configuration file `/usr/local/pf/conf/switches.conf` and set the following parameters or :

```
cliTransport = SSH (or Telnet)
cliUser = admin
cliPwd = admin_pwd
cliEnablePwd =
```

This can also be configured with the admin interface in *Configuration → Policies and Access Control → Switches*.

26.4.5. Web Services Interface

PacketFence can occasionally establish a Web Services dialog with a switch. Edit the switch config file `/usr/local/pf/conf/switches.conf` and set the following parameters:

```
wsTransport = http (or https)
wsUser = admin
wsPwd = admin_pwd
```

This can also be configured with the admin interface in *Configuration → Policies and Access Control → Switches*.

26.4.6. Role-based Enforcement

Some network devices support the assignment of a specific set of rules (firewall or ACLs) to a user. These rules are more accurate in controlling what a user can or cannot do compared to VLAN, which has a larger overhead with network management. PacketFence can assign roles on devices with switches and WiFi controllers that support role-based assignment.

NOTE The current role assignment strategy is to assign the role along with the VLAN (this may change in the future).

A special internal-role to external-role assignment must be configured in the switch configuration file `/usr/local/pf/conf/switches.conf` using the format `<role_name>Role=<controller_role>`. Provide the internal-role to external-role assignments on either the switch, or the parent switch group.

Example that returns the `full-access` role to the nodes categorized as admin or engineering and the role `little-access` to nodes categorized as sales:

```
adminRole=full-access
engineeringRole=full-access
salesRole=little-access
```

This can also be configured with the admin interface in *Configuration → Policies and Access Control → Switches*.

CAUTION Ensure the roles are defined in the network devices prior to configuring role-based assignment.

26.4.7. VoIP Integration with CDP, LLDP and LLDP-MED

Cisco Discovery Protocol (CDP) is device-discovery protocol supported on all Cisco-manufactured equipment including routers, access servers, bridges, and switches. Using CDP, a device can advertise its existence to other devices and receive information about other devices on the same LAN or on the remote side of a WAN. CDP can determine if the connecting device is an IP Phone, and instruct the IP Phone to tag ethernet frames using

the configured voice VLAN on the switchport.

Many other vendors support LLDP or LLDP-MED. Link Layer Discovery Protocol (LLDP) is a vendor-neutral Link Layer protocol in the Internet Protocol Suite used by network devices for advertising their identity, capabilities, and neighbors. Same as CDP, LLDP can instruct an IP Phone which VLAN ID is the voice VLAN.

26.4.8. VoIP and VLAN assignment

VLAN assignment techniques such as port-security, MAC authentication and 802.1X are supported.

Port-security

Using port-security, the VoIP device relies on CDP/LLDP to tag the ethernet frames using the configured voice VLAN on the switch port. Afterwards a security trap is sent from the voice VLAN so PacketFence can authorize the MAC address on the port. When the device connects another security trap is sent from the data VLAN. That way, 1 MAC address is authorized on the voice VLAN, and 1 on the access VLAN.

NOTE | Not all vendors support VoIP on port-security, please refer to the *Network Configuration Guide*.

MAC Authentication and 802.1X

Cisco switches support a multi-domain configuration using Vendor-Specific Attributes (VSA), which allows one device on the VOICE domain and one device on the DATA domain. When the phone connects to the switch port, PacketFence will only respond with the proper VSA, no RADIUS tunneled attributes. CDP then instructs the phone to tag ethernet frames using the configured voice VLAN on the switch port. When a PC connects, the RADIUS server returns the tunneled attributes, and the switch will place the port in the provided access VLAN.

On other vendor hardware VoIP works using RADIUS VSAs. When an IP phone connects to a switch port, the proper VSA is returned to instruct the switch to allow tagged frames from this device. When a PC connects, PacketFence will return the standard RADIUS tunnel attributes to the switch, for the untagged VLAN.

NOTE | Refer to the *Network Configuration Guide* for switch hardware VoIP support.

26.4.9. What if CDP/LLDP feature is missing

If an IP phone does not support CDP or LLDP, DHCP can be used to provision the device with a voice VLAN. Some models require a specific DHCP option in order for the DHCP server to lease the device a voice VLAN ID. After rebooting the ethernet frames are tagged using the provided VLAN tag.

For this scenario to work, the Registration and Production DHCP servers must be configured to provide the DHCP option, there is a voice VLAN configured on the port, and IP Phones are auto-registered (On the first connection, the phone is assigned on the registration VLAN).

26.5. DHCP Option 82

PacketFence is able to locate a device on the network even if the switch port is not managed by PacketFence.

All switches must be added and *SNMP read* (switch and PacketFence side) enabled in *Configuration → Policies and Access Control → Network Devices → Switches*.

Enable *DHCP option 82* in *Configuration → Network Configuration → Networks → Network*. Once enabled, restart the `pfdhcplistener` and `pfmon` (or `pfcron`, if Packetfence version is ≥ 10.2) services. `pfmon` (or `pfcron`) queries all the switches via SNMP to maintain a map (MAC address → switch). `pfdhcplistener` parses DHCP Option 82 and uses the map to resolve the MAC to the switch while updating the locationlog of the device.

27. Additional Integration

27.1. DHCP Remote Sensor

The DHCP remote sensor consists of a lightweight binary installed on the production DHCP server to replicate all DHCP traffic (1-to-1) to the PacketFence server. This solution is more reliable than DHCP relaying since PacketFence receives a copy of all the DHCP traffic including broadcast traffic. Supported DHCP servers include Microsoft DHCP server and CentOS 6 and 7.

These sensors capture low-level packets on the DHCP server and forwards them to the PacketFence management interface.

27.1.1. Microsoft Remote Sensor

The PacketFence-Forwarder is an optimized version of the udp-reflector, which installs easily and only forwards DHCPREQUESTS and DHCPACK packets from the source to the destination as well optionally mirroring DNS traffic for integration with the Fingerbank Collector

Download the [DHCP Forwarder installer](#).

This installs `nPCAP`, `nssm`, launches a configurator for the interface, IP and port, saves the configuration, and finally installs and launches the DHCP-Forwarder service.

When asked for a host IP and UDP port for DHCP mirroring provide the PacketFence management IP and 767 respectively.

Visit the [PacketFence Forwarder project page](#).

27.1.2. Linux-based Sensor

First download the RPM on your DHCP server.

CentOS 6 and 7 servers

For CentOS 6 (x86_64):

```
wget http://inverse.ca/downloads/PacketFence/CentOS6/extra/x86_64/RPMS/udp-reflector-1.0-6.1.x86_64.rpm
```

For CentOS 7 (x86_64):

```
wget http://inverse.ca/downloads/PacketFence/CentOS7/extra/x86_64/RPMS/udp-
```



```
reflector-1.0-6.1.x86_64.rpm
```

Install the sensor with `rpm`:

```
rpm -i udp-reflector-*.rpm
```

Compiling the sensor from source on a Linux system

First ensure the following packages are installed:

- libpcap
- libpcap-devel
- gcc-c++

Get the sensor source code:

```
mkdir -p ~/udp-reflector && cd ~/udp-reflector
wget http://inverse.ca/downloads/PacketFence/udp-reflector/udp_reflector.cpp
g++ udp_reflector.cpp -o /usr/local/bin/udp_reflector -lpcap
```

Configure the Sensor

Place the following line in `/etc/rc.local`

- where `pcap0` is the pcap interface where the DHCP server listens on. (List them using `udp_reflector -l`)
- where `192.168.1.5` is the management IP of the PacketFence server

```
/usr/local/bin/udp_reflector -s pcap0:67 -d 192.168.1.5:767 -b 25000 &
```

Start the sensor:

```
/usr/local/bin/udp_reflector -s pcap0:67 -d 192.168.1.5:767 -b 25000 &
```

All DHCP traffic is now reflected to the PacketFence server.

27.2. Active Directory Integration

27.2.1. Deleted Account

Create the script `unreg_node_deleted_account.ps1` on the Windows Server with the following content:

```
#####
```

```
#####
#Powershell script to unregister deleted Active Directory account based on the
#UserName.#
#####

Get-EventLog -LogName Security -InstanceId 4726 |
    Select ReplacementStrings,"Account name"|
    % {
        $url = "https://@IP_PACKETFENCE:9090/"
        $username = "admin" # Username for the webservices
        $password = "admin" # Password for the webservices
        [System.Net.ServicePointManager]::ServerCertificateValidationCallback =
        {$true}
        $command = '{"jsonrpc": "2.0", "method": "unreg_node_for_pid", "params":
        ["pid", "'+$_.ReplacementStrings[0]+'"]}'

        $bytes = [System.Text.Encoding]::ASCII.GetBytes($command)
        $web = [System.Net.WebRequest]::Create($url)
        $web.Method = "POST"
        $web.ContentLength = $bytes.Length
        $web.ContentType = "application/json-rpc"
        $web.Credentials = new-object System.Net.NetworkCredential($username,
        $password)
        $stream = $web.GetRequestStream()
        $stream.Write($bytes,0,$bytes.Length)
        $stream.close()

        $reader = New-Object System.IO.Streamreader -ArgumentList
        $web.GetResponse().GetResponseStream()
        $reader.ReadToEnd()
        $reader.Close()
    }
}
```

NOTE

Change **@IP_PACKETFENCE** to the IP address of the PacketFence server and change the **\$username** and **\$password** so they match the credentials defined in the Web admin interface under *Configuration → Integration → Web Services*.

Create a scheduled task for an event ID

Start → Run → Task sched.msc

Task Scheduler → Task Scheduler Library → Event Viewer Task → Create Task

General

Name: PacketFence-Unreg_node-for-deleted-account

Check: Run whether user is logged on or not
Check: Run with highest privileges

Triggers → New

Begin on the task: On an event
Log: Security
Source: Microsoft Windows security auditing.
Event ID: 4726

Actions → New

Action: Start a program
Program/script: powershell.exe
Add arguments (optional): C:\scripts\unreg_node_deleted_account.ps1

Settings:

At the bottom, select in the list "Run a new instance in parallel" in order to unregister multiple nodes at the same time.

Validate with Ok and provide the account that will run this task (usually *DOMAIN\Administrator*).

27.2.2. Disabled Account

Preventing Authentication of Disabled Accounts via LDAP Filter

You can prevent disabled Active Directory accounts from authenticating through PacketFence by adding an LDAP filter that excludes accounts with the **ACCOUNTDISABLE** flag set.

In Active Directory, the **userAccountControl** attribute contains bitwise flags that indicate account properties. Bit 2 (**0x2**) corresponds to **ACCOUNTDISABLE**. The following LDAP filter uses the bitwise AND matching rule (**1.2.840.113556.1.4.803**) to check whether this bit is set, and excludes those accounts from search results:

```
(!(userAccountControl:1.2.840.113556.1.4.803:=2))
```

To configure this in PacketFence:

1. Go to *Configuration → Policies and Access Control → Authentication Sources*.
2. Edit your Active Directory authentication source.
3. In the *Append search attributes LDAP filter* field, paste the filter above.
4. Save the configuration.

With this filter in place, LDAP search filters generated for authentication lookups, such as username-based authentication and matching, will exclude disabled accounts and help prevent them from authenticating.

NOTE

This is a **preventive** approach that blocks authentication at LDAP search time. It applies to LDAP filters generated through the authentication source's append-search-attributes mechanism, rather than globally to every search path supported by the source. To apply the check at the level of individual authentication rules instead, see the next section.

Rejecting Disabled Accounts in Authentication Rules

You can also check the `userAccountControl` attribute directly in authentication rule conditions using the **has bit** and **not has bit** operators. These operators perform a bitwise AND check against the attribute value, which is the correct way to test individual flags in a bitmask attribute like `userAccountControl`.

In Active Directory, bit 2 (0x2) of `userAccountControl` corresponds to `ACCOUNTDISABLE`: when this bit is set, the account is disabled. A rule that matches disabled accounts and assigns the `REJECT` role is therefore the correct way to block them.

To create a rule that rejects disabled accounts:

1. Go to *Configuration → Policies and Access Control → Authentication Sources*.
2. Edit your Active Directory authentication source and create a new authentication rule (place it **above** your other rules so it is evaluated first).
3. Add a condition: `userAccountControl → has bit → 2`.
4. In the rule actions, set *Role* to `REJECT` and set an *Access duration* (for example, `1 hour`).
5. Save the rule.

This rule matches any account that has the `ACCOUNTDISABLE` bit set (bit 2), regardless of what other flags are present in `userAccountControl`, and rejects the authentication.

NOTE

Standard operators like *equals* or *not equals* perform a simple string comparison on the full `userAccountControl` value and are not suitable for bitmask attributes. Always use *has bit* or *not has bit* when checking individual flags.

Unregistering Nodes When an Account is Disabled (Event-Based)

Create the script `unreg_node_disabled_account.ps1` on the Windows Server with the following content:

```
#####
#####
#Powershell script to unregister disabled Active Directory account based on the
UserName.#
#####
#####

Get-EventLog -LogName Security -InstanceId 4725 |
```

```

Select ReplacementStrings,"Account name"|
% {
    $url = "https://@IP_PACKETFENCE:9090/"
    $username = "admin" # Username for the webservises
    $password = "admin" # Password for the webservises
    [System.Net.ServicePointManager]::ServerCertificateValidationCallback =
{$true}
    $command = '{"jsonrpc": "2.0", "method": "unreg_node_for_pid", "params":
["pid", "'+$_.ReplacementStrings[0]+'"]}'

    $bytes = [System.Text.Encoding]::ASCII.GetBytes($command)
    $web = [System.Net.WebRequest]::Create($url)
    $web.Method = "POST"
    $web.ContentLength = $bytes.Length
    $web.ContentType = "application/json-rpc"
    $web.Credentials = new-object System.Net.NetworkCredential($username,
$password)
    $stream = $web.GetRequestStream()
    $stream.Write($bytes,0,$bytes.Length)
    $stream.close()

    $reader = New-Object System.IO.Streamreader -ArgumentList
$web.GetResponse().GetResponseStream()
    $reader.ReadToEnd()
    $reader.Close()

}

```

NOTE

Change **@IP_PACKETFENCE** to the IP address of the PacketFence server and change the **\$username** and **\$password** so they match the credentials defined in the Web admin interface under *Configuration* → *Integration* → *Web Services*.

Create a scheduled task for an event ID

Start → Run → Taskshcd.msc

Task Scheduler → Task Scheduler Library → Event Viewer Task → Create Task

General

Name: PacketFence-Unreg_node-for-disabled-account
 Check: Run whether user is logged on or not
 Check: Run with highest privileges

Triggers → New

Begin on the task: On an event

```
Log: Security
Source: Microsoft Windows security auditing.
Event ID: 4725
```

Actions → New

```
Action: Start a program
Program/script: powershell.exe
Add arguments (optional): C:\scripts\unreg_node_disabled_account.ps1
```

Settings:

At the bottom, select in the list "Run a new instance in parallel"

Validate with Ok and provide the account that will run this task (usually *DOMAIN\Administrator*).

27.2.3. Locked Account

Create the script `unreg_node_locked_account.ps1` on the Windows Server with the following content:

```
#####
#####
#Powershell script to unregister locked Active Directory account based on the
UserName.#
#####
#####

Get-EventLog -LogName Security -InstanceId 4740 |
    Select ReplacementStrings,"Account name"|
    % {
        $url = "https://@IP_PACKETFENCE:9090/"
        $username = "admin" # Username for the webservises
        $password = "admin" # Password for the webservises
        [System.Net.ServicePointManager]::ServerCertificateValidationCallback =
        {$true}
        $command = '{"jsonrpc": "2.0", "method": "unreg_node_for_pid", "params":
        ["pid", "' + $_.ReplacementStrings[0] + '"]}'

        $bytes = [System.Text.Encoding]::ASCII.GetBytes($command)
        $web = [System.Net.WebRequest]::Create($url)
        $web.Method = "POST"
        $web.ContentLength = $bytes.Length
        $web.ContentType = "application/json-rpc"
        $web.Credentials = new-object System.Net.NetworkCredential($username,
```

```

$password)
    $stream = $web.GetRequestStream()
    $stream.Write($bytes,0,$bytes.Length)
    $stream.close()

    $reader = New-Object System.IO.Streamreader -ArgumentList
$web.GetResponse().GetResponseStream()
    $reader.ReadToEnd()
    $reader.Close()

}

```

NOTE

Change **@IP_PACKETFENCE** to the IP address of the PacketFence server and change the **\$username** and **\$password** so they match the credentials defined in the Web admin interface under *Configuration → Integration → Web Services*.

Create the scheduled task based on an event ID

Start → Run → Task sched.msc

Task Scheduler → Task Scheduler Library → Event Viewer Task → Create Task

General

Name: PacketFence-Unreg_node-for-locked-account
 Check: Run whether user is logged on or not
 Check: Run with highest privileges

Triggers → New

Begin on the task: On an event
 Log: Security
 Source: Microsoft Windows security auditing.
 Event ID: 4740

Actions → New

Action: Start a program
 Program/script: powershell.exe
 Add arguments (optional): C:\scripts\unreg_node_locked_account.ps1

Settings:

At the bottom, select in the list "Run a new instance in parallel"

Validate with Ok and provide the account that will run this task (usually `DOMAIN\Administrator`).

27.3. Switch Login Access

PacketFence is able to provide an authentication and authorization service on port 1815 for granting command-line interface (CLI) access to switches. PacketFence currently supports Cisco switches which must be configured using the following guide: <https://www.cisco.com/c/en/us/support/docs/security-vpn/remote-authentication-dial-user-service-radius/116291-configure-freeradius-00.html>. From the PacketFence admin interface, configure an Admin Access role (*Configuration* → *System Configuration* → *Admin Access*) that contains the action 'Switches CLI - Read' or 'Switches CLI - Write' and assign this role to an internal user or with an Administration rule in an internal source.

Then enable **CLI Access Enabled** setting on the switch(s) to manage in *Configuration* → *Network devices* → *Switches*.

NOTE The **ALL** administrative role allows the user to login into the switches. Change this role to **ALL_PF_ONLY** to allow the user all the necessary administrative roles except for switch login.

27.4. Syslog forwarding

Syslog forwarding forwards PacketFence logs (all or specific log files) to a remote Syslog server using the Syslog protocol.

Configure this feature in *Configuration* → *Integration* → *Syslog Forwarding*

After adding a new Syslog server, perform the following commands:

```
systemctl restart rsyslog
```

Logs are retained on the PacketFence server **and** a copy is sent to the remote Syslog server(s).

27.5. Monit

monit manages and monitors processes, files, directories and filesystems on a Unix system. Monit conducts automatic maintenance and repair, and can execute meaningful causal-actions in error situations. E.g. Monit can start a process if it stops running, restart a process if it does not respond and stop a process if it uses too much resources.

For further reference the monit documentation is available at: <https://mmonit.com/monit/documentation/monit.html>

The monit configuration path is different between EL and Debian systems:

EL based systems:

- **MONIT_PATH=/etc/monit.d**

Debian based systems:

- `MONIT_PATH=/etc/monit/conf.d`

To simplify further documentation, `$MONIT_PATH` will be used as a reference to these paths herein.

Starting from PacketFence 11.1, the Monit configuration is directly managed by PacketFence.

To enable Monit, configure the following settings in *Configuration → System Configuration → Main Configuration → Monit*:

- Status: enabled
- Alert Email To: The email address(es) to send the alerts. If left empty, the default email addresses defined in *Configuration → System Configuration → Main Configuration → Alerting* will be used.
- Configuration: Enter the configurations for monit to use. If left empty, the defaults should be fine unless port-security enforcement or active/passive cluster is used.
- Mailserver: Specify the mailserver to use. This can only be used for unauthenticated relaying. If using localhost, ensure postfix is installed and properly configured. If left empty, the SMTP server settings in *Configuration → System Configuration → Main Configuration → Alerting* are used. Note that monit doesn't support StartTLS so 'none' or 'ssl' must be configured for SMTP encryption in the alerting configuration. If StartTLS is required, configure postfix for relaying and use 'localhost' as the Mailserver in the monit configuration.

Restart the monit service:

```
systemctl restart monit
```

27.5.1. Monitoring scripts

Digitally signed scripts are included in the monit configuration which are fetched from <https://inverse.ca/downloads/PacketFence/monitoring-scripts/v1/>. These scripts will be updated and run at regular intervals to ensure the environment follows the best practices defined by Inverse and to email alerts of any important changes that may need to be performed.

Run manually to help with troubleshooting:

```
/usr/local/pf/addons/monit/monitoring-scripts/update.sh  
/usr/local/pf/addons/monit/monitoring-scripts/run-all.sh
```

Ignoring some checks

To ignore one of the checks that are being performed, add its script name in `$MONIT_PATH/packetfence/local-ignores`.

For example, to ignore the script that generated the following output add

`/usr/local/pf/var/monitoring-scripts/.check-epel.sh` to `$MONIT_PATH/packetfence/local-ignores`:

```
-----  
/usr/local/pf/var/monitoring-scripts/.check-epel.sh failed  
Result of /usr/local/pf/var/monitoring-scripts/.check-epel.sh  
The EPEL repository is enabled. This can cause disastrous issues by having the  
wrong versions of certain packages installed. It is recommended to disable it  
using the following command: sed -i 's/enabled\s*=\s*1/enabled = 0/g'  
/etc/yum.repos.d/epel.repo  
-----
```

Run some checks as root

Some scripts need to run as root but are disabled by default. To run these checks add the following in `$MONIT_PATH/packetfence/local-vars`:

```
export RUN_ROOT_SCRIPTS=1
```

27.5.2. Monit Summary

View the monit summary and ensure all services show status **Running**, **Accessible**, or **Status ok**. Any services that display a failed status will need to be investigated. Monit will process and display the services in the same order that they are listed. If the summary appears stuck, troubleshoot the next service in the list.

```
monit summary
```

TIP

More information on the monit command line arguments is available at <https://mmonit.com/monit/documentation/monit.html>

27.6. FleetDM Integration

27.6.1. Background

PacketFence provides flexible osquery support, regular vulnerability checks, and policy compliance through FleetDM integration. From PacketFence v14.0, FleetDM can report policy violations and CVE vulnerabilities of managed nodes to PacketFence.

27.6.2. Install and Configure FleetDM

Follow FleetDM's official best practices to deploy the FleetDM service:

- FleetDM official website: <https://fleetdm.com/>
- Documentation: <https://fleetdm.com/docs/get-started/why-fleet>

NOTE

This guide assumes a running FleetDM service on the local network or hosted in the cloud, with Internet access to the PacketFence server.

27.6.3. Configure PacketFence

- Check if the **FleetDM Events Handler** role exists. Navigate to **Admin UI → Configuration → System Configuration → Admin Access** and verify the role appears in the right panel. If the role exists, skip the next step.
- Create the role if missing. Click **New admin role**, set name to **FleetDM Event Handler**, Description to **Receives FleetDM events**, actions to **FLEETDM_EVENTS_READ**, then click Save.
- Create a user from **Admin UI → Users → Create**. Choose a **Username (PID)** and **strong password**, set Access Level to **FleetDM Event Handler**

27.6.4. Configure FleetDM API in PacketFence

NOTE

PacketFence requires FleetDM API access to retrieve MAC addresses for affected hosts (policy violations or CVE vulnerabilities). Configure an API endpoint and credentials for these API calls.

NOTE


When both **API Token** and **email & password** are specified, PacketFence uses only the API token for authentication. Ensure a **Permanent** API Token is configured rather than a temporary one.

- Navigate to **Admin UI → Configuration → System Configuration → FleetDM** to configure the FleetDM endpoint.
- Enter **FleetDM login email** and **password** OR **FleetDM API Token**, then click Save.
- Temporary API tokens: Login to FleetDM, click the user icon (top right), select **My Account → Get API Token**
- To create a permanent API Key in FleetDM, please refer to official documents: https://fleetdm.com/docs/using-fleet/fleetctl-cli?utm_medium=fleetui&utm_campaign=get-api-token#using-fleetctl-with-an-api-only-user

The screenshot shows the PacketFence Admin UI Configuration page for FleetDM. The left sidebar contains a navigation menu with categories: Policies and Access Control, Compliance, Integration, Advanced Access Configuration, Network Configuration, and System Configuration. The System Configuration section is expanded, showing Main Configuration, General Configuration, Alerting, and Monit. The main content area is titled 'FleetDM' and contains the following fields:

- FleetDM Host:** https://YOUR_FLEETDM_HOST:8080
- FleetDM API Host:** (empty field)
- Email:** (empty field, with a note: Email / username for making fleetDM API calls.)
- Password:** (empty field, with a note: Password for making fleetDM API calls.)
- FleetDM API Token:** (empty field, with a note: Token used for making FleetDM API calls.)

At the bottom of the form are 'Save' and 'Reset' buttons.



27.6.5. Configure FleetDM

NOTE

Configure FleetDM and PacketFence with **valid SSL Certificates** rather than self-signed certificates. Valid certificates ensure successful device enrollment to FleetDM and reliable reporting of policy violations and CVEs to PacketFence. Policy violation webhooks and CVE webhooks are configured individually in the FleetDM admin UI.

Policy Violations

- Login to FleetDM admin Panel → **Policies** → **Manage Automations**.
- In the popup window, enable **Policy automations enabled**, workflow: **Webhook**.
- For destination URL, fill in <https://USER:PASS@packetfence.fqdn:9999/api/v1/fleetdm-events/policy>.
- Replace **USER** and **PASS** with the credentials created for the FleetDM Events Handler user in PacketFence. Replace **packetfence.fqdn** with the domain name or IP address of the PacketFence server.

Other workflows



☒ Policy automations enabled

Workflow

- ☐ Ticket
- ☒ Webhook

Destination URL

`https://user:pass@packetfence.fqdn:9999/api/v1/fleetdm-events/policy`

For each policy, Fleet will send a JSON payload to this URL with a list of the hosts that updated their answer to "No."

Show example payload

Policies:

- ☒ Antivirus healthy (Linux) (All teams)asasasasas
- ☒ No unencrypted SSH keys present - (All)
- ☒ System are rebooted in recent 7 days
- ☒ Test Policy Violations


The workflow will be triggered when hosts fail these policies. [Learn more](#)

Cancel

Save

CVEs

- Login to FleetDM admin Panel → **Software** → **Manage Automations**.
- In the popup window, enable **Vulnerability automations enabled**, workflow: **Webhook**.
- For destination URL, fill in <https://USER:PASS@packetfence.fqdn:9999/api/v1/fleetdm-events/cve>.
- Replace **USER** and **PASS** with the credentials created for the FleetDM Events Handler user in PacketFence. Replace **packetfence.fqdn** with the domain name or IP address of the PacketFence server.



27.6.6. Test and Validate Webhooks

Test webhook functionality from PacketFence with these steps:

- Complete PacketFence and FleetDM configurations.
- Login to the PacketFence node and use `journalctl -f` to watch PacketFence logs. Or you can choose not to use "-f" and search occurrences of webhook calls instead as well.
- Use any tool such as `grep` or built-in search highlights of your terminal application and search / watch for keyword `fleetdm`
- Manually trigger a policy violation or CVE to verify the webhook API returns a 2xx response.
- A successful report will be something like `api-frontend-access xx.xx.xx.xx - - [30/May/2024:12:42:00 -0400] "POST /api/v1/fleetdm-events/policy HTTP/2.0" 2xx xx "-" "Go-http-client/2.0"`

27.6.7. Customize and Integrate with Security Events

FleetDM integrates with PacketFence's Security Events system, enabling administrators to take actions such as isolating devices, sending notification emails, or triggering scripts when FleetDM reports policy violations or CVE vulnerabilities.

PacketFence 14.0+ includes 3 built-in security event templates: policy IDs "3500001", "3500002", and "3500003". Each template corresponds to a specific rule type supported in PacketFence. Modify these existing security events, add custom policy triggers, or use them as templates for new events. These security events are disabled by default and must be manually enabled.

27.6.8. How Security Events Work with FleetDM

PacketFence identifies and manages devices through its node list (**Admin UI → Nodes**). FleetDM uses unique host IDs to identify enrolled devices. PacketFence builds a mapping between these two identification systems.

The mapping process:

1. When FleetDM reports a policy violation or CVE vulnerability via webhook, the payload includes a **host id**.
2. PacketFence receives the payload, extracts the host id, and looks it up in the internal cache. If found, PacketFence uses the cached MAC address.
3. If the host ID is not cached, PacketFence makes a FleetDM API call to obtain the host's primary MAC address and caches it. FleetDM API responses do not always guarantee a MAC address.
4. PacketFence compares the trigger rules of filtered security events. If a match is found, the security event triggers for each reported device.

NOTE

If a mac address can not be retrieved from FleetDM API call (step 3), it may be due to either an unsuccessful API call or a response does not contain a **primary_mac**, PacketFence will fail to trigger security event. You will see an error in PacketFence logs like: "unable to extract primary mac from host API response for host id", or "unable to perform API call", etc. Please check the logs if you believe a security event should be triggered.

Security Event 3500001

Default security event for FleetDM policy violation checks. Uses regular expressions to match policy names. For example, with a FleetDM policy named "test policy" and a security event with FleetDM policy regex set to **^test**, the security event triggers when a device violates "test policy" in FleetDM.

Security Event 3500002

Default security event for FleetDM CVE Vulnerability checks. Uses regular expressions to match CVE names. For example, with a CVE named "CVE-2024-6387" and a security event trigger "FleetDM Vulnerability CVE Regex" set to "CVE\\-2024", the security event triggers when a device is reported at risk for CVE-2024-6387.

Security Event 3500003

Default security event for high-risk FleetDM CVE Vulnerability checks. Compares the CVE severity value against a configured threshold. If the severity exceeds the threshold, the security event triggers. The "CVE Severity" value is a premium feature requiring a FleetDM subscription (see FleetDM's official website for details) to be included in CVE Vulnerability webhooks.

Customized Email Templates

Email templates are located in `/usr/local/pf/html/captive-portal/templates/emails:` **email-fleetdm-policy-violation.html** for FleetDM policy violations. **email-fleetdm-cve.html** for FleetDM CVE vulnerabilities.

Customized Additional Email Messages

Add extra information to emails sent to device owners or additional recipients without modifying email templates. Configure the additional message section when "email device owner" or "email recipient" is enabled using supported variables.

To use variables in the extra message template, quote them with **[% ` and ` %]**. For

example, use [% mac %] to include the MAC address in the extra message.

Check the FleetDM payload example for all supported variables. The example payload appears when configuring webhooks for policies or CVEs in the FleetDM admin UI.

NOTE

Variables in extra messages are "double quoted" when saved in the security event config file (/usr/local/pf/conf/security_events.conf*). When editing the file directly without PacketFence's admin UI, quote variables as [% ENV.BRL %] variable [% ENV.BRR %], where [% ENV.BRL %] is the double quoted form of [% ` and `[% ENV.BRR %] is the double quoted form of `%]. After changing the config file, reload with `/usr/local/pf/bin/pfcmd configreload or /usr/local/pf/bin/pfcmd configreload hard.

28. Advanced Topics

Advanced PacketFence topics. PacketFence can be configured manually using configuration files instead of the admin interface (admin interface recommended).

`/usr/local/pf/conf/pf.conf` contains PacketFence general configuration, including VLAN isolation mode settings.

Default parameters and descriptions are in `/usr/local/pf/conf/pf.conf.defaults`.

Override default parameters by defining them in `/usr/local/pf/conf/pf.conf`.

`/usr/local/pf/conf/documentation.conf` holds the complete list of all available parameters.

All parameters accessible via admin interface Configuration tab. Web interface highly recommended for configuration changes.

28.1. Reports

Define reports in `report.conf` creating SQL queries to view PacketFence database tables. Reports appear under *Reports* menu in admin interface.

PacketFence includes preloaded reports optimized for common production use-cases in `reports.conf.defaults`. Don't modify this file; use for working examples.

NOTE

Improperly formed reports consume significant server resources. Profile and optimize all queries to avoid service outages. Using `type=sql` (script/batch mode) increases query and transaction control.

TIP

Use Master/Slave replication to offload query execution to read-only database outside cluster. Prevents reporting from degrading production environment; provides more resources for report generation.

28.1.1. Configuration Attributes

Configure reports by editing `/usr/local/pf/conf/report.conf` and adding a report section. Run `/usr/local/pf/bin/pfcmd configreload hard`.

The admin interface builds the structured menu by splitting and separating all the section identifier's by double colons `::`. Identifiers without this separator are shown at the top level. Up to a maximum of 2 sets of double colons can be used for a maximum menu depth of 3 levels. All identifiers must be unique and any identifier partially reused by another sibling will make it inaccessible. (ex: `[A::B]` will lose its place as a report and become a parent category for `[A::B::*]` if it is also defined. Either rename the former to include a 3rd part, or rename the latter to use a different 1st or 2nd part.

```
[Top Category::Sub Category::Report]
```

The following attributes are available to define a report (* mandatory attributes are marked with an asterisk):

- **type***: The type of report. Use **type=abstract** to use SQL Abstract and **type=sql** to use MySQL script/batch mode. Each of these types have their own additional attributes which are explained in more detail below.
- **description***: A user-friendly description that provides more details about the report. Used as a title for all charts.
- **charts**: A comma delimited list of charts to display. Each chart is displayed in its own tab above the table data. There is no limit to the number of charts that can be defined. Charts are explained in more detail below.
- **columns***: A comma separated list of columns or aliases that are displayed in the table from the SQL query (ex: **node.mac**, **Node MAC**). The table columns are displayed in the respective order. Columns can be aliased to a more friendly name, but these aliases must be used throughout the other attributes.
- **date_limit**: A PacketFence interval that defines the maximum date range allowed between **start_date** and **end_date**. The reports user is restricted from choosing a date range that exceeds this limit. This is used to prevent the MySQL query from consuming too much resources with large datasets. The duration is defined as **date_limit=[unit][interval]** (ex: **date_limit=1D**), where the unit is a positive integer and the interval is one of the following characters:
 - **s**: second(s)
 - **m**: minute(s)
 - **h**: hour(s)
 - **D**: Day(s)
 - **W**: Week(s)
 - **M**: Month(s)
 - **Y**: Year(s)
- **formatting**: A comma separated list of column or alias formatters. Each column is defined followed by a colon and the internal PacketFence function used to format the column value for every row (ex: **formatting=vendor:oui_to_vendor**). This is used to format the query result columns using a function to access internal PacketFence memory. The supported formatters:
 - **oui_to_vendor**: format a MAC OUI to a vendor.
- **has_date_range**: *[enabled/disabled]* Display a datetime range and provide **start_date** and **end_date** bindings. See **date_limit** to restrict the maximum date range.
- **has_limit**: *[enabled/disabled]* Display a limit selection and provide a **limit** binding.
- **node_fields**: A comma delimited list of fields (columns or aliases) that will be clickable from the table of the Report and linked to the specific Node - only clickable if the reports' user has the "Node - View" admin role. All fields must be a valid PacketFence node identifier (*mac*).
- **person_fields**: A comma delimited list of fields (columns or aliases) that will be clickable from the table of the Report and linked to the specific User - only clickable if the reports' user has the "User - View" admin role. All fields must be a valid PacketFence user identifier (*pid*)`.

- **role_fields**: A comma delimited list of fields (columns or aliases) that will be clickable from the table of the Report and linked to the specific Role. All fields must be a valid PacketFence role identifier (*category_id*).

NOTE

Configuration attributes can optionally use a **columnName** reference with simple queries that use a single table (ex: **attribute=columnA,columnB**). The attributes must use **tableName.columnName** reference when using **joins** with 2+ tables (ex: **attribute=tableA.columnA,tableB.columnB**). Aliased **columns** can be used with the table reference (ex: **attribute=tableA.Alias A,tableB.Alias B**).

28.1.2. SQL Abstract

When **type=abstract** PacketFence uses Perl **SQL::Abstract::More** to automatically build the SQL query.

The following attributes are available when using **type=abstract**(* mandatory attributes are marked with an asterisk):

- **base_conditions**: A comma delimited list of conditions that is applied to the SQL query. Conditions should match the following format : **field:operator:value** (ex: **auth_log.source=:sms,auth_log.status!=:completed**).
- **base_conditions_operator**: [*all/any*] The logical SQL operator (AND|OR respectively) used with the **base_conditions**.
- **base_table***: The base SQL table used in the SQL query.
- **date_field***: The table field (column) used to filter by the date range. When used the column will also be used for the default sorting, unless **order_fields** is explicitly defined.
- **group_field**: The field (column) to group the query results by. No grouping is performed if this field is empty or omitted.
- **joins** : The table(s), columns and aliases used to join on the **base_table**. See example below and [the following documentation](#). This attribute supports multi line blocks (heredoc), see below.
- **order_fields**: A comma delimited list of fields (columns) used to order the SQL query. The field should be prefixed of - if the sort should be made in descending order for the field (ex: **-node.regdate,locationlog.start_time,+iplog.start_time**).
- **searches**: A comma delimited list of searchable fields (columns) that are presented to the reports' user. This allows the user to optionally include additional criteria for the query. Each item is defined as **type:Friendly Name:tableName.columnName** (ex: **searches=string:Owner:person.pid,string:Node:node.mac**). Currently only the type **string** is supported.
 - **type** defines the type of the search, the only one currently supported is **string**.
 - **Display Name** is the user-friendly name of the field for display.
 - **field** is the SQL name of the field to search

WARNING

Replace operators **IS** and **<>** by **=** and **!=**, respectively.

NOTE

Prefix the fields with the table name and a dot (ex: **node.mac**, **locationlog.role**, ...) so that they are not ambiguous. Wrap table names and column names with backticks **``** to avoid naming issues with current and

future MySQL reserved words.

Examples

View of the auth_log table:

```
[auth_log]
description=Authentication report
# The table to search from
base_table=auth_log
# The columns to select
columns=auth_log.*
# The date field that should be used for date ranges
date_field=attempted_at
# The mac field is a node in the database
node_fields=mac
# Allow searching on the PID displayed as Username
searches=string:Username:auth_log.pid
```

In this simple example, select the whole content of the **auth_log** table and use the date range on the **attempted_at** field as well as search on the **pid** field when viewing the report.

View of the opened security events:

```
[open_security_events]
description=Open security events
# The table to search from
base_table=security_event
# The columns to select
columns=security_event.security_event_id as "Security event ID",
security_event.mac as "MAC Address", class.description as "Security event
description", node.computername as "Hostname", node.pid as "Username",
node.notes as "Notes", locationlog.switch_ip as "Last switch IP",
security_event.start_date as "Opened on"
# Left join node, locationlog on the MAC address and class on the security
event ID
joins=<<EOT
=>{security_event.mac=node.mac} node|node
=>{security_event.mac=locationlog.mac} locationlog|locationlog
=>{security_event.security_event_id=class.security_event_id} class|class
EOT
date_field=start_date
# filter on open locationlog entries or null locationlog entries via the
end_date field
base_conditions_operator=any
base_conditions=locationlog.end_time:=:0000-00-00,locationlog.end_time:IS:
# The MAC Address field represents a node
node_fields=MAC Address
```

```
# The Username field represents a user
person_fields=Username
```

In the example above, the `security_event` table is *left joined* to the `class`, `node` and `locationlog` tables. Using that strategy we make sure all the security events are listed even on deleted nodes. Then, base conditions are added to filter out outdated `locationlog` entries as well as include devices without `locationlog` entries. Removing those conditions would lead to duplicate entries being shown since the report would reflect all the historical `locationlog` entries.

28.1.3. SQL

When `type=sql` PacketFence uses MySQL script/batch mode to manually build the SQL query including the execution of multiple statements. This provides complete query control as well as the ability to manage the SQL session and the SQL transaction. This is the preferred mode where SQL optimization is needed to execute complex queries, or for those more comfortable with raw (non-abstract) SQL.

```
sql=SELECT * FROM sponsors;
```

Multiline block (heredoc) is required when executing multiple statements. Each statement should be terminated with a semi-color ";".

NOTE SQL execution exits on the first error and returns the result set of the last successful statement.

The following attributes are available when using `type=sql`:

- `bindings`: A comma delimited list of ordered bindings to send to the SQL script (ex: `bindings=tenant_id,start_date,end_date,cursor,limit`). See Bindings below.
- `cursor_type`: `[node|field_multi_field]` Adds a cursor binding to the sql script that implements pagination of the results. The cursor is automatically handled in the admin interface, but its use in the `sql` requires special attention. If omitted the default `none` is used. More information about cursors is provided below. There are 2 types of cursors:
 - `cursor_type=field`: Use a single field (column or alias) for the cursor.
 - `cursor_type=multi_field`: Use multiple fields (columns or aliases) for the cursor.
 - `cursor_type=offset`: Use integer based offset for the cursor.
 - `cursor_type=none`: No cursor is used.
- `cursor_default`: The default cursor used to conditionally query the results for the first page. On subsequent pages this is replaced with the results from N+1 row of the previous page, meaning the cursor for page 2 (with `default_limit=25`) will contain the value from the column of the 26th row from the previous page.
- `cursor_field`: A comma delimited list of fields (columns) used for pagination.
- `default_limit`: The default limit passed into the bindings of the SQL script. When `has_limit=enabled` the reports' user can override the default with a manual selection.
- `sql`: Either a single MySQL query, or a multi line block of statements within a heredoc (see Heredoc below).

28.1.4. Bindings

The **bindings** attribute defines an ordered comma delimited list of columns (or aliases) that are made available to the **sql** script. There is no limit with the number of bindings that can be used and a binding can be repeated more than once.

The available bindings are:

- **tenant_id**: The scoped tenant identifier of the reports' session.
- **start_date**, **end_date**: The start and end datetime. Formatted as "YYYY-MM-DD HH:mm:ss". Use native MySQL date functions to reformat it.
- **cursor**: On the first page this value is the **cursor_default**. On subsequent pages this value is taken from the **cursor_field** column of the last result row from the previous page. When using **cursor_type=multi_field** the cursor is split into the bindings as **cursor.0**, **cursor.1**, etc.
- **limit**: Uses **default_limit** (+1, see pagination) unless overridden by the user.

Bindings are consumed in the **sql** using "?" in the same order that they are defined.

```
[single binding]
type=sql
bindings=limit
sql=SELECT * FROM table LIMIT ?;
default_limit=100
has_limit=enabled
```

If a binding is needed more than once within the **sql**, it can either be defined multiple times, or defined once and consumed to SET a MySQL variable.

```
[many bindings]
type=sql
bindings=start_date,end_date,tenant_id,start_date,end_date,limit
sql= << EOT
    SELECT
        *
    FROM tableA
    JOIN tableB ON tableA.id = tableB.id
        AND date BETWEEN ? AND ?
    WHERE tenant_id = ?
        AND date BETWEEN ? AND ?
    LIMIT ?;
EOT
default_limit=100
has_date_range=enabled
has_limit=enabled
```

28.1.5. Pagination

Pagination is supported through the use of the `cursor_type`, `cursor_default`, `cursor_field`, `bindings` and `sql` attributes. Pagination supports the use of one to many columns. Special attention must be given to the order of the final result set in order to utilize the cursor properly. Symptoms of too few pages, or infinite loops through subsequent pages are signs of a mismatched cursor and/or query results order.

The `limit` binding always has +1 added to it as PacketFence always consumes an extra row to determine the cursor for the following page. Due to this all conditional statements must be inclusive (ex: Bad operators "<, >", Good operators: "<=", ">="). If the column value is not unique then `cursor_type=multi_field` should be used instead to avoid infinite loops.

Examples of a single column cursor:

```
[all nodes in ascending order]
type=sql
sql= <<EOT
    SELECT mac FROM node WHERE mac >= ? ORDER BY mac LIMIT ?;
EOT
bindings=cursor,limit
cursor_type=field
cursor_field=mac
default_cursor=00:00:00:00:00:00
```

```
[all nodes in descending order]
type=sql
sql= <<EOT
    SELECT mac FROM node WHERE mac <= ? ORDER BY mac DESC LIMIT ?;
EOT
columns=mac
bindings=cursor,limit
cursor_type=field
cursor_field=mac
default_cursor=ff:ff:ff:ff:ff:ff
```

Example of a multi column cursor:

```
[all ip4log logs]
type=sql
sql= <<EOT
    SELECT
        ip4log.ip,
        ip4log.start_time,
        node.mac
    FROM ip4log
    INNER JOIN node
```

```

    ON ip4log.mac = node.mac
  WHERE ip4log.start_time >= ?
    AND node.mac >= ?
  ORDER BY ip4log.start_time, node.mac
  LIMIT ?;
EOT
columns=mac
bindings=cursor.0,cursor.1,limit
cursor_type=multi_field
cursor_field=start_time,mac
default_cursor=0000-00-00 00:00:00:00,00:00:00:00:00:00

```

28.1.6. Charts

Charts are defined as a comma delimited list using the **chart** attribute. An optional "@" symbol can be used to delimit a chart name. A mandatory pipe (vertical-bar) | is used to delimit the chart type and the fields. Within the fields a colon ":" is used to delimit each of the fields (if more than one field is necessary). The general syntax is:

```
charts=[pie,bar,parallel,scatter] [@ Chart Name] | field1 [:fieldN:...]
```

There are 4 types of charts available:

- **pie**: A pie chart with 2 dimensions. Must contain 2 fields (**charts=pie|field1:field2**):
 - **field0**: The dimensions label.
 - **field1**: The dimensions value.
- **bar**: A bar chart with 2 dimensions. Must contain 2 fields (**charts=bar|field1:field2**):
 - **field0**: The dimensions label.
 - **field1**: The dimensions value.
- **parallel**: A parallel category (sankey) diagram with 2+ dimensions. Must contain 3+ fields (**charts=parallel|field1:field2:field3[:...:fieldN]**):
 - **fieldN**: The N dimensions label of 2+ fields. A category is created for each field and order is maintained. The palette is applied to the last field (right-most).
 - **fieldLast**: The last field always contains the dimensions value.
- **scatter**: A date/time based line graph with 1+ dimensions. The date/time column is always defined in the first field and the query should return this using the "YYYY-MM-DD HH:mm:ss" format.
 - When only one field is defined (**charts=scatter|field1**) then a value of 1 is implied for each row.
 - When 2 fields are defined (**charts=scatter|field1:field2**) then the 2nd field is used as the dimensions value. The query results are automatically aggregated to produce dimensions for several terms (year/month/week/day/hour/minute).
 - When 3+ fields are defined (**charts=scatter|field1:field2:field3[:...:fieldN]**) the automatic aggregation is disabled and a dimension is used for each field.

NOTE All charts use the same color palette to provide a visual continuity.

28.1.7. Heredoc

The `joins` and `sql` attribute support multi line block statements. All whitespace characters are preserved. All multi line statements are pure SQL, thus the `--` prefix can be used as a remark.

```
attribute= <<EOT
-- multi-line
-- block
-- statement
EOT
```

28.1.8. Troubleshooting

- If the API request returns an error or an empty response refer to the `packetfence.log` to obtain the full MySQL error message.
- SQL scripts are transactional. After the script is run any variables or stored procedures created or temporary tables created are destroyed. Any locks obtained are released.
- Modification to the configuration file only requires a `/usr/local/pf/bin/pfcmd configreload hard` for the changes to take effect. The admin interface will begin using the new script on its next request.

28.2. Admin Access

Manage access levels for PacketFence administrators. Go through *Configuration* → *System Configuration* → *Admin Access*. Then go to the source which authenticates administrator and create an *administration* rule and assign the desired Admin role. This functionality allows granular control on which section of the admin interface is available to whom.

28.2.1. Built-in roles

- ALL: Provides the user with all the admin roles without any exception.
- ALL_PF_ONLY: Provides the user with all the admin roles related to the PacketFence deployment (excludes switch login rights).
- Node Manager: Provides the user the ability to manage the nodes.
- User Manager: Provides the user the ability to manage other users.
- Security Event Manager: Provides the user the ability to manage the security events (trigger, open, close) for the nodes.

28.3. Guest pre-registration

Pre-registration is disabled by default. Once enabled, PacketFence's firewall and Apache ACLs allow access to the `/signup` page on the portal even from a remote location. All that should be required from the administrators is to open the perimeter firewall to allow access

to PacketFence's management interface IP on port 443 and ensure a domain name to reach said IP is configured (and that the SSL cert matches it). Then promote the pre-registration link from the extranet web site: <https://<hostname>/signup>.

To minimally configure guest pre-registration, ensure that the following statement is set under `[guests_self_registration]` in `/usr/local/pf/conf/pf.conf`:

```
[guests_self_registration]
preregistration=enabled
```

This parameter should be configured from the *Configuration → Policies and Access Control → Connection Profiles → Profile Name* section.

CAUTION

A valid MTA configured in PacketFence is needed to correctly relay emails related to the guest module. If `localhost` is used as smtpserver, ensure that a MTA is installed and configured on the server.

CAUTION

Pre-registration increases the attack surface of the PacketFence system since a subset of it's functionality is exposed on the Internet. Ensure understanding of the risks, apply the critical operating system updates and apply PacketFence's security fixes.

NOTE

A 'portal' interface type is required to use this feature. A 'portal' interface type can be added to any network interface using the admin interface.

28.4. Content-Security-Policy (CSP)

The Content-Security-Policy HTTP response header tells modern browsers what can be accessed from a generated web page. The default policy is pushed for the captive portal and enforces that everything the browser executes comes from within PacketFence, with the exception of the configured network detection host that is by default the Inverse IP address.

If the portal is modified with content that needs to be accessed from PacketFence generated web pages, deactivate CSP through *Configuration → System Configuration → Main Configuration → Advanced → CSP headers for Captive Portal*.

28.5. pfacct: track bandwidth usage

Starting from v10, `pfacct` daemon is used to track bandwidth usage of nodes using [RADIUS Accounting](#) or NetFlow v5 traffic. It is enabled by default and replaced `packetfence-radiusd-acct` service. `pfacct` will store data into `bandwidth_accounting` table. Using a security event with a bandwidth limit trigger, you can limit data usage of the nodes. The admin interface also uses `bandwidth_accounting` table informations to display online/offline status of nodes. Bandwidth usage reports are available in *Reports* menu under *Accounting* section.

To get bandwidth reports, security events or online/offline features, enable 'Process Bandwidth Accounting' in *Configuration → System Configuration → RADIUS → General* menu. `pfacct` service needs to be restarted to apply changes.

28.5.1. NetFlow traffic

`pfacct` can get NetFlow traffic from two kind of sources:

- network devices which send directly NetFlow traffic to PacketFence
- inline L2/L3 networks (using NetFlow kernel module)

By default, `pfacct` listens NetFlow traffic on localhost, using `udp/2056` port to not conflict with the `fingerbank-collector` (which listens NetFlow traffic on all interfaces).

`pfacct` must be able to map an IP address to a MAC address (from NetFlow traffic) in order to create a record in `bandwidth_accounting` table. It means that PacketFence needs to be aware of IP addresses of the nodes (default behavior on inline L2/L3 networks).

Adjust `pfacct` configuration based on the NetFlow traffic source.

NetFlow traffic from network devices

Configure the following:

- make `pfacct` listens on IP address where you want to receive NetFlow traffic using `netflow_address` setting in *Configuration → System Configuration → Services* menu
- enable *NetFlow on all networks* in *Configuration → System Configuration → Advanced* menu

Then restart `packetfence-pfacct` services for it to take effect.

NetFlow traffic from inline L2/L3 networks

Enable *Netflow Accounting Enabled* setting when defining an inline network.

If *NetFlow on all networks* is enabled in *Configuration → System configuration → Advanced* menu, `pfacct` will collect NetFlow bandwidth usage for all networks instead of the ones defined in `/usr/local/pf/conf/networks.conf`.

Then restart `packetfence-pfacct` services for it to take effect.

28.6. Kafka configuration

28.6.1. Setting the configuration for a standalone

To setup a Kafka standalone you need the following information.

Node ID, Hostname and IP address. (run the `hostname` command on the server, `packetfence` is the example)

- hostname 172.16.3.1

The IP addresses of the clients (the server itself and the external IP addresses)

- 172.16.3.1 (The server ip)
- 172.16.4.1 (An external IP)

Username and passwords

- admin: admin-pass
- user: pass

A unique cluster id which could be generated by the command below.

```
uuidgen | tr -d '-' | base64 | cut -b 1-22
```

Example

```
[packetfence]
KAFKA_NODE_ID=1
KAFKA_ADVERTISED_LISTENERS=INTERNAL://172.16.3.1:9094,EXTERNAL://172.16.1.100:9092,PF://100.64.0.1:9095,PFCONNECTOR://127.0.0.1:9096

[auth user]
pass=pass

[admin]
pass=admin-pass
user=admin

[iptables]
clients=172.16.3.1,172.16.4.1
cluster_ips=172.16.3.1

[cluster]
KAFKA_LOG_DIRS=/usr/local/pf/var/kafka
CLUSTER_ID=Y2I2MTdkMGNlMjI4NDUyMm
KAFKA_CONTROLLER_LISTENER_NAMES=CONTROLLER
KAFKA_LISTENER_SECURITY_PROTOCOL_MAP=CONTROLLER:PLAINTEXT,INTERNAL:PLAINTEXT,EXTERNAL:SASL_PLAINTEXT,PF:PLAINTEXT,PFCONNECTOR:PLAINTEXT
KAFKA_INTER_BROKER_LISTENER_NAME=INTERNAL
KAFKA_LISTENERS=PF://0.0.0.0:9095,INTERNAL://0.0.0.0:9094,CONTROLLER://0.0.0.0:9093,EXTERNAL://0.0.0.0:9092,PFCONNECTOR://0.0.0.0:9096
KAFKA_OPTS=-
Djava.security.auth.login.config=/usr/local/pf/conf/kafka/kafka_server_jaas.conf
KAFKA_CONTROLLER_QUORUM_VOTERS=1@172.16.3.1:9093
KAFKA_SASL_ENABLED_MECHANISMS=PLAIN
KAFKA_PROCESS_ROLES=broker,controller
KAFKA_OFFSETS_TOPIC_REPLICATION_FACTOR=1
```

28.6.2. Setting the configuration of the Kafka cluster

To setup a Kafka cluster you need the following information.

Node ID, Hostname and IP address, of each member.

- 1 hostname1 172.16.3.1
- 2 hostname2 172.16.3.2
- 3 hostname3 172.16.3.3

The IP addresses of the clients

- 172.16.4.1
- 172.16.4.2

Username of passwords

- admin: admin-pass
- user1: pass1
- user2: pass2

A unique cluster id which could be generated by the command below.

```
uuidgen | tr -d '-' | base64 | cut -b 1-22
```

Example

```
## Iptables rules

[iptables]
# The list of client
clients=172.16.4.1,172.16.4.2
# All the IP address of the cluster members
cluster_ips=172.16.3.1,172.16.3.2,172.16.3.3

#
[auth user1]
pass=pass1

[auth user2]
pass=pass2

#The Admin username and password
[admin]
user=admin
pass=admin-pass

#Global ENV variables
```

```

[cluster]
#The unique Cluster ID
CLUSTER_ID=MkU30EVbNTcwNTJENDM2Qk
KAFKA_CONTROLLER_LISTENER_NAMES=CONTROLLER
# List out each member using the following format <id>@<ip>:9093 comma
separated
KAFKA_CONTROLLER_QUORUM_VOTERS=1@172.16.3.1:9093,2@172.16.3.2:9093,3@172.16.3.3
:9093
KAFKA_INTER_BROKER_LISTENER_NAME=INTERNAL
KAFKA_LISTENER_SECURITY_PROTOCOL_MAP=CONTROLLER:PLAINTEXT,INTERNAL:PLAINTEXT,EX
TERNAL:SASL_PLAINTEXT,PF:PLAINTEXT
KAFKA_LISTENERS=PF://0.0.0.0:9095,INTERNAL://0.0.0.0:29092,CONTROLLER://0.0.0.0
:9093,EXTERNAL://0.0.0.0:9092
KAFKA_LOG_DIRS=/usr/local/pf/var/kafka
KAFKA_OFFSETS_TOPIC_REPLICATION_FACTOR=2
KAFKA_OPTS=-
Djava.security.auth.login.config=/usr/local/pf/conf/kafka/kafka_server_jaas.con
f
KAFKA_PROCESS_ROLES=broker,controller
KAFKA_SASL_ENABLED_MECHANISMS=PLAIN
...

##Member specific ENV variables
##List each cluster member using the following format
#[<hostname>]
#KAFKA_NODE_ID=<id>
#KAFKA_ADVERTISED_LISTENERS=INTERNAL://<ip>:29092,EXTERNAL://<ip>:9092
#
[hostname1]
KAFKA_NODE_ID=1
KAFKA_ADVERTISED_LISTENERS=INTERNAL://172.16.3.1:29092,EXTERNAL://172.16.3.1:90
92,PF://100.64.0.1:9095

[hostname2]
KAFKA_NODE_ID=2
KAFKA_ADVERTISED_LISTENERS=INTERNAL://172.16.3.2:29092,EXTERNAL://172.16.3.2:90
92,PF://100.64.0.1:9095

[hostname3]
KAFKA_NODE_ID=3
KAFKA_ADVERTISED_LISTENERS=INTERNAL://172.16.3.3:29092,EXTERNAL://172.16.3.3:90
92,PF://100.64.0.1:9095

```

28.6.3. FingerBank collector kafka configuration

FingerBank collector can be configured to store the NetFlow, sFlow, IPFIX traffic to Kafka in order to allow pfflow to process it.

Here a sample of configuration that can be use with the Kafka server configured above.

```
[collector]
additional_env=<<EOT
COLLECTOR_DISABLE_KAFKA=false
COLLECTOR_KAFKA_HOSTS=100.64.0.1:9095
COLLECTOR_DISABLE_IPFIX_SERVICE=false
COLLECTOR_DISABLE_SFLOW_KAFKA=false
COLLECTOR_KAFKA_USER=
COLLECTOR_KAFKA_PASS=
EOT
```

28.6.4. pfflow configuration

pfflow cron task can be configured to talk to kafka in order to compile the netflow events to json payloads.

Here is the configuration that can be use in pfcron.conf to communicate with the Kafka server configured above.

```
[pfflow]
#
# status
#
# If the task is enabled
status=enabled
#
# kafka_brokers
#
# Kafka Brokers to read from
kafka_brokers=100.64.0.1:9095
#
# uuid
#
# The UUID of the packetfence aggregator
uuid=f1e53295-c052-4602-a02f-8a6c90346c08
#
# kafka_user
#
# The Kafka username
kafka_user=
#
# kafka_pass
#
# The Kafka password
kafka_pass=
#
```

```
#filter_events=1
```

28.6.5. Restarting Services

```
systemctl restart packetfence-kafka
systemctl restart packetfence-fingerbank-collector
systemctl restart packetfence-pfcron
```

Monitoring with Netdata Cloud

PacketFence includes Netdata that is pre-installed and configured for most use-cases.

The metrics are displayed in 2 separate sections

- **Dashboard:** This section displays the metrics collected by pfstats for the unregistration/registration status of all nodes managed by PacketFence.
- **Monitoring:** This section displays system metrics collected by Netdata for the local host (standalone), or all hosts in a cluster.

All metrics are retained for a maximum of 28 days. Older metrics are automatically pruned to limit disk usage. To increase the retention rate edit the configuration and restart the service:

```
vi /usr/local/pf/conf/monitoring/netdata.conf

[db]
    retention = 2419200 # 28 days (seconds)
```

Dashboard

The dashboard displays the metrics collected by pfstats for the unregistration/registration status of all nodes managed by PacketFence. These metrics are common across all cluster members, therefore a complete view is displayed from any host that is a member of the same cluster.

NOTE

Monitoring: The monitoring section displays the metrics collected by netdata for the health of the system. Whether the setup is standalone, or a cluster, a section is dedicated to each host in the deployment. When using one host to view metrics from another, the external host must be up and running.

The User Interface (Web Admin) now includes:

- A duration selection that can be used to zoom-in/zoom-out the timeline, up to a maximum of 28 days. If the retention rate is increased, these selections will remain the same.
- A "Netdata Cloud" button that opens a new window with the Netdata UI. Once launched the user can login anonymously (bottom-right), or the session_id can be used to attach the PacketFence instance to the Netdata Cloud.

- A zoom-able popup that displays and compares a single metric for all members in the cluster. Click any metric title to open this popup.

To obtain the local Netdata random session identifier:

```
cat /usr/local/pf/var/netdata-lib/netdata_random_session_id
```

Once connected to Netdata Cloud, Netdata alerts will be sent to the email address used to register the Netdata Cloud account.

To attach all members of a cluster, each member has its own unique session id; where each must be used to login to Netdata Cloud manually.

Restarting Service

```
systemctl restart packetfence-netdata
```

Dynamic iptables and ip6tables rules

Iptables and ip6tables are dynamic and each service is adding or removing port(s) according to their needs.

/!\ Packetfence is NOT fully compatible with ipv6 /!\

Default ipv6 rules are set to protect Packetfence server and for convenient usage.

Starting Service

```
systemctl start packetfence-iptables
systemctl start packetfence-ip6tables
```

Restarting the service should be done only when there is a modification on `/usr/local/pf/lib/pf/iptables.pm` or on `/usr/local/pf/lib/pf/ip6tables.pm`. Once started, the iptable service is checking modifications on the directory `/usr/local/pf/var/conf/iptables/` and on the file `/usr/local/pf/conf/iptables-custom.conf.inc`. Once started, the ip6table service is checking modifications on the directory `/usr/local/pf/var/conf/ip6tables/` and on the file `/usr/local/pf/conf/ip6tables-custom.conf.inc`.

Any modification will result in a restart of iptables and ip6tables configuration rules.

Each service generated rules can be find in the directory `/usr/local/pf/var/conf/iptables/` and `/usr/local/pf/var/conf/ip6tables/`.

Reload iptables rules

`/usr/local/pf/bin/pfcmd` is offering two ways to reload iptables configuration. The soft reload will trigger rebuild iptables rules according to running services. The hard reload will trigger a flush of all tables, a remove of all config files from the directory

[/usr/local/pf/var/conf/iptables/](#) and then do the same a soft reload.

```
/usr/local/pf/bin/pfcmd reloadiptablesrules
/usr/local/pf/bin/pfcmd reloadiptablesrules hard
```

Reload ip6tables rules

[/usr/local/pf/bin/pfcmd](#) is offering two ways to reload ip6tables configuration. The soft reload will trigger rebuild ip6tables rules according to running services. The hard reload will trigger a flush of all tables, a remove of all config files from the directory [/usr/local/pf/var/conf/ip6tables/](#) and then do the same a soft reload.

```
/usr/local/pf/bin/pfcmd reloadip6tablesrules
/usr/local/pf/bin/pfcmd reloadip6tablesrules hard
```

Setting custom iptables rules

It is possible to create custom iptables entry from a json file located in [/usr/local/pf/conf/iptables-custom.conf.inc](#).

An example of the file is available here [/usr/local/pf/conf/iptables-custom.conf.inc.example](#). That file is a json file will add rules on top of all other Packetfence rules for each tables or chains. The entry should only contain the rule without the "-A", the table and the chain. For example: to open tcp port 123, and udp port 234 with interface the eth0 on filter→INPUT, the file will be:

```
{
  "filter" : {
    "FORWARD" : [],
    "INPUT" : [
      "# allow tcp port 123 and udp port 234 on eth0 interface",
      "-i eth0 --protocol tcp --match tcp --dport 123 --jump ACCEPT",
      "-i eth0 -p udp -m udp --dport 234 --jump ACCEPT"
    ],
    "OUTPUT" : []
  },
  "mangle" : {
    "PREROUTING" : [],
    "INPUT" : [],
    "FORWARD" : [],
    "OUTPUT" : [],
    "POSTROUTING" : []
  },
  "nat" : {
    "POSTROUTING" : [],
    "OUTPUT" : [],
    "PREROUTING" : []
  }
}
```

```
}
}
```

Setting custom ip6tables rules

It is possible to create custom ip6tables entry from a json file located in [/usr/local/pf/conf/ip6tables-custom.conf.inc](#).

An example of the file is available here [/usr/local/pf/conf/ip6tables-custom.conf.inc.example](#). That file is a json file will add rules on top of all other Packetfence rules for each tables or chains. The entry should only contain the rule without the "-A", the table and the chain. For example: to open tcp port 123, and udp port 234 with interface the eth0 on filter→INPUT, the file will be:

```
{
  "filter" : {
    "FORWARD" : [],
    "INPUT" : [
      "# allow tcp port 123 and udp port 234 on eth0 interface",
      "-i eth0 --protocol tcp --match tcp --dport 123 --jump ACCEPT",
      "-i eth0 -p udp -m udp --dport 234 --jump ACCEPT"
    ],
    "OUTPUT" : [],
    "RFC3964_IPv4" => []
  },
  "raw" : {
    "PREROUTING" : [],
    "OUTPUT" : []
  }
}
```

Check iptables or ip6tables applied rules

Generated and applied iptables rules are available in [/usr/local/pf/var/conf/iptables_generated_rules.conf](#). Generated and applied ip6tables rules are available in [/usr/local/pf/var/conf/ip6tables_generated_rules.conf](#).

It is also possible to check rules with the following command lines:

```
# iptables ipv4
iptables -L -n -v -t filter
iptables -L -n -v -t mangle
iptables -L -n -v -t nat
# ip6tables ipv6
ip6tables -L -n -v -t filter
ip6tables -L -n -v -t raw
```

29. Export/Import mechanism

This section covers export/import mechanism available since PacketFence 11.0. It can be used to automate parts of upgrades or to restore PacketFence installations.

29.1. Assumptions and limitations

- Export is supported on any PacketFence version above 10.3
- With export from 10.3, import is supported on any PacketFence version after 11.0 except if using mariadb-backup for mysql backup.
- If using mariadb-backup and wanting to jump to Debian 12 (packetfence 14.0 or later), it will be necessary to:
 - be at least on Packetfence version 11.0
 - follow these steps in order to backup the database with the right [mariadb-backup version](#).
- The import process needs to be done on a **standalone** server. Restoring directly to clusters is currently unsupported
 - NOTE: Once restored to the standalone server, it can be made a cluster by joining other machines to it and creating the [cluster.conf](#) but this is relatively advanced and out of scope of this document
- Restoring on a fresh install of PacketFence is recommended although restoring on an existing instance can work but results may vary
- The import process will not modify network cards configuration of the server: it will only update PacketFence IP configuration. Recommend defining targeted IP addresses on network cards before running import process even if it can be done at end of import process.
- The import process will not join server to Active Directory domains automatically. Rejoin server manually.
- The import process restores the configuration files tracked by PacketFence (the [@pf::file_paths::stored_config_files](#) list), which include:
 - Standard configuration files in [/usr/local/pf/conf/.conf](#), including [log.conf](#) and [pfconfig.conf](#) (but **not* [cluster.conf](#), see below)
 - A few non-[.conf](#) data files stored alongside the configuration: [oui.txt](#), [allowed_device_oui.txt](#), [allowed_device_types.txt](#) and [fingerbank-collector.env.defaults](#)
 - The [vlan_filters.conf.defaults](#) and [radius_filters.conf.defaults](#) default files
 - Files referenced from the configuration that live outside the standard set, discovered automatically at export time (for example [/usr/local/pf/conf/iptables-custom.conf.inc](#) and [/usr/local/pf/conf/ip6tables-custom.conf.inc](#))
 - Connection profiles HTML templates in [/usr/local/pf/html/captive-portal/profile-templates/](#)

- Standard certificates
 - `/usr/local/pf/conf/ssl/*`
 - `/usr/local/pf/raddb/certs/*`

NOTE Because the `*.conf.defaults` files above are restored as-is, importing an older export can overwrite the default files shipped with the running version. Review them after a cross-version import.

- Here is a short list of the configuration files that will not be restored. Changes to these files need to be migrated manually. This list is not meant to be complete:

- `/usr/local/pf/conf/radiusd/*`
- `/usr/local/pf/conf/log.conf.d/*`
- `/usr/local/pf/conf/iptables.conf.tt`

- `cluster.conf` is **not** restored by default. The imported server is left standalone with an empty `cluster.conf`, and the export's copy is kept as `/usr/local/pf/conf/cluster.conf.imported` for reference. This matches the recommendation to import onto a standalone server. Two options change this behaviour:

- `--update-cluster-conf` restores the export's `cluster.conf` and adjusts it for this server: the local node's section (`[<hostname>]`) has its interface IPs and management IP rewritten to match the values applied to `pf.conf`, and any interface rename is propagated to the `CLUSTER` (virtual IP) sections.
- `--restore-as-is` leaves this server's **current** `cluster.conf` untouched (it is neither reset nor overwritten from the export).

WARNING With `--update-cluster-conf`, only the local node is adjusted. Virtual IP addresses are never rewritten, and peer-node sections cannot be derived from a single server. After the import, verify the `CLUSTER` sections and the other nodes' sections in `/usr/local/pf/conf/cluster.conf`, and ensure there are no stale references to the previous cluster's virtual IP addresses.

29.2. Export on current installation

NOTE When in a cluster, perform this process on the first member of the incoming addresses of the database cluster. To find the member, run `show status like 'wsrep_incoming_addresses'`; inside the MariaDB instance and the first IP will be the one where to perform the export process.

29.2.1. Installation (for PacketFence version 10.3 only)

On PacketFence version 10.3, install `packetfence-export` package using following instructions:

RHEL / CentOS based systems only

```
yum localinstall
https://www.packetfence.org/downloads/PacketFence/RHEL8/packetfence-export-
```

```
15.2.el8.noarch.rpm
```

Debian 9 systems only

```
wget https://www.packetfence.org/downloads/PacketFence/debian/packetfence-  
export_15.2.deb  
dpkg -i packetfence-export_15.2.deb
```

29.2.2. Start the export process

The export process will try to use files created by the nightly backup done at 00:30am everyday. If this is fine and the latest data is not needed, then skip this step. Otherwise to have the latest data and configuration in the export, run:

```
/usr/local/pf/addons/exportable-backup.sh -f /tmp/export.tgz
```

The command above will create the export archive in `/tmp/export.tgz`. It will now be necessary to copy this file to the new server using SCP or the preferred mechanism.

29.3. Import on new installation

First have a PacketFence installation with latest version done on a standalone server following the instructions in our install guide. It is not necessary to go through the configurator unless wanting to modify IP settings of the server.

WARNING

If wanting to use the first step of the configurator to configure the server, do it **before** running the import.

29.3.1. Note on Mariabackup

The import script could try to install Mariabackup to import the database dump. If that is the case, it will remove it at end of import.

Consequently, if Mariabackup was installed **before** running the import script, ensure that Mariabackup is still installed at end of import.

29.3.2. Start the import process

The import script will guide through the restore of the database, if necessary it will assist with the configuration files and adjust the PacketFence IP configuration.

To start the import process using the export archive made on the current installation:

```
/usr/local/pf/addons/full-import/import.sh -f /tmp/export.tgz
```

Once the process is completed, the following should appear:

Completed import of the database and the configuration! Complete any necessary adjustments and restart PacketFence

If that's not the case, check the output above to understand why the process failed.

If any issues are experienced during import, run it again.

If all goes well, restart services using [following instructions](#).

Import options

Without any option, `import.sh` performs a full import (database and configuration) and upgrades them to the running version when the export comes from an older one.

`-f, --file <archive>`

Path to the export archive to import (mandatory).

`--db`

Import only the database.

`--conf`

Import only the configuration.

`--restore-as-is`

Restore the export exactly as it was backed up. Intended for restoring onto the **same** PacketFence version: no database, MariaDB or configuration upgrade is performed, the backup's database host and port are kept, and no question is asked (fully non-interactive). This server's current `cluster.conf` is kept untouched (it is not reset nor overwritten from the export).

`--update-cluster-conf`

Restore the export's `cluster.conf` and adjust it for this server (see the assumptions and limitations above). Without this option, `cluster.conf` is not imported: the server is left standalone with an empty `cluster.conf` and the export's copy is kept as `cluster.conf.imported`. Ignored when `--restore-as-is` is used.

`--skip-adjust-db-conf`

On a configuration import, keep the backup's database host and port instead of rewriting them to `localhost`. Useful on a cross-version import that must preserve a non-local database host. (`--restore-as-is` already implies this.)

Additional steps to build or rebuild a cluster

To build or rebuild a cluster, follow instructions in [Cluster setup section](#).

If the previous installation was a cluster, some steps may not be necessary to do. By default the import leaves the server standalone and keeps the export's `cluster.conf` as `cluster.conf.imported` for reference. To reuse the previous cluster configuration, run the import with `--update-cluster-conf`, then review the `CLUSTER` and peer-node sections before starting the cluster (see the assumptions and limitations above).

WARNING | if Mariabackup was installed before running the import, it's possible that

it needs to be reinstalled.

30. PacketFence Certificates (for v11.2 and later)

30.1. Introduction

30.1.1. Context and Objectives of the Documentation

This documentation for PacketFence v11.2+ provides implementation and renewal instructions for SSL/TLS certificates for HTTP (captive web portal + web admin) and RADIUS.

Captive portal provides user authentication on wireless/wired networks by redirecting users to authentication pages for login information. RADIUS protocol handles user authentication and authorization on networks.

30.1.2. Definitions and Basic Concepts

Understanding basic security and certificate concepts is essential for SSL/TLS certificate implementation and management:

- SSL/TLS: Secure Sockets Layer/Transport Layer Security, a security protocol that allows encrypting communications between a client and a server.
- SSL/TLS certificate: an electronic file that contains information to verify the identity of a server and establish a secure connection.
- Certificate Authority (CA): an entity that issues and manages SSL/TLS certificates by verifying the identity of the certificate owner.
- Intermediate Certificate: a type of digital certificate that is issued by a trusted root certificate authority and is used to establish a chain of trust between the root certificate and end-entity certificates.
- Private key: an encryption key used to protect confidential information, known only to the certificate owner.
- Public key: an encryption key used to decrypt information encrypted using the private key, known to all users.

These concepts aid SSL/TLS certificate understanding and implementation for captive web portal and RADIUS.

30.1.3. Important notes before starting

This documentation covers PacketFence v11.2+.

Wildcard certificates restricted to HTTP only; cannot be used for RADIUS. Recommend using single certificate for both HTTP and RADIUS to simplify management.

30.2. Why a certificate

30.2.1. Generate a Certificate Signing Request (CSR)


To implement an SSL/TLS certificate for HTTP (captive web portal + web admin) and/or RADIUS, the first step is to generate a Certificate Signing Request (CSR). The CSR includes information about the organization requesting the certificate, the domain name of the captive portal, and the private key that will be used to encrypt communications.

NOTE

Generating a CSR from HTTP or RADIUS is strictly the same. One CSR is needed to add a certificate for both HTTP and RADIUS. In this case, the same private key can be used for HTTP and RADIUS.

Example: If the CSR is generated through HTTP, copy the HTTPs server private key to the RADIUS server private key. The private key can be found on the web admin *Configuration* → *System Configuration* → *SSL Certificates* → *Edit HTTP Certificates*

- Log on the admin web interface (GUI)
- Go to *Configuration* → *System Configuration* → *SSL Certificates*



- Click on “Generate Signing Request (CSR)”
- Complete the following using personal information

Generate Signing Request for HTTP certificate



Country	Canada
State	QC
Locality	Montreal
Organization Name	Akamai
Common Name	portal.inverse.ca
Subject Alternative Names (DNS only)	portal.inverse.ca, admin-pf.inverse.ca

Comma-delimited list of DNS names who should be added as Subject Alternative Names. When left empty, the common name will be used.

Close

Generate

WARNING

This capture have been made on PacketFence v13. If Packetfence Version is a lower version (not under v11.2), Subject Alternative Names will be automatically generated from Common Name field.

- Save CSR to secure location; required for certificate renewal.

30.2.2. Submit the CSR to a Certificate Authority (CA)

Once the CSR is generated, the next step is to submit it to a Certificate Authority (CA) for validation and issuance of the SSL/TLS certificate. There are many CAs to choose from, and it is important to select a reputable one that is trusted by major web browsers.

To submit the CSR to a CA, follow these steps:

- Select a CA and follow their instructions for submitting a CSR.
- The Subject Alternative Name must exactly match the captive portal FQDN in *Configuration → System Configuration → General Configuration*.
- Ensure that the selected Certificate Authority (CA) supports X509 in base 64 format.
- Provide the CSR and any other required information, such as payment and proof of identity.
- Wait for the CA to validate the CSR and issue the SSL/TLS certificate.
- Download the certificate in Apache format (base 64).

In the event that several types of certificates are offered, like in the following example:

Available formats:

- as Certificate only, PEM encoded:
- as Certificate (w/ issuer after), PEM encoded:
- as Certificate (w/ chain), PEM encoded:
- as PKCS#7:
- as PKCS#7, PEM encoded:

Issuing CA certificates only:

- as Root/Intermediate(s) only, PEM encoded:
- as Intermediate(s)/Root only, PEM encoded:

Choose **as Certificate (w/ issuer after), PEM encoded:**


It can be different from one issuer to another.

30.2.3. Install the SSL/TLS HTTP Certificate on the Server


Once the SSL/TLS certificate is received from the Certificate Authority (CA), the final step is to install it on PacketFence. This involves configuring the web server to use the SSL/TLS certificate for encrypted communications.

To install the SSL/TLS certificate, follow these steps:

- Open the web admin interface.
- Go to *Configuration* → *System Configuration* → *SSL Certificates* → *HTTP* → *Edit HTTP Certificates*.



- Import or open the certificate file (.crt) with a text editor and copy/paste the content into the "HTTPs Server Certificate" field.




- Turn on the options "Find HTTPs intermediate CA(s) automatically" and "Validate certificate chain".

Find HTTPs Server intermediate CA(s)
automatically  True

Validate certificate chain  Enabled

- Restart `haproxy-admin` and `haproxy-portal`, one server at a time. This can be done through the web admin page: *Status* → *Services*.



Alternatively, one server at a time, the following CLI commands can be run on each servers:

```
systemctl restart packetfence-haproxy-admin
systemctl restart packetfence-haproxy-portal
```

By following these steps, a SSL/TLS certificate for HTTP (captive web portal + web admin) has been implemented and provide a secure connection for user authentication.

30.2.4. Install the SSL/TLS RADIUS Certificate on the Server


Once the SSL/TLS certificate is received from the Certificate Authority (CA), the final step is to install it on the RADIUS server. This involves configuring the RADIUS server to use the SSL/TLS certificate for encrypted communications.

WARNING


Wildcard certificate is strictly restricted to HTTP, it can't be used for RADIUS.

To install the SSL/TLS certificate on the RADIUS server, follow these steps:

- Open the web admin interface.
- Go to *Configuration* → *System Configuration* → *SSL Certificates* → *RADIUS* → *Edit RADIUS Certificates*.



- Import or open the certificate file (.crt) with a text editor, then copy and paste the key into the "RADIUS Server Certificate" field.




- Turn on the "Find RADIUS Server intermediate CA(s) automatically" and "Validate certificate chain" option.

Find RADIUS Server intermediate CA(s)
automatically  True

Validate certificate chain  Enabled

NOTE If a private certificate (that is not signed by a public Certification Authority CA) is used, disable "Find RADIUS Server intermediate CA(s) automatically" and add manually all needed "Intermediate CA certificate(s)"

- Restart all **radiusd** services that are running, including **radius-auth**, **radiusd-load-balancer**, **radiusd-acct**, **radiusd-eduroam**, and **radiusd-cli**. Restart them one server at a time. On the web admin page, go to **Status** → **Services**.



Alternatively, one server at a time, the following CLI commands can be run on each servers:

```
/usr/local/pf/bin/pfcmd service radiusd restart
```

30.3. From an existing certificate

If an existing certificate is already used, then there is already two dedicated files: - a certificate in base64 - a private key If the certificate and the private key are in one file, it is possible to extract them with command lines available here: [Useful commands](#).

30.3.1. Install the SSL/TLS HTTP Certificate on the server

Follow the same step of [Install the SSL/TLS HTTP Certificate on the Server](#) but before saving the configuration and restarting the services add this step:


- Import or open the private key file (.key) and copy/paste the content into the **RADIUS Server Private Key** field.

The screenshot shows a configuration window for SSL/TLS. It has two main text input areas. The first is labeled 'HTTPs Server Certificate' and contains the text '-----BEGIN CERTIFICATE-----' and '-----END CERTIFICATE-----'. The second is labeled 'HTTPs Server Private Key' and contains the text '-----BEGIN RSA PRIVATE KEY-----' and '-----END RSA PRIVATE KEY-----'. Below these are two toggle switches: 'Find HTTPs Server intermediate CA(s) automatically' set to 'True' and 'Validate certificate chain' set to 'Enabled'. At the bottom are three buttons: 'Save', 'Reset', and 'Cancel'.

30.3.2. Install the SSL/TLS RADIUS certificate on the server

Follow the same step of [Install the SSL/TLS RADIUS Certificate on the Server](#) but before saving the configuration and restarting the services add this step:

- Import or open your private key file (.key) and copy/paste the content into the **RADIUS Server Private Key** field.



30.4. Renewal certificate with a CSR

When it is time to renew a certificate, it is possible to reuse an existing CSR.

There are two use cases:

- The CSR has been generated from PacketFence web admin, then follow these instructions under **Why a certificate** section:
 - [Install the SSL/TLS HTTP Certificate on the Server](#)
 - [Install the SSL/TLS RADIUS Certificate on the Server](#)
- The CSR has been generated from another tool, then follow these instructions under **From an existing certificate** section:
 - [Install the SSL/TLS HTTP Certificate on the server](#)
 - [Install the SSL/TLS RADIUS certificate on the server](#)


30.5. Renew a certificate without the CSR

If no CSR is available, please restart from here [Why a certificate](#).


30.6. Renew a certificate signed by the PF_PKI

The following steps explain how to renew HTTP/Radius certificates in PacketFence when they are signed by **PF-PKI**.

- Locate the Certificate:
 - Go to **Configuration → Integration → PKI → Certificates**.
 - Search using the **Common Name (CN)** of the certificate.



- Open and Resign the Certificate:
 - ❑ Open the certificate entry.
 - ❑ Click **Resign**.



- Fill the Resign Form:
 - ❑ Keep the same details (CN, Email, etc.) as the existing certificate.
 - ❑ Click **Resign** to generate a renewed certificate.

Resign Certificate

Common Name

172-nt.com

Email

adad@afasdas.caa

DNS Names

List of domains separated by a comma.

IP Addresses

List of IP Addresses separated by a comma.

Organisational Unit

Organisation

Changing this value will invalidate the previously signed certificates using EAP-TLS.

Country

Select option

Changing this value will invalidate the previously signed certificates using EAP-TLS.

State or Province

Changing this value will invalidate the previously signed certificates using EAP-TLS.

Locality

Changing this value will invalidate the previously signed certificates using EAP-TLS.

Street Address

Cancel

Resign

- Copy the Renewed Certificate:
 - After resigning, copy the updated certificate.

Certificate 1

General

Copy Certificate Download Email Resign Revoke

Identifier 1

Certificate Template Abhi-PKI - ABHI-Cert-Template

Certificate template used for this certificate.

Common Name 172.17.0.1.com

Email adad@afasdas.caa

DNS Names

List of domains separated by a comma.

IP Addresses

List of IP Addresses separated by a comma.

Organisational Unit

Organisation

Country Select option

State or Province

Locality

Street Address

Clone Reset Cancel

- To Apply the Certificate:

Go to **Configuration → System Configuration → SSL Certificates**, paste the renewed certificate into the HTTP or RADIUS section, and save.

SSL Certificates

HTTP RADIUS

View HTTP Certificates Edit HTTP Certificates

Use Let's Encrypt

HTTPs Server Certificate

Past the copied Certificate Here

```
-----BEGIN CERTIFICATE-----
MIIDWjCCAKKgAwIBATANBgkqhkiG9w0BAQsFAADBMQswCQYDVQQGEwJJTEJO
MAwGA1UECBMFRG9saGxkCzAJBgNVBAMTAk5BMQswCQYDVQQKEwZBQmhpTlUx
BgNVBAMTCFJlbnNpdjE1MDg5ODQ5NDQ5ODQ5NDQ5NDQ5NDQ5NDQ5NDQ5NDQ5
MjEwMA4GA1UEAxMnMTc5LTcwNS0xNDQ5NDQ5NDQ5NDQ5NDQ5NDQ5NDQ5NDQ5
Y291MjEwMA4GA1UEAxMnMTc5LTcwNS0xNDQ5NDQ5NDQ5NDQ5NDQ5NDQ5NDQ5
+JterM6pB1nPyFrAQGIZuH1M10Mkw6T+ya0ZQ17qVH8ICBbUuJADoGSNlauH
PB9A1jkwkK0yAvBf4jhnk/onC2gc5zoNBqr76Y2PD8BuMLJGZAsfqQ3+GGSMY
VbWPCz2egY+y66P-----
u3LZQGHMw057dd+JbnJ5m2fPIMF7s4Br63c7cl3P5McaQpvs/2+M4x0AG2E6ve
M3prGgF7uKEPIOMVHqWTPsbZKkdIX7uF8EkvX5wDjRoxUkmbBrl3aUz6O9ep
RxOmUQIDAQABo18wTAdBgNVHQ4EFgQUdAAR8AdolNqU9WriEwz8B84ZwqHwYD
VR0JBGgwFoAUnpDDibEsOCavPM1c8uByXNLFgwGwYDVRORBBQwEoEQYWRhZEBh
ZmFzZGFzLmNhyTANBgkqhkiG9w0BAQsFAADCAQEAAG7Ck3ZiX7TLuQVkw7nMcTJ
QdGKzz3FwyQ9/rmJafqHqAJuQDQ06hosAftvoltrQbPy6wX7USim3Ku4915m75f
DXKv4uImCfHvMjP5SSL4g2cseY5+gweZ0x18QmNtoBgd4N1C1xS8yqPzQMIG
IAP1e5wM1co2D8PeKeYI5CEKQuDhks24vKu07oGT2G4yN2j079wNAICf
UES7avoRamN/FfoxzaMXDkoE9enNlprAG9XigJfNIMMCAckzOnZck7O5Xr0E
W3r2ODUpUwmrlyT4Q4ki0ZJlocApKPTIZgDDUVNhh9rq5JWelwfpPa8RQFH86KQ==
-----END CERTIFICATE-----
```

Find HTTPs Server intermediate CA(s) automatically

Intermediate CA certificate(s)

```
-----BEGIN CERTIFICATE-----
MIIDHDCCAmygAwIBATANBgkqhkiG9w0BAQsFAADBMQswCQYDVQQGEwJJTEJO
MAwGA1UECBMFRG9saGxkCzAJBgNVBAMTAk5BMQswCQYDVQQKEwZBQmhpTlUx
BgNVBAMTCFJlbnNpdjE1MDg5ODQ5NDQ5NDQ5NDQ5NDQ5NDQ5NDQ5NDQ5NDQ5
MjEwMA4GA1UEAxMnMTc5LTcwNS0xNDQ5NDQ5NDQ5NDQ5NDQ5NDQ5NDQ5NDQ5
Y291MjEwMA4GA1UEAxMnMTc5LTcwNS0xNDQ5NDQ5NDQ5NDQ5NDQ5NDQ5NDQ5
+JterM6pB1nPyFrAQGIZuH1M10Mkw6T+ya0ZQ17qVH8ICBbUuJADoGSNlauH
PB9A1jkwkK0yAvBf4jhnk/onC2gc5zoNBqr76Y2PD8BuMLJGZAsfqQ3+GGSMY
VbWPCz2egY+y66P-----
u3LZQGHMw057dd+JbnJ5m2fPIMF7s4Br63c7cl3P5McaQpvs/2+M4x0AG2E6ve
M3prGgF7uKEPIOMVHqWTPsbZKkdIX7uF8EkvX5wDjRoxUkmbBrl3aUz6O9ep
RxOmUQIDAQABo18wTAdBgNVHQ4EFgQUdAAR8AdolNqU9WriEwz8B84ZwqHwYD
VR0JBGgwFoAUnpDDibEsOCavPM1c8uByXNLFgwGwYDVRORBBQwEoEQYWRhZEBh
ZmFzZGFzLmNhyTANBgkqhkiG9w0BAQsFAADCAQEAAG7Ck3ZiX7TLuQVkw7nMcTJ
QdGKzz3FwyQ9/rmJafqHqAJuQDQ06hosAftvoltrQbPy6wX7USim3Ku4915m75f
DXKv4uImCfHvMjP5SSL4g2cseY5+gweZ0x18QmNtoBgd4N1C1xS8yqPzQMIG
IAP1e5wM1co2D8PeKeYI5CEKQuDhks24vKu07oGT2G4yN2j079wNAICf
UES7avoRamN/FfoxzaMXDkoE9enNlprAG9XigJfNIMMCAckzOnZck7O5Xr0E
W3r2ODUpUwmrlyT4Q4ki0ZJlocApKPTIZgDDUVNhh9rq5JWelwfpPa8RQFH86KQ==
-----END CERTIFICATE-----
```

NOTE If the previous certificate was signed by the same **PF-PKI**, you do **not** need to replace the **Private Key** or ****Intermediate CA Certificate**.

- Restart the appropriate services for the changes to take effect from the PacketFence UI:
 - Restart **haproxy-admin** and **haproxy-portal** if it's the HTTP certificate.
 - Restart **radiusd-auth** if it's the Radius certificate.

30.7. Useful commands

If a certificate has been created without using PacketFence for the CSR, the key and the certificate can be extracted from the .p12 file (or file with the .p12 extension).

Extract certificate

```
openssl pkcs12 -in certificate_bundle.p12 -clcerts -nokeys -out  
/usr/local/pf/conf/ssl/server.crt -passin pass:secret
```

Extract private key

```
openssl pkcs12 -in certificate_bundle.p12 -nocerts -nodes -out  
/usr/local/pf/conf/ssl/server.key -passin pass:secret
```

Check content of a CSR

```
openssl req -in mycsr.csr -noout -text
```

30.8. Glossary

- .pem (Privacy Enhanced Mail): PEM is a base64-encoded certificate or key that is commonly used for transporting certificates over the internet or through email. It is a text file that contains a certificate or a private key in plain text.
- .pfx (Personal Information Exchange): PFX is a binary format used for storing a certificate with its associated private key. It is often used in Microsoft Windows systems and can also contain additional intermediate certificates required to establish a chain of trust.
- .crt (Certificate): CRT is a commonly used file extension for a digital certificate. It contains a public key, along with additional information about the certificate, such as the issuer and expiration date.
- .key (Key): KEY is a file extension used to indicate a private key. Private keys are used to decrypt data that has been encrypted using the corresponding public key in a digital certificate.

31. Troubleshooting PacketFence

31.1. RADIUS Audit Log

PacketFence RADIUS auditing module tracks all incoming RADIUS requests/responses. Access via *Auditing* → *RADIUS Audit Log*. Advanced search criteria create complex, savable search expressions. Click log entries to view endpoint information, request origin, and RADIUS payload between NAS and PacketFence.

31.2. Log files

Log files are in `/usr/local/pf/logs`. Each service has its own log file, except `packetfence.log` which contains logs from multiple services. View complete log file list via *Audit* → *Live logs* menu in web admin.

Main logging configuration is in `/usr/local/pf/conf/log.conf`. Contains `packetfence.log` configuration (`Log::Log4Perl`) – normally no modification needed. Service-specific logging configurations are in `/usr/local/pf/conf/log.conf.d/`.

Key Log Files for Troubleshooting:

- `packetfence.log`: General PacketFence application logs
- `radius.log`: FreeRADIUS authentication and accounting logs
- `mariadb.log`: Database server logs (renamed from `mariadb_error.log` in v12+)
- `httpd.apache`: Apache web server logs (consolidated from multiple `httpd` logs in v12+)

Useful Log Monitoring Commands:

```
# Monitor live PacketFence logs
tail -f /usr/local/pf/logs/packetfence.log

# Watch for database errors
tail -f /usr/local/pf/logs/mariadb.log

# Monitor RADIUS authentication
tail -f /usr/local/pf/logs/radius.log

# Check system messages for hardware issues
dmesg | grep -i error

# Real-time system log monitoring
journalctl -f
```

Log File Name Changes (v12.0+): - MariaDB: `mariadb_error.log` → `mariadb.log` - Apache logs: Multiple files consolidated to `httpd.apache`

31.3. RADIUS Debugging

Check FreeRADIUS logs at `/usr/local/pf/logs/radius.log`.

If needed, run FreeRADIUS in debug mode using these commands:

For the authentication radius process:

```
radiusd -X -d /usr/local/pf/raddb -n auth
```

For the accounting radius process:

```
radiusd -X -d /usr/local/pf/raddb -n acct
```

Additionally there is a `raddebug` tool that can extract debug logs from a running FreeRADIUS daemon. PacketFence's FreeRADIUS is pre-configured with such support.

In order to have an output from `raddebug`, you need to either:

1. Make sure user `pf` has a shell in `/etc/passwd`, add `/usr/sbin` to `PATH` (`export PATH=/usr/sbin:$PATH`) and execute `raddebug` as `pf`
2. Run `raddebug` as root (less secure!)

Now you can run `raddebug` easily:

```
raddebug -t 300 -f /usr/local/pf/var/run/radiusd.sock
```

The above will output FreeRADIUS' authentication debug logs for 5 minutes.

Use the following to debug radius accounting:

```
raddebug -t 300 -f /usr/local/pf/var/run/radiusd-acct.sock
```

See `man raddebug` for all the options.

31.4. Authentication Failures

If authentication fails for users or devices:

1. Check RADIUS audit log via *Auditing* → *RADIUS Audit Log* to trace authentication flow
2. Verify authentication source configuration in *Configuration* → *Policies and Access Control* → *Authentication Sources*
3. For Active Directory issues:

- ❑ Verify domain join status: `realm list`
 - ❑ Check domain controller connectivity: `kinit username@DOMAIN.COM`
 - ❑ Test LDAP connectivity from PacketFence server
4. For external authentication sources (LDAP, RADIUS), verify network connectivity and credentials
 5. Check that user/device exists in authentication source and has proper permissions
 6. For certificate-based authentication (802.1X), verify:
 - ❑ Certificate Authority (CA) configuration
 - ❑ Certificate validity and expiration
 - ❑ EAP-TLS profile settings

Advanced Active Directory Troubleshooting:

1. **Domain Controller Failover:** For multiple AD servers, ensure:
 - ❑ Set 'Sticky DC' parameter to `*` in domain configuration
 - ❑ Specify multiple DNS servers alternating between availability zones
 - ❑ Example: `10.0.1.100,10.0.2.100,10.0.1.101,10.0.2.101`
2. **Winbindd Failover Issues:** Some samba/winbindd versions don't failover correctly:
 - ❑ Enable monit to automatically restart winbindd on DC failures
 - ❑ Monitor authentication failures and restart services when needed
3. **Individual Machine Accounts:** For cluster deployments, use individual machine accounts for each node to avoid secure connection binding issues
4. **Certificate Issues:** For AD/DCS/PKI integration:
 - ❑ Apply required hotfixes before configuration
 - ❑ Check for "The RPC Server is unavailable" errors after AD/DCS service restart
 - ❑ Verify SSL certificate validity and hostname matching

31.5. Network Connectivity Issues

For network-related problems:

Basic Network Diagnostics:

1. Verify interface configuration and IP addresses:

```
ip addr show
```

2. Check network service status:

```
/usr/local/pf/bin/pfcmd service pf status | grep -E  
"(dhcpd|pfdhcp|keepalived)"
```


3. Test connectivity to network devices (switches, wireless controllers):

```
ping switch-ip-address
```

4. Verify SNMP connectivity to network devices:

```
snmpwalk -v2c -c community switch-ip-address system
```

5. For VLAN enforcement issues, check switch configuration and trunk port settings
6. Verify firewall rules allow required traffic between PacketFence and network devices

31.5.1. Advanced Network Issues

1. **Large Registration Network Issues:** In large environments, check for ARP table overflow symptoms:
 - DHCP not assigning IPs properly
 - Failed pings in registration/quarantine VLANs
 - Check system logs: `dmesg | grep "Neighbour table overflow"`
2. **VLAN Segmentation:** Ensure VLAN reaches from client to DHCP infrastructure to PacketFence server
3. **Keepalived Issues:** If virtual IP addresses aren't working properly:

```
/usr/local/pf/bin/pfcmd service keepalived restart
```

31.6. Service Startup Failures

If services fail to start after upgrade or configuration changes:

1. Check service status using:

```
/usr/local/pf/bin/pfcmd service pf status
```

2. Examine log files in `/usr/local/pf/logs` for specific service error messages
3. Verify database connectivity before starting services
4. Check configuration syntax using:

```
/usr/local/pf/bin/pfcmd checksum
```

5. For network-related service failures, verify interface configuration and IP addresses
6. If httpd services fail, check Apache error logs and verify SSL certificate validity

31.6.1. Common Service Issues

1. **Admin Interface Access Issues:** If admin interface shows "Internet Explorer cannot display the webpage":
 - Check if admin interface is started: `/usr/local/pf/bin/pfcmd service httpd.admin start`
 - For IE 8-10: Enable TLS v1.2 in browser settings (Tools → Internet Options → Advanced)
 - Verify SSL certificate matches hostname
2. **MariaDB Service Issues:** If MariaDB fails to start, check:

```
tail -f /usr/local/pf/logs/mariadb.log
```

3. **Service Restart Commands:** For specific service troubleshooting:

```
# Restart RADIUS services
/usr/local/pf/bin/pfcmd service radiusd restart

# Restart NTLM authentication API
systemctl restart packetfence-ntlm-auth-api

# Restart specific detection services
/usr/local/pf/bin/pfcmd service pfdetect restart
/usr/local/pf/bin/pfcmd service pfqueue restart
```

4. **Monitoring Service Logs:** Use journalctl for real-time log monitoring:

```
journalctl -f -u packetfence-mariadb
journalctl -f # Monitor all system logs
```

31.7. Database Connectivity Issues

Check PacketFence application can connect to the database by emulating how PacketFence connects:

For PacketFence versions 11.0 and later

```
mysql -u $(perl -I/usr/local/pf/lib_perl/lib/perl5 -I/usr/local/pf/lib -Mpf::db -e 'print $pf::db::DB_Config->{user}') -p$(perl -I/usr/local/pf/lib_perl/lib/perl5 -I/usr/local/pf/lib -Mpf::db -e 'print $pf::db::DB_Config->{pass}') -h $(perl -I/usr/local/pf/lib_perl/lib/perl5 -I/usr/local/pf/lib -Mpf::db -e 'print $pf::db::DB_Config->{host}') pf
```

For PacketFence versions prior to 11.0

```
mysql -u $(perl -I/usr/local/pf/lib -Mpf::db -e 'print $pf::db::DB_Config->{user}')
```

```
-p$(perl -I/usr/local/pf/lib -Mpf::db -e 'print $pf::db::DB_Config->{pass}')
```

```
-h $(perl -I/usr/local/pf/lib -Mpf::db -e 'print $pf::db::DB_Config->{host}')
```

```
pf
```

If you got a prompt, it means PacketFence must be able to connect to the database.

To perform a small query to the database using PacketFence codebase:

```
/usr/local/pf/bin/pfcmd checkup
```

If the command doesn't return any database error, PacketFence is able to perform reads on database.

Common Database Connection Issues:

1. **Too Many Connections:** Default MariaDB limit is often too low (100). Increase to at least 300 for wireless environments with heavy RADIUS traffic.
2. **Host Blocked:** After 10 connection timeouts, MariaDB may block the host. Check for "Host <hostname> is blocked" errors.
3. **Custom Database Configuration:** If API requests return errors, check [packetfence.log](#) for full MySQL error messages.
4. **Configuration Reload:** After database configuration changes, run:

```
/usr/local/pf/bin/pfcmd configreload hard
```

31.8. Performance and Optimization Issues

Large Environment Considerations:

1. **ARP Table Overflow:** In large registration networks, symptoms include:
 - DHCP not assigning IPs properly
 - Failed pings in registration/quarantine VLANs
 - System log message: "Neighbour table overflow"

```
**Solution**: Increase kernel ARP cache settings in `/etc/sysctl.conf`:
```

```
net.ipv4.neigh.default.gc_thresh1 = 2048  
net.ipv4.neigh.default.gc_thresh2 = 4096  
net.ipv4.neigh.default.gc_thresh3 = 8192  
sysctl -p
```

2. **Database Connection Limits:** For wireless environments with heavy RADIUS traffic:
 - Increase MariaDB max_connections from default 100 to at least 300
 - Monitor for "Too many connections" errors
 - Check for "Host <hostname> is blocked" messages after connection timeouts
3. **Memory and Resource Usage:** Monitor system resources during peak usage:

```
# Check memory usage
free -m

# Monitor active processes
top -p $(pgrep -d', ' -f packetfence)

# Check disk space
df -h /usr/local/pf/logs /var/lib/mysql
```

Guest Pre-registration Security: - Pre-registration exposes PacketFence functionality on the Internet - Apply critical OS updates and PacketFence security fixes - Ensure valid MTA configuration for email relay - Monitor [/signup](#) page access logs for suspicious activity

31.9. Captive Portal Issues

Portal Not Appearing:

1. **Network Configuration:** Verify portal interface configuration:
 - Check that 'portal' interface type is configured
 - Verify IP addresses and VLAN configuration
 - Test network connectivity from client to PacketFence portal IP
2. **Apache/HTTP Services:** Check portal web services:

```
/usr/local/pf/bin/pfcmd service pf status | grep httpd
systemctl status httpd.portal
```

3. **DNS and Redirection:** Verify DNS redirection is working:
 - Check that unregistered devices receive portal IP in DNS responses
 - Verify iptables rules for portal redirection
 - Test with: `nslookup google.com` from unregistered client

31.9.1. Content Security Policy (CSP) Issues

1. **CSP Blocking Content:** If portal content is blocked by CSP:
 - Disable CSP headers via *Configuration → System Configuration → Main Configuration → Advanced → CSP headers for Captive Portal*
 - Check browser developer tools for CSP violation errors

- Verify all external content sources are whitelisted

31.9.2. SSL/TLS Certificate Issues

1. **Certificate Problems:** For HTTPS portal access:
 - Verify SSL certificate matches portal hostname
 - Check certificate expiration date
 - For self-signed certificates, ensure proper trust chain

31.9.3. Pre-registration Security

1. **External Access Issues:** When pre-registration is enabled:
 - Verify perimeter firewall allows access to port 443
 - Check that domain name resolves to management interface IP
 - Monitor for security attacks on exposed `/signup` endpoint

32. Commercial Support and Contact Information

For any questions or comments, do not hesitate to contact us by writing an email to: support@inverse.ca.

Akamai - Inverse team (<https://www.packetfence.com>) offers professional services around PacketFence to help organizations deploy the solution, customize, migrate versions or from another system, performance tuning or aligning with best practices.

Hourly rates or support packages are offered to best suit your needs.

Please visit <https://www.packetfence.com> for details.

33. GNU Free Documentation License

Please refer to <https://www.gnu.org/licenses/fdl-1.2.txt> for the full license.

34. Appendix

Appendix A: Administration Tools

34.A.1. pfcmd

`pfcmd` is the command line interface to most PacketFence functionalities.

When executed without any arguments `pfcmd` returns a basic help message with all main options:

```
Usage:
  pfcmd <command> [options]

Commands
  cache                        | manage the cache subsystem
  checkrequirements            | check system hardware requirements (RAM,
CPU, disk)
  checkup                      | perform a sanity checkup and report any
problems
  class                        | view security event classes
  configreload                 | reload the configuration
  connectionprofileconfig     | query/modify connection profile
configuration parameters
  fingerbank                   | Fingerbank related commands
  fixpermissions               | fix permissions on pf tree
  floatingnetworkdeviceconfig | query/modify floating network devices
configuration parameters
  generatemariadbconfig        | generate the MariaDB configuration
  generatemonitconfig          | generate the monit configuration
  generatesyslogconfig         | generate the syslog configuration
  help                         | show help for pfcmd commands
  import                       | bulk import of information into the
database
  ipmachistory                 | IP/MAC history
  locationhistorymac            | Switch/Port history
  locationhistoryswitch        | Switch/Port history
  networkconfig                | query/modify network configuration
parameters
  node                         | manipulate node entries
  pfconfig                     | interact with pfconfig
  pfcron                       | run pfcron tasks
  pfqueue                      | query/modify pfqueue tasks and counters
```


reload	rebuild fingerprint or security events
tables without restart	
reloadiptablesrules	rebuild iptables rules without restart
reloadiptablesrules	rebuild ip6tables rules without restart
service	start/stop/restart and get PF daemon status
switchconfig	query/modify switches.conf configuration
parameters	
version	output version information
security_event	manipulate security events
security_eventconfig	query/modify security_events.conf
configuration parameters	

Please view "pfcmd help <command>" for details on each option

The node view option shows all information contained in the node database table for a specified MAC address

```
# /usr/local/pf/bin/pfcmd node view 52:54:00:12:35:02
mac|pid|detect_date|regdate|unregdate|status|user_agent|computername|notes|last
_arp|last_dhcp|switch|port|vlan|dhcp_fingerprint
52:54:00:12:35:02|1|2008-10-23 17:32:16|||unreg|||2008-10-23 21:12:21|
```

Appendix B: Restoring a Percona XtraBackup or Mariabackup dump

When Percona XtraBackup or Mariabackup is enabled for nightly backup, use the following instructions to restore it. In this example `/root/backup/packetfence-db-dump-innobackup-2016-12-20_00h31.xbstream.gz` will be restored

First, create a restore directory, move the backup to it and gunzip the backup:

```
# mkdir /root/backup/restore
# cd /root/backup/restore
# cp ../packetfence-db-dump-innobackup-2016-12-20_00h31.xbstream.gz .
# gunzip packetfence-db-dump-innobackup-2016-12-20_00h31.xbstream.gz
```

Then extract the xbstream data (for XtraBackup):

```
# xbstream -x < packetfence-db-dump-innobackup-2016-12-20_00h31.xbstream
```

Then extract the xbstream data (for Mariabackup):

```
# mbstream -x < packetfence-db-dump-innobackup-2016-12-20_00h31.xbstream
```

Once done, many files should be extracted in the restore dir. Now, place the xstream back in the backup directory

```
# mv packetfence-db-dump-innobackup-2016-12-20_00h31.xstream ../
```

Next, apply the innodb log (for XtraBackup):

```
# innobackupex --apply-log ./
```

Next, apply the innodb log (for Mariabackup):

```
# mariabackup --prepare --target-dir=.
```

We will now stop MariaDB, move the existing data directory and replace it by the data that was extracted:

NOTE | Adjust the commands above to match the specific environment.

For XtraBackup:

```
# service packetfence-mariadb stop
# mv /var/lib/mysql /var/lib/mysql.bak
# mkdir /var/lib/mysql
# mv * /var/lib/mysql
# chown -R mysql: /var/lib/mysql
# service packetfence-mariadb start
```

For Mariabackup:

```
# service packetfence-mariadb stop
# mv /var/lib/mysql /var/lib/mysql.bak
# mkdir /var/lib/mysql
# mariabackup --innobackupex --defaults
-file=/usr/local/pf/var/conf/mariadb.conf --move-back --force-non-empty
-directories ./
# chown -R mysql: /var/lib/mysql
# service packetfence-mariadb start
```

Should the service fail to start, check the MariaDB logs.

Appendix C: How to restore a standalone PacketFence server ?

Starting from PacketFence 11.0, use [the export/import mechanism](#).

Appendix D: How to deploy PacketFence on Linode ?

34.D.1. Introduction

This section will guide you into the high-level steps required to deploy PacketFence on Linode. Linode is an Infrastructure as a Service (IaaS) that provides cloud computing services which can be leveraged by PacketFence. This is often the preferred deployment option for Cloud-first organizations.

34.D.2. Installation and Configuration Steps

First, you need to create three 'Debian 12' or 'Rocky 8' Linodes in the same region. The 'Dedicated 16GB' plan or above is required and make sure Private IP is enabled for each instance.

Once done, make sure to configure the firewall policy similar to the following screenshot:

Firewalls / pf-secured

Rules Linodes

Inbound Rules [Add an Inbound Rule](#)

Label	Protocol	Port Range	Sources	Action	
accept-inbound-SSH	TCP	22	All IPv4, All IPv6	Accept	Edit Clone Delete
accept-inbound-HTTP	TCP	80	All IPv4, All IPv6	Accept	Edit Clone Delete
accept-inbound-HTTPS	TCP	443	All IPv4, All IPv6	Accept	Edit Clone Delete
accept-inbound-ADMIN-INTERFACE	TCP	1443	All IPv4, All IPv6	Accept	Edit Clone Delete
accept-inbound-API-FRONTEND	TCP	9999	All IPv4, All IPv6	Accept	Edit Clone Delete
accept-private-nets-tcp	TCP	All Ports	192.168.0.0/16, 10.0.0.0/8, 172.16.0.0/12	Accept	Edit Clone Delete
accept-private-nets-udp	UDP	All Ports	192.168.0.0/16, 10.0.0.0/8, 172.16.0.0/12	Accept	Edit Clone Delete
accept-private-nets-icmp	ICMP		192.168.0.0/16, 10.0.0.0/8, 172.16.0.0/12	Accept	Edit Clone Delete

Default inbound policy: This policy applies to any traffic not covered by the inbound rules listed above. Drop

Outbound Rules [Add an Outbound Rule](#)

Label	Protocol	Port Range	Destinations	Action	
No outbound rules have been added.					

Default outbound policy: This policy applies to any traffic not covered by the outbound rules listed above. Accept

Discard Changes Save Changes

Then, perform a standard PacketFence installation on each Linode. Once completed, from Linode's cloud management interface, configure a NodeBalancer for ports 80, 443, 1443, 9090 and 9999 as shown in the following screenshot:

346

Once completed, Go through the [PacketFence Clustering Installation Guide](#).

For the IP addresses in the CLUSTER sections, use the public IP of the NodeBalancer above. For the IP addresses of the servers themselves, use their private IP addresses. No registration/isolation VLANs are supported at the moment. If you want to perform enforcement with PacketFence, you will have to use Web Authentication. Once done building the cluster, disable 'Proxy RADIUS using virtual IP' and 'Use virtual IP for access reevaluation' from the *Configuration* → *System Configuration* → *Cluster* configuration section and restart the `radiusd-load_balancer` service. Once completed, the file `/usr/local/pf/conf/cluster.conf` should be similar to:

```
[CLUSTER]
management_ip=172.105.12.210

[CLUSTER interface eth0]
ip=172.105.12.210

[cluster-1]
management_ip=192.168.139.40

[cluster-1 interface eth0]
ip=192.168.139.40

[cluster-2]
management_ip=192.168.129.9

[cluster-2 interface eth0]
ip=192.168.129.9

[cluster-3]
management_ip=192.168.139.254

[cluster-3 interface eth0]
ip=192.168.139.254
```

Then, make sure you mask `keepalived` so it does not mount a VIP on your server:

```
systemctl mask packetfence-keepalived
```

Finally, you must configure a secure way to reach your Cloud-hosted version of PacketFence so that your NAS devices can talk to it in a secure way. One approach is to use a site-to-site VPN. Another approach is to use the [PacketFence Connector](#).